

# Package ‘mmpca’

March 20, 2020

**Title** Integrative Analysis of Several Related Data Matrices

**Version** 2.0.1

**Author** Jonatan Kallus [aut, cre]

**Maintainer** Jonatan Kallus <kallus@chalmers.se>

**Description** A generalization of principal component analysis for integrative analysis. The method finds principal components that describe single matrices or that are common to several matrices. The solutions are sparse. Rank of solutions is automatically selected using cross validation. The method is described in Kallus, Johansson, Nelander and Jörnsten (2019) <arXiv:1911.04927>.

**Depends** R (>= 3.3.0)

**Imports** digest (>= 0.6.0), gsl (>= 1.9)

**LinkingTo** Rcpp, RcppEigen

**License** GPL-3

**LazyData** true

**NeedsCompilation** yes

**Encoding** UTF-8

**RoxygenNote** 7.0.2

**Repository** CRAN

**Date/Publication** 2020-03-20 12:40:03 UTC

## R topics documented:

mmpca . . . . .	2
<b>Index</b>	<b>4</b>

mmpca

*Multiview principal component analysis***Description**

Analyzes several related matrices of data.

**Usage**

```
mmpca(x, inds, k, lambda = NULL, trace = 0, init_theta = NULL,
      cachepath = NULL, enable_rank_selection = TRUE, enable_sparsity = TRUE,
      enable_variable_selection = FALSE, parallel = TRUE)
```

**Arguments**

x	List of matrices to analyze
inds	Matrix containing view indices. The matrix should have two columns and the same number of rows as the length of x. The first (second) column contains the view index of the rows (columns) of the corresponding matrix.
k	Integer giving the maximum rank of the analysis, i.e. the maximum number of principal components for each view.
lambda	Vector or matrix of lambda values. The length (or width if it is a matrix) depends on the number of active penalties (2, 3 or 4). If it is a matrix, try different lambda values (one try for each row). Default: a matrix where each column is the sequence $\exp(\text{seq}(-6, 0))$ .
trace	Integer selecting the amount of log messages. 0 (default): no output, 3: all output.
init_theta	NULL, functions or numeric. NULL (default) use initial values based on ordinary SVD. If init_theta is a list of three functions (CMF, matrix_to_triplets and getCMFOpts from package CMF) use the supplied functions to find initial values with collaborative matrix factorization (CMF). If init_theta is a numeric vector it is used as initial value.
cachepath	Character vector with path to directory to store intermediate results. If NULL (default) intermediate results are not stored. For caching to work it is required that the random number generation seed is constant between calls to mmpca, so <code>set.seed</code> needs to be called before mmpca.
enable_rank_selection	Boolean deciding if the second penalty that imposes a low rank model should be enabled.
enable_sparsity	Boolean deciding if the third penalty that imposes sparsity in V should be enabled.
enable_variable_selection	Boolean deciding if the fourth penalty that increases the tendency for sparsity structure of different V columns to be similar. Defaults to FALSE meaning this penalty is not used.

`parallel` Boolean deciding if computations should be run on multiple cores simultaneously.

**Value**

A list with components

`initial` initial values used in optimization  
`cmf` solution found with CMF (if `init_theta == c(CMF, matrix_to_triplets, getCM-Fopts)`)  
`training` solutions for different values of lambda  
`solution` solution for optimal lambda value

**Author(s)**

Jonatan Kallus, <kallus@chalmers.se>

**Examples**

```
x <- list(matrix(rnorm(110), 10, 11), matrix(rnorm(120), 10, 12))
inds <- matrix(c(1, 1, 2, 3), 2, 2)
result <- mmpca(x, inds, 3, parallel=FALSE)
```

# Index

\*Topic **models**

mmpca, 2

\*Topic **multivariate**

mmpca, 2

\*Topic **pca**

mmpca, 2

mmpca, 2