

Package ‘psychometrics’

October 26, 2020

Type Package

Title Structural Equation Modeling and Confirmatory Network Analysis

Version 0.8

Author Sacha Epskamp

Maintainer Sacha Epskamp <mail@sachaepskamp.com>

Description

Multi-group (dynamical) structural equation models in combination with confirmatory network models from cross-sectional, time-series and panel data <doi:10.31234/osf.io/8ha93>. Allows for confirmatory testing and fit as well as exploratory model search.

License GPL-2

LinkingTo Rcpp (>= 0.11.3), RcppArmadillo, pbv, roptim

Depends R (>= 3.5)

Imports methods, qgraph, numDeriv, dplyr, abind, matrixcalc, Matrix, lavaan, corpcor, ucminf, glasso, mgcv, optimx, mvtnorm, VCA, pbapply, parallel, magrittr, IsingSampler, ggplot2, tidyr, psych, GA, combinat

Suggests psychTools, semPlot, graphicalVAR, metaSEM

ByteCompile true

URL <http://psychometrics.org/>

BugReports <https://github.com/SachaEpskamp/psychometrics/issues>

StagedInstall true

NeedsCompilation yes

Repository CRAN

Date/Publication 2020-10-26 21:50:03 UTC

R topics documented:

psychometrics-package	3
bifactor	5

bootstrap	6
changedata	6
compare	7
covML	8
dlvm1	9
duplicationMatrix	15
emergencystart	16
esa	16
factorscores	17
fit	18
fixpar	19
generate	20
getmatrix	20
getVCOV	21
groupequal	22
Ising	23
Jonas	26
latentgrowth	27
lvm	28
meta_varcov	39
MI	43
ml_lvm	44
ml_tsdvm1	49
modelsearch	50
parameters	51
parequal	52
partialprune	53
prune	54
psychometrics-class	55
psychometrics_update	57
runmodel	58
setestimator	59
setverbose	60
simplestructure	60
StarWars	61
stepup	62
tsdvm1	64
unionmodel	68
var1	69
varcov	74

psychometrics-package *Structural Equation Modeling and Confirmatory Network Analysis*

Description

Multi-group (dynamical) structural equation models in combination with confirmatory network models from cross-sectional, time-series and panel data <doi:10.31234/osf.io/8ha93>. Allows for confirmatory testing and fit as well as exploratory model search.

Details

The DESCRIPTION file:

```

Package:      psychometrics
Type:         Package
Title:        Structural Equation Modeling and Confirmatory Network Analysis
Version:      0.8
Author:       Sacha Epskamp
Maintainer:   Sacha Epskamp <mail@sachaepskamp.com>
Description:  Multi-group (dynamical) structural equation models in combination with confirmatory network models from
License:      GPL-2
LinkingTo:    Rcpp (>= 0.11.3), RcppArmadillo, pbv, roptim
Depends:      R (>= 3.5)
Imports:      methods, qgraph, numDeriv, dplyr, abind, matrixcalc, Matrix, lavaan, corpcor, ucminf, glasso, mgcv, optimx,
Suggests:    psychTools, semPlot, graphicalVAR, metaSEM
ByteCompile:  true
URL:          http://psychometrics.org/
BugReports:   https://github.com/SachaEpskamp/psychometrics/issues
StagedInstall: true

```

Index of help topics:

Ising	Ising model
Jonas	Jonas dataset
MIs	Print modification indices
StarWars	Star Wars dataset
addMIs	Model updating functions
bifactor	Bi-factor models
bootstrap	Bootstrap a psychometrics model
changedata	Change the data of a psychometrics object
compare	Model comparison
covML	Maximum likelihood covariance estimate
dlvm1	Lag-1 dynamic latent variable model family of psychometrics models for panel data
duplicationMatrix	Model matrices used in derivatives
emergencystart	Reset starting values to simple defaults

esa	Ergodic Subspace Analysis
factorscores	Compute factor scores
fit	Print fit indices
fixpar	Parameters modification
generate	Generate data from a fitted psychonetrics object
getVCOV	Obtain the asymptotic covariance matrix
getmatrix	Extract an estimated matrix
groupequal	Group equality constrains
latentgrowth	Latnet growth curve model
lvm	Continuous latent variable family of psychonetrics models
meta_varcov	Variance-covariance and GGM meta analysis
ml_lvm	Multi-level latent variable model family
ml_tsd1vm1	Multi-level Lag-1 dynamic latent variable model family of psychonetrics models for time-series data
modelsearch	Stepwise model search
parameters	Print parameter estimates
parequal	Set equality constrains across parameters
partialprune	Partial pruning of multi-group models
prune	Stepdown model search by pruning non-significant parameters.
psychonetrics-class	Class "psychonetrics"
psychonetrics-package	Structural Equation Modeling and Confirmatory Network Analysis
runmodel	Run a psychonetrics model
setestimator	Convenience functions
setverbose	Should messages of computation progress be printed?
simplestructure	Generate factor loadings matrix with simple structure
stepup	Stepup model search along modification indices
tsd1vm1	Lag-1 dynamic latent variable model family of psychonetrics models for time-series data
unionmodel	Unify models across groups
var1	Lag-1 vector autoregression family of psychonetrics models
varcov	Variance-covariance family of psychonetrics models

This package can be used to perform Structural Equation Modeling and confirmatory network modeling. Current implemented families of models are (1) the variance-covariance matrix (`varcov`), (2) the latent variable model (`lvm`), (3) the lag-1 vector autoregression model (`var1`), and (4) the dynamical lag-1 latent variable model for panel data (`dlvm1`) and for time-series data (`tsd1vm1`).

Author(s)

Sacha Epskamp

Maintainer: Sacha Epskamp <mail@sachaepskamp.com>

References

More information: psychonetrics.org

bifactor	<i>Bi-factor models</i>
----------	-------------------------

Description

Wrapper to `lvm` to specify a bi-factor model.

Usage

```
bifactor(data, lambda, latents, bifactor = "g", ...)
```

Arguments

<code>data</code>	The data as used by <code>lvm</code>
<code>lambda</code>	The factor loadings matrix <i>without</i> the bifactor, as used by <code>lvm</code>
<code>latents</code>	A vector of names of the latent variables, as used by <code>lvm</code>
<code>bifactor</code>	Name of the bifactor
<code>...</code>	Arguments sent to <code>lvm</code>

Value

An object of the class `psychonetrics` ([psychonetrics-class](#))

Author(s)

Sacha Epskamp

bootstrap	<i>Bootstrap a psychometrics model</i>
-----------	----------------------------------------

Description

This function will bootstrap the data (once) and return a new unevaluated psychometrics object. It requires `storedata = TRUE` to be used when forming a model.

Usage

```
bootstrap(x, replacement = TRUE, proportion = 1, verbose = TRUE, storedata = FALSE,
          baseline_saturated = TRUE)
```

Arguments

<code>x</code>	A psychometrics model.
<code>replacement</code>	Logical, should new samples be drawn with replacement?
<code>proportion</code>	Proportion of sample to be drawn. Set to lower than 1 for subsampling.
<code>verbose</code>	Logical, should messages be printed?
<code>storedata</code>	Logical, should the bootstrapped data also be stored?
<code>baseline_saturated</code>	Logical, should the baseline and saturated models be included?

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

changedata	<i>Change the data of a psychometrics object</i>
------------	--------------------------------------------------

Description

This function can be used to change the data in a psychometrics object.

Usage

```
changedata(x, data, covs, nobs, means, groups, missing = "listwise")
```

Arguments

x	A psychometrics model.
data	A data frame encoding the data used in the analysis. Can be missing if covs and nobs are supplied.
covs	A sample variance–covariance matrix, or a list/array of such matrices for multiple groups. IMPORTANT NOTE: psychometrics expects the maximum likelihood (ML) covariance matrix, which is NOT obtained from <code>cov</code> directly. Manually rescale the result of <code>cov</code> with $(nobs - 1)/nobs$ to obtain the ML covariance matrix.
nobs	The number of observations used in covs and means, or a vector of such numbers of observations for multiple groups.
means	A vector of sample means, or a list/matrix containing such vectors for multiple groups.
groups	An optional string indicating the name of the group variable in data.
missing	How should missingness be handled in computing the sample covariances and number of observations when data is used. Can be "listwise" for listwise deletion, or "pairwise" for pairwise deletion.

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

compare

Model comparison

Description

This function will print a table comparing multiple models on chi-square, AIC and BIC.

Usage

```
compare(...)

## S3 method for class 'psychometrics_compare'
print(x, ...)
```

Arguments

...	Any number of psychometrics models. Can be named to change the rownames of the output.
x	Output of the compare function.

Value

A data frame with chi-square values, degrees of freedoms, RMSEAs, AICs, and BICs.

Author(s)

Sacha Epskamp

covML

Maximum likelihood covariance estimate

Description

These functions complement the base R cov function by simplifying obtaining maximum likelihood (ML) covariance estimates (denominator n) instead of unbiased (UB) covariance estimates (denominator n-1). The function covML can be used to obtain ML estimates, the function covUBtoML transforms from UB to ML estimates, and the function covMLtoUB transforms from ML to UB estimates.

Usage

```
covML(x, ...)  
covUBtoML(x, n, ...)  
covMLtoUB(x, n, ...)
```

Arguments

x	A dataset
n	The sample size
...	Arguments sent to the cov function.

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

Examples

```
data("StarWars")  
Y <- StarWars[,1:10]  
  
# Unbiased estimate:  
UB <- cov(Y)  
  
# ML Estimate:  
ML <- covML(Y)  
  
# Check:  
all(abs(UB - covMLtoUB(ML, nrow(Y))) < sqrt(.Machine$double.eps))  
all(abs(ML - covUBtoML(UB, nrow(Y))) < sqrt(.Machine$double.eps))
```

dlvm1	<i>Lag-1 dynamic latent variable model family of psychometrics models for panel data</i>
-------	------------------------------------------------------------------------------------------

Description

This is the family of models that models a dynamic factor model on panel data. There are four covariance structures that can be modeled in different ways: `within_latent`, `between_latent` for the within-person and between-person latent (contemporaneous) models respectively, and `within_residual`, `between_residual` for the within-person and between-person residual models respectively. The `panelgvar` wrapper function sets the `lambda` to an identity matrix, all residual variances to zero, and models within-person and between-person latent (contemporaneous) models as GGMs. The `panelvar` wrapper does the same but models contemporaneous relations as a variance-covariance matrix. Finally, the `panel_lvlgvar` wrapper automatically models all latent networks as GGMs.

Usage

```
dlvm1(data, vars, lambda, within_latent = c("cov", "chol",
      "prec", "ggm"), within_residual = c("cov", "chol",
      "prec", "ggm"), between_latent = c("cov", "chol",
      "prec", "ggm"), between_residual = c("cov", "chol",
      "prec", "ggm"), beta = "full", omega_zeta_within =
      "full", delta_zeta_within = "full", kappa_zeta_within
      = "full", sigma_zeta_within = "full",
      lowertri_zeta_within = "full", omega_epsilon_within =
      "empty", delta_epsilon_within = "empty",
      kappa_epsilon_within = "empty", sigma_epsilon_within =
      "empty", lowertri_epsilon_within = "empty",
      omega_zeta_between = "full", delta_zeta_between =
      "full", kappa_zeta_between = "full",
      sigma_zeta_between = "full", lowertri_zeta_between =
      "full", omega_epsilon_between = "empty",
      delta_epsilon_between = "empty", kappa_epsilon_between
      = "empty", sigma_epsilon_between = "empty",
      lowertri_epsilon_between = "empty", nu, mu_eta,
      identify = TRUE, identification = c("loadings",
      "variance"), latents, groups, covs, means, nobs,
      covtype = c("choose", "ML", "UB"), missing =
      "listwise", equal = "none", baseline_saturated = TRUE,
      estimator = "ML", optimizer, storedata = FALSE,
      verbose = FALSE, sampleStats)
```

```
panelgvar(data, vars, ...)
```

```
panelvar(data, vars, ...)
```

```
panel_lvlgvar(...)
```

Arguments

<code>data</code>	A data frame encoding the data used in the analysis. Can be missing if covs and nobs are supplied.
<code>vars</code>	Required argument. Different from in other psychometrics models, this must be a <i>matrix</i> with each row indicating a variable and each column indicating a measurement. The matrix must be filled with names of the variables in the dataset corresponding to variable <i>i</i> at wave <i>j</i> . NAs can be used to indicate missing waves. The rownames of this matrix will be used as variable names.
<code>lambda</code>	Required argument. A model matrix encoding the factor loading structure. Each row indicates an indicator and each column a latent. A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>within_latent</code>	The type of within-person latent contemporaneous model to be used.
<code>within_residual</code>	The type of within-person residual model to be used.
<code>between_latent</code>	The type of between-person latent model to be used.
<code>between_residual</code>	The type of between-person residual model to be used.
<code>beta</code>	A model matrix encoding the temporal relationships (transpose of temporal network). A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix. Can also be "full" for a full temporal network or "empty" for an empty temporal network.
<code>omega_zeta_within</code>	Only used when <code>within_latent = "ggm"</code> . Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>delta_zeta_within</code>	Only used when <code>within_latent = "ggm"</code> . Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>kappa_zeta_within</code>	Only used when <code>within_latent = "prec"</code> . Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>sigma_zeta_within</code>	Only used when <code>within_latent = "cov"</code> . Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating

free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

lowertri_zeta_within

Only used when `within_latent = "chol"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

omega_epsilon_within

Only used when `within_residual = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

delta_epsilon_within

Only used when `within_residual = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

kappa_epsilon_within

Only used when `within_residual = "prec"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

sigma_epsilon_within

Only used when `within_residual = "cov"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

lowertri_epsilon_within

Only used when `within_residual = "chol"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

omega_zeta_between

Only used when `between_latent = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

delta_zeta_between

Only used when `between_latent = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating

free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`kappa_zeta_between`

Only used when `between_latent = "prec"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`sigma_zeta_between`

Only used when `between_latent = "cov"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`lowertri_zeta_between`

Only used when `between_latent = "chol"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`omega_epsilon_between`

Only used when `between_residual = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`delta_epsilon_between`

Only used when `between_residual = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`kappa_epsilon_between`

Only used when `between_residual = "prec"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`sigma_epsilon_between`

Only used when `between_residual = "cov"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`lowertri_epsilon_between`

Only used when `between_residual = "chol"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s

	indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
nu	Optional vector encoding the intercepts of the observed variables. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
mu_eta	Optional vector encoding the means of the latent variables. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
identify	Logical, should the model be automatically identified?
identification	Type of identification used. "loadings" to fix the first factor loadings to 1, and "variance" to fix the diagonal of the latent variable model matrix (sigma_zeta, lowertri_zeta, delta_zeta or kappa_zeta) to 1.
latents	An optional character vector with names of the latent variables.
groups	An optional string indicating the name of the group variable in data.
covs	A sample variance–covariance matrix, or a list/array of such matrices for multiple groups. IMPORTANT NOTE: psychometrics expects the maximum likelihood (ML) covariance matrix, which is NOT obtained from <code>cov</code> directly. Manually rescale the result of <code>cov</code> with $(nobs - 1)/nobs$ to obtain the ML covariance matrix.
means	A vector of sample means, or a list/matrix containing such vectors for multiple groups.
nobs	The number of observations used in covs and means, or a vector of such numbers of observations for multiple groups.
missing	How should missingness be handled in computing the sample covariances and number of observations when data is used. Can be "listwise" for listwise deletion, or "pairwise" for pairwise deletion.
equal	A character vector indicating which matrices should be constrained equal across groups.
baseline_saturated	A logical indicating if the baseline and saturated model should be included. Mostly used internally and NOT Recommended to be used manually.
estimator	The estimator to be used. Currently implemented are "ML" for maximum likelihood estimation, "FIML" for full-information maximum likelihood estimation, "ULS" for unweighted least squares estimation, "WLS" for weighted least squares estimation, and "DWLS" for diagonally weighted least squares estimation.
optimizer	The optimizer to be used. Can be one of "nlmminb" (the default R nlmminb function), "ucminf" (from the optimr package), and C++ based optimizers "cpp_L-BFGS-B", "cpp_BFGS", "cpp_CG", "cpp_SANN", and "cpp_Nelder-Mead". The C++ optimizers are faster but slightly less stable. Defaults to "nlminb".
storedata	Logical, should the raw data be stored? Needed for bootstrapping (see bootstrap).
verbose	Logical, should progress be printed to the console?

sampleStats	An optional sample statistics object. Mostly used internally.
covtype	If 'covs' is used, this is the type of covariance (maximum likelihood or unbiased) the input covariance matrix represents. Set to "ML" for maximum likelihood estimates (denominator n) and "UB" to unbiased estimates (denominator n-1). The default will try to find the type used, by investigating which is most likely to result from integer valued datasets.
...	Arguments sent to dlvm1.

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

Examples

```
library("dplyr")

# Smoke data cov matrix, based on LISS data panel https://www.dataarchive.lissdata.nl
smoke <- structure(c(47.2361758611759, 43.5366809116809, 41.0057465682466,
                    43.5366809116809, 57.9789886039886, 47.6992521367521,
                    41.0057465682466,
                    47.6992521367521, 53.0669434731935), .Dim = c(3L, 3L),
                  .Dimnames = list(
                    c("smoke2008", "smoke2009", "smoke2010"), c("smoke2008",
                    "smoke2009", "smoke2010")))

# Design matrix:
design <- matrix(rownames(smoke),1,3)

# Form model:
mod <- panelvar(vars = design,
                covs = smoke, nobs = 352
)

# Run model:
mod <- mod %>% runmodel

# Evaluate fit:
mod %>% fit
```

duplicationMatrix *Model matrices used in derivatives*

Description

These matrices are used in the analytic gradients

Usage

```
duplicationMatrix(n, diag = TRUE)
```

```
eliminationMatrix(n, diag = TRUE)
```

```
diagonalizationMatrix(n)
```

Arguments

n	Number of rows and columns in the original matrix
diag	Logical indicating if the diagonal should be included (set to FALSE for derivative of vech(x))

Value

A sparse matrix

Author(s)

Sacha Epskamp

Examples

```
# Duplication matrix for 10 variables:  
duplicationMatrix(10)  
  
# Elimination matrix for 10 variables:  
eliminationMatrix(10)  
  
# Diagonalization matrix for 10 variables:  
diagonalizationMatrix(10)
```

emergencystart *Reset starting values to simple defaults*

Description

This function overwrites the starting values to simple defaults. This can help in cases where optimization fails.

Usage

```
emergencystart(x)
```

Arguments

x A psychometrics model.

Value

A psychometrics model.

Author(s)

Sacha Epskamp

esa *Ergodic Subspace Analysis*

Description

These functions implement Ergodic Subspace Analysis by von Oertzen, Schmiedek & Voelkle (2020). The functions can be used on the output of a [dlvm1](#) model, or manually by supplying a within persons and between persons variance-covariance matrix.

Usage

```
esa(x, cutoff = 0.1,
    between = c("crosssection", "between"))
esa_manual(sigma_wp, sigma_bp, cutoff = 0.1)
## S3 method for class 'esa'
print(x, printref = TRUE, ...)
## S3 method for class 'esa_manual'
print(x, printref = TRUE, ...)
## S3 method for class 'esa'
plot(x, plot = c("observed", "latent"), ...)
## S3 method for class 'esa_manual'
plot(x, ...)
```


Arguments

x	Output of a <code>dlvm1</code> model
sigma_wp	Manual within-person variance-covariance matrix
sigma_bp	Manual between-person variance-covariance matrix
cutoff	Cutoff used to determine ergodicity
printref	Logical, should the reference be printed?
plot	Should ergodicity of observed or latent variables be plotted?
between	Should the between-persons variance-covariance matrix be based on exected cross-sectional or between-person relations
...	Not used

Value

For each group a `esa_manual` object with the following elements:

ergodicity	Ergodicity values of each component
Q_esa	Component loadings
V_bp	Between persons subspace
V_ergodic	Ergodic subspace
V_wp	Within person subspace
cutoff	Cutoff value used

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

References

von Oertzen, T., Schmiedek, F., & Voelkle, M. C. (2020). Ergodic Subspace Analysis. *Journal of Intelligence*, 8(1), 3.

factorscores

Compute factor scores

Description

Currently, only the `lvm` framework with single group and no missing data is supported.

Usage

```
factorscores(data, model, method = c("bartlett", "regression"))
```

Arguments

data	Dataset to compute factor scores for
model	A psychometrics model
method	The method to use: "regression" or "bartlett"

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

fit *Print fit indices*

Description

This function will print all fit indices of the model/

Usage

```
fit(x)
```

Arguments

x A psychometrics model.

Value

Invisibly returns a data frame with fit measure estimates.

Author(s)

Sacha Epskamp

Examples

```
# Load bfi data from psych package:
library("psychTools")
data(bfi)

# Also load dplyr for the pipe operator:
library("dplyr")

# Let's take the agreeableness items, and gender:
ConsData <- bfi %>%
  select(A1:A5, gender) %>%
  na.omit # Let's remove missingness (otherwise use Estimator = "FIML")

# Define variables:
vars <- names(ConsData)[1:5]
```

```
# Let's fit an empty GGM:
mod0 <- ggm(ConsData, vars = vars, omega = "empty")

# Run model:
mod0 <- mod0 %>% runmodel

# Inspect fit:
mod0 %>% fit # Pretty bad fit...
```

fixpar

Parameters modification

Description

The `fixpar` function can be used to fix a parameter to some value (Typically zero), and the `freepar` function can be used to free a parameter from being fixed to a value.

Usage

```
fixpar(x, matrix, row, col, value = 0, group, verbose,
       log = TRUE, runmodel = FALSE, ...)
```

```
freepar(x, matrix, row, col, start, group, verbose, log =
        TRUE, runmodel = FALSE, startEPC = TRUE, ...)
```

Arguments

<code>x</code>	A psychometrics model.
<code>matrix</code>	String indicating the matrix of the parameter
<code>row</code>	Integer or string indicating the row of the matrix of the parameter
<code>col</code>	Integer or string indicating the column of the matrix of the parameter
<code>value</code>	Used in <code>fixpar</code> to indicate the value to which a parameters is constrained
<code>start</code>	Used in <code>freepar</code> to indicate the starting value of the parameter
<code>group</code>	Integer indicating the group of the parameter to be constrained
<code>verbose</code>	Logical, should messages be printed?
<code>log</code>	Logical, should the log be updated?
<code>runmodel</code>	Logical, should the model be updated?
<code>startEPC</code>	Logical, should the starting value be set at the expected parameter change?
<code>...</code>	Arguments sent to <code>runmodel</code>

Value

An object of the class `psychometrics` ([psychometrics-class](#))

Author(s)

Sacha Epskamp

generate	<i>Generate data from a fitted psychometrics object</i>
----------	---------------------------------------------------------

Description

This function will generate new data from the estimated mean and variance-covariance structure of a psychometrics model.

Usage

```
generate(x, n = 500)
```

Arguments

x	A psychometrics model.
n	Number of cases to sample per group.

Value

A data frame with simulated data

Author(s)

Sacha Epskamp

getmatrix	<i>Extract an estimated matrix</i>
-----------	------------------------------------

Description

This function will extract an estimated matrix, and will either return a single matrix for single group models or a list of such matrices for multiple group models.

Usage

```
getmatrix(x, matrix, group)
```

Arguments

x	A psychometrics model.
matrix	String indicating the matrix to be extracted.
group	Integer indicating the group for the matrix to be extracted.

Value

A matrix of parameter estimates, of a list of such matrices for multiple group models.

Author(s)

Sacha Epskamp

Examples

```
# Load bfi data from psych package:
library("psychTools")
data(bfi)

# Also load dplyr for the pipe operator:
library("dplyr")

# Let's take the agreeableness items, and gender:
ConsData <- bfi %>%
  select(A1:A5, gender) %>%
  na.omit # Let's remove missingness (otherwise use Estimator = "FIML")

# Define variables:
vars <- names(ConsData)[1:5]

# Let's fit a full GGM:
mod <- ggm(ConsData, vars = vars, omega = "full")

# Run model:
mod <- mod %>% runmodel

# Obtain network:
mod %>% getmatrix("omega")
```

getVCOV

Obtain the asymptotic covariance matrix

Description

This function can be used to obtain the estimated asymptotic covariance matrix from a psychonetrics object.

Usage

```
getVCOV(model)
```

Arguments

model A psychonetrics model.

Value

This function returns a matrix.

Author(s)

Sacha Epskamp

groupequal

Group equality constrains

Description

The `groupequal` function constrains parameters equal across groups, and the `groupfree` function frees equality constrains across groups.

Usage

```
groupequal(x, matrix, row, col, verbose, log = TRUE, runmodel =
           FALSE, identify = TRUE, ...)
```

```
groupfree(x, matrix, row, col, verbose, log = TRUE, runmodel =
           FALSE, identify = TRUE, ...)
```

Arguments

<code>x</code>	A psychometrics model.
<code>matrix</code>	String indicating the matrix of the parameter
<code>row</code>	Integer or string indicating the row of the matrix of the parameter
<code>col</code>	Integer or string indicating the column of the matrix of the parameter
<code>verbose</code>	Logical, should messages be printed?
<code>log</code>	Logical, should the log be updated?
<code>runmodel</code>	Logical, should the model be updated?
<code>identify</code>	Logical, should the model be identified?
<code>...</code>	Arguments sent to <code>runmodel</code>

Value

An object of the class `psychometrics` ([psychometrics-class](#))

Author(s)

Sacha Epskamp

Ising

*Ising model***Description**

This is the family of Ising models fit to dichotomous datasets. Note that the input matters (see also <https://arxiv.org/abs/1811.02916>) in this model! Models based on a dataset that is encoded with -1 and 1 are not entirely equivalent to models based on datasets encoded with 0 and 1 (non-equivalences occur in multi-group settings with equality constrains).

Usage

```
Ising(data, omega = "full", tau, beta, vars, groups, covs,
      means, nobs, covtype = c("choose", "ML", "UB"),
      responses, missing = "listwise", equal = "none",
      baseline_saturated = TRUE, estimator = "default",
      optimizer, storedata = FALSE, WLS.W, sampleStats,
      identify = TRUE, verbose = FALSE, maxNodes = 20)
```

Arguments

data	A data frame encoding the data used in the analysis. Can be missing if covs and nobs are supplied.
omega	The network structure. Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions nNode x nNode with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
tau	Optional vector encoding the threshold/intercept structure. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
beta	Optional scalar encoding the inverse temperature. 1 indicate free beta parameters, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such scalars.
vars	An optional character vector encoding the variables used in the analysis. Must equal names of the dataset in data.
groups	An optional character vector encoding the variables used in the analysis. Must equal names of the dataset in data.
covs	A sample variance–covariance matrix, or a list/array of such matrices for multiple groups. Make sure covtype argument is set correctly to the type of covariances used.
means	A vector of sample means, or a list/matrix containing such vectors for multiple groups.

nobs	The number of observations used in covs and means, or a vector of such numbers of observations for multiple groups.
covtype	If 'covs' is used, this is the type of covariance (maximum likelihood or unbiased) the input covariance matrix represents. Set to "ML" for maximum likelihood estimates (denominator n) and "UB" to unbiased estimates (denominator n-1). The default will try to find the type used, by investigating which is most likely to result from integer valued datasets.
responses	A vector of dichotomous responses used (e.g., c(-1, 1) or c(0, 1). Only needed when 'covs' is used.)
missing	How should missingness be handled in computing the sample covariances and number of observations when data is used. Can be "listwise" for listwise deletion, or "pairwise" for pairwise deletion. NOT RECOMMENDED TO BE USED YET IN ISING MODEL.
equal	A character vector indicating which matrices should be constrained equal across groups.
baseline_saturated	A logical indicating if the baseline and saturated model should be included. Mostly used internally and NOT Recommended to be used manually.
estimator	The estimator to be used. Currently implemented are "ML" for maximum likelihood estimation, "FIML" for full-information maximum likelihood estimation, "ULS" for unweighted least squares estimation, "WLS" for weighted least squares estimation, and "DWLS" for diagonally weighted least squares estimation. Only ML estimation is currently supported for the Ising model.
optimizer	The optimizer to be used. Can be one of "nlmminb" (the default R nlmminb function), "ucminf" (from the optimr package), and C++ based optimizers "cpp_L-BFGS-B", "cpp_BFGS", "cpp_CG", "cpp_SANN", and "cpp_Nelder-Mead". The C++ optimizers are faster but slightly less stable. Defaults to "nlmminb".
storedata	Logical, should the raw data be stored? Needed for bootstrapping (see bootstrap).
WLS.W	Optional WLS weights matrix. CURRENTLY NOT USED.
sampleStats	An optional sample statistics object. Mostly used internally.
identify	Logical, should the model be identified?
verbose	Logical, should messages be printed?
maxNodes	The maximum number of nodes allowed in the analysis. This function will stop with an error if more nodes are used (it is not recommended to set this higher).

Details

The Ising Model takes the following form:

$$\Pr(\mathbf{Y} = \mathbf{y}) = \frac{\exp(-\beta H(\mathbf{y}; \boldsymbol{\tau}, \boldsymbol{\Omega}))}{Z(\boldsymbol{\tau}, \boldsymbol{\Omega})}$$

With Hamiltonian:

$$H(\mathbf{y}; \boldsymbol{\tau}, \boldsymbol{\Omega}) = -\sum_{i=1}^m \tau_i y_i - \sum_{i=2}^m \sum_{j=1}^{i-1} \omega_{ij} y_i y_j.$$

And Z representing the partition function or normalizing constant.

Value

An object of the class psychonetrics

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

References

Epskamp, S., Maris, G., Waldorp, L. J., & Borsboom, D. (2018). Network Psychometrics. In: Irwing, P., Hughes, D., & Booth, T. (Eds.), *The Wiley Handbook of Psychometric Testing, 2 Volume Set: A Multidisciplinary Reference on Survey, Scale and Test Development*. New York: Wiley.

Examples

```
library("dplyr")
data("Jonas")

# Variables to use:
vars <- names(Jonas)[1:10]

# Arranged groups to put unfamiliar group first (beta constrained to 1):
Jonas <- Jonas[order(Jonas$group),]

# Form saturated model:
model1 <- Ising(Jonas, vars = vars, groups = "group")

# Run model:
model1 <- model1 %>% runmodel

# Prune-stepup to find a sparse model:
model1b <- model1 %>% prune(alpha = 0.05) %>% stepup(alpha = 0.05)

# Equal networks:
suppressWarnings(
  model2 <- model1 %>% groupequal("omega") %>% runmodel
)

# Prune-stepup to find a sparse model:
model2b <- model2 %>% prune(alpha = 0.05) %>% stepup(mi = "mi_equal", alpha = 0.05)

# Equal thresholds:
model3 <- model2 %>% groupequal("tau") %>% runmodel

# Prune-stepup to find a sparse model:
model3b <- model3 %>% prune(alpha = 0.05) %>% stepup(mi = "mi_equal", alpha = 0.05)

# Equal beta:
model4 <- model3 %>% groupequal("beta") %>% runmodel

# Prune-stepup to find a sparse model:
```

```

model4b <- model4 %>% prune(alpha = 0.05) %>% stepup(mi = "mi_equal", alpha = 0.05)

# Compare all models:
compare(
  `1. all parameters free (dense)` = model1,
  `2. all parameters free (sparse)` = model1b,
  `3. equal networks (dense)` = model2,
  `4. equal networks (sparse)` = model2b,
  `5. equal networks and thresholds (dense)` = model3,
  `6. equal networks and thresholds (sparse)` = model3b,
  `7. all parameters equal (dense)` = model4,
  `8. all parameters equal (sparse)` = model4b
) %>% arrange(BIC)

```

Jonas

*Jonas dataset***Description**

Responses of 10 attitude items towards a researcher named Jonas. Participants were shown three photos of Jonas with the text: "This is Jonas, a researcher from Germany who is now becoming a PhD in Psychology". Subsequently, the participants had to answer 10 yes / no questions starting with "I believe that Jonas...", as well as rate their familiarity with Jonas. The sample consists of people familiar with Jonas and not familiar with Jonas, and allows for testing Attitudinal Entropy Framework <doi:10.1080/1047840X.2018.1537246>.

Usage

```
data("Jonas")
```

Format

A data frame with 215 observations on the following 12 variables.

scientist ... is a good scientist

jeans ... Is a person that wears beautiful jeans

cares ... really cares about people like you

economics ... would solve our economic problems

hardworking ... is hardworking

honest ... is honest

intouch ... is in touch with ordinary people

knowledgeable ... is knowledgeable

makeupmind ... can't make up his mind

getsthingsdone ... gets things done

familiar Answers to the question "How familiar are you with Jonas?" (three responses possible)

group The question 'familiar' categorized in two groups ("Knows Jonas" and "Doesn't Know Jonas")

Examples

```
data(Jonas)
```

latentgrowth	<i>Latnet growth curve model</i>
--------------	----------------------------------

Description

Wrapper to `lvm` to specify a latent growth curve model.

Usage

```
latentgrowth(vars, time = seq_len(ncol(vars)) - 1, covariates =
  character(), covariates_as = c("regression",
  "covariance"), ...)
```

Arguments

<code>vars</code>	Different from in other psychometrics models, this must be a <i>matrix</i> with each row indicating a variable and each column indicating a measurement. The matrix must be filled with names of the variables in the dataset corresponding to variable <i>i</i> at wave <i>j</i> . NAs can be used to indicate missing waves. The rownames of this matrix will be used as variable names.
<code>time</code>	A vector with the encoding of each measurement (e.g., 0, 1, 2, 3).
<code>covariates</code>	A vector with strings indicating names of between-person covariate variables in the data
<code>covariates_as</code>	Should covariates be included as regressions or actual covariates?
<code>...</code>	Arguments sent to <code>lvm</code>

Details

See https://github.com/SachaEpskamp/SEM-code-examples/tree/master/Latent_growth_examples/psychometrics for examples

Value

An object of the class `psychometrics` ([psychometrics-class](#)). See for an example https://github.com/SachaEpskamp/SEM-code-examples/tree/master/Latent_growth_examples/psychometrics.

Author(s)

Sacha Epskamp

Examples

```

library("dplyr")

# Smoke data cov matrix, based on LISS data panel https://www.dataarchive.lisssdata.nl
smoke <- structure(c(47.2361758611759, 43.5366809116809, 41.0057465682466,
                    43.5366809116809, 57.9789886039886, 47.6992521367521,
                    41.0057465682466,
                    47.6992521367521, 53.0669434731935), .Dim = c(3L, 3L),
                  .Dimnames = list(
                    c("smoke2008", "smoke2009", "smoke2010"), c("smoke2008",
                    "smoke2009", "smoke2010")))

# Design matrix:
design <- matrix(rownames(smoke),1,3)

# Form model:
mod <- latentgrowth(vars = design,
                   covs = smoke, nobs = 352
)

## Not run:
# Run model:
mod <- mod %>% runmodel

# Evaluate fit:
mod %>% fit

# Look at parameters:
mod %>% parameters

## End(Not run)

```

lvm

Continuous latent variable family of psychometrics models

Description

This is the family of models that models the data as a structural equation model (SEM), allowing the latent and residual variance-covariance matrices to be further modeled as networks. The latent and residual arguments can be used to define what latent and residual models are used respectively: "cov" (default) models a variance-covariance matrix directly, "chol" models a Cholesky decomposition, "prec" models a precision matrix, and "ggm" models a Gaussian graphical model (Epskamp, Rhemtulla and Borsboom, 2017). The wrapper `lnm()` sets latent = "ggm" for the latent network model (LNM), the wrapper `rnm()` sets residual = "ggm" for the residual network model (RNM), and the wrapper `lrnm()` combines the LNM and RNM.

Usage

```
lvm(data, lambda, latent = c("cov", "chol", "prec",
```

```

"ggm"), residual = c("cov", "chol", "prec", "ggm"),
sigma_zeta = "full", kappa_zeta = "full", omega_zeta =
"full", lowertri_zeta = "full", delta_zeta = "full",
sigma_epsilon = "empty", kappa_epsilon = "empty",
omega_epsilon = "empty", lowertri_epsilon = "empty",
delta_epsilon = "empty", beta = "empty", nu, nu_eta,
identify = TRUE, identification = c("loadings",
"variance"), vars, latents, groups, covs, means, nobs,
missing = "listwise", equal = "none",
baseline_saturated = TRUE, estimator = "ML",
optimizer, storedata = FALSE, WLS.W, covtype =
c("choose", "ML", "UB"), standardize = c("none", "z",
"quantile"), sampleStats, verbose = FALSE,
simplelambdastart = FALSE)

```

```

lnm(...)
rnm(...)
lrnm(...)

```

Arguments

data	A data frame encoding the data used in the analysis. Can be missing if covs and nobs are supplied.
lambda	A model matrix encoding the factor loading structure. Each row indicates an indicator and each column a latent. A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
latent	The type of latent model used. See description.
residual	The type of residual model used. See description.
sigma_zeta	Only used when latent = "cov". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
kappa_zeta	Only used when latent = "prec". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
omega_zeta	Only used when latent = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

lowertri_zeta	Only used when latent = "chol". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
delta_zeta	Only used when latent = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
sigma_epsilon	Only used when residual = "cov". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
kappa_epsilon	Only used when residual = "prec". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
omega_epsilon	Only used when residual = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
lowertri_epsilon	Only used when residual = "chol". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
delta_epsilon	Only used when residual = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
beta	A model matrix encoding the structural relations between latent variables. A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

nu	Optional vector encoding the intercepts of the observed variables. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
nu_eta	Optional vector encoding the intercepts of the latent variables. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
identify	Logical, should the model be automatically identified?
identification	Type of identification used. "loadings" to fix the first factor loadings to 1, and "variance" to fix the diagonal of the latent variable model matrix (sigma_zeta, lowertri_zeta, delta_zeta or kappa_zeta) to 1.
vars	An optional character vector encoding the variables used in the analysis. Must equal names of the dataset in data.
latents	An optional character vector with names of the latent variables.
groups	An optional string indicating the name of the group variable in data.
covs	A sample variance–covariance matrix, or a list/array of such matrices for multiple groups. Make sure covtype argument is set correctly to the type of covariances used.
means	A vector of sample means, or a list/matrix containing such vectors for multiple groups.
nobs	The number of observations used in covs and means, or a vector of such numbers of observations for multiple groups.
missing	How should missingness be handled in computing the sample covariances and number of observations when data is used. Can be "listwise" for listwise deletion, or "pairwise" for pairwise deletion.
equal	A character vector indicating which matrices should be constrained equal across groups.
baseline_saturated	A logical indicating if the baseline and saturated model should be included. Mostly used internally and NOT Recommended to be used manually.
estimator	The estimator to be used. Currently implemented are "ML" for maximum likelihood estimation, "FIML" for full-information maximum likelihood estimation, "ULS" for unweighted least squares estimation, "WLS" for weighted least squares estimation, and "DWLS" for diagonally weighted least squares estimation.
optimizer	The optimizer to be used. Can be one of "nlminb" (the default R nlminb function), "ucminf" (from the optimr package), and C++ based optimizers "cpp_L-BFGS-B", "cpp_BFGS", "cpp_CG", "cpp_SANN", and "cpp_Nelder-Mead". The C++ optimizers are faster but slightly less stable. Defaults to "nlminb".
storedata	Logical, should the raw data be stored? Needed for bootstrapping (see bootstrap).
verbose	Logical, should progress be printed to the console?
WLS.W	The weights matrix used in WLS estimation (experimental)
sampleStats	An optional sample statistics object. Mostly used internally.

covtype	If 'covs' is used, this is the type of covariance (maximum likelihood or unbiased) the input covariance matrix represents. Set to "ML" for maximum likelihood estimates (denominator n) and "UB" to unbiased estimates (denominator n-1). The default will try to find the type used, by investigating which is most likely to result from integer valued datasets.
standardize	Which standardization method should be used? "none" (default) for no standardization, "z" for z-scores, and "quantile" for a non-parametric transformation to the quantiles of the marginal standard normal distribution.
simplelambdastart	Logical, should simple start values be used for lambda? Setting this to TRUE can avoid some estimation problems.
...	Arguments sent to varcov

Details

The model used in this family is:

$$\text{var}(\mathbf{y}) = \mathbf{\Lambda}(\mathbf{I} - \mathbf{B})^{-1}\mathbf{\Sigma}_{\zeta}(\mathbf{I} - \mathbf{B})^{-1\top}\mathbf{\Lambda}^{\top} + \mathbf{\Sigma}_{\varepsilon}$$

$$\mathcal{E}(\mathbf{y}) = \boldsymbol{\nu} + \mathbf{\Lambda}(\mathbf{I} - \mathbf{B})^{-1}\boldsymbol{\nu}_{\varepsilon}$$

in which the latent covariance matrix can further be modeled in three ways. With latent = "chol" as Cholesky decomposition:

$$\mathbf{\Sigma}_{\zeta} = \mathbf{L}_{\zeta}\mathbf{L}_{\zeta}^{\top},$$

with latent = "prec" as Precision matrix:

$$\mathbf{\Sigma}_{\zeta} = \mathbf{K}_{\zeta}^{-1},$$

and finally with latent = "ggm" as Gaussian graphical model:

$$\mathbf{\Sigma}_{\zeta} = \mathbf{\Delta}_{\zeta}(\mathbf{I} - \mathbf{\Omega}_{\zeta})^{-1}\mathbf{\Delta}_{\zeta}.$$

Likewise, the residual covariance matrix can also further be modeled in three ways. With residual = "chol" as Cholesky decomposition:

$$\mathbf{\Sigma}_{\varepsilon} = \mathbf{L}_{\varepsilon}\mathbf{L}_{\varepsilon}^{\top},$$

with latent = "prec" as Precision matrix:

$$\mathbf{\Sigma}_{\varepsilon} = \mathbf{K}_{\varepsilon}^{-1},$$

and finally with latent = "ggm" as Gaussian graphical model:

$$\mathbf{\Sigma}_{\varepsilon} = \mathbf{\Delta}_{\varepsilon}(\mathbf{I} - \mathbf{\Omega}_{\varepsilon})^{-1}\mathbf{\Delta}_{\varepsilon}.$$

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

References

Epskamp, S., Rhemtulla, M., & Borsboom, D. (2017). Generalized network psychometrics: Combining network and latent variable models. *Psychometrika*, 82(4), 904-927.

Examples

```
library("dplyr")

### Confirmatory Factor Analysis ###

# Example also shown in https://youtu.be/Hdu5z-fwuk8

# Load data:
data(StarWars)

# Originals only:
Lambda <- matrix(1,4)

# Model:
mod0 <- lvm(StarWars, lambda = Lambda, vars = c("Q1","Q5","Q6","Q7"),
            identification = "variance", latents = "Originals")

# Run model:
mod0 <- mod0 %>% runmodel

# Evaluate fit:
mod0 %>% fit

# Full analysis
# Factor loadings matrix:
Lambda <- matrix(0, 10, 3)
Lambda[1:4,1] <- 1
Lambda[c(1,5:7),2] <- 1
Lambda[c(1,8:10),3] <- 1

# Observed variables:
obsvars <- paste0("Q",1:10)

# Latents:
latents <- c("Prequels","Original","Sequels")

# Make model:
mod1 <- lvm(StarWars, lambda = Lambda, vars = obsvars,
            identification = "variance", latents = latents)

# Run model:
mod1 <- mod1 %>% runmodel

# Look at fit:
mod1

# Look at parameter estimates:
mod1 %>% parameters

# Look at modification indices:
mod1 %>% MIs
```

```

# Add and refit:
mod2 <- mod1 %>% freepar("sigma_epsilon","Q10","Q4") %>% runmodel

# Compare:
compare(original = mod1, adjusted = mod2)

# Fit measures:
mod2 %>% fit

### Path diagrams ###
# semPlot is not (yet) supported by default, but can be used as follows:
# Load packages:
library("semPlot")

# Estimates:
lambdaEst <- getmatrix(mod2, "lambda")
psiEst <- getmatrix(mod2, "sigma_zeta")
thetaEst <- getmatrix(mod2, "sigma_epsilon")

# LISREL Model: LY = Lambda (lambda-y), TE = Theta (theta-epsilon), PS = Psi
mod <- lisrelModel(LY = lambdaEst, PS = psiEst, TE = thetaEst)

# Plot with semPlot:
semPaths(mod, "std", "est", as.expression = "nodes")

# We can make this nicer (set whatLabels = "none" to hide labels):
semPaths(mod,

# this argument controls what the color of edges represent. In this case,
# standardized parameters:
  what = "std",

# This argument controls what the edge labels represent. In this case, parameter
# estimates:
  whatLabels = "est",

# This argument draws the node and edge labels as mathematical expressions:
  as.expression = "nodes",

# This will plot residuals as arrows, closer to what we use in class:
  style = "lisrel",

# This makes the residuals larger:
  residScale = 10,

# qgraph colorblind friendly theme:
  theme = "colorblind",

# tree layout options are "tree", "tree2", and "tree3":
  layout = "tree2",

```

```
# This makes the latent covariances connect at a cardinal center point:
  cardinal = "lat cov",

# Changes curve into rounded straight lines:
  curvePivot = TRUE,

# Size of manifest variables:
  sizeMan = 4,

# Size of latent variables:
  sizeLat = 10,

# Size of edge labels:
  edge.label.cex = 1,

# Sets the margins:
  mar = c(9,1,8,1),

# Prevents re-ordering of observed variables:
  reorder = FALSE,

# Width of the plot:
  width = 8,

# Height of plot:
  height = 5,

# Colors according to latents:
  groups = "latents",

# Pastel colors:
  pastel = TRUE,

# Disable borders:
  borders = FALSE
)

# Use arguments filetype = "pdf" and filename = "semPlotExample1" to store PDF

### Latent Network Modeling ###

# Latent network model:
lnm <- lvm(StarWars, lambda = Lambda, vars = obsvars,
          latents = latents, identification = "variance",
          latent = "ggm")

# Run model:
lnm <- lnm %>% runmodel

# Look at parameters:
lnm %>% parameters

# Remove non-sig latent edge:
```

```

lnm <- lnm %>% prune(alpha = 0.05)

# Compare to the original CFA model:
compare(cfa = mod1, lnm = lnm)

# Plot network:
library("qgraph")
qgraph(lnm@modelmatrices[[1]]$omega_zeta, labels = latents,
       theme = "colorblind", vsize = 10)

# A wrapper for the latent network model is the lnm function:
lnm2 <- lnm(StarWars, lambda = Lambda, vars = obsvars,
           latents = latents, identification = "variance")
lnm2 <- lnm2 %>% runmodel %>% prune(alpha = 0.05)
compare(lnm, lnm2) # Is the same as the model before.

# I could also estimate a "residual network model", which adds partial correlations to
# the residual level:
# This can be done using lvm(..., residual = "ggm") or with rnm(...)
rnm <- rnm(StarWars, lambda = Lambda, vars = obsvars,
          latents = latents, identification = "variance")
# Stepup search:
rnm <- rnm %>% stepup

# It will estimate the same model (with link Q10 - Q4) as above. In the case of only one
# partial correlation, There is no difference between residual covariances (SEM) or
# residual partial correlations (RNM).

# For more information on latent and residual network models, see:
# Epskamp, S., Rhemtulla, M.T., & Borsboom, D. Generalized Network Psychometrics:
# Combining Network and Latent Variable Models
# (2017). Psychometrika. doi:10.1007/s11336-017-9557-x

### Gaussian graphical models ###

# All psychometrics functions (e.g., lvm, lnm, rnm...) allow input via a covariance
# matrix, with the "covs" and "nobs" arguments.
# The following fits a baseline GGM network with no edges:
S <- (nrow(StarWars) - 1) / (nrow(StarWars)) * cov(StarWars[,1:10])
ggmmod <- ggm(covs = S, nobs = nrow(StarWars))

# Run model with stepup search and pruning:
ggmmod <- ggmmod %>% prune %>% modelsearch

# Fit measures:
ggmmod %>% fit

# Plot network:
nodeNames <- c(
  "I am a huge Star Wars fan! (star what?)",
  "I would trust this person with my democracy.",
  "I enjoyed the story of Anakin's early life.",

```

```

"The special effects in\nthis scene are awful (Battle of\nGeonosis).",
"I would trust this person\nwith my life.",
"I found Darth Vader's big\nreveal in 'Empire' one of the greatest
moments in movie history.",
"The special effects in\nthis scene are amazing (Death Star\nExplosion).",
"If possible, I would\ndefinitely buy this\nndroid.",
"The story in the Star\nWars sequels is an improvement to\nthe previous movies.",
"The special effects in\nthis scene are marvellous (Starkiller\nBase Firing)."
)
library("qgraph")
qgraph(as.matrix(ggmod@modelmatrices[[1]]$omega), nodeNames = nodeNames,
       legend.cex = 0.25, theme = "colorblind", layout = "spring")

# We can actually compare this model statistically (note they are not nested) to the
# latent variable model:
compare(original_cfa = mod1, adjusted_cfa = mod2, exploratory_ggm = ggmod)

### Measrement invariance ###
# Let's say we are interested in seeing if people >= 30 like the original trilogy better
# than people < 30.
# First we can make a grouping variable:
StarWars$agegroup <- ifelse(StarWars$Q12 < 30, "young", "less young")

# Let's look at the distribution:
table(StarWars$agegroup) # Pretty even...

# Observed variables:
obsvars <- paste0("Q",1:10)

# Let's look at the mean scores:
StarWars %>% group_by(agegroup) %>% summarize_each_(funs(mean),vars = obsvars)
# Less young people seem to score higher on prequel questions and lower on other
# questions

# Factor loadings matrix:
Lambda <- matrix(0, 10, 3)
Lambda[1:4,1] <- 1
Lambda[c(1,5:7),2] <- 1
Lambda[c(1,8:10),3] <- 1

# Residual covariances:
Theta <- diag(1, 10)
Theta[4,10] <- Theta[10,4] <- 1

# Latents:
latents <- c("Prequels","Original","Sequels")

# Make model:
mod_configural <- lvm(StarWars, lambda = Lambda, vars = obsvars,
                    latents = latents, sigma_epsilon = Theta,
                    identification = "variance",
                    groups = "agegroup")

```

```

# Run model:
mod_configural <- mod_configural %>% runmodel

# Look at fit:
mod_configural
mod_configural %>% fit

# Looks good, let's try weak invariance:
mod_weak <- mod_configural %>% groupequal("lambda") %>% runmodel

# Compare models:
compare(configural = mod_configural, weak = mod_weak)

# weak invariance can be accepted, let's try strong:
mod_strong <- mod_weak %>% groupequal("nu") %>% runmodel
# Means are automatically identified

# Compare models:
compare(configural = mod_configural, weak = mod_weak, strong = mod_strong)

# Questionable p-value and AIC difference, but ok BIC difference. This is quite good, but
# let's take a look. I have not yet implemented LM tests for equality constrains, but we
# can look at something called "equality-free" MIs:
mod_strong %>% MIs(matrices = "nu", type = "free")

# Indicates that Q10 would improve fit. We can also look at residuals:
residuals(mod_strong)

# Let's try freeing intercept 10:
mod_strong_partial <- mod_strong %>% groupfree("nu",10) %>% runmodel

# Compare all models:
compare(configural = mod_configural,
        weak = mod_weak,
        strong = mod_strong,
        strong_partial = mod_strong_partial)

# This seems worth it and lead to an acceptable model! It seems that older people find
# the latest special effects more marvellous!
mod_strong_partial %>% getmatrix("nu")

# Now let's investigate strict invariance:
mod_strict <- mod_strong_partial %>% groupequal("sigma_epsilon") %>% runmodel

# Compare all models:
compare(configural = mod_configural,
        weak = mod_weak,
        strong_partial = mod_strong_partial,
        strict = mod_strict)
# Strict invariance can be accepted!

# Now we can test for homogeneity!

```

```

# Are the latent variances equal?
mod_eqvar <- mod_strict %>% groupequal("sigma_zeta") %>% runmodel

# Compare:
compare(strict = mod_strict, eqvar = mod_eqvar)

# This is acceptable. What about the means? (alpha = nu_eta)
mod_eqmeans <- mod_eqvar %>% groupequal("nu_eta") %>% runmodel

# Compare:
compare(eqvar = mod_eqvar, eqmeans = mod_eqmeans)

# Rejected! We could look at MIs again:
mod_eqmeans %>% MIs(matrices = "nu_eta", type = "free")

# Indicates the strongest effect for prequels. Let's see what happens:
eqmeans2 <- mod_eqvar %>%
  groupequal("nu_eta", row = c("Original", "Sequels")) %>% runmodel

# Compare:
compare(eqvar = mod_eqvar, eqmeans = eqmeans2)
# Questionable, what about the sequels as well?

eqmeans3 <- mod_eqvar %>% groupequal("nu_eta", row = "Original") %>% runmodel

# Compare:
compare(eqvar = mod_eqvar, eqmeans = eqmeans3)

# Still questionable.. Let's look at the mean differences:
mod_eqvar %>% getmatrix("nu_eta")

# Looks like people over 30 like the prequels better and the other two trilogies less!

```

meta_varcov

Variance-covariance and GGM meta analysis

Description

Meta analysis of correlation matrices to fit a homogenous correlation matrix or Gaussian graphical model. Based on meta-analytic SEM (Jak & Cheung, 2019).

Usage

```

meta_varcov(cors, nobs, Vmats, Vmethod = c("individual", "pooled",
      "metaSEM_individual", "metaSEM_weighted"), Vestimation
      = c("averaged", "per_study"), type = c("cor", "ggm"),
      sigma_y = "full", kappa_y = "full", omega_y = "full",
      lowertri_y = "full", delta_y = "full", rho_y = "full",
      SD_y = "full", randomEffects = c("chol", "cov",

```

```
"prec", "ggm", "cor"), sigma_randomEffects = "full",
kappa_randomEffects = "full", omega_randomEffects =
"full", lowertri_randomEffects = "full",
delta_randomEffects = "full", rho_randomEffects =
"full", SD_randomEffects = "full", vars,
baseline_saturated = TRUE, optimizer, estimator =
c("FIML", "ML"), sampleStats, verbose = FALSE)
```

```
meta_ggm(...)
```

Arguments

<code>cors</code>	A list of correlation matrices. Must contain rows and columns with NAs for variables not included in a study.
<code>nobs</code>	A vector with the number of observations per study.
<code>Vmats</code>	Optional list with 'V' matrices (sampling error variance approximations).
<code>Vmethod</code>	Which method should be used to apprximate the sampling error variance?
<code>Vestimation</code>	How should the sampling error estimates be evaluated?
<code>type</code>	What to model? Currently only "cor" and "ggm" are supported.
<code>sigma_y</code>	Only used when <code>type = "cov"</code> . Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>kappa_y</code>	Only used when <code>type = "prec"</code> . Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>omega_y</code>	Only used when <code>type = "ggm"</code> . Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>lowertri_y</code>	Only used when <code>type = "chol"</code> . Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>delta_y</code>	Only used when <code>type = "ggm"</code> . Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

- `rho_y` Only used when `type = "cor"`. Either `"full"` to estimate every element freely, `"empty"` to set all elements to zero, or a matrix of the dimensions `node x node` with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
- `SD_y` Only used when `type = "cor"`. Either `"full"` to estimate every element freely, `"empty"` to set all elements to zero, or a matrix of the dimensions `node x node` with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
- `randomEffects` What to model for the random effects?
- `sigma_randomEffects` Only used when `type = "cov"`. Either `"full"` to estimate every element freely, `"empty"` to only include diagonal elements, or a matrix of the dimensions `node x node` with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
- `kappa_randomEffects` Only used when `randomEffects = "prec"`. Either `"full"` to estimate every element freely, `"empty"` to only include diagonal elements, or a matrix of the dimensions `node x node` with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
- `omega_randomEffects` Only used when `randomEffects = "ggm"`. Either `"full"` to estimate every element freely, `"empty"` to set all elements to zero, or a matrix of the dimensions `node x node` with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
- `lowertri_randomEffects` Only used when `randomEffects = "chol"`. Either `"full"` to estimate every element freely, `"empty"` to only include diagonal elements, or a matrix of the dimensions `node x node` with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
- `delta_randomEffects` Only used when `randomEffects = "ggm"`. Either `"full"` to estimate every element freely, `"empty"` to set all elements to zero, or a matrix of the dimensions `node x node` with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

<code>rho_randomEffects</code>	Only used when <code>randomEffects = "cor"</code> . Either <code>"full"</code> to estimate every element freely, <code>"empty"</code> to set all elements to zero, or a matrix of the dimensions <code>node x node</code> with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>SD_randomEffects</code>	Only used when <code>randomEffects = "cor"</code> . Either <code>"full"</code> to estimate every element freely, <code>"empty"</code> to set all elements to zero, or a matrix of the dimensions <code>node x node</code> with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>vars</code>	Variables to be included.
<code>baseline_saturated</code>	A logical indicating if the baseline and saturated model should be included. Mostly used internally and NOT Recommended to be used manually.
<code>optimizer</code>	The optimizer to be used. Can be one of <code>"nlminb"</code> (the default R <code>nlminb</code> function), <code>"ucminf"</code> (from the <code>optimr</code> package), and C++ based optimizers <code>"cpp_L-BFGS-B"</code> , <code>"cpp_BFGS"</code> , <code>"cpp_CG"</code> , <code>"cpp_SANN"</code> , and <code>"cpp_Nelder-Mead"</code> . The C++ optimizers are faster but slightly less stable. Defaults to <code>"nlminb"</code> .
<code>estimator</code>	The estimator to be used. Currently implemented are <code>"ML"</code> for maximum likelihood estimation or <code>"FIML"</code> for full-information maximum likelihood estimation.
<code>sampleStats</code>	An optional sample statistics object. Mostly used internally.
<code>verbose</code>	Logical, should progress be printed to the console?
<code>...</code>	Arguments sent to <code>meta_varcov</code>

Value

An object of the class `psychometrics` ([psychometrics-class](#))

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

References

Jak, S., & Cheung, M. W. L. (2019). Meta-analytic structural equation modeling with moderating effects on SEM parameters. *Psychological methods*.

MIs *Print modification indices*

Description

This function prints a list of modification indices (MIs)

Usage

```
MIs(x, all = FALSE, matrices, type = c("normal", "equal", "free"), top = 10,  
    verbose = TRUE, nonZero = FALSE)
```

Arguments

x	A psychometrics model.
all	Logical, should all MIs be printed or only the highest?
matrices	Optional vector of matrices to include in the output.
type	String indicating which kind of modification index should be printed. ("mi" is the typical MI, "mi_free" is the modification index free from equality constraints across groups, and "mi_equal" is the modification index if the parameter is added constrained equal across all groups).
top	Number of MIs to include in output if all = FALSE
verbose	Logical, should messages be printed?
nonZero	Logical, should only MIs be printed of non-zero parameters? Useful to explore violations of group equality.

Value

Invisibly returns a relevant subset of the data frame containing all information on the parameters, or a list of such data frames if multiple types of MIs are requested.

Author(s)

Sacha Epskamp

Examples

```
# Load bfi data from psych package:  
library("psychTools")  
data(bfi)  
  
# Also load dplyr for the pipe operator:  
library("dplyr")  
  
# Let's take the agreeableness items, and gender:  
ConsData <- bfi %>%
```

```

select(A1:A5, gender) %>%
na.omit # Let's remove missingness (otherwise use Estimator = "FIML)

# Define variables:
vars <- names(ConsData)[1:5]

# Let's fit a full GGM:
mod <- ggm(ConsData, vars = vars, omega = "empty")

# Run model:
mod <- mod %>% runmodel

# Modification indices:
mod %>% MIs

```

ml_lvm

Multi-level latent variable model family

Description

This family is the two-level random intercept variant of the [lvm](#) model family. It is mostly a special case of the [dlvm1](#) family, with the addition of structural effects rather than temporal effects in the beta matrix.

Usage

```

ml_lnm(...)
ml_rnm(...)
ml_lrnm(...)
ml_lvm(data, lambda, clusters, within_latent = c("cov",
"chol", "prec", "ggm"), within_residual = c("cov",
"chol", "prec", "ggm"), between_latent = c("cov",
"chol", "prec", "ggm"), between_residual = c("cov",
"chol", "prec", "ggm"), beta_within = "empty",
beta_between = "empty", omega_zeta_within = "full",
delta_zeta_within = "full", kappa_zeta_within =
"full", sigma_zeta_within = "full",
lowertri_zeta_within = "full", omega_epsilon_within =
"empty", delta_epsilon_within = "empty",
kappa_epsilon_within = "empty", sigma_epsilon_within =
"empty", lowertri_epsilon_within = "empty",
omega_zeta_between = "full", delta_zeta_between =
"full", kappa_zeta_between = "full",
sigma_zeta_between = "full", lowertri_zeta_between =
"full", omega_epsilon_between = "empty",
delta_epsilon_between = "empty", kappa_epsilon_between
= "empty", sigma_epsilon_between = "empty",
lowertri_epsilon_between = "empty", nu, nu_eta,

```

```

identify = TRUE, identification = c("loadings",
"variance"), vars, latents, groups, equal = "none",
baseline_saturated = TRUE, estimator = c("FIML",
"MUML"), optimizer, storedata = FALSE, verbose =
FALSE, standardize = c("none", "z", "quantile"),
sampleStats)

```

Arguments

<code>data</code>	A data frame encoding the data used in the analysis. Must be a raw dataset.
<code>lambda</code>	A model matrix encoding the factor loading structure. Each row indicates an indicator and each column a latent. A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix. Could also be the result of simplestructure .
<code>clusters</code>	A string indicating the variable in the dataset that describes group membership.
<code>within_latent</code>	The type of within-person latent contemporaneous model to be used.
<code>within_residual</code>	The type of within-person residual model to be used.
<code>between_latent</code>	The type of between-person latent model to be used.
<code>between_residual</code>	The type of between-person residual model to be used.
<code>beta_within</code>	A model matrix encoding the within-cluster structural. A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix. Defaults to "empty".
<code>beta_between</code>	A model matrix encoding the between-cluster structural. A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix. Defaults to "empty".
<code>omega_zeta_within</code>	Only used when <code>within_latent = "ggm"</code> . Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>delta_zeta_within</code>	Only used when <code>within_latent = "ggm"</code> . Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>kappa_zeta_within</code>	Only used when <code>within_latent = "prec"</code> . Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple

groups, this argument can be a list or array with each element/slice encoding such a matrix.

`sigma_zeta_within`

Only used when `within_latent = "cov"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constraints. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`lowertri_zeta_within`

Only used when `within_latent = "chol"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constraints. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`omega_epsilon_within`

Only used when `within_residual = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constraints. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`delta_epsilon_within`

Only used when `within_residual = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constraints. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`kappa_epsilon_within`

Only used when `within_residual = "prec"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constraints. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`sigma_epsilon_within`

Only used when `within_residual = "cov"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constraints. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`lowertri_epsilon_within`

Only used when `within_residual = "chol"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constraints. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`omega_zeta_between`

Only used when `between_latent = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constraints. For multiple

groups, this argument can be a list or array with each element/slice encoding such a matrix.

`delta_zeta_between`

Only used when `between_latent = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`kappa_zeta_between`

Only used when `between_latent = "prec"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`sigma_zeta_between`

Only used when `between_latent = "cov"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`lowertri_zeta_between`

Only used when `between_latent = "chol"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`omega_epsilon_between`

Only used when `between_residual = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`delta_epsilon_between`

Only used when `between_residual = "ggm"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`kappa_epsilon_between`

Only used when `between_residual = "prec"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.

`sigma_epsilon_between`

Only used when `between_residual = "cov"`. Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For

	multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
lowertri_epsilon_between	Only used when <code>between_residual = "chol"</code> . Can be "full", "empty", or a typical model matrix with 0s indicating parameters constrained to zero, 1s indicating free parameters, and higher integers indicating equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
nu	Optional vector encoding the intercepts of the observed variables. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
nu_eta	Optional vector encoding the intercepts of the latent variables. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
identify	Logical, should the model be automatically identified?
identification	Type of identification used. "loadings" to fix the first factor loadings to 1, and "variance" to fix the diagonal of the latent variable model matrix (<code>sigma_zeta</code> , <code>lowertri_zeta</code> , <code>delta_zeta</code> or <code>kappa_zeta</code>) to 1.
vars	An optional character vector with names of the variables used.
latents	An optional character vector with names of the latent variables.
groups	An optional string indicating the name of the group variable in data.
equal	A character vector indicating which matrices should be constrained equal across groups.
baseline_saturated	A logical indicating if the baseline and saturated model should be included. Mostly used internally and NOT Recommended to be used manually.
estimator	Estimator used. Currently only "FIML" is supported.
optimizer	The optimizer to be used. Usually either "nlminb" (with box constrains) or "ucminf" (ignoring box constrains), but any optimizer supported by <code>optimr</code> can be used.
storedata	Logical, should the raw data be stored? Needed for bootstrapping (see bootstrap).
verbose	Logical, should progress be printed to the console?
standardize	Which standardization method should be used? "none" (default) for no standardization, "z" for z-scores, and "quantile" for a non-parametric transformation to the quantiles of the marginal standard normal distribution.
sampleStats	An optional sample statistics object. Mostly used internally.
...	Arguments sent to 'ml_lvm'

Value

An object of the class `psychometrics` ([psychometrics-class](#))

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

ml_tsd1vm1

Multi-level Lag-1 dynamic latent variable model family of psychometrics models for time-series data

Description

This function is a wrapper around [dlvm1](#) that allows for specifying the model using a long format data and similar input as the mlVAR package.

Usage

```
ml_tsd1vm1(data, beepvar, idvar, vars, groups, estimator = "FIML",
            standardize = c("none", "z", "quantile"), ...)
```

```
ml_ts_lvgvar(...)
```

Arguments

data	The data to be used. Must be raw data in long format (each row indicates one person at one time point).
beepvar	Optional string indicating assessment beep per day. Adding this argument will cause non-consecutive beeps to be treated as missing!
idvar	String indicating the subject ID
vars	Vectors of variables to include in the analysis
groups	An optional string indicating the name of the group variable in data.
estimator	Estimator to be used. Must be "FIML".
standardize	Which standardization method should be used? "none" (default) for no standardization, "z" for z-scores, and "quantile" for a non-parametric transformation to the quantiles of the marginal standard normal distribution.
...	Arguments sent to dlvm1

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

modelsearch	<i>Stepwise model search</i>
-------------	------------------------------

Description

This function performs stepwise model search to find an optimal model that (locally) minimizes some criterion (by default, the BIC).

Usage

```
modelsearch(x, criterion = "bic", matrices, prunealpha = 0.01,
            addalpha = 0.01, verbose, ...)
```

Arguments

x	A psychometrics model.
criterion	String indicating the criterion to minimize. Any criterion from fit can be used.
matrices	Vector of strings indicating which matrices should be searched. Will default to network structures and factor loadings.
prunealpha	Minimal alpha used to consider edges to be removed
addalpha	Maximum alpha used to consider edges to be added
verbose	Logical, should messages be printed?
...	Arguments sent to runmodel

Details

The full algorithm is as follows:

1. Evaluate all models in which an edge is removed that has $p > \text{prunealpha}$, or an edge is added that has a modification index with $p < \text{addalpha}$
2. If none of these models improve the criterion, return the previous model and stop the algorithm
3. Update the model to the model that improved the criterion the most
4. Evaluate all other considered models that improved the criterion
5. If none of these models improve the criterion, go to 1, else go to 3

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

See Also

[prune](#), [stepup](#)

Examples

```
# Load bfi data from psych package:
library("psychTools")
data(bfi)

# Also load dplyr for the pipe operator:
library("dplyr")

# Let's take the agreeableness items, and gender:
ConsData <- bfi %>%
  select(A1:A5, gender) %>%
  na.omit # Let's remove missingness (otherwise use Estimator = "FIML")

# Define variables:
vars <- names(ConsData)[1:5]

# Let's fit a full GGM:
mod <- ggm(ConsData, vars = vars)

# Run model:
mod <- mod %>% runmodel

# Model search
mod <- mod %>% prune(alpha= 0.01) %>% modelsearch
```

parameters

Print parameter estimates

Description

This function will print a list of parameters of the model

Usage

```
parameters(x)
```

Arguments

x A psychometrics model.

Value

Invisibly returns a data frame containing information on all parameters.

Author(s)

Sacha Epskamp

Examples

```

# Load bfi data from psych package:
library("psychTools")
data(bfi)

# Also load dplyr for the pipe operator:
library("dplyr")

# Let's take the agreeableness items, and gender:
ConsData <- bfi %>%
  select(A1:A5, gender) %>%
  na.omit # Let's remove missingness (otherwise use Estimator = "FIML")

# Define variables:
vars <- names(ConsData)[1:5]

# Let's fit a full GGM:
mod <- ggm(ConsData, vars = vars, omega = "empty")

# Run model:
mod <- mod %>% runmodel

# Parameter estimates:
mod %>% parameters

```

parequal

Set equality constrains across parameters

Description

This function can be used to set parameters equal

Usage

```

parequal(x, ..., inds = integer(0), verbose, log = TRUE,
         runmodel = FALSE)

```

Arguments

x	A psychometrics model.
...	Arguments sent to runmodel
inds	Parameter indices of parameters to be constrained equal
verbose	Logical, should messages be printed?
log	Logical, should the log be updated?
runmodel	Logical, should the model be updated?

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

partialprune

Partial pruning of multi-group models

Description

This function will search for a multi-group model with equality constrains on some but not all parameters. This is called partial pruning (Epskamp, Isvoranu, & Cheung, 2020; Haslbeck, 2020). The algorithm is as follows: 1. remove all parameters not significant at alpha in all groups (without equality constrains), 2. create a union model with all parameters included in any group included in all groups and constrained equal. 3. Stepwise free equality constrains of the parameter that features the largest sum of modification indices until BIC can no longer be improved. 4. Select and return the best model according to BIC (original model, pruned model, union model and partially pruned model).

Usage

```
partialprune(x, alpha = 0.01, matrices, verbose, combinefun = unionmodel, ...)
```

Arguments

x	A psychometrics model.
alpha	Significance level to use.
matrices	Vector of strings indicating which matrices should be pruned. Will default to network structures.
verbose	Logical, should messages be printed?
combinefun	Function used to combine models of different groups.
...	Arguments sent to prune .

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

References

Epskamp, S., Isvoranu, A. M., & Cheung, M. (2020). Meta-analytic gaussian network aggregation. PsyArXiv preprint. DOI:10.31234/osf.io/236w8.

Haslbeck, J. (2020). Estimating Group Differences in Network Models using Moderation Analysis. PsyArXiv preprint. DOI:10.31234/osf.io/926pv.

prune

*Stepdown model search by pruning non-significant parameters.***Description**

This function will (recursively) remove parameters that are not significant and refit the model.

Usage

```
prune(x, alpha = 0.01, adjust = c("none", "holm",
  "hochberg", "hommel", "bonferroni", "BH", "BY",
  "fdr"), matrices, runmodel = TRUE, recursive = FALSE,
  verbose, log = TRUE, identify = TRUE, startreduce = 1,
  limit = Inf, ...)
```

Arguments

x	A psychonetrics model.
alpha	Significance level to use.
adjust	p-value adjustment method to use. See p.adjust.
matrices	Vector of strings indicating which matrices should be pruned. Will default to network structures.
runmodel	Logical, should the model be evaluated after pruning?
recursive	Logical, should the pruning process be repeated?
verbose	Logical, should messages be printed?
log	Logical, should the log be updated?
identify	Logical, should models be identified automatically?
startreduce	A numeric value indicating a factor with which the starting values should be reduced. Can be useful when encountering numeric problems.
limit	The maximum number of parameters to be pruned.
...	Arguments sent to runmodel

Value

An object of the class psychonetrics ([psychonetrics-class](#))

Author(s)

Sacha Epskamp

See Also

[stepup](#)

Examples

```

# Load bfi data from psych package:
library("psychTools")
data(bfi)

# Also load dplyr for the pipe operator:
library("dplyr")

# Let's take the agreeableness items, and gender:
ConsData <- bfi %>%
  select(A1:A5, gender) %>%
  na.omit # Let's remove missingness (otherwise use Estimator = "FIML)

# Define variables:
vars <- names(ConsData)[1:5]

# Let's fit a full GGM:
mod <- ggm(ConsData, vars = vars, omega = "full")

# Run model:
mod <- mod %>% runmodel

# Prune model:
mod <- mod %>% prune(adjust = "fdr", recursive = FALSE)

```

psychometrics-class *Class "psychometrics"*

Description

Main class for psychometrics results.

Objects from the Class

Objects can be created by calls of the form `new("psychometrics", ...)`.

Slots

```

model: Object of class "character" ~~
submodel: Object of class "character" ~~
parameters: Object of class "data.frame" ~~
matrices: Object of class "data.frame" ~~
meanstructure: Object of class "logical" ~~
computed: Object of class "logical" ~~
sample: Object of class "psychometrics_samplestats" ~~
modelmatrices: Object of class "list" ~~

```

```
log: Object of class "psychonetrics_log" ~~  
optim: Object of class "list" ~~  
fitmeasures: Object of class "list" ~~  
baseline_saturated: Object of class "list" ~~  
equal: Object of class "character" ~~  
objective: Object of class "numeric" ~~  
information: Object of class "matrix" ~~  
identification: Object of class "character" ~~  
optimizer: Object of class "character" ~~  
estimator: Object of class "character" ~~  
distribution: Object of class "character" ~~  
extramatrices: Object of class "list" ~~  
rawts: Object of class "logical" ~~  
Drawts: Object of class "list" ~~  
types: Object of class "list" ~~  
cpp: Object of class "logical" ~~  
verbose: Object of class "logical" ~~
```

Methods

```
resid signature(object = "psychonetrics"): ...  
residuals signature(object = "psychonetrics"): ...  
show signature(object = "psychonetrics"): ...
```

Author(s)

Sacha Epskamp

Examples

```
showClass("psychonetrics")
```

psychometrics_update *Model updating functions*

Description

These functions update a psychometrics model. Typically they are not required.

Usage

```
addMIs(x, matrices = "all", type = c("normal", "free",  
                                     "equal"), verbose, analyticFisher = TRUE)
```

```
addSEs(x, verbose)
```

```
addfit(x, verbose)
```

```
identify(x)
```

Arguments

x	A psychometrics model.
matrices	Optional vector of matrices to include in MIs.
type	String indicating which modification indices should be updated.
verbose	Logical, should messages be printed?
analyticFisher	Logical indicating if an analytic Fisher information matrix should be used.

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

runmodel

Run a psychometrics model

Description

This is the main function used to run a psychometrics model.

Usage

```
runmodel(x, level = c("gradient", "fitfunction"), addfit =
  TRUE, addMIs = TRUE, addSEs = TRUE, addInformation =
  TRUE, log = TRUE, verbose, optim.control = list(),
  analyticFisher = TRUE, return_improper = FALSE)
```

Arguments

x	A psychometrics model.
level	Level at which the model should be estimated. Defaults to "gradient" to indicate the analytic gradient should be used.
addfit	Logical, should fit measures be added?
addMIs	Logical, should modification indices be added?
addSEs	Logical, should standard errors be added?
addInformation	Logical, should the Fisher information be added?
log	Logical, should the log be updated?
verbose	Logical, should messages be printed?
optim.control	A list with options for optimr
analyticFisher	Logical, should the analytic Fisher information be used? If FALSE, numeric information is used instead.
return_improper	Should a result in which improper computation was used be return? Improper computation can mean that a pseudoinverse of small spectral shift was used in computing the inverse of a matrix.

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

Examples

```

# Load bfi data from psych package:
library("psychTools")
data(bfi)

# Also load dplyr for the pipe operator:
library("dplyr")

# Let's take the agreeableness items, and gender:
ConsData <- bfi %>%
  select(A1:A5, gender) %>%
  na.omit # Let's remove missingness (otherwise use Estimator = "FIML)

# Define variables:
vars <- names(ConsData)[1:5]

# Let's fit a full GGM:
mod <- ggm(ConsData, vars = vars, omega = "full")

# Run model:
mod <- mod %>% runmodel

```

setestimator

Convenience functions

Description

These functions can be used to change some estimator options.

Usage

```

setestimator(x, estimator)

setoptimizer(x, optimizer = c("default", "nlminb", "ucminf", "cpp_L-BFGS-B",
  "cpp_BFGS", "cpp_CG", "cpp_SANN", "cpp_Nelder-Mead"))

usecpp(x, use = TRUE)

```

Arguments

x	A psychometrics model.
estimator	A string indicating the estimator to be used
optimizer	The optimizer to be used. Can be one of "nlminb" (the default R nlminb function), "ucminf" (from the optimr package), and C++ based optimizers "cpp_L-BFGS-B", "cpp_BFGS", "cpp_CG", "cpp_SANN", and "cpp_Nelder-Mead". The C++ optimizers are faster but slightly less stable. Defaults to "nlminb".
use	Logical indicating if C++ should be used (currently only used in FIML)

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

setverbose	<i>Should messages of computation progress be printed?</i>
------------	------------------------------------------------------------

Description

This function controls if messages should be printed for a psychometrics model.

Usage

```
setverbose(x, verbose = TRUE)
```

Arguments

x	A psychometrics model.
verbose	Logical indicating if verbose should be enabled

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

simplestructure	<i>Generate factor loadings matrix with simple structure</i>
-----------------	--------------------------------------------------------------

Description

This function generates the input for lambda arguments in latent variable models using a simple structure. The input is a vector with an element for each variable indicating the factor the variable loads on.

Usage

```
simplestructure(x)
```

Arguments

x A vector indicating which factor each indicator loads on.

Author(s)

Sacha Epskamp <mail@sachaepskamp.com>

StarWars

Star Wars dataset

Description

This questionnaire was constructed by Carolin Katzera, Charlotte Tanis, Esther Niehoff, Myrthe Veenman, and Jason Nak as part of an assignment for a course on confirmatory factor analysis (<http://sachaepskamp.com/SEM2018>). They also collected the data among fellow psychology students as well as through social media.

Usage

```
data("StarWars")
```

Format

A data frame with 271 observations on the following 13 variables.

- Q1 I am a huge Star Wars fan! (star what?)
- Q2 I would trust this person with my democracy <picture of Jar Jar Binks>
- Q3 I enjoyed the story of Anakin's early life
- Q4 The special effects in this scene are awful <video of the Battle of Geonosis>
- Q5 I would trust this person with my life <picture of Han Solo>
- Q6 I found Darth Vader's big reveal in "Empire" one of the greatest moments in movie history
- Q7 The special effects in this scene are amazing <video of the Death Star explosion>
- Q8 If possible, I would definitely buy this droid <picture of BB-8>
- Q9 The story in the Star Wars sequels is an improvement to the previous movies
- Q10 The special effects in this scene are marvellous <video of the Starkiller Base firing>
- Q11 What is your gender?
- Q12 How old are you?
- Q13 Have you seen any of the Star Wars movies?

Details

The questionnaire is online at https://github.com/SachaEpskamp/SEM-code-examples/blob/master/CFA_fit_examples/StarWars. The authors of the questionnaire defined a measurement model before collecting data: Q2 - Q4 are expected to load on a "prequel" factor, Q5 - Q7 are expected to load in a "originals" factor, and Q8 - Q10 are expected to load on a "sequel" factor. Finally, Q1 is expected to load on all three.

Source

https://github.com/SachaEpskamp/SEM-code-examples/blob/master/CFA_fit_examples

Examples

```
data(StarWars)
```

stepup

Stepup model search along modification indices

Description

This function automatically performs step-up search by adding the parameter with the largest modification index until some criterion is reached or no modification indices are significant at alpha.

Usage

```
stepup(x, alpha = 0.01, criterion = "bic", matrices, mi =
  c("mi", "mi_free", "mi_equal"), greedyadjust =
  c("bonferroni", "none", "holm", "hochberg", "hommel",
  "fdr", "BH", "BY"), stopif, greedy = FALSE, verbose,
  checkinformation = TRUE, singularinformation =
  c("tryfix", "skip", "continue", "stop"), startEPC =
  TRUE, ...)
```

Arguments

x	A psychometrics model.
alpha	Significance level to use.
criterion	String indicating the criterion to minimize. Any criterion from <code>fit</code> can be used.
matrices	Vector of strings indicating which matrices should be searched. Will default to network structures and factor loadings.
mi	String indicating which kind of modification index should be used ("mi" is the typical MI, "mi_free" is the modification index free from equality constraints across groups, and "mi_equal" is the modification index if the parameter is added constrained equal across all groups).
greedyadjust	String indicating which p-value adjustment should be used in greedy start. Any method from <code>p.adjust</code> can be used.
stopif	An R expression, using objects from <code>fit</code> , which will break stepup search if it evaluates to TRUE. For example, <code>stopif = rmsea < 0.05</code> will lead to search to stop if rmsea is below 0.05.
greedy	Logical, should a greedy start be used? If TRUE, the first step adds any parameter that is significant (after adjustment)
verbose	Logical, should messages be printed?

`checkinformation` Logical, should the Fisher information be checked for potentially non-identified models?
`singularinformation` String indicating how to proceed if the information matrix is singular. "tryfix" will adjust starting values to try to fix the problem, "skip" will lead to the algorithm to skip the current parameter, "continue" will ignore the situation, and "stop" will break the algorithm and return a list with the last two models.
`startEPC` Logical, should the starting value be set at the expected parameter change?
`...` Arguments sent to [runmodel](#)

Value

An object of the class `psychometrics` ([psychometrics-class](#))

Author(s)

Sacha Epskamp

See Also

[prune](#)

Examples

```

# Load bfi data from psych package:
library("psychTools")
data(bfi)

# Also load dplyr for the pipe operator:
library("dplyr")

# Let's take the agreeableness items, and gender:
ConsData <- bfi %>%
  select(A1:A5, gender) %>%
  na.omit # Let's remove missingness (otherwise use Estimator = "FIML)

# Define variables:
vars <- names(ConsData)[1:5]

# Let's fit a full GGM:
mod <- ggm(ConsData, vars = vars, omega = "full")

# Run model:
mod <- mod %>%runmodel %>%prune(alpha = 0.05)

# Remove an edge (example):
mod <- mod %>%fixpar("omega",1,2) %>%runmodel

# Stepup search

```

```
mod <- mod %>%stepup(alpha = 0.05)
```

tsdlvm1	<i>Lag-1 dynamic latent variable model family of psychometrics models for time-series data</i>
---------	------------------------------------------------------------------------------------------------

Description

This is the family of models that models a dynamic factor model on time-series. There are two covariance structures that can be modeled in different ways: contemporaneous for the contemporaneous model and residual for the residual model. These can be set to "cov" for covariances, "prec" for a precision matrix, "ggm" for a Gaussian graphical model and "chol" for a Cholesky decomposition. The `ts_lvlgvar` wrapper function sets contemporaneous = "ggm" for the graphical VAR model.

Usage

```
tsdlvm1(data, lambda, contemporaneous = c("cov", "chol",
    "prec", "ggm"), residual = c("cov", "chol", "prec",
    "ggm"), beta = "full", omega_zeta = "full", delta_zeta
    = "full", kappa_zeta = "full", sigma_zeta = "full",
    lowertri_zeta = "full", omega_epsilon = "empty",
    delta_epsilon = "empty", kappa_epsilon = "empty",
    sigma_epsilon = "empty", lowertri_epsilon = "empty",
    nu, mu_eta, identify = TRUE, identification =
    c("loadings", "variance"), latents, beepvar, dayvar,
    idvar, vars, groups, covs, means, nobs, missing =
    "listwise", equal = "none", baseline_saturated = TRUE,
    estimator = "ML", optimizer, storedata = FALSE,
    sampleStats, covtype = c("choose", "ML", "UB"),
    centerWithin = FALSE, standardize = c("none", "z",
    "quantile"), verbose = FALSE)
```

```
ts_lvlgvar(...)
```

Arguments

data	A data frame encoding the data used in the analysis. Can be missing if covs and nobs are supplied.
lambda	A model matrix encoding the factor loading structure. Each row indicates an indicator and each column a latent. A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
contemporaneous	The type of contemporaneous model used. See description.

residual	The type of residual model used. See description.
beta	A model matrix encoding the temporal relationships (transpose of temporal network) between latent variables. A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix. Can also be "full" for a full temporal network or "empty" for an empty temporal network.
omega_zeta	Only used when contemporaneous = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
delta_zeta	Only used when contemporaneous = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
kappa_zeta	Only used when contemporaneous = "prec". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
sigma_zeta	Only used when contemporaneous = "cov". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
lowertri_zeta	Only used when contemporaneous = "chol". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
omega_epsilon	Only used when residual = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
delta_epsilon	Only used when residual = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate

	element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>kappa_epsilon</code>	Only used when <code>residual = "prec"</code> . Either <code>"full"</code> to estimate every element freely, <code>"empty"</code> to only include diagonal elements, or a matrix of the dimensions <code>node x node</code> with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>sigma_epsilon</code>	Only used when <code>residual = "cov"</code> . Either <code>"full"</code> to estimate every element freely, <code>"empty"</code> to only include diagonal elements, or a matrix of the dimensions <code>node x node</code> with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>lowertri_epsilon</code>	Only used when <code>residual = "chol"</code> . Either <code>"full"</code> to estimate every element freely, <code>"empty"</code> to only include diagonal elements, or a matrix of the dimensions <code>node x node</code> with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>nu</code>	Optional vector encoding the intercepts of the observed variables. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
<code>mu_eta</code>	Optional vector encoding the means of the latent variables. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free intercepts, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
<code>identify</code>	Logical, should the model be automatically identified?
<code>identification</code>	Type of identification used. <code>"loadings"</code> to fix the first factor loadings to 1, and <code>"variance"</code> to fix the diagonal of the latent variable model matrix (<code>sigma_zeta</code> , <code>lowertri_zeta</code> , <code>delta_zeta</code> or <code>kappa_zeta</code>) to 1.
<code>latents</code>	An optional character vector with names of the latent variables.
<code>beepvar</code>	Optional string indicating assessment beep per day. Adding this argument will cause non-consecutive beeps to be treated as missing!
<code>dayvar</code>	Optional string indicating assessment day. Adding this argument makes sure that the first measurement of a day is not regressed on the last measurement of the previous day. IMPORTANT: only add this if the data has multiple observations per day.
<code>idvar</code>	Optional string indicating the subject ID
<code>vars</code>	An optional character vector encoding the variables used in the analysis. Must equal names of the dataset in data.
<code>groups</code>	An optional string indicating the name of the group variable in data.

covs	A sample variance–covariance matrix, or a list/array of such matrices for multiple groups. Make sure covtype argument is set correctly to the type of covariances used.
means	A vector of sample means, or a list/matrix containing such vectors for multiple groups.
nobs	The number of observations used in covs and means, or a vector of such numbers of observations for multiple groups.
missing	How should missingness be handled in computing the sample covariances and number of observations when data is used. Can be "listwise" for listwise deletion, or "pairwise" for pairwise deletion.
equal	A character vector indicating which matrices should be constrained equal across groups.
baseline_saturated	A logical indicating if the baseline and saturated model should be included. Mostly used internally and NOT Recommended to be used manually.
estimator	The estimator to be used. Currently implemented are "ML" for maximum likelihood estimation, "FIML" for full-information maximum likelihood estimation, "ULS" for unweighted least squares estimation, "WLS" for weighted least squares estimation, and "DWLS" for diagonally weighted least squares estimation.
optimizer	The optimizer to be used. Can be one of "nlminb" (the default R nlminb function), "ucminf" (from the optimr package), and C++ based optimizers "cpp_L-BFGS-B", "cpp_BFGS", "cpp_CG", "cpp_SANN", and "cpp_Nelder-Mead". The C++ optimizers are faster but slightly less stable. Defaults to "nlminb".
storedata	Logical, should the raw data be stored? Needed for bootstrapping (see bootstrap).
standardize	Which standardization method should be used? "none" (default) for no standardization, "z" for z-scores, and "quantile" for a non-parametric transformation to the quantiles of the marginal standard normal distribution.
sampleStats	An optional sample statistics object. Mostly used internally.
centerWithin	Logical, should data be within-person centered?
covtype	If 'covs' is used, this is the type of covariance (maximum likelihood or unbiased) the input covariance matrix represents. Set to "ML" for maximum likelihood estimates (denominator n) and "UB" to unbiased estimates (denominator n-1). The default will try to find the type used, by investigating which is most likely to result from integer valued datasets.
verbose	Logical, should messages be printed?
...	Arguments sent to tsdlvm1

Value

An object of the class psychometrics ([psychometrics-class](#))

Author(s)

Sacha Epskamp

Examples

```

# Note: this example is wrapped in a dontrun environment because the data is not
# available locally.
## Not run:
# Obtain the data from:
#
# Epskamp, S., van Borkulo, C. D., van der Veen, D. C., Servaas, M. N., Isvoranu, A. M.,
# Riese, H., & Cramer, A. O. (2018). Personalized network modeling in psychopathology:
# The importance of contemporaneous and temporal connections. Clinical Psychological
# Science, 6(3), 416-427.
#
# Available here: https://osf.io/c8wjz/
tsdata <- read.csv("Supplementary2_data.csv")

# Encode time variable in a way R understands:
tsdata$time <- as.POSIXct(tsdata$time, tz = "Europe/Amsterdam")

# Extract days:
tsdata$Day <- as.Date(tsdata$time, tz = "Europe/Amsterdam")

# Variables to use:
vars <- c("relaxed", "sad", "nervous", "concentration", "tired", "rumination",
         "bodily.discomfort")

# Create lambda matrix (in this case: one factor):
Lambda <- matrix(1,7,1)

# Estimate dynamical factor model:
model <- tsdlvm1(
  tsdata,
  lambda = Lambda,
  vars = vars,
  dayvar = "Day",
  estimator = "FIML"
)

# Run model:
model <- model %>% runmodel

# Look at fit:
model %>% print
model %>% fit # Pretty bad fit

## End(Not run)

```

Description

The `unionmodel` will add all parameters to all groups that are free in at least one group, and the `intersectionmodel` will constrain all parameters across groups to zero unless they are free to estimate in all groups.

Usage

```
unionmodel(x, runmodel = FALSE, verbose, log = TRUE, identify =
          TRUE, ...)
```

```
intersectionmodel(x, runmodel = FALSE, verbose, log = TRUE, identify =
                 TRUE, ...)
```

Arguments

<code>x</code>	A psychometrics model.
<code>runmodel</code>	Logical, should the model be updated?
<code>verbose</code>	Logical, should messages be printed?
<code>log</code>	Logical, should the log be updated?
<code>identify</code>	Logical, should the model be identified?
<code>...</code>	Arguments sent to <code>runmodel</code>

Value

An object of the class `psychometrics` ([psychometrics-class](#))

Author(s)

Sacha Epskamp

var1

Lag-1 vector autoregression family of psychometrics models

Description

This is the family of models that models time-series data using a lag-1 vector autoregressive model (VAR; Epskamp, Waldorp, Mottus, Borsboom, 2018). The model is fitted to the Toeplitz matrix, but unlike typical SEM software the block of covariances of the lagged variables is not used in estimating the temporal and contemporaneous relationships (the block is modeled completely separately using a cholesky decomposition, and does not enter the model elsewhere). The contemporaneous argument can be used to define what contemporaneous model is used: `contemporaneous = "cov"` (default) models a variance-covariance matrix, `contemporaneous = "chol"` models a Cholesky decomposition, `contemporaneous = "prec"` models a precision matrix, and `contemporaneous = "ggm"` (alias: `gvar()`) models a Gaussian graphical model, also then known as a graphical VAR model.

Usage

```
var1(data, contemporaneous = c("cov", "chol", "prec",
    "ggm"), beta = "full", omega_zeta = "full", delta_zeta
    = "full", kappa_zeta = "full", sigma_zeta = "full",
    lowertri_zeta = "full", mu, beepvar, dayvar, idvar,
    vars, groups, covs, means, nobs, missing = "listwise",
    equal = "none", baseline_saturated = TRUE, estimator =
    "ML", optimizer, storedata = FALSE, covtype =
    c("choose", "ML", "UB"), standardize = c("none", "z",
    "quantile"), sampleStats, verbose = FALSE)
```

```
gvar(...)
```

Arguments

<code>data</code>	A data frame encoding the data used in the analysis. Can be missing if covs and nobs are supplied.
<code>contemporaneous</code>	The type of contemporaneous model used. See description.
<code>beta</code>	A model matrix encoding the temporal relationships (transpose of temporal network). A 0 encodes a fixed to zero element, a 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix. Can also be "full" for a full temporal network or "empty" for an empty temporal network.
<code>omega_zeta</code>	Only used when <code>contemporaneous = "ggm"</code> . Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>delta_zeta</code>	Only used when <code>contemporaneous = "ggm"</code> . Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>kappa_zeta</code>	Only used when <code>contemporaneous = "prec"</code> . Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
<code>sigma_zeta</code>	Only used when <code>contemporaneous = "cov"</code> . Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For

	multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
lowertri_zeta	Only used when contemporaneous = "chol". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
mu	Optional vector encoding the mean structure. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free means, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
beepvar	Optional string indicating assessment beep per day. Adding this argument will cause non-consecutive beeps to be treated as missing!
dayvar	Optional string indicating assessment day. Adding this argument makes sure that the first measurement of a day is not regressed on the last measurement of the previous day. IMPORTANT: only add this if the data has multiple observations per day.
idvar	Optional string indicating the subject ID
vars	An optional character vector encoding the variables used in the analysis. Must equal names of the dataset in data.
groups	An optional string indicating the name of the group variable in data.
covs	A sample variance-covariance matrix, or a list/array of such matrices for multiple groups. Make sure covtype argument is set correctly to the type of covariances used.
means	A vector of sample means, or a list/matrix containing such vectors for multiple groups.
nobs	The number of observations used in covs and means, or a vector of such numbers of observations for multiple groups.
missing	How should missingness be handled in computing the sample covariances and number of observations when data is used. Can be "listwise" for listwise deletion, or "pairwise" for pairwise deletion.
equal	A character vector indicating which matrices should be constrained equal across groups.
baseline_saturated	A logical indicating if the baseline and saturated model should be included. Mostly used internally and NOT Recommended to be used manually.
estimator	The estimator to be used. Currently implemented are "ML" for maximum likelihood estimation, "FIML" for full-information maximum likelihood estimation, "ULS" for unweighted least squares estimation, "WLS" for weighted least squares estimation, and "DWLS" for diagonally weighted least squares estimation.
optimizer	The optimizer to be used. Can be one of "nlminb" (the default R nlminb function), "ucminf" (from the optimr package), and C++ based optimizers "cpp_L-BFGS-B", "cpp_BFGS", "cpp_CG", "cpp_SANN", and "cpp_Nelder-Mead". The C++ optimizers are faster but slightly less stable. Defaults to "nlminb".

storedata	Logical, should the raw data be stored? Needed for bootstrapping (see <code>bootstrap</code>).
standardize	Which standardization method should be used? "none" (default) for no standardization, "z" for z-scores, and "quantile" for a non-parametric transformation to the quantiles of the marginal standard normal distribution.
sampleStats	An optional sample statistics object. Mostly used internally.
covtype	If 'covs' is used, this is the type of covariance (maximum likelihood or unbiased) the input covariance matrix represents. Set to "ML" for maximum likelihood estimates (denominator n) and "UB" to unbiased estimates (denominator n-1). The default will try to find the type used, by investigating which is most likely to result from integer valued datasets.
verbose	Logical, should messages be printed?
...	Arguments sent to <code>var1</code>

Details

This will be updated in a later version.

Value

An object of the class `psychonetrics`

Author(s)

Sacha Epskamp

References

Epskamp, S., Waldorp, L. J., Mottus, R., & Borsboom, D. (2018). The Gaussian graphical model in cross-sectional and time-series data. *Multivariate Behavioral Research*, 53(4), 453-480.

See Also

[lvm](#), [varcov](#), [dlvm1](#)

Examples

```
library("dplyr")
library("graphicalVAR")

beta <- matrix(c(
  0,0.5,
  0.5,0
),2,2,byrow=TRUE)
kappa <- diag(2)
simData <- graphicalVARsim(50, beta, kappa)

# Form model:
model <- gvar(simData)
```



```

# Evaluate model:
model <- model %>% runmodel

# Parameter estimates:
model %>% parameters

# Note: this example is wrapped in a dontrun environment because the data is not
# available locally.
## Not run:
# Longer example:
#
# Obtain the data from:
#
# Epskamp, S., van Borkulo, C. D., van der Veen, D. C., Servaas, M. N., Isvoranu, A. M.,
# Riese, H., & Cramer, A. O. (2018). Personalized network modeling in psychopathology:
# The importance of contemporaneous and temporal connections. Clinical Psychological
# Science, 6(3), 416-427.
#
# Available here: https://osf.io/c8wjz/

tsdata <- read.csv("Supplementary2_data.csv")

# Encode time variable in a way R understands:
tsdata$time <- as.POSIXct(tsdata$time, tz = "Europe/Amsterdam")

# Extract days:
tsdata$Day <- as.Date(tsdata$time, tz = "Europe/Amsterdam")

# Variables to use:
vars <- c("relaxed", "sad", "nervous", "concentration", "tired", "rumination",
          "bodily.discomfort")

# Estimate, prune with FDR, and perform stepup search:
model_FDRprune <- gvar(
  tsdata,
  vars = vars,
  dayvar = "Day",
  estimator = "FIML"
) %>%
runmodel %>%
prune(adjust = "fdr", recursive = FALSE) %>%
stepup(criterion = "bic")

# Estimate with greedy stepup search:
model_stepup <- gvar(
  tsdata,
  vars = vars,
  dayvar = "Day",
  estimator = "FIML",
  omega_zeta = "empty",
  beta = "empty"
) %>%
runmodel %>%

```

```

stepup(greedy = TRUE, greedyadjust = "bonferroni", criterion = "bic")

# Compare models:
compare(
  FDRprune = model_FDRprune,
  stepup = model_stepup
)
# Very similar but not identical. Stepup is preferred here according to AIC and BIC

# Stepup results:
temporal <- getmatrix(model_stepup, "PDC") # PDC = Partial Directed Correlations
contemporaneous <- getmatrix(model_stepup, "omega_zeta")

# Average layout:
library("qgraph")
L <- averageLayout(temporal, contemporaneous)

# Labels:
labs <- gsub("\\.", "\n", vars)

# Plot:
layout(t(1:2))
qgraph(temporal, layout = L, theme = "colorblind", directed=TRUE, diag=TRUE,
  title = "Temporal", vsize = 12, mar = rep(6,4), asize = 5,
  labels = labs)
qgraph(contemporaneous, layout = L, theme = "colorblind",
  title = "Contemporaneous", vsize = 12, mar = rep(6,4), asize = 5,
  labels = labs)

## End(Not run)

```

varcov

Variance-covariance family of psychometrics models

Description

This is the family of models that models only a variance-covariance matrix with mean structure. The type argument can be used to define what model is used: type = "cov" (default) models a variance-covariance matrix directly, type = "chol" (alias: cholesky()) models a Cholesky decomposition, type = "prec" (alias: precision()) models a precision matrix, type = "ggm" (alias: ggm()) models a Gaussian graphical model (Epskamp, Rhemtulla and Borsboom, 2017), and type = "cor" (alias: corr()) models a correlation matrix.

Usage

```

varcov(data, type = c("cov", "chol", "prec", "ggm", "cor"),
  sigma = "full", kappa = "full", omega = "full",
  lowertri = "full", delta = "full", rho = "full", SD =
  "full", mu, tau, vars, ordered = character(0), groups,

```

```

covs, means, nobs, missing = "listwise", equal =
"none", baseline_saturated = TRUE, estimator =
"default", optimizer, storedata = FALSE, WLS.W,
sampleStats, meanstructure, corinput, verbose = FALSE,
covtype = c("choose", "ML", "UB"), standardize =
c("none", "z", "quantile"), fullFIML = FALSE)

cholesky(...)
precision(...)
prec(...)
ggm(...)
corr(...)

```

Arguments

data	A data frame encoding the data used in the analysis. Can be missing if covs and nobs are supplied.
type	The type of model used. See description.
sigma	Only used when type = "cov". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
kappa	Only used when type = "prec". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
omega	Only used when type = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
lowertri	Only used when type = "chol". Either "full" to estimate every element freely, "empty" to only include diagonal elements, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
delta	Only used when type = "ggm". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
rho	Only used when type = "cor". Either "full" to estimate every element freely, "empty" to set all elements to zero, or a matrix of the dimensions node x node

	with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
SD	Only used when <code>type = "cor"</code> . Either <code>"full"</code> to estimate every element freely, <code>"empty"</code> to set all elements to zero, or a matrix of the dimensions <code>node x node</code> with 0 encoding a fixed to zero element, 1 encoding a free to estimate element, and higher integers encoding equality constrains. For multiple groups, this argument can be a list or array with each element/slice encoding such a matrix.
mu	Optional vector encoding the mean structure. Set elements to 0 to indicate fixed to zero constrains, 1 to indicate free means, and higher integers to indicate equality constrains. For multiple groups, this argument can be a list or array with each element/column encoding such a vector.
tau	Optional list encoding the thresholds per variable.
vars	An optional character vector encoding the variables used in the analysis. Must equal names of the dataset in <code>data</code> .
groups	An optional string indicating the name of the group variable in <code>data</code> .
covs	A sample variance–covariance matrix, or a list/array of such matrices for multiple groups. Make sure <code>covtype</code> argument is set correctly to the type of covariances used.
means	A vector of sample means, or a list/matrix containing such vectors for multiple groups.
nobs	The number of observations used in <code>covs</code> and <code>means</code> , or a vector of such numbers of observations for multiple groups.
covtype	If <code>'covs'</code> is used, this is the type of covariance (maximum likelihood or unbiased) the input covariance matrix represents. Set to <code>"ML"</code> for maximum likelihood estimates (denominator <code>n</code>) and <code>"UB"</code> to unbiased estimates (denominator <code>n-1</code>). The default will try to find the type used, by investigating which is most likely to result from integer valued datasets.
missing	How should missingness be handled in computing the sample covariances and number of observations when <code>data</code> is used. Can be <code>"listwise"</code> for listwise deletion, or <code>"pairwise"</code> for pairwise deletion.
equal	A character vector indicating which matrices should be constrained equal across groups.
baseline_saturated	A logical indicating if the baseline and saturated model should be included. Mostly used internally and NOT Recommended to be used manually.
estimator	The estimator to be used. Currently implemented are <code>"ML"</code> for maximum likelihood estimation, <code>"FIML"</code> for full-information maximum likelihood estimation, <code>"ULS"</code> for unweighted least squares estimation, <code>"WLS"</code> for weighted least squares estimation, and <code>"DWLS"</code> for diagonally weighted least squares estimation.
optimizer	The optimizer to be used. Can be one of <code>"nlmminb"</code> (the default R <code>nlminb</code> function), <code>"ucminf"</code> (from the <code>optimr</code> package), and C++ based optimizers <code>"cpp_L-BFGS-B"</code> , <code>"cpp_BFGS"</code> , <code>"cpp_CG"</code> , <code>"cpp_SANN"</code> , and <code>"cpp_Nelder-Mead"</code> . The C++ optimizers are faster but slightly less stable. Defaults to <code>"nlminb"</code> .

storedata	Logical, should the raw data be stored? Needed for bootstrapping (see <code>bootstrap</code>).
standardize	Which standardization method should be used? "none" (default) for no standardization, "z" for z-scores, and "quantile" for a non-parametric transformation to the quantiles of the marginal standard normal distribution.
WLS.W	Optional WLS weights matrix.
sampleStats	An optional sample statistics object. Mostly used internally.
verbose	Logical, should progress be printed to the console?
ordered	A vector with strings indicating the variables that are ordered categorical, or set to TRUE to model all variables as ordered categorical.
meanstructure	Logical, should the meanstructure be modeled explicitly?
corinput	Logical, is the input a correlation matrix?
fullFIML	Logical, should row-wise FIML be used? Not recommended!
...	Arguments sent to <code>varcov</code>

Details

The model used in this family is:

$$\text{var}(\mathbf{y}) = \Sigma$$

$$\mathcal{E}(\mathbf{y}) = \boldsymbol{\mu}$$

in which the covariance matrix can further be modeled in three ways. With `type = "chol"` as Cholesky decomposition:

$$\Sigma = LL^T,$$

with `type = "prec"` as Precision matrix:

$$\Sigma = K^{-1},$$

and finally with `type = "ggm"` as Gaussian graphical model:

$$\Sigma = \Delta(\mathbf{I} - \Omega)^{-1}\Delta.$$

Value

An object of the class `psychometrics`

Author(s)

Sacha Epskamp

References

Epskamp, S., Rhemtulla, M., & Borsboom, D. (2017). Generalized network psychometrics: Combining network and latent variable models. *Psychometrika*, 82(4), 904-927.

See Also

[lvm](#), [var1](#), [dlvm1](#)

Examples

```
# Load bfi data from psych package:
library("psychTools")
data(bfi)

# Also load dplyr for the pipe operator:
library("dplyr")

# Let's take the agreeableness items, and gender:
ConsData <- bfi %>%
  select(A1:A5, gender) %>%
  na.omit # Let's remove missingness (otherwise use Estimator = "FIML")

# Define variables:
vars <- names(ConsData)[1:5]

# Let's fit an empty GGM:
mod0 <- ggm(ConsData, vars = vars, omega = "empty")

# Run the model:
mod0 <- mod0 %>% runmodel

# We can look at the modification indices:
mod0 %>% MIs

# To automatically add along modification indices, we can use stepup:
mod1 <- mod0 %>% stepup

# Let's also prune all non-significant edges to finish:
mod1 <- mod1 %>% prune

# Look at the fit:
mod1 %>% fit

# Compare to original (baseline) model:
compare(baseline = mod0, adjusted = mod1)

# We can also look at the parameters:
mod1 %>% parameters

# Or obtain the network as follows:
getmatrix(mod1, "omega")
```

Index

- * **classes**
 - psychonetrics-class, 55
- * **datasets**
 - Jonas, 26
 - StarWars, 61
- addfit (psychonetrics_update), 57
- addMIs (psychonetrics_update), 57
- addSEs (psychonetrics_update), 57

- bifactor, 5
- bootstrap, 6, 13, 31, 48

- changedata, 6
- cholesky (varcov), 74
- compare, 7
- corr (varcov), 74
- cov, 7, 13
- covML, 8
- covMLtoUB (covML), 8
- covUBtoML (covML), 8

- diagonalizationMatrix
 - (duplicationMatrix), 15
- d1vm1, 4, 9, 16, 17, 44, 49, 72, 77
- duplicationMatrix, 15

- eliminationMatrix (duplicationMatrix), 15
- emergencystart, 16
- esa, 16
- esa_manual (esa), 16

- factorscores, 17
- fit, 18, 50, 62
- fixpar, 19
- freepar (fixpar), 19

- generate, 20
- getmatrix, 20
- getVCOV, 21

- ggm (varcov), 74
- groupequal, 22
- groupfree (groupequal), 22
- gvar (var1), 69

- identify (psychonetrics_update), 57
- intersectionmodel (unionmodel), 68
- Ising, 23

- Jonas, 26

- latentgrowth, 27
- lnm (lvm), 28
- lrnm (lvm), 28
- lvm, 4, 5, 27, 28, 44, 72, 77

- meta_ggm (meta_varcov), 39
- meta_varcov, 39
- MIs, 43
- ml_lnm (ml_lvm), 44
- ml_lrnm (ml_lvm), 44
- ml_lvm, 44
- ml_rnm (ml_lvm), 44
- ml_ts_lvgvar (ml_tsdlvm1), 49
- ml_tsdlvm1, 49
- modelsearch, 50

- panel_lvgvar (dlvm1), 9
- panelgvar (dlvm1), 9
- panelvar (dlvm1), 9
- parameters, 51
- parequal, 52
- partialprune, 53
- plot.esa (esa), 16
- plot.esa_manual (esa), 16
- prec (varcov), 74
- precision (varcov), 74
- print.esa (esa), 16
- print.esa_manual (esa), 16
- print.psychonetrics_compare (compare), 7
- prune, 50, 53, 54, 63

psychonetrics (psychonetrics-package), 3
psychonetrics-class, 5–7, 14, 19, 22, 27,
32, 42, 48, 50, 53, 54, 55, 57, 58, 60,
63, 67, 69
psychonetrics-package, 3
psychonetrics_update, 57

resid, psychonetrics-method
 (psychonetrics-class), 55
residuals, psychonetrics-method
 (psychonetrics-class), 55
rnm (lvm), 28
runmodel, 50, 54, 58, 63

setestimator, 59
setoptimizer (setestimator), 59
setverbose, 60
show, psychonetrics-method
 (psychonetrics-class), 55
simplestructure, 45, 60
StarWars, 61
stepup, 50, 54, 62

ts_lvgvar (tsdlvm1), 64
tsdlvm1, 4, 64

unionmodel, 68
usecpp (setestimator), 59

var1, 4, 69, 77
varcov, 4, 72, 74