

Package ‘rgbif’

January 13, 2021

Title Interface to the Global 'Biodiversity' Information Facility API

Description A programmatic interface to the Web Service methods provided by the Global Biodiversity Information Facility ('GBIF'; <<https://www.gbif.org/developer/summary>>). 'GBIF' is a database of species occurrence records from sources all over the globe. 'rgbif' includes functions for searching for taxonomic names, retrieving information on data providers, getting species occurrence records, getting counts of occurrence records, and using the 'GBIF' tile map service to make 'rasters' summarizing huge amounts of data.

Version 3.5.0

License MIT + file LICENSE

URL <https://github.com/ropensci/rgbif> (devel),
<https://docs.ropensci.org/rgbif/> (documentation),
<https://books.ropensci.org/occurrences/> (user manual)

BugReports <https://github.com/ropensci/rgbif/issues>

LazyData true

LazyLoad true

Encoding UTF-8

Language en-US

Imports xml2, ggplot2, crul (>= 0.7.4), data.table, whisker, magrittr, jsonlite (>= 1.6), oai (>= 0.2.2), tibble, wellknown (>= 0.7.2), lazyeval, R6, conditionz

Suggests testthat, sp, rgeos, png, raster, protolite (>= 2.0), sf, randgeo, vcr (>= 0.5.0)

RoxygenNote 7.1.1

X-schema.org-applicationCategory Biodiversity

X-schema.org-keywords GBIF, specimens, API, web-services, occurrences, species, taxonomy

X-schema.org-isPartOf <https://ropensci.org>

NeedsCompilation no

Author Scott Chamberlain [aut, cre] (<<https://orcid.org/0000-0003-1444-9135>>),
 Damiano Oldoni [aut] (<<https://orcid.org/0000-0003-3445-7562>>),
 Vijay Barve [ctb] (<<https://orcid.org/0000-0002-4852-2567>>),
 Peter Desmet [ctb] (<<https://orcid.org/0000-0002-8442-8025>>),
 Laurens Geffert [ctb],
 Dan Mcglinn [ctb] (<<https://orcid.org/0000-0003-2359-3526>>),
 Karthik Ram [ctb] (<<https://orcid.org/0000-0002-0233-1757>>),
 rOpenSci [fnd] (<https://ropensci.org/>)

Maintainer Scott Chamberlain <myrmecocystus@gmail.com>

Repository CRAN

Date/Publication 2021-01-13 22:50:03 UTC

R topics documented:

rgbif-package	3
check_wkt	4
count_facet	5
datasets	6
dataset_metrics	8
dataset_search	8
dataset_suggest	11
downloads	14
download_predicate_dsl	16
elevation	20
enumeration	22
gbif_bbox2wkt	23
gbif_citation	24
gbif_issues	25
gbif_issues_lookup	26
gbif_names	27
gbif_oai	27
gbif_photos	29
installations	30
isocodes	32
many-values	32
map_fetch	33
mvt_fetch	36
name_backbone	39
name_issues	41
name_lookup	42
name_suggest	47
name_usage	49
networks	52
nodes	53
occ_count	56
occ_data	59
occ_download	77

occ_download_cached	81
occ_download_cancel	83
occ_download_datasets	84
occ_download_dataset_activity	85
occ_download_get	86
occ_download_import	87
occ_download_list	89
occ_download_meta	90
occ_download_queue	91
occ_download_wait	93
occ_facet	94
occ_fields	95
occ_get	96
occ_issues	97
occ_metadata	99
occ_search	101
organizations	120
parsenames	121
rgbif-defunct	122
rgb_country_codes	123
taxrank	123
typestatus	124
wkt_parse	124

Index	126
--------------	------------

rgbif-package	<i>Interface to the Global Biodiversity Information Facility API.</i>
---------------	---

Description

rgbif: A programmatic interface to the Web Service methods provided by the Global Biodiversity Information Facility.

About

This package gives you access to data from GBIF <https://www.gbif.org/> via their API.

A note about the old GBIF API

The old GBIF API is now defunct - that is, not available anymore. We used to have functions that worked with the old API, but those functions are now not available anymore because GBIF made the old API defunct.

Documentation for the GBIF API

- summary <https://www.gbif.org/developer/summary> - Summary of the GBIF API
- registry <https://www.gbif.org/developer/registry> - Metadata on datasets, and contributing organizations
- species names <https://www.gbif.org/developer/species> - Species names and metadata
- occurrences <https://www.gbif.org/developer/occurrence> - Occurrences
- maps <https://www.gbif.org/developer/maps> - Maps - these APIs are not implemented in **rgbif**, and are meant more for intergration with web based maps.

Note

See [many-values](#) for discussion of how functions vary in how they accept values (single vs. many for the same HTTP request vs. many for different HTTP requests)

Author(s)

Scott Chamberlain

Karthik Ram

Dan Mcglinn

Vijay Barve

check_wkt

Check input WKT

Description

Check input WKT

Usage

```
check_wkt(wkt = NULL, skip_validate = FALSE)
```

Arguments

wkt (character) one or more Well Known Text objects

skip_validate (logical) whether to skip `wellknown::validate_wkt` call or not. Default: FALSE

Examples

```
## Not run:
check_wkt('POLYGON((30.1 10.1, 10 20, 20 60, 60 60, 30.1 10.1))')
check_wkt('POINT(30.1 10.1)')
check_wkt('LINESTRING(3 4,10 50,20 25)')

# check many passed in at once
check_wkt(c('POLYGON((30.1 10.1, 10 20, 20 60, 60 60, 30.1 10.1))',
  'POINT(30.1 10.1)'))

# bad WKT
# wkt <- 'POLYGON((30.1 10.1, 10 20, 20 60, 60 60, 30.1 a))'
# check_wkt(wkt)

# many wkt's, semi-colon separated, for many repeated "geometry" args
wkt <- "POLYGON((-102.2 46.0,-93.9 46.0,-93.9 43.7,-102.2 43.7,-102.2 46.0))
;POLYGON((30.1 10.1, 10 20, 20 40, 40 40, 30.1 10.1))"
check_wkt(gsub("\n", '', wkt))

## End(Not run)
```

count_facet

Facetted count occurrence search.

Description

Facetted count occurrence search.

Usage

```
count_facet(keys = NULL, by = "country", countries = 10, removezeros = FALSE)
```

Arguments

keys	(numeric) GBIF keys, a vector. optional
by	(character) One of georeferenced, basisOfRecord, country, or publishingCountry. default: country
countries	(numeric) Number of countries to facet on, or a vector of country names. default: 10
removezeros	(logical) remove zeros or not? default: FALSE

Examples

```
## Not run:
# Select number of countries to facet on
count_facet(by='country', countries=3, removezeros = TRUE)
# Or, pass in country names
count_facet(by='country', countries='AR', removezeros = TRUE)
```

```

spplist <- c('Geothlypis trichas', 'Tiaris olivacea', 'Pterodroma axillaris',
            'Calidris ferruginea', 'Pterodroma macroptera',
            'Gallirallus australis',
            'Falco cenchroides', 'Telespiza cantans', 'Oreomystis bairdi',
            'Cistothorus palustris')
keys <- sapply(spplist,
              function(x) name_backbone(x, rank="species")$usageKey)
count_facet(keys, by='country', countries=3, removezeros = TRUE)
count_facet(keys, by='country', countries=3, removezeros = FALSE)
count_facet(by='country', countries=20, removezeros = TRUE)
count_facet(keys, by='basisOfRecord', countries=5, removezeros = TRUE)

# Pass in country names instead
countries <- isocodes$code[1:10]
count_facet(by='country', countries=countries, removezeros = TRUE)

# get occurrences by georeferenced state
## across all records
count_facet(by='georeferenced')

## by keys
count_facet(keys, by='georeferenced')

# by basisOfRecord
count_facet(by="basisOfRecord")

## End(Not run)

```

datasets

Search for datasets and dataset metadata.

Description

Search for datasets and dataset metadata.

Usage

```

datasets(
  data = "all",
  type = NULL,
  uuid = NULL,
  query = NULL,
  id = NULL,
  limit = 100,
  start = NULL,
  curlopts = list()
)

```

Arguments

data	The type of data to get. One or more of: 'organization', 'contact', 'endpoint', 'identifier', 'tag', 'machinetag', 'comment', 'constituents', 'document', 'metadata', 'deleted', 'duplicate', 'subDataset', 'withNoEndpoint', or the special 'all'. Default: all
type	Type of dataset. Options: include occurrence, checklist, metadata, or sampling_event.
uuid	UUID of the data node provider. This must be specified if data is anything other than all
query	Query term(s). Only used when data=all
id	A metadata document id.
limit	Number of records to return. Default: 100. Maximum: 1000.
start	Record number to start at. Default: 0. Use in combination with limit to page through results.
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

A list.

References

<https://www.gbif.org/developer/registry#datasets>

Examples

```
## Not run:
datasets(limit=5)
datasets(type="occurrence", limit=10)
datasets(uuid="a6998220-7e3a-485d-9cd6-73076bd85657")
datasets(data='contact', uuid="a6998220-7e3a-485d-9cd6-73076bd85657")
datasets(data='metadata', uuid="a6998220-7e3a-485d-9cd6-73076bd85657")
datasets(data='metadata', uuid="a6998220-7e3a-485d-9cd6-73076bd85657",
  id=598)
datasets(data=c('deleted','duplicate'))
datasets(data=c('deleted','duplicate'), limit=1)

# curl options
datasets(data=c('deleted','duplicate'), curlopts = list(verbose=TRUE))

## End(Not run)
```

dataset_metrics *Get details on a GBIF dataset.*

Description

Get details on a GBIF dataset.

Usage

```
dataset_metrics(uuid, curlopts = list())
```

Arguments

uuid (character) One or more dataset UUIDs. See examples.
curlopts list of named curl options passed on to `HttpClient`. see `curl::curl_options` for curl options

Note

Dataset metrics are only available for checklist type datasets.

References

<https://www.gbif.org/developer/registry#datasetMetrics>

Examples

```
## Not run:  
dataset_metrics(uuid='863e6d6b-f602-4495-ac30-881482b6f799')  
dataset_metrics(uuid='66dd0960-2d7d-46ee-a491-87b9adcfe7b1')  
dataset_metrics(uuid=c('863e6d6b-f602-4495-ac30-881482b6f799',  
                      '66dd0960-2d7d-46ee-a491-87b9adcfe7b1'))  
dataset_metrics(uuid='66dd0960-2d7d-46ee-a491-87b9adcfe7b1',  
                  curlopts = list(verbose=TRUE))  
  
## End(Not run)
```

dataset_search *Search datasets in GBIF.*

Description

This function does not search occurrence data, only metadata on the datasets that contain occurrence data.

Usage

```
dataset_search(
  query = NULL,
  country = NULL,
  type = NULL,
  keyword = NULL,
  publishingOrg = NULL,
  hostingOrg = NULL,
  publishingCountry = NULL,
  decade = NULL,
  facet = NULL,
  facetMincount = NULL,
  facetMultiselect = NULL,
  limit = 100,
  start = NULL,
  pretty = FALSE,
  return = NULL,
  curlopts = list()
)
```

Arguments

query	Query term(s) for full text search. The value for this parameter can be a simple word or a phrase. Wildcards can be added to the simple word parameters only, e.g. q=*puma*
country	NOT YET IMPLEMENTED. Filters by country as given in isocodes\$gbif_name, e.g. country=CANADA
type	Type of dataset, options include occurrene, metadata, checklist, sampling_event (http://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/DatasetType.html)
keyword	Keyword to search by. Datasets can be tagged by keywords, which you can search on. The search is done on the merged collection of tags, the dataset keywordCollections and temporalCoverages.
publishingOrg	Publishing organization. A uuid string. See organizations
hostingOrg	Hosting organization. A uuid string. See organizations
publishingCountry	Publishing country. See options at isocodes\$gbif_name
decade	Decade, e.g., 1980. Filters datasets by their temporal coverage broken down to decades. Decades are given as a full year, e.g. 1880, 1960, 2000, etc, and will return datasets wholly contained in the decade as well as those that cover the entire decade or more. Facet by decade to get the break down, e.g. /search?facet=DECADE&facet_only=true (see example below)
facet	A list of facet names used to retrieve the 100 most frequent values for a field. Allowed facets are: datasetKey, highertaxonKey, rank, status, extinct, habitat, and nameType. Additionally threat and nomenclaturalStatus are legal values but not yet implemented, so data will not yet be returned for them.

facetMincount	Used in combination with the facet parameter. Set facetMincount={#} to exclude facets with a count less than #
facetMultiselect	Used in combination with the facet parameter. Set facetMultiselect=true to still return counts for values that are not currently filtered
limit	Number of records to return. Default: 100. Maximum: 1000.
start	Record number to start at. Default: 0. Use in combination with limit to page through results.
pretty	Print informative metadata using <code>cat</code> . Not easy to manipulate output though.
return	Defunct. All components are returned; index to the one(s) you want
curlopts	list of named curl options passed on to <code>HttpClient</code> . see <code>curl::curl_options</code> for curl options

Value

A data.frame, list, or message printed to console (using pretty=TRUE).

Repeat parameter inputs

Some parameters can take many inputs, and treated as 'OR' (e.g., a or b or c). The following take many inputs:

- type
- keyword
- publishingOrg
- hostingOrg
- publishingCountry
- decade

References

<https://www.gbif.org/developer/registry#datasetSearch>

Examples

```
## Not run:
# Gets all datasets of type "OCCURRENCE".
dataset_search(type="OCCURRENCE", limit = 10)

# Fulltext search for all datasets having the word "amsterdam" somewhere in
# its metadata (title, description, etc).
dataset_search(query="amsterdam", limit = 10)

# Limited search
dataset_search(type="OCCURRENCE", limit=2)
dataset_search(type="OCCURRENCE", limit=2, start=10)

# Return metadata in a more human readable way (hard to manipulate though)
```

```

dataset_search(type="OCCURRENCE", pretty=TRUE, limit = 10)

# Search by country code. Lookup isocodes first, and use US for United States
isocodes[agrep("UNITED", isocodes$gbif_name),]
dataset_search(country="US", limit = 10)

# Search by decade
dataset_search(decade=1980, limit = 10)

# Faceting
## just facets
dataset_search(facet="decade", facetMincount="10", limit=0)

## data and facets
dataset_search(facet="decade", facetMincount="10", limit=2)

# Some parameters accept many inputs, treated as OR
dataset_search(type = c("metadata", "checklist"))$data
dataset_search(keyword = c("fern", "algae"))$data
dataset_search(publishingOrg = c("e2e717bf-551a-4917-bdc9-4fa0f342c530",
  "90fd6680-349f-11d8-aa2d-b8a03c50a862"))$data
dataset_search(hostingOrg = c("c5f7ef70-e233-11d9-a4d6-b8a03c50a862",
  "c5e4331-7f2f-4a8d-aa56-81ece7014fc8"))$data
dataset_search(publishingCountry = c("DE", "NZ"))$data
dataset_search(decade = c(1910, 1930))$data

## curl options
dataset_search(facet="decade", facetMincount="10", limit=2,
  curlopts = list(verbose=TRUE))

## End(Not run)

```

dataset_suggest

Suggest datasets in GBIF.

Description

Suggest datasets in GBIF.

Usage

```

dataset_suggest(
  query = NULL,
  country = NULL,
  type = NULL,
  subtype = NULL,
  keyword = NULL,
  publishingOrg = NULL,
  hostingOrg = NULL,

```

```

publishingCountry = NULL,
decade = NULL,
continent = NULL,
limit = 100,
start = NULL,
pretty = FALSE,
description = FALSE,
curlopts = list()
)

```

Arguments

query	Query term(s) for full text search. The value for this parameter can be a simple word or a phrase. Wildcards can be added to the simple word parameters only, e.g. q=*puma*
country	NOT YET IMPLEMENTED. Filters by country as given in isocodes\$gbif_name, e.g. country=CANADA
type	Type of dataset, options include occurrence, metadata, checklist, sampling_event (http://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/DatasetType.html)
subtype	NOT YET IMPLEMENTED. Will allow filtering of datasets by their dataset subtypes, DC or EML.
keyword	Keyword to search by. Datasets can be tagged by keywords, which you can search on. The search is done on the merged collection of tags, the dataset keywordCollections and temporalCoverages.
publishingOrg	Publishing organization. A uuid string. See organizations
hostingOrg	Hosting organization. A uuid string. See organizations
publishingCountry	Publishing country. See options at isocodes\$gbif_name
decade	Decade, e.g., 1980. Filters datasets by their temporal coverage broken down to decades. Decades are given as a full year, e.g. 1880, 1960, 2000, etc, and will return datasets wholly contained in the decade as well as those that cover the entire decade or more. Facet by decade to get the break down, e.g. /search?facet=DECADE&facet_only=true (see example below)
continent	Not yet implemented, but will eventually allow filtering datasets by their continent(s) as given in our Continent enum.
limit	Number of records to return. Default: 100. Maximum: 1000.
start	Record number to start at. Default: 0. Use in combination with limit to page through results.
pretty	Print informative metadata using cat . Not easy to manipulate output though.
description	Return descriptions only (TRUE) or all data (FALSE, default)
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

A data.frame, list, or message printed to console (using pretty=TRUE).

Repeat parameter inputs

Some parameters can take many inputs, and are treated as 'OR' (e.g., a or b or c). The following take many inputs:

- type
- keyword
- publishingOrg
- hostingOrg
- publishingCountry
- decade

References

<https://www.gbif.org/developer/registry#datasetSearch>

Examples

```
## Not run:
# Suggest datasets of type "OCCURRENCE".
# dataset_suggest(query="Amazon", type="OCCURRENCE")

# Suggest datasets tagged with keyword "france".
# dataset_suggest(keyword="france")

# Fulltext search for all datasets having the word "amsterdam" somewhere in
# its metadata (title, description, etc).
# dataset_suggest(query="amsterdam")

# Limited search
# dataset_suggest(type="OCCURRENCE", limit=2)
# dataset_suggest(type="OCCURRENCE", limit=2, start=10)

# Return just descriptions
# dataset_suggest(type="OCCURRENCE", limit = 5, description=TRUE)

# Return metadata in a more human readable way (hard to manipulate though)
# dataset_suggest(type="OCCURRENCE", limit = 5, pretty=TRUE)

# Search by country code. Lookup isocodes first, and use US for United States
isocodes[agrep("UNITED", isocodes$gbif_name),]
# dataset_suggest(country="US", limit = 25)

# Search by decade
# dataset_suggest(decade=1980, limit = 30)

# Some parameters accept many inputs, treated as OR
# dataset_suggest(type = c("metadata", "checklist"))
# dataset_suggest(keyword = c("fern", "algae"))
# dataset_suggest(publishingOrg = c("e2e717bf-551a-4917-bdc9-4fa0f342c530",
# "90fd6680-349f-11d8-aa2d-b8a03c50a862"))
```

```
# dataset_suggest(hostingOrg = c("c5f7ef70-e233-11d9-a4d6-b8a03c50a862",
#   "c5e4331-7f2f-4a8d-aa56-81ece7014fc8"))
# dataset_suggest(publishingCountry = c("DE", "NZ"))
# dataset_suggest(decade = c(1910, 1930))

# curl options
# dataset_suggest(type="OCCURRENCE", limit = 2, curlopts = list(verbose=TRUE))

## End(Not run)
```

 downloads

Downloads interface

Description

GBIF provides two ways to get occurrence data: through the `/occurrence/search` route (see [occ_search\(\)](#)), or via the `/occurrence/download` route (many functions, see below). [occ_search\(\)](#) is more appropriate for smaller data, while `occ_download*()` functions are more appropriate for larger data requests.

Settings

You'll use [occ_download\(\)](#) to kick off a download. You'll need to give that function settings from your GBIF profile: your user name, your password, and your email. These three settings are required to use the function. You can specify them in one of three ways:

- Pass them to `occ_download` as parameters
- Use R options: As options either in the current R session using the [options\(\)](#) function, or by setting them in your `.Rprofile` file, after which point they'll be read in automatically
- Use environment variables: As env vars either in the current R session using the [Sys.setenv\(\)](#) function, or by setting them in your `.Renviron/.bash_profile` or similar files, after which point they'll be read in automatically

BEWARE

You can not perform that many downloads, so plan wisely. See *Rate limiting* below.

Rate limiting

If you try to launch too many downloads, you will receive an 420 "Enhance Your Calm" response. If there is less than 100 in total across all GBIF users, then you can have 3 running at a time. If there are more than that, then each user is limited to 1 only. These numbers are subject to change.

Functions

- [occ_download\(\)](#) - Start a download
- [occ_download_prep\(\)](#) - Prepare a download request
- [occ_download_queue\(\)](#) - Start many downloads in a queue
- [occ_download_cached\(\)](#) - Check for downloads already in your GBIF account
- [occ_download_wait\(\)](#) - Re-run [occ_download_meta\(\)](#) until ready
- [occ_download_meta\(\)](#) - Get metadata progress on a single download
- [occ_download_list\(\)](#) - List your downloads
- [occ_download_cancel\(\)](#) - Cancel a download
- [occ_download_cancel_staged\(\)](#) - Cancels any jobs with status RUNNING or PREPARING
- [occ_download_get\(\)](#) - Retrieve a download
- [occ_download_import\(\)](#) - Import a download from local file system
- [occ_download_datasets\(\)](#) - List datasets for a download
- [occ_download_dataset_activity\(\)](#) - Lists the downloads activity of a dataset

Download query composer methods:

See [download_predicate_dsl](#)

Query length

GBIF has a limit of 12,000 characters for a download query. This means that you can have a pretty long query, but at some point it may lead to an error on GBIF's side and you'll have to split your query into a few.

Download status

The following statuses can be found with any download:

- PREPARING: just submitted by user and awaiting processing (typically only a few seconds)
- RUNNING: being created (takes typically 1-15 minutes)
- FAILED: something unexpected went wrong
- KILLED: user decided to abort the job while it was in PREPARING or RUNNING phase
- SUCCEEDED: The download was created and the user was informed
- FILE_ERASED: The download was deleted according to the retention policy, see <https://www.gbif.org/faq?question=how-long-will-does-gbif-store-downloads>

download_predicate_dsl

Download predicate DSL (domain specific language)

Description

Download predicate DSL (domain specific language)

Usage

pred(key, value)

pred_gt(key, value)

pred_gte(key, value)

pred_lt(key, value)

pred_lte(key, value)

pred_not(...)

pred_like(key, value)

pred_within(value)

pred_notnull(key)

pred_or(..., .list = list())

pred_and(..., .list = list())

pred_in(key, value)

Arguments

key (character) the key for the predicate. See "Keys" below

value (various) the value for the predicate

..., .list For pred_or() or pred_and(), one or more objects of class occ_predicate, created by any pred* function

predicate methods and their equivalent types

pred* functions are named for the 'type' of operation they do, following the terminology used by GBIF, see <https://www.gbif.org/developer/occurrence#predicates>

Function names are given, with the equivalent GBIF type value (e.g., pred_gt and greaterThan)

The following functions take one key and one value:

- pred: equals
- pred_lt: lessThan
- pred_lte: lessThanOrEquals
- pred_gt: greaterThan
- pred_gte: greaterThanOrEquals
- pred_like: like

The following function is only for geospatial queries, and only accepts a WKT string:

- pred_within: within

The following function is only for stating the you don't want a key to be null, so only accepts one key:

- pred_notnull: isNotNull

The following two functions accept multiple individual predicates, separating them by either "and" or "or":

- pred_and: and
- pred_or: or

The not predicate accepts one predicate; that is, this negates whatever predicate is passed in, e.g., not the taxonKey of 12345:

- pred_not: not

The following function is special in that it accepts a single key but many values; stating that you want to search for all the values:

- pred_in: in

What happens internally

Internally, the input to pred* functions turns into JSON to be sent to GBIF. For example ...

pred_in("taxonKey",c(2480946,5229208)) gives:

```
{
  "type": "in",
  "key": "TAXON_KEY",
  "values": ["2480946", "5229208"]
}
```

pred_gt("elevation",5000) gives:

```
{
  "type": "greaterThan",
  "key": "ELEVATION",
  "value": "5000"
}
```

pred_or(pred("taxonKey", 2977832), pred("taxonKey", 2977901)) gives:

```
{
  "type": "or",
  "predicates": [
    {
      "type": "equals",
      "key": "TAXON_KEY",
      "value": "2977832"
    },
    {
      "type": "equals",
      "key": "TAXON_KEY",
      "value": "2977901"
    }
  ]
}
```

Keys

Acceptable arguments to the key parameter are (with the version of the key in parens that must be sent if you pass the query via the body parameter; see below for examples):

- taxonKey (TAXON_KEY)
- scientificName (SCIENTIFIC_NAME)
- country (COUNTRY)
- publishingCountry (PUBLISHING_COUNTRY)
- hasCoordinate (HAS_COORDINATE)
- hasGeospatialIssue (HAS_GEOSPATIAL_ISSUE)
- typeStatus (TYPE_STATUS)
- recordNumber (RECORD_NUMBER)
- lastInterpreted (LAST_INTERPRETED)
- continent (CONTINENT)
- geometry (GEOMETRY)
- basisOfRecord (BASIS_OF_RECORD)
- datasetKey (DATASET_KEY)
- eventDate (EVENT_DATE)
- catalogNumber (CATALOG_NUMBER)
- year (YEAR)
- month (MONTH)
- decimalLatitude (DECIMAL_LATITUDE)
- decimalLongitude (DECIMAL_LONGITUDE)
- elevation (ELEVATION)

- depth (DEPTH)
- institutionCode (INSTITUTION_CODE)
- collectionCode (COLLECTION_CODE)
- issue (ISSUE)
- mediatype (MEDIA_TYPE)
- recordedBy (RECORDED_BY)
- establishmentMeans (ESTABLISHMENT_MEANS)

References

Download predicates docs: <https://www.gbif.org/developer/occurrence#predicates>

See Also

Other downloads: [occ_download_cached\(\)](#), [occ_download_cancel\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_datasets\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_meta\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```

pred("taxonKey", 3119195)
pred_gt("elevation", 5000)
pred_gte("elevation", 5000)
pred_lt("elevation", 1000)
pred_lte("elevation", 1000)
pred_within("POLYGON((-14 42, 9 38, -7 26, -14 42))")
pred_and(pred_within("POLYGON((-14 42, 9 38, -7 26, -14 42))"),
  pred_gte("elevation", 5000))
pred_or(pred_lte("year", 1989), pred("year", 2000))
pred_and(pred_lte("year", 1989), pred("year", 2000))
pred_in("taxonKey", c(2977832, 2977901, 2977966, 2977835))
pred_in("basisOfRecord", c("MACHINE_OBSERVATION", "HUMAN_OBSERVATION"))
pred_not(pred("taxonKey", 729))
pred_like("catalogNumber", "PAPS5-560%")
pred_notnull("issue")
pred("basisOfRecord", "LITERATURE")
pred("hasCoordinate", TRUE)
pred("hasGeospatialIssue", FALSE)
pred_within("POLYGON((-14 42, 9 38, -7 26, -14 42))")
pred_or(pred("taxonKey", 2977832), pred("taxonKey", 2977901),
  pred("taxonKey", 2977966))
pred_in("taxonKey", c(2977832, 2977901, 2977966, 2977835))

```

elevation *Get elevation for lat/long points from a data.frame or list of points.*

Description

Uses the GeoNames web service

Usage

```
elevation(
  input = NULL,
  latitude = NULL,
  longitude = NULL,
  latlong = NULL,
  elevation_model = "srtm3",
  username = Sys.getenv("GEONAMES_USER"),
  key,
  curlopts,
  ...
)
```

Arguments

input	A data.frame of lat/long data. There must be columns decimalLatitude and decimalLongitude.
latitude	A vector of latitude's. Must be the same length as the longitude vector.
longitude	A vector of longitude's. Must be the same length as the latitude vector.
latlong	A vector of lat/long pairs. See examples.
elevation_model	(character) one of srtm3 (default), srtm1, astergdem, or gtopo30. See "Elevation models" below for more
username	(character) Required. An GeoNames user name. See Details.
key, curlopts	defunct. see docs
...	curl options passed on to curl::verb-GET see curl::curl_options() for curl options

Value

A new column named `elevation_geonames` in the supplied data.frame or a vector with elevation of each location in meters. Note that data from GBIF can already have a column named `elevation`, thus the column we add is named differently.

GeoNames user name

To get a GeoNames user name, register for an account at <http://www.geonames.org/login> - then you can enable your account for the GeoNames webservice on your account page. Once you are enabled to use the webservice, you can pass in your username to the username parameter. Better yet, store your username in your `.Renvi` file, or similar (e.g., `.zshrc` or `.bash_profile` files) and read it in via `Sys.getenv()` as in the examples below. By default we do `Sys.getenv("GEONAMES_USER")` for the username parameter.

Elevation models

- `srtm3`:
 - sample area: ca 90m x 90m
 - result: a single number giving the elevation in meters according to `srtm3`, ocean areas have been masked as "no data" and have been assigned a value of -32768
- `srtm1`:
 - sample area: ca 30m x 30m
 - result: a single number giving the elevation in meters according to `srtm1`, ocean areas have been masked as "no data" and have been assigned a value of -32768
- `astergdem` (Aster Global Digital Elevation Model V2 2011):
 - sample area: ca 30m x 30m, between 83N and 65S latitude
 - result: a single number giving the elevation in meters according to `aster gdem`, ocean areas have been masked as "no data" and have been assigned a value of -32768
- `gtopo30`:
 - sample area: ca 1km x 1km
 - result: a single number giving the elevation in meters according to `gtopo30`, ocean areas have been masked as "no data" and have been assigned a value of -9999

References

GeoNames <http://www.geonames.org/export/web-services.html>

Examples

```
## Not run:
user <- Sys.getenv("GEONAMES_USER")

occ_key <- name_suggest('Puma concolor')$key[1]
dat <- occ_search(taxonKey = occ_key, limit = 300, hasCoordinate = TRUE)
head( elevation(dat$data, username = user) )

# Pass in a vector of lat's and a vector of long's
elevation(latitude = dat$data$decimalLatitude[1:10],
           longitude = dat$data$decimalLongitude[1:10],
           username = user, verbose = TRUE)

# Pass in lat/long pairs in a single vector
pairs <- list(c(31.8496,-110.576060), c(29.15503,-103.59828))
```

```
elevation(latlong=pairs, username = user)

# Pass on curl options
pairs <- list(c(31.8496,-110.576060), c(29.15503,-103.59828))
elevation(latlong=pairs, username = user, verbose = TRUE)

# different elevation models
lats <- dat$data$decimalLatitude[1:5]
lons <- dat$data$decimalLongitude[1:5]
elevation(latitude = lats, longitude = lons, elevation_model = "srtm3")
elevation(latitude = lats, longitude = lons, elevation_model = "srtm1")
elevation(latitude = lats, longitude = lons, elevation_model = "astergdem")
elevation(latitude = lats, longitude = lons, elevation_model = "gtopo30")

## End(Not run)
```

enumeration

Enumerations.

Description

Many parts of the GBIF API make use of enumerations, i.e. controlled vocabularies for specific topics - and are available via these functions

Usage

```
enumeration(x = NULL, curlopts = list())
```

```
enumeration_country(curlopts = list())
```

Arguments

x	A given enumeration.
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

enumeration returns a character vector, while enumeration_country returns a data.frame.

Examples

```
## Not run:
# basic enumeration
enumeration()
enumeration("NameType")
enumeration("MetadataType")
enumeration("TypeStatus")
```

```
# country enumeration
enumeration_country()

# curl options
enumeration(curlopts = list(verbose=TRUE))

## End(Not run)
```

gbif_bbox2wkt	<i>Convert a bounding box to a Well Known Text polygon, and a WKT to a bounding box</i>
---------------	---

Description

Convert a bounding box to a Well Known Text polygon, and a WKT to a bounding box

Usage

```
gbif_bbox2wkt(minx = NA, miny = NA, maxx = NA, maxy = NA, bbox = NULL)

gbif_wkt2bbox(wkt = NULL)
```

Arguments

minx	(numeric) Minimum x value, or the most western longitude
miny	(numeric) Minimum y value, or the most southern latitude
maxx	(numeric) Maximum x value, or the most eastern longitude
maxy	(numeric) Maximum y value, or the most northern latitude
bbox	(numeric) A vector of length 4, with the elements: minx, miny, maxx, maxy
wkt	(character) A Well Known Text object.

Value

gbif_bbox2wkt returns an object of class `character`, a Well Known Text string of the form `'POLYGON((minx miny, maxx miny, maxx maxy, minx maxy, minx miny))'`.

gbif_wkt2bbox returns a numeric vector of length 4, like `c(minx, miny, maxx, maxy)`

Examples

```
## Not run:
# Convert a bounding box to a WKT
## Pass in a vector of length 4 with all values
gbif_bbox2wkt(bbox=c(-125.0,38.4,-121.8,40.9))

## Or pass in each value separately
gbif_bbox2wkt(minx=-125.0, miny=38.4, maxx=-121.8, maxy=40.9)
```

```
# Convert a WKT object to a bounding box
wkt <- "POLYGON((-125 38.4,-125 40.9,-121.8 40.9,-121.8 38.4,-125 38.4))"
gbif_wkt2bbox(wkt)

## End(Not run)
```

gbif_citation

Get citation for datasets used

Description

Get citation for datasets used

Usage

```
gbif_citation(x)
```

Arguments

x (character) Result of call to `occ_search()`, `occ_data()`, `occ_download_get()`, `occ_download_meta()`, a dataset key, or occurrence key (character or numeric)

Details

Returns a set of citations, one for each dataset. We pull out unique dataset keys and get citations, so the length of citations may not be equal to the number of records you pass in.

Currently, this function gives back citations at the dataset level, not at the individual occurrence level. If occurrence keys are passed in, then we track down the dataset the key is from, and get the citation for the dataset.

Value

list with S3 class assigned, used by a print method to pretty print citation information. Though you can unclass the output or just index to the named items as needed.

Examples

```
## Not run:
res1 <- occ_search(taxonKey=9206251, limit=2)
(xx <- gbif_citation(res1))

# each individual citation object is a list
## rights and/or citation may be NULL
xx[[1]]
xx[[1]]$rights
xx[[1]]$citation
xx[[1]]$citation$title
xx[[1]]$citation$text
xx[[1]]$citation$accessed
```



```

xx[[1]]$citation$citation

## access many citations
unlist(lapply(xx, "[", c("citation", "citation")))

res2 <- occ_search(datasetKey='7b5d6a48-f762-11e1-a439-00145eb45e9a',
limit=20)
(xx <- gbif_citation(res2))

# if no datasetKey field included, we attempt to identify the dataset
## key field included - still works
res3 <- occ_search(taxonKey=9206251, fields=c('name','basisOfRecord','key'),
limit=20)
(xx <- gbif_citation(res3))
## key field not included - errors
# res3 <- occ_search(taxonKey=9206251, fields=c('name','basisOfRecord','
# protocol'), limit=20)
# (xx <- gbif_citation(res3))

# occ_data
res1 <- occ_data(taxonKey=9206251, limit=2)
(xx <- gbif_citation(res1))

# character class inputs
## pass in a dataset key
gbif_citation(x='0ec3229f-2b53-484e-817a-de8ceb1fce2b')
## pass in an occurrence key
# gbif_citation(x='1101144669')

# pass in an occurrence key as a numeric (won't work for a dataset key)
# gbif_citation(x=1101144669)

# Downloads
## occ_download_get()
# d1 <- occ_download(pred("country", "BG"), pred_gte("year", 2020))
# occ_download_meta(d1) # wait until status = succeeded
# d1 <- occ_download_get(d1, overwrite = TRUE)
# gbif_citation(d1)

## occ_download_meta()
# key <- "0000122-171020152545675"
# res <- occ_download_meta(key)
# gbif_citation(res)

## End(Not run)

```

Description

Returns a data.frame of all GBIF issues with the following columns:

- code: issue short code, e.g. gass84
- code: issue full name, e.g. GEODETIC_DATUM_ASSUMED_WGS84
- description: issue description
- type: issue type, either related to occurrence or name

Usage

```
gbif_issues()
```

Source

<https://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/OccurrenceIssue.html> <https://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/NameUsageIssue.html>

gbif_issues_lookup *Lookup issue definitions and short codes*

Description

Lookup issue definitions and short codes

Usage

```
gbif_issues_lookup(issue = NULL, code = NULL)
```

Arguments

issue	Full name of issue, e.g. CONTINENT_COUNTRY_MISMATCH
code	An issue short code, e.g. 'ccm'

Examples

```
gbif_issues_lookup(issue = 'CONTINENT_COUNTRY_MISMATCH')
gbif_issues_lookup(code = 'ccm')
gbif_issues_lookup(issue = 'COORDINATE_INVALID')
gbif_issues_lookup(code = 'cdiv')
```

gbif_names	<i>View highlighted terms in name results from GBIF.</i>
------------	--

Description

View highlighted terms in name results from GBIF.

Usage

```
gbif_names(input, output = NULL, browse = TRUE)
```

Arguments

input	Input output from occ_search
output	Output folder path. If not given uses temporary folder.
browse	(logical) Browse output (default: TRUE)

Examples

```
## Not run:  
# browse=FALSE returns path to file  
gbif_names(name_lookup(query='snake', hl=TRUE), browse=FALSE)  
  
(out <- name_lookup(query='canada', hl=TRUE, limit=5))  
gbif_names(out)  
gbif_names(name_lookup(query='snake', hl=TRUE))  
gbif_names(name_lookup(query='bird', hl=TRUE))  
  
# or not highlight  
gbif_names(name_lookup(query='bird', limit=200))  
  
## End(Not run)
```

gbif_oai	<i>GBIF registry data via OAI-PMH</i>
----------	---------------------------------------

Description

GBIF registry data via OAI-PMH

Usage

```

gbif_oai_identify(...)

gbif_oai_list_identifiers(
  prefix = "oai_dc",
  from = NULL,
  until = NULL,
  set = NULL,
  token = NULL,
  as = "df",
  ...
)

gbif_oai_list_records(
  prefix = "oai_dc",
  from = NULL,
  until = NULL,
  set = NULL,
  token = NULL,
  as = "df",
  ...
)

gbif_oai_list_metadataformats(id = NULL, ...)

gbif_oai_list_sets(token = NULL, as = "df", ...)

gbif_oai_get_records(ids, prefix = "oai_dc", as = "parsed", ...)

```

Arguments

...	Curl options passed on to <code>httr::GET</code>
prefix	(character) A string to specify the metadata format in OAI-PMH requests issued to the repository. The default ("oai_dc") corresponds to the mandatory OAI unqualified Dublin Core metadata schema.
from	(character) string giving datestamp to be used as lower bound for datestamp-based selective harvesting (i.e., only harvest records with datestamps in the given range). Dates and times must be encoded using ISO 8601. The trailing Z must be used when including time. OAI-PMH implies UTC for data/time specifications.
until	(character) Datestamp to be used as an upper bound, for datestamp-based selective harvesting (i.e., only harvest records with datestamps in the given range).
set	(character) A set to be used for selective harvesting (i.e., only harvest records in the given set).
token	(character) a token previously provided by the server to resume a request where it last left off. 50 is max number of records returned. We will loop for you internally to get all the records you asked for.

`as` (character) What to return. One of "df" (for data.frame; default), "list" (get a list), or "raw" (raw text). For `gbif_oai_get_records`, one of "parsed" or "raw"

`id, ids` (character) The OAI-PMH identifier for the record. Optional.

Details

These functions only work with GBIF registry data, and do so via the OAI-PMH protocol (<https://www.openarchives.org/OAI/>)

Value

raw text, list or data.frame, depending on requested output via `as` parameter

Examples

```
## Not run:
gbif_oai_identify()

today <- format(Sys.Date(), "%Y-%m-%d")
gbif_oai_list_identifiers(from = today)
gbif_oai_list_identifiers(set = "country:NL")

gbif_oai_list_records(from = today)
gbif_oai_list_records(set = "country:NL")

gbif_oai_list_metadataformats()
gbif_oai_list_metadataformats(id = "9c4e36c1-d3f9-49ce-8ec1-8c434fa9e6eb")

gbif_oai_list_sets()
gbif_oai_list_sets(as = "list")

gbif_oai_get_records("9c4e36c1-d3f9-49ce-8ec1-8c434fa9e6eb")
ids <- c("9c4e36c1-d3f9-49ce-8ec1-8c434fa9e6eb",
        "e0f1bb8a-2d81-4b2a-9194-d92848d3b82e")
gbif_oai_get_records(ids)

## End(Not run)
```

`gbif_photos`

View photos from GBIF.

Description

View photos from GBIF.

Usage

```
gbif_photos(input, output = NULL, which = "table", browse = TRUE)
```

Arguments

input	Input output from occ_search
output	Output folder path. If not given uses temporary folder.
which	One of map or table (default).
browse	(logical) Browse output (default: TRUE)

Details

The max number of photos you can see when which="map" is ~160, so cycle through if you have more than that.

BEWARE

The maps in the table view may not show up correctly if you are using RStudio

Examples

```
## Not run:
res <- occ_search(mediaType = 'StillImage', limit = 100)
gbif_photos(res)
gbif_photos(res, which='map')

res <- occ_search(scientificName = "Aves", mediaType = 'StillImage',
  limit=150)
gbif_photos(res)
gbif_photos(res, output = '~/barfoo')

## End(Not run)
```

installations

Installations metadata.

Description

Installations metadata.

Usage

```
installations(
  data = "all",
  uuid = NULL,
  query = NULL,
  identifier = NULL,
  identifierType = NULL,
  limit = 100,
  start = NULL,
  curlopts = list()
)
```

Arguments

data	The type of data to get. One or more of: 'contact', 'endpoint', 'dataset', 'comment', 'deleted', 'nonPublishing', or the special 'all'. Default: 'all'
uuid	UUID of the data node provider. This must be specified if data is anything other than 'all'.
query	Query nodes. Only used when data='all'. Ignored otherwise.
identifier	The value for this parameter can be a simple string or integer, e.g. identifier=120. This parameter doesn't seem to work right now.
identifierType	Used in combination with the identifier parameter to filter identifiers by identifier type. See details. This parameter doesn't seem to work right now.
limit	Number of records to return. Default: 100. Maximum: 1000.
start	Record number to start at. Default: 0. Use in combination with limit to page through results.
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Details

identifierType options:

- DOI No description.
- FTP No description.
- GBIF_NODE Identifies the node (e.g: DK for Denmark, sp2000 for Species 2000).
- GBIF_PARTICIPANT Participant identifier from the GBIF IMS Filemaker system.
- GBIF_PORTAL Indicates the identifier originated from an auto_increment column in the portal.data_provider or portal.data_resource table respectively.
- HANDLER No description.
- LSID Reference controlled by a separate system, used for example by DOI.
- SOURCE_ID No description.
- UNKNOWN No description.
- URI No description.
- URL No description.
- UUID No description.

References

<https://www.gbif.org/developer/registry#installations>

Examples

```
## Not run:
installations(limit=5)
installations(query="france", limit = 25)
installations(uuid="b77901f9-d9b0-47fa-94e0-dd96450aa2b4")
installations(data='contact', uuid="2e029a0c-87af-42e6-87d7-f38a50b78201")
installations(data='endpoint', uuid="b77901f9-d9b0-47fa-94e0-dd96450aa2b4")
installations(data='dataset', uuid="b77901f9-d9b0-47fa-94e0-dd96450aa2b4")
installations(data='deleted', limit = 25)
installations(data='deleted', limit=2)
installations(data=c('deleted','nonPublishing'), limit=2)
installations(identifierType='DOI', limit=2)

# Pass on curl options
installations(data='deleted', curlopts = list(verbose=TRUE))

## End(Not run)
```

isocodes

Table of country two character ISO codes, and GBIF names

Description

- code. Two character ISO country code.
- name. Name of country.
- gbif_name. Name of country used by GBIF - this is the name you want to use when searching by country in this package.

many-values

Many value inputs to some parameters

Description

Many value inputs to some parameters

Details

There are some differences in how functions across **rgbif** behave with respect to many values given to a single parameter (let's call it foo).

The following functions originally only iterated over many values passed to foo as a vector (e.g., `foo = c(1,2)`) with completely separate HTTP requests. But now these functions also support passing in many values to the same HTTP request (e.g., `foo = "1;2"`). This is a bit awkward, but means that we don't break existing code. See "Multiple values passed to a parameter" in `occ_search/occ_data` for more information.

- `occ_search()`
- `occ_data()`

The following functions, unlike those above, only support passing in many values to the same HTTP request, which is done like `foo = c("1", "2")`.

- `dataset_search()`
- `dataset_suggest()`
- `name_lookup()`
- `name_suggest()`
- `name_usage()`

Last, some parameters in the functions above don't accept more than one, and some functions don't have any parameters that accept more than one value (i.e., none of those listed above).

Each function that has at least some parameters that accept many values also has documentation on this issue.

map_fetch

Fetch aggregated density maps of GBIF occurrences

Description

This function is a wrapper for the GBIF mapping api version 2.0. The mapping API is a web map tile service making it straightforward to visualize GBIF content on interactive maps, and overlay content from other sources. It returns tile maps with number of GBIF records per area unit that can be used in a variety of ways, for example in interactive leaflet web maps. Map details are specified by a number of query parameters, some of them optional. Full documentation of the GBIF mapping api can be found at <https://www.gbif.org/developer/maps>

Usage

```
map_fetch(  
  source = "density",  
  x = 0,  
  y = 0,  
  z = 0,  
  format = "@1x.png",  
  srs = "EPSG:4326",  
  bin = NULL,  
  hexPerTile = NULL,  
  squareSize = NULL,  
  style = "classic.point",  
  taxonKey = NULL,  
  datasetKey = NULL,  
  country = NULL,  
  publishingOrg = NULL,
```

```

publishingCountry = NULL,
year = NULL,
basisOfRecord = NULL,
...
)

```

Arguments

source	(character) Either density for fast, precalculated tiles, or adhoc for any search. Default: density
x	(integer) the column. Default: 0
y	(integer) the row. Default: 0
z	(integer) the zoom. Default: 0
format	(character) The data format, one of: <ul style="list-style-type: none"> • @Hx.png for a 256px raster tile • @1x.png for a 512px raster tile (the default) • @2x.png for a 1024px raster tile • @3x.png for a 2048px raster tile • @4x.png for a 4096px raster tile
srs	(character) Spatial reference system. One of: <ul style="list-style-type: none"> • EPSG: 3857 (Web Mercator) • EPSG: 4326 (WGS84 plate care?) • EPSG: 3575 (Arctic LAEA on 10 degrees E) • EPSG: 3031 (Antarctic stereographic)
bin	(character) square or hex to aggregate occurrence counts into squares or hexagons. Points by default. optional
hexPerTile	(integer) sets the size of the hexagons (the number horizontally across a tile). optional
squareSize	(integer) sets the size of the squares. Choose a factor of 4096 so they tessellate correctly: probably from 8, 16, 32, 64, 128, 256, 512. optional
style	(character) for raster tiles, choose from the available styles. Defaults to classic.point. optional. THESE DON'T WORK YET.
taxonKey	(integer/numeric/character) search by taxon key, can only supply 1. optional
datasetKey	(character) search by taxon key, can only supply 1. optional
country	(character) search by taxon key, can only supply 1. optional
publishingOrg	(character) search by taxon key, can only supply 1. optional
publishingCountry	(character) search by taxon key, can only supply 1. optional
year	(integer) integer that limits the search to a certain year or, if passing a vector of integers, multiple years, for example 1984 or c(2016, 2017, 2018) or 2010:2015 (years 2010 to 2015). optional
basisOfRecord	(character) one or more basis of record states to include records with that basis of record. The full list is: c("OBSERVATION", "HUMAN_OBSERVATION", "MACHINE_OBSERVATION", "MATERIAL"). optional
...	curl options passed on to curl::HttpClient

Details

This function uses the arguments passed on to generate a query to the GBIF web map API. The API returns a web tile object as png that is read and converted into an R raster object. The break values or nbreaks generate a custom colour palette for the web tile, with each bin corresponding to one grey value. After retrieval, the raster is reclassified to the actual break values. This is a somewhat hacky but nonetheless functional solution in the absence of a GBIF raster API implementation.

We add extent and set the projection for the output. You can reproject after retrieving the output.

Value

an object of class RasterLayer

Note

Styles don't work yet, sorry, we'll try to fix it asap.

Author(s)

Laurens Geffert <laurensgeffert@gmail.com>

References

<https://www.gbif.org/developer/maps>

See Also

[mvt_fetch\(\)](#)

Examples

```
## Not run:
if (
  requireNamespace("png", quietly = TRUE) &&
  requireNamespace("raster", quietly = TRUE)
) {
  x <- map_fetch(taxonKey = 2480498, year = 2007:2011)
  x
  # gives a RasterLayer object
  class(x)
  # visualize
  library(raster)
  plot(x)

  # different srs
  ## 3857
  y <- map_fetch(taxonKey = 2480498, year = 2010, srs = "EPSG:3857")
  plot(y)
  ## 3031
  z <- map_fetch(taxonKey = 2480498, year = 2010, srs = "EPSG:3031", verbose = TRUE)
  plot(z)
  # 3575
```

```

z <- map_fetch(taxonKey = 2480498, year = 2010, srs = "EPSG:3575")
plot(z)

# bin
plot(map_fetch(taxonKey = 212, year = 1998, bin = "hex",
  hexPerTile = 30, style = "classic-noborder.poly"))

# styles
plot(map_fetch(taxonKey = 2480498, style = "purpleYellow.point"))

# query with basisOfRecord
map_fetch(taxonKey = 2480498, year = 2010,
  basisOfRecord = "HUMAN_OBSERVATION")
map_fetch(taxonKey = 2480498, year = 2010,
  basisOfRecord = c("HUMAN_OBSERVATION", "LIVING_SPECIMEN"))
}

## End(Not run)

```

mvt_fetch

Fetch Map Vector Tiles (MVT)

Description

This function is a wrapper for the GBIF mapping api version 2.0. The mapping API is a web map tile service making it straightforward to visualize GBIF content on interactive maps, and overlay content from other sources. It returns maps vector tiles with number of GBIF records per area unit that can be used in a variety of ways, for example in interactive leaflet web maps. Map details are specified by a number of query parameters, some of them optional. Full documentation of the GBIF mapping api can be found at <https://www.gbif.org/developer/maps>

Usage

```

mvt_fetch(
  source = "density",
  x = 0,
  y = 0,
  z = 0,
  srs = "EPSG:4326",
  bin = NULL,
  hexPerTile = NULL,
  squareSize = NULL,
  style = "classic.point",
  taxonKey = NULL,
  datasetKey = NULL,
  country = NULL,
  publishingOrg = NULL,
  publishingCountry = NULL,

```

```

    year = NULL,
    basisOfRecord = NULL,
    ...
)

```

Arguments

source	(character) Either density for fast, precalculated tiles, or adhoc for any search. Default: density
x	(integer) the column. Default: 0
y	(integer) the row. Default: 0
z	(integer) the zoom. Default: 0
srs	(character) Spatial reference system for the output (input srs for mvt from GBIF is always EPSG:3857). One of: <ul style="list-style-type: none"> • EPSG:3857 (Web Mercator) • EPSG:4326 (WGS84 plate care?) • EPSG:3575 (Arctic LAEA on 10 degrees E) • EPSG:3031 (Antarctic stereographic)
bin	(character) square or hex to aggregate occurrence counts into squares or hexagons. Points by default. optional
hexPerTile	(integer) sets the size of the hexagons (the number horizontally across a tile). optional
squareSize	(integer) sets the size of the squares. Choose a factor of 4096 so they tessalate correctly: probably from 8, 16, 32, 64, 128, 256, 512. optional
style	(character) for raster tiles, choose from the available styles. Defaults to classic.point. optional. THESE DON'T WORK YET.
taxonKey	(integer/numeric/character) search by taxon key, can only supply 1. optional
datasetKey	(character) search by taxon key, can only supply 1. optional
country	(character) search by taxon key, can only supply 1. optional
publishingOrg	(character) search by taxon key, can only supply 1. optional
publishingCountry	(character) search by taxon key, can only supply 1. optional
year	(integer) integer that limits the search to a certain year or, if passing a vector of integers, multiple years, for example 1984 or c(2016,2017,2018) or 2010:2015 (years 2010 to 2015). optional
basisOfRecord	(character) one or more basis of record states to include records with that basis of record. The full list is: c("OBSERVATION", "HUMAN_OBSERVATION", "MACHINE_OBSERVATION", "MATERIAL") optional
...	curl options passed on to curl::HttpClient

Details

This function uses the arguments passed on to generate a query to the GBIF web map API. The API returns a web tile object as png that is read and converted into an R raster object. The break values or nbreaks generate a custom colour palette for the web tile, with each bin corresponding to one grey value. After retrieval, the raster is reclassified to the actual break values. This is a somewhat hacky but nonetheless functional solution in the absence of a GBIF raster API implementation.

We add extent and set the projection for the output. You can reproject after retrieving the output.

Value

an sf object

References

<https://www.gbif.org/developer/maps>

See Also

[map_fetch\(\)](#)

Examples

```
## Not run:
if (
  requireNamespace("sf", quietly = TRUE) &&
  requireNamespace("protolite", quietly = TRUE)
) {
  x <- mvt_fetch(taxonKey = 2480498, year = 2007:2011)
  x

  # gives an sf object
  class(x)

  # different srs
  ## 3857
  y <- mvt_fetch(taxonKey = 2480498, year = 2010, srs = "EPSG:3857")
  y
  ## 3031
  z <- mvt_fetch(taxonKey = 2480498, year = 2010, srs = "EPSG:3031", verbose = TRUE)
  z
  # 3575
  z <- mvt_fetch(taxonKey = 2480498, year = 2010, srs = "EPSG:3575")
  z

  # bin
  x <- mvt_fetch(taxonKey = 212, year = 1998, bin = "hex",
    hexPerTile = 30, style = "classic-noborder.poly")
  x

  # query with basisOfRecord
  mvt_fetch(taxonKey = 2480498, year = 2010,
```

```
basisOfRecord = "HUMAN_OBSERVATION")
mvt_fetch(taxonKey = 2480498, year = 2010,
  basisOfRecord = c("HUMAN_OBSERVATION", "LIVING_SPECIMEN"))
}

## End(Not run)
```

name_backbone	<i>Lookup names in the GBIF backbone taxonomy.</i>
---------------	--

Description

Lookup names in the GBIF backbone taxonomy.

Usage

```
name_backbone(
  name,
  rank = NULL,
  kingdom = NULL,
  phylum = NULL,
  class = NULL,
  order = NULL,
  family = NULL,
  genus = NULL,
  strict = FALSE,
  verbose = NULL,
  start = NULL,
  limit = 100,
  curlopts = list()
)

name_backbone_verbose(
  name,
  rank = NULL,
  kingdom = NULL,
  phylum = NULL,
  class = NULL,
  order = NULL,
  family = NULL,
  genus = NULL,
  strict = FALSE,
  start = NULL,
  limit = 100,
  curlopts = list()
)
```

Arguments

name	(character) Full scientific name potentially with authorship (required)
rank	(character) The rank given as our rank enum. (optional)
kingdom	(character) If provided default matching will also try to match against this if no direct match is found for the name alone. (optional)
phylum	(character) If provided default matching will also try to match against this if no direct match is found for the name alone. (optional)
class	(character) If provided default matching will also try to match against this if no direct match is found for the name alone. (optional)
order	(character) If provided default matching will also try to match against this if no direct match is found for the name alone. (optional)
family	(character) If provided default matching will also try to match against this if no direct match is found for the name alone. (optional)
genus	(character) If provided default matching will also try to match against this if no direct match is found for the name alone. (optional)
strict	(logical) If TRUE it (fuzzy) matches only the given name, but never a taxon in the upper classification (optional)
verbose	(logical) Defunct. See function name_backbone_verbose()
start	Record number to start at. Default: 0. Use in combination with limit to page through results.
limit	Number of records to return. Default: 100. Maximum: 1000.
curlopts	list of named curl options passed on to <code>HttpClient</code> . see <code>curl::curl_options</code> for curl options

Details

If you don't get a match, GBIF gives back a data.frame with columns synonym, confidence, and matchType='NONE'.

Value

For name_backbone, a data.frame for a single taxon with many columns. For name_backbone_verbose a list of length two (data and alternatives), first data.frame for the suggested taxon match, and a data.frame with alternative name suggestions resulting from fuzzy matching

References

<https://www.gbif.org/developer/species#searching>

Examples

```
## Not run:
name_backbone(name='Helianthus annuus', kingdom='plants')
name_backbone(name='Helianthus', rank='genus', kingdom='plants')
name_backbone(name='Poa', rank='genus', family='Poaceae')
```



```

# Verbose - gives back alternatives
## Strictness
name_backbone_verbose(name='Poa', kingdom='plants',
  strict=FALSE)
name_backbone_verbose(name='Helianthus annuus', kingdom='plants',
  strict=TRUE)

# Non-existent name - returns list of length 3 stating no match
name_backbone(name='Aso')
name_backbone(name='Oenante')

# Pass on curl options
name_backbone(name='Oenante', curlopts = list(verbose=TRUE))

## End(Not run)

```

name_issues

Parse and examine further GBIF name issues on a dataset.

Description

Parse and examine further GBIF name issues on a dataset.

Usage

```
name_issues(.data, ..., mutate = NULL)
```

Arguments

.data	Output from a call to name_usage()
...	Named parameters to only get back (e.g. bbmn), or to remove (e.g. -bbmn).
mutate	(character) One of: <ul style="list-style-type: none"> split Split issues into new columns. expand Expand issue abbreviated codes into descriptive names. for downloads datasets, this is not super useful since the issues come to you as expanded already. split_expand Split into new columns, and expand issue names.

For split and split_expand, values in cells become y ("yes") or n ("no")

References

<https://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/NameUsageIssue.html>

Examples

```
## Not run:
# what do issues mean, can print whole table
head(gbif_issues())
# or just name related issues
gbif_issues()[which(gbif_issues()$type %in% c("name")),]
# or search for matches
gbif_issues()[gbif_issues()$code %in% c('bbmn','clasna','scina'),]
# compare out data to after name_issues use
(aa <- name_usage(name = "Lupus"))
aa %>% name_issues("clasna")

## or parse issues in various ways
### remove data rows with certain issue classes
aa %>% name_issues(-clasna, -scina)

### expand issues to more descriptive names
aa %>% name_issues(mutate = "expand")

### split and expand
aa %>% name_issues(mutate = "split_expand")

### split, expand, and remove an issue class
aa %>% name_issues(-bbmn, mutate = "split_expand")

## Or you can use name_issues without %>%
name_issues(aa, -bbmn, mutate = "split_expand")

## End(Not run)
```

name_lookup

Lookup names in all taxonomies in GBIF.

Description

This service uses fuzzy lookup so that you can put in partial names and you should get back those things that match. See examples below.

Faceting: If facet=FALSE or left to the default (NULL), no faceting is done. And therefore, all parameters with facet in their name are ignored (facetOnly, facetMincount, facetMultiselect).

Usage

```
name_lookup(
  query = NULL,
  rank = NULL,
  higherTaxonKey = NULL,
  status = NULL,
  isExtinct = NULL,
```

```

    habitat = NULL,
    nameType = NULL,
    datasetKey = NULL,
    origin = NULL,
    nomenclaturalStatus = NULL,
    limit = 100,
    start = 0,
    facet = NULL,
    facetMincount = NULL,
    facetMultiselect = NULL,
    type = NULL,
    hl = NULL,
    issue = NULL,
    verbose = FALSE,
    return = NULL,
    curlopts = list()
)

```

Arguments

query	Query term(s) for full text search.
rank	CLASS, CULTIVAR, CULTIVAR_GROUP, DOMAIN, FAMILY, FORM, GENUS, INFORMAL, INFRAGENERIC_NAME, INFRAORDER, INFRASPECIFIC_NAME, INFRASUBSPECIFIC_NAME, KINGDOM, ORDER, PHYLUM, SECTION, SERIES, SPECIES, STRAIN, SUBCLASS, SUBFAMILY, SUBFORM, SUBGENUS, SUBKINGDOM, SUBORDER, SUBPHYLUM, SUBSECTION, SUBSERIES, SUBSPECIES, SUBTRIBE, SUBVARIETY, SUPERCLASS, SUPERFAMILY, SUPERORDER, SUPERPHYLUM, SUPRAGENERIC_NAME, TRIBE, UNRANKED, VARIETY
higherTaxonKey	Filters by any of the higher Linnean rank keys. Note this is within the respective checklist and not searching nub keys across all checklists. This parameter accepts many inputs in a vector (passed in the same request).
status	Filters by the taxonomic status as one of: <ul style="list-style-type: none"> • ACCEPTED • DETERMINATION_SYNONYM Used for unknown child taxa referred to via spec, ssp, ... • DOUBTFUL Treated as accepted, but doubtful whether this is correct. • HETEROTYPIC_SYNONYM More specific subclass of SYNONYM. • HOMOTYPIC_SYNONYM More specific subclass of SYNONYM. • INTERMEDIATE_RANK_SYNONYM Used in nub only. • MISAPPLIED More specific subclass of SYNONYM. • PROPORTE_SYNONYM More specific subclass of SYNONYM. • SYNONYM A general synonym, the exact type is unknown.
isExtinct	(logical) Filters by extinction status (e.g. isExtinct=TRUE)
habitat	(character) Filters by habitat. One of: marine, freshwater, or terrestrial
nameType	Filters by the name type as one of:

- BLACKLISTED surely not a scientific name.
- CANDIDATUS Candidatus is a component of the taxonomic name for a bacterium that cannot be maintained in a Bacteriology Culture Collection.
- CULTIVAR a cultivated plant name.
- DOUBTFUL doubtful whether this is a scientific name at all.
- HYBRID a hybrid formula (not a hybrid name).
- INFORMAL a scientific name with some informal addition like "cf." or indetermined like *Abies spec.*
- SCINAME a scientific name which is not well formed.
- VIRUS a virus name.
- WELLFORMED a well formed scientific name according to present nomenclatural rules.

datasetKey	Filters by the dataset's key (a uuid)
origin	(character) Filters by origin. One of: <ul style="list-style-type: none"> • SOURCE • DENORMED_CLASSIFICATION • VERBATIM_ACCEPTED • EX_AUTHOR_SYNONYM • AUTONYM • BASIONYM_PLACEHOLDER • MISSING_ACCEPTED • IMPLICIT_NAME • PROPORTE • VERBATIM_BASIONYM
nomenclaturalStatus	Not yet implemented, but will eventually allow for filtering by a nomenclatural status enum.
limit	Number of records to return. Hard maximum limit set by GBIF API: 99999.
start	Record number to start at. Default: 0.
facet	A vector/list of facet names used to retrieve the 100 most frequent values for a field. Allowed facets are: datasetKey, higherTaxonKey, rank, status, isExtinct, habitat, and nameType. Additionally threat and nomenclaturalStatus are legal values but not yet implemented, so data will not yet be returned for them.
facetMincount	Used in combination with the facet parameter. Set facetMincount=# to exclude facets with a count less than #, e.g. http://bit.ly/2osAUQB only shows the type values 'CHECKLIST' and 'OCCURRENCE' because the other types have counts less than 10000
facetMultiselect	(logical) Used in combination with the facet parameter. Set facetMultiselect=TRUE to still return counts for values that are not currently filtered, e.g. http://bit.ly/2JAymaC still shows all type values even though type is being filtered by type=CHECKLIST.
type	Type of name. One of occurrence, checklist, or metadata.

hl	(logical) Set hl=TRUE to highlight terms matching the query when in fulltext search fields. The highlight will be an emphasis tag of class gbifH1 e.g. query='plant',hl=TRUE. Fulltext search fields include: title, keyword, country, publishing country, publishing organization title, hosting organization title, and description. One additional full text field is searched which includes information from metadata documents, but the text of this field is not returned in the response.
issue	Filters by issue. Issue has to be related to names. Type gbif_issues() to get complete list of issues.
verbose	(logical) If TRUE, all data is returned as a list for each element. If FALSE (default) a subset of the data that is thought to be most essential is organized into a data.frame.
return	Defunct. All components are returned; index to the one(s) you want
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

An object of class gbif, which is a S3 class list, with slots for metadata (meta), the data itself (data), the taxonomic hierarchy data (hierarchies), and vernacular names (names). In addition, the object has attributes listing the user supplied arguments and type of search, which is, differently from occurrence data, always equals to 'single' even if multiple values for some parameters are given. meta is a list of length four with offset, limit, endOfRecords and count fields. data is a tibble (aka data.frame) containing all information about the found taxa. hierarchies is a list of data.frame's, one per GBIF key (taxon), containing its taxonomic classification. Each data.frame contains two columns: rankkey and name. names returns a list of data.frame's, one per GBIF key (taxon), containing all vernacular names. Each data.frame contains two columns: vernacularName and language.

A list of length five:

- **metadata**
- **data**: either a data.frame (verbose=FALSE, default) or a list (verbose=TRUE).
- **facets**
- **hierarchies**
- **names**

Repeat parameter inputs

Some parameters can take many inputs, and treated as 'OR' (e.g., a or b or c). The following take many inputs:

- **rank**
- **higherTaxonKey**
- **status**
- **habitat**
- **nameType**

- **datasetKey**
- **origin**

see also [many-values](#)

References

<https://www.gbif.org/developer/species#searching>

Examples

```
## Not run:
# Look up names like mammalia
name_lookup(query='mammalia', limit = 20)

# Start with an offset
name_lookup(query='mammalia', limit=1)
name_lookup(query='mammalia', limit=1, start=2)

# large requests (paging is internally implemented).
# hard maximum limit set by GBIF API: 99999
# name_lookup(query = "Carnivora", limit = 10000)

# Get all data and parse it, removing descriptions which can be quite long
out <- name_lookup('Helianthus annuus', rank="species", verbose=TRUE)
lapply(out$data, function(x) {
  x[!names(x) %in% c("descriptions","descriptionsSerialized")]
})

# Search for a genus
name_lookup(query="Cnaemidophorus", rank="genus")
# Limit records to certain number
name_lookup('Helianthus annuus', rank="species", limit=2)

# Query by habitat
name_lookup(habitat = "terrestrial", limit=2)
name_lookup(habitat = "marine", limit=2)
name_lookup(habitat = "freshwater", limit=2)

# Using faceting
name_lookup(facet='status', limit=0, facetMincount='70000')
name_lookup(facet=c('status','higherTaxonKey'), limit=0,
  facetMincount='700000')

name_lookup(facet='nameType', limit=0)
name_lookup(facet='habitat', limit=0)
name_lookup(facet='datasetKey', limit=0)
name_lookup(facet='rank', limit=0)
name_lookup(facet='isExtinct', limit=0)

name_lookup(isExtinct=TRUE, limit=0)
```

```

# text highlighting
## turn on highlighting
res <- name_lookup(query='canada', hl=TRUE, limit=5)
res$data
name_lookup(query='canada', hl=TRUE, limit=45)
## and you can pass the output to gbif_names() function
res <- name_lookup(query='canada', hl=TRUE, limit=5)
gbif_names(res)

# Lookup by datasetKey (set up sufficient high limit, API maximum: 99999)
# name_lookup(datasetKey='3f8a1297-3259-4700-91fc-acc4170b27ce',
#   limit = 50000)

# Some parameters accept many inputs, treated as OR
name_lookup(rank = c("family", "genus"))
name_lookup(higherTaxonKey = c("119", "120", "121", "204"))
name_lookup(status = c("misapplied", "synonym"))$data
name_lookup(habitat = c("marine", "terrestrial"))
name_lookup(nameType = c("cultivar", "doubtful"))
name_lookup(datasetKey = c("73605f3a-af85-4ade-bbc5-522bfb90d847",
  "d7c60346-44b6-400d-ba27-8d3fbefc8a5"))
name_lookup(datasetKey = "289244ee-e1c1-49aa-b2d7-d379391ce265",
  origin = c("SOURCE", "DENORMED_CLASSIFICATION"))

# Pass on curl options
name_lookup(query='Cnaemidophorus', rank="genus",
  curlopts = list(verbose = TRUE))

## End(Not run)

```

name_suggest

Suggest up to 20 name usages.

Description

A quick and simple autocomplete service that returns up to 20 name usages by doing prefix matching against the scientific name. Results are ordered by relevance.

Usage

```

name_suggest(
  q = NULL,
  datasetKey = NULL,
  rank = NULL,
  fields = NULL,
  start = NULL,
  limit = 100,
  curlopts = list()
)

```

Arguments

q	(character, required) Simple search parameter. The value for this parameter can be a simple word or a phrase. Wildcards can be added to the simple word parameters only, e.g. <code>q=puma</code>
datasetKey	(character) Filters by the checklist dataset key (a uuid, see examples)
rank	(character) A taxonomic rank. One of class, cultivar, cultivar_group, domain, family, form, genus, informal, infrageneric_name, infraorder, infraspecific_name, infrasubspecific_name, kingdom, order, phylum, section, series, species, strain, subclass, subfamily, subform, subgenus, subkingdom, suborder, subphylum, subsection, subseries, subspecies, subtribe, subvariety, superclass, superfamily, superorder, superphylum, suprageneric_name, tribe, unranked, or variety.
fields	(character) Fields to return in output data.frame (simply prunes columns off)
start	Record number to start at. Default: 0. Use in combination with <code>limit</code> to page through results.
limit	Number of records to return. Default: 100. Maximum: 1000.
curlopts	list of named curl options passed on to <code>HttpClient</code> . see <code>curl::curl_options</code> for curl options

Value

A list, with two elements `data` (tibble) and `hierarchy` (list of data.frame's). If 'higherClassificationMap' is one of the fields requested, then `hierarchy` is a list of data.frame's; if not included, `hierarchy` is an empty list.

Repeat parameter inputs

Some parameters can take many inputs, and treated as 'OR' (e.g., a or b or c). The following take many inputs:

- **rank**
- **datasetKey**

see also [many-values](#)

References

<https://www.gbif.org/developer/species#searching>

Examples

```
## Not run:
name_suggest(q='Puma concolor')
name_suggest(q='Puma')
name_suggest(q='Puma', rank="genus")
name_suggest(q='Puma', rank="subspecies")
name_suggest(q='Puma', rank="species")
name_suggest(q='Puma', rank="infraspecific_name")
```



```

name_suggest(q='Puma', limit=2)
name_suggest(q='Puma', fields=c('key','canonicalName'))
name_suggest(q='Puma', fields=c('key','canonicalName',
  'higherClassificationMap'))

# Some parameters accept many inputs, treated as OR
name_suggest(rank = c("family", "genus"))
name_suggest(datasetKey = c("73605f3a-af85-4ade-bbc5-522bfb90d847",
  "d7c60346-44b6-400d-ba27-8d3fbefc8a5"))

# If 'higherClassificationMap' in fields, a list is returned
name_suggest(q='Puma', fields=c('key','higherClassificationMap'))

# Pass on curl options
name_suggest(q='Puma', limit=200, curlopts = list(verbose=TRUE))

## End(Not run)

```

name_usage

Lookup details for specific names in all taxonomies in GBIF.

Description

Lookup details for specific names in all taxonomies in GBIF.

Usage

```

name_usage(
  key = NULL,
  name = NULL,
  data = "all",
  language = NULL,
  datasetKey = NULL,
  uuid = NULL,
  rank = NULL,
  shortname = NULL,
  start = 0,
  limit = 100,
  return = NULL,
  curlopts = list()
)

```

Arguments

key	(numeric or character) A GBIF key for a taxon
name	(character) Filters by a case insensitive, canonical namestring, e.g. 'Puma concolor'

data	(character) Specify an option to select what data is returned. See Description below.
language	(character) Language, default is english
datasetKey	(character) Filters by the dataset's key (a uuid). Must be length=1
uuid	(character) A dataset key
rank	(character) Taxonomic rank. Filters by taxonomic rank as one of: CLASS, CULTIVAR, CULTIVAR_GROUP, DOMAIN, FAMILY, FORM, GENUS, INFORMAL, INFRAGENERIC_NAME, INFRAORDER, INFRASPECIFIC_NAME, INFRASUBSPECIFIC_NAME, KINGDOM, ORDER, PHYLUM, SECTION, SERIES, SPECIES, STRAIN, SUBCLASS, SUBFAMILY, SUBFORM, SUBGENUS, SUBKINGDOM, SUBORDER, SUBPHYLUM, SUBSECTION, SUBSERIES, SUBSPECIES, SUBTRIBE, SUBVARIETY, SUPERCLASS, SUPERFAMILY, SUPERORDER, SUPERPHYLUM, SUPRAGENERIC_NAME, TRIBE, UNRANKED, VARIETY
shortname	(character) A short name for a dataset - it may not do anything
start	Record number to start at. Default: 0.
limit	Number of records to return. Default: 100.
return	Defunct. All components are returned; index to the one(s) you want
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Details

This service uses fuzzy lookup so that you can put in partial names and you should get back those things that match. See examples below.

This function is different from [name_lookup\(\)](#) in that that function searches for names. This function encompasses a bunch of API endpoints, most of which require that you already have a taxon key, but there is one endpoint that allows name searches (see examples below).

Note that `data="verbatim"` hasn't been working.

Options for the data parameter are: 'all', 'verbatim', 'name', 'parents', 'children', 'related', 'synonyms', 'descriptions', 'distributions', 'media', 'references', 'speciesProfiles', 'vernacularNames', 'typeSpecimens', 'root'

This function used to be vectorized with respect to the data parameter, where you could pass in multiple values and the function internally loops over each option making separate requests. This has been removed. You can still loop over many options for the data parameter, just use an `lapply` family function, or a for loop, etc.

See [name_issues\(\)](#) for more information about issues in issues column.

Value

An object of class `gbif`, which is a S3 class list, with slots for metadata (`meta`) and the data itself (`data`). In addition, the object has attributes listing the user supplied arguments and type of search, which is, differently from occurrence data, always equals to 'single' even if multiple values for some parameters are given. `meta` is a list of length four with `offset`, `limit`, `endOfRecords` and `count` fields. `data` is a tibble (aka `data.frame`) containing all information about the found taxa.

Repeat parameter inputs

These parameters used to accept many inputs, but no longer do:

- **rank**
- **name**
- **language**
- **datasetKey**

see also [many-values](#)

References

<https://www.gbif.org/developer/species#nameUsages>

Examples

```
## Not run:
# A single name usage
name_usage(key=1)

# Name usage for a taxonomic name
name_usage(name='Puma', rank="GENUS")

# Name usage for all taxa in a dataset
# (set sufficient high limit, but less than 100000)
# name_usage(datasetKey = "9ff7d317-609b-4c08-bd86-3bc404b77c42",
# limit = 10000)
# All name usages
name_usage()

# References for a name usage
name_usage(key=2435099, data='references')

# Species profiles, descriptions
name_usage(key=3119195, data='speciesProfiles')
name_usage(key=3119195, data='descriptions')
name_usage(key=2435099, data='children')

# Vernacular names for a name usage
name_usage(key=3119195, data='vernacularNames')

# Limit number of results returned
name_usage(key=3119195, data='vernacularNames', limit=3)

# Search for names by dataset with datasetKey parameter
name_usage(datasetKey="d7ddbf4-2cf0-4f39-9b2a-bb099caae36c")

# Search for a particular language
name_usage(key=3119195, language="FRENCH", data='vernacularNames')

# get root usage with a uuid
```

```

name_usage(data = "root", uuid = "73605f3a-af85-4ade-bbc5-522bfb90d847")

# search by language
name_usage(language = "spanish")

# Pass on curl options
name_usage(name='Puma concolor', limit=300, curlopts = list(verbose=TRUE))

## End(Not run)

```

networks

Networks metadata.

Description

Networks metadata.

Usage

```

networks(
  data = "all",
  uuid = NULL,
  query = NULL,
  identifier = NULL,
  identifierType = NULL,
  limit = 100,
  start = NULL,
  curlopts = list()
)

```

Arguments

<code>data</code>	The type of data to get. One or more of: 'contact', 'endpoint', 'identifier', 'tag', 'machineTag', 'comment', 'constituents', or the special 'all'. Default: 'all'
<code>uuid</code>	UUID of the data network provider. This must be specified if data is anything other than 'all'. Only 1 can be passed in
<code>query</code>	Query nodes. Only used when data='all'. Ignored otherwise.
<code>identifier</code>	The value for this parameter can be a simple string or integer, e.g. identifier=120. This parameter doesn't seem to work right now.
<code>identifierType</code>	Used in combination with the identifier parameter to filter identifiers by identifier type. See details. This parameter doesn't seem to work right now.
<code>limit</code>	Number of records to return. Default: 100. Maximum: 1000.
<code>start</code>	Record number to start at. Default: 0. Use in combination with limit to page through results.
<code>curlopts</code>	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Details

identifierType options:

- DOI No description.
- FTP No description.
- GBIF_NODE Identifies the node (e.g: DK for Denmark, sp2000 for Species 2000).
- GBIF_PARTICIPANT Participant identifier from the GBIF IMS Filemaker system.
- GBIF_PORTAL Indicates the identifier originated from an auto_increment column in the portal.data_provider or portal.data_resource table respectively.
- HANDLER No description.
- LSID Reference controlled by a separate system, used for example by DOI.
- SOURCE_ID No description.
- UNKNOWN No description.
- URI No description.
- URL No description.
- UUID No description.

References

<https://www.gbif.org/developer/registry#networks>

Examples

```
## Not run:
networks()
networks(uuid='2b7c7b4f-4d4f-40d3-94de-c28b6fa054a6')

# curl options
networks(curlopts = list(verbose=TRUE))

## End(Not run)
```

nodes

Nodes metadata.

Description

Nodes metadata.

Usage

```

nodes(
  data = "all",
  uuid = NULL,
  query = NULL,
  identifier = NULL,
  identifierType = NULL,
  limit = 100,
  start = NULL,
  isocode = NULL,
  curlopts = list()
)

```

Arguments

<code>data</code>	The type of data to get. One or more of: 'organization', 'endpoint', 'identifier', 'tag', 'machineTag', 'comment', 'pendingEndorsement', 'country', 'dataset', 'installation', or the special 'all'. Default: 'all'
<code>uuid</code>	UUID of the data node provider. This must be specified if data is anything other than 'all'.
<code>query</code>	Query nodes. Only used when data='all'
<code>identifier</code>	The value for this parameter can be a simple string or integer, e.g. identifier=120. This parameter doesn't seem to work right now.
<code>identifierType</code>	Used in combination with the identifier parameter to filter identifiers by identifier type. See details. This parameter doesn't seem to work right now.
<code>limit</code>	Number of records to return. Default: 100. Maximum: 1000.
<code>start</code>	Record number to start at. Default: 0. Use in combination with limit to page through results.
<code>isocode</code>	A 2 letter country code. Only used if data='country'.
<code>curlopts</code>	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Details

identifierType options:

- DOI No description.
- FTP No description.
- GBIF_NODE Identifies the node (e.g: DK for Denmark, sp2000 for Species 2000).
- GBIF_PARTICIPANT Participant identifier from the GBIF IMS Filemaker system.
- GBIF_PORTAL Indicates the identifier originated from an auto_increment column in the portal.data_provider or portal.data_resource table respectively.
- HANDLER No description.
- LSID Reference controlled by a separate system, used for example by DOI.

- SOURCE_ID No description.
- UNKNOWN No description.
- URI No description.
- URL No description.
- UUID No description.

References

<https://www.gbif.org/developer/registry#nodes>

Examples

```
## Not run:
nodes(limit=5)
nodes(uuid="1193638d-32d1-43f0-a855-8727c94299d8")
nodes(data='identifrier', uuid="03e816b3-8f58-49ae-bc12-4e18b358d6d9")
nodes(data=c('identifrier', 'organization', 'comment'),
  uuid="03e816b3-8f58-49ae-bc12-4e18b358d6d9")

uuids = c("8cb55387-7802-40e8-86d6-d357a583c596",
  "02c40d2a-1cba-4633-90b7-e36e5e97aba8",
  "7a17efec-0a6a-424c-b743-f715852c3c1f",
  "b797ce0f-47e6-4231-b048-6b62ca3b0f55",
  "1193638d-32d1-43f0-a855-8727c94299d8",
  "d3499f89-5bc0-4454-8cdb-60bead228a6d",
  "cdc9736d-5ff7-4ece-9959-3c744360cdb3",
  "a8b16421-d80b-4ef3-8f22-098b01a89255",
  "8df8d012-8e64-4c8a-886e-521a3bdfa623",
  "b35cf8f1-748d-467a-adca-4f9170f20a4e",
  "03e816b3-8f58-49ae-bc12-4e18b358d6d9",
  "073d1223-70b1-4433-bb21-dd70afe3053b",
  "07dfe2f9-5116-4922-9a8a-3e0912276a72",
  "086f5148-c0a8-469b-84cc-cce5342f9242",
  "0909d601-bda2-42df-9e63-a6d51847ebce",
  "0e0181bf-9c78-4676-bdc3-54765e661bb8",
  "109aea14-c252-4a85-96e2-f5f4d5d088f4",
  "169eb292-376b-4cc6-8e31-9c2c432de0ad",
  "1e789bc9-79fc-4e60-a49e-89dfc45a7188",
  "1f94b3ca-9345-4d65-afe2-4bace93aa0fe")

res <- lapply(uuids, function(x) nodes(x, data='identifrier')$data)
res <- res[!sapply(res, NROW)==0]
res[1]

# Pass on curl options
nodes(limit=20, curlopts=list(verbose=TRUE))

## End(Not run)
```

occ_count *Get number of occurrence records.*

Description

Get number of occurrence records.

Usage

```
occ_count(
  taxonKey = NULL,
  georeferenced = NULL,
  basisOfRecord = NULL,
  datasetKey = NULL,
  date = NULL,
  typeStatus = NULL,
  country = NULL,
  year = NULL,
  from = 2000,
  to = 2012,
  type = "count",
  publishingCountry = "US",
  protocol = NULL,
  curlopts = list()
)
```

Arguments

taxonKey	Species key
georeferenced	Return only occurrence records with lat/long data (TRUE) or those that don't have that data (FALSE, default). Note that you can also get record count with occ_search() by setting <code>limit=0</code>
basisOfRecord	Basis of record
datasetKey	Dataset key
date	Collection date
typeStatus	A type status. See tpestatus() dataset for options
country	Country data was collected in, two letter abbreviation. See https://countrycode.org/ for abbreviations.
year	Year data were collected in
from	Year to start at
to	Year to end at
type	One of count (default), schema, basisOfRecord, countries, or year.
publishingCountry	Publishing country, two letter ISO country code

protocol	Protocol. E.g., 'DWC_ARCHIVE'
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Details

There is a slight difference in the way records are counted here vs. results from [occ_search\(\)](#). For equivalent outcomes, in the [occ_search\(\)](#) function use `hasCoordinate=TRUE`, and `hasGeospatialIssue=FALSE` to have the same outcome for this function using `georeferenced=TRUE`.

Value

A single numeric value, or a list of numerics.

Supported dimensions

That is, there are only a certain set of supported query parameter combinations that GBIF allows on this API route. They can be found with the call `occ_count(type='schema')`. They are also presented below:

- basisOfRecord
- basisOfRecord, country
- basisOfRecord, country, isGeoreferenced
- basisOfRecord, country, isGeoreferenced, taxonKey
- basisOfRecord, country, taxonKey
- basisOfRecord, datasetKey
- basisOfRecord, datasetKey, isGeoreferenced
- basisOfRecord, datasetKey, isGeoreferenced, taxonKey
- basisOfRecord, datasetKey, taxonKey
- basisOfRecord, isGeoreferenced, taxonKey
- basisOfRecord, isGeoreferenced, publishingCountry
- basisOfRecord, isGeoreferenced, publishingCountry, taxonKey
- basisOfRecord, publishingCountry
- basisOfRecord, publishingCountry, taxonKey
- basisOfRecord, taxonKey
- country
- country, datasetKey, isGeoreferenced
- country, isGeoreferenced
- country, isGeoreferenced, publishingCountry
- country, isGeoreferenced, taxonKey
- country, publishingCountry
- country, taxonKey

- country, typeStatus
- datasetKey
- datasetKey, isGeoreferenced
- datasetKey, isGeoreferenced, taxonKey
- datasetKey, issue
- datasetKey, taxonKey
- datasetKey, typeStatus
- isGeoreferenced
- isGeoreferenced, publishingCountry
- isGeoreferenced, publishingCountry, taxonKey
- isGeoreferenced, taxonKey
- issue
- publishingCountry
- publishingCountry, taxonKey
- publishingCountry, typeStatus
- taxonKey
- taxonKey, typeStatus
- typeStatus
- protocol
- year

References

<https://www.gbif.org/developer/occurrence#metrics>

Examples

```
## Not run:
occ_count(basisOfRecord='OBSERVATION')
occ_count(georeferenced=TRUE)
occ_count(country='DE')
occ_count(country='CA', georeferenced=TRUE, basisOfRecord='OBSERVATION')
occ_count(datasetKey='9e7ea106-0bf8-4087-bb61-dfe4f29e0f17')
occ_count(year=2012)
occ_count(taxonKey=2435099)
occ_count(taxonKey=2435099, georeferenced=TRUE)

# Just schema
occ_count(type='schema')

# Counts by basisOfRecord types
occ_count(type='basisOfRecord')

# Counts by basisOfRecord types and taxonkey
occ_count(taxonKey=2435099, basisOfRecord='OBSERVATION')
```

```

# Counts by typeStatus
occ_count(typeStatus='ALLOTYPE')
occ_count(typeStatus='HOLOTYPE')

# Counts by countries. publishingCountry must be supplied (default to US)
occ_count(type='countries')

# Counts by year. from and to years have to be supplied, default to 2000
# and 2012
occ_count(type='year', from=2000, to=2012)

# Counts by publishingCountry, must supply a country (default to US)
occ_count(type='publishingCountry')
occ_count(type='publishingCountry', country='BZ')

# Pass on curl options
occ_count(type='year', from=2000, to=2012, curlopts = list(verbose = TRUE))

## End(Not run)

```

occ_data

Search for GBIF occurrences - simplified for speed

Description

Search for GBIF occurrences - simplified for speed

Usage

```

occ_data(
  taxonKey = NULL,
  scientificName = NULL,
  country = NULL,
  publishingCountry = NULL,
  hasCoordinate = NULL,
  typeStatus = NULL,
  recordNumber = NULL,
  lastInterpreted = NULL,
  continent = NULL,
  geometry = NULL,
  geom_big = "asis",
  geom_size = 40,
  geom_n = 10,
  recordedBy = NULL,
  recordedByID = NULL,
  identifiedByID = NULL,
  basisOfRecord = NULL,
  datasetKey = NULL,

```

```

eventDate = NULL,
catalogNumber = NULL,
year = NULL,
month = NULL,
decimalLatitude = NULL,
decimalLongitude = NULL,
elevation = NULL,
depth = NULL,
institutionCode = NULL,
collectionCode = NULL,
hasGeospatialIssue = NULL,
issue = NULL,
search = NULL,
mediaType = NULL,
subgenusKey = NULL,
repatriated = NULL,
phylumKey = NULL,
kingdomKey = NULL,
classKey = NULL,
orderKey = NULL,
familyKey = NULL,
genusKey = NULL,
establishmentMeans = NULL,
protocol = NULL,
license = NULL,
organismId = NULL,
publishingOrg = NULL,
stateProvince = NULL,
waterBody = NULL,
locality = NULL,
limit = 500,
start = 0,
skip_validate = TRUE,
curlopts = list()
)

```

Arguments

- | | |
|----------------|--|
| taxonKey | (numeric) A taxon key from the GBIF backbone. All included and synonym taxa are included in the search, so a search for aves with taxonKey=212 (i.e. /occurrence/search?taxonKey=212) will match all birds, no matter which species. You can pass many keys by passing occ_search in a call to an lapply-family function (see last example below). |
| scientificName | A scientific name from the GBIF backbone. All included and synonym taxa are included in the search. |
| country | The 2-letter country code (as per ISO-3166-1) of the country in which the occurrence was recorded. See here https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2 |

publishingCountry	The 2-letter country code (as per ISO-3166-1) of the country in which the occurrence was recorded.
hasCoordinate	(logical) Return only occurrence records with lat/long data (TRUE) or all records (FALSE, default).
typeStatus	Type status of the specimen. One of many options. See ?typestatus
recordNumber	Number recorded by collector of the data, different from GBIF record number. See http://rs.tdwg.org/dwc/terms/#recordNumber for more info
lastInterpreted	Date the record was last modified in GBIF, in ISO 8601 format: yyyy, yyyy-MM, yyyy-MM-dd, or MM-dd. Supports range queries, smaller, larger (e.g., '1990,1991', whereas '1991,1990' wouldn't work)
continent	Continent. One of africa, antarctica, asia, europe, north_america (North America includes the Caribbean and reaches down and includes Panama), oceania, or south_america
geometry	Searches for occurrences inside a polygon described in Well Known Text (WKT) format. A WKT shape written as either POINT, LINESTRING, LINEARRING POLYGON, or MULTIPOLYGON. Example of a polygon: POLYGON((30.1 10.1, 20, 20 40, 40 40, 30.1 10.1)) would be queried as http://bit.ly/1BzNwDq See also the section WKT below.
geom_big	(character) One of "axe", "bbox", or "asis" (default). See Details.
geom_size	(integer) An integer indicating size of the cell. Default: 40. See Details.
geom_n	(integer) An integer indicating number of cells in each dimension. Default: 10. See Details.
recordedBy	The person who recorded the occurrence.
recordedByID	(character) Identifier (e.g. ORCID) for the person who recorded the occurrence
identifiedByID	(character) Identifier (e.g. ORCID) for the person who provided the taxonomic identification of the occurrence.
basisOfRecord	Basis of record, as defined in our BasisOfRecord enum here https://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/BasisOfRecord.html Acceptable values are: <ul style="list-style-type: none"> • FOSSIL_SPECIMEN An occurrence record describing a fossilized specimen. • HUMAN_OBSERVATION An occurrence record describing an observation made by one or more people. • LITERATURE An occurrence record based on literature alone. • LIVING_SPECIMEN An occurrence record describing a living specimen, e.g. • MACHINE_OBSERVATION An occurrence record describing an observation made by a machine. • OBSERVATION An occurrence record describing an observation. • PRESERVED_SPECIMEN An occurrence record describing a preserved specimen. • UNKNOWN Unknown basis for the record.

datasetKey	The occurrence dataset key (a uuid)
eventDate	Occurrence date in ISO 8601 format: yyyy, yyyy-MM, yyyy-MM-dd, or MM-dd. Supports range queries, smaller,larger (e.g., '1990,1991', whereas '1991,1990' wouldn't work)
catalogNumber	An identifier of any form assigned by the source within a physical collection or digital dataset for the record which may not unique, but should be fairly unique in combination with the institution and collection code.
year	The 4 digit year. A year of 98 will be interpreted as AD 98. Supports range queries, smaller,larger (e.g., '1990,1991', whereas '1991,1990' wouldn't work)
month	The month of the year, starting with 1 for January. Supports range queries, smaller,larger (e.g., '1,2', whereas '2,1' wouldn't work)
decimalLatitude	Latitude in decimals between -90 and 90 based on WGS 84. Supports range queries, smaller,larger (e.g., '25,30', whereas '30,25' wouldn't work)
decimalLongitude	Longitude in decimals between -180 and 180 based on WGS 84. Supports range queries (e.g., '-0.4,-0.2', whereas '-0.2,-0.4' wouldn't work).
elevation	Elevation in meters above sea level. Supports range queries, smaller,larger (e.g., '5,30', whereas '30,5' wouldn't work)
depth	Depth in meters relative to elevation. For example 10 meters below a lake surface with given elevation. Supports range queries, smaller,larger (e.g., '5,30', whereas '30,5' wouldn't work)
institutionCode	An identifier of any form assigned by the source to identify the institution the record belongs to. Not guaranteed to be que.
collectionCode	An identifier of any form assigned by the source to identify the physical collection or digital dataset uniquely within the text of an institution.
hasGeospatialIssue	(logical) Includes/excludes occurrence records which contain spatial issues (as determined in our record interpretation), i.e. hasGeospatialIssue=TRUE returns only those records with spatial issues while hasGeospatialIssue=FALSE includes only records without spatial issues. The absence of this parameter returns any record with or without spatial issues.
issue	(character) One or more of many possible issues with each occurrence record. See Details. Issues passed to this parameter filter results by the issue.
search	Query terms. The value for this parameter can be a simple word or a phrase.
mediaType	Media type. Default is NULL, so no filtering on mediatype. Options: NULL, 'MovingImage', 'Sound', and 'StillImage'.
subgenusKey	(numeric) Subgenus classification key.
repatriated	(character) Searches for records whose publishing country is different to the country where the record was recorded in.
phylumKey	(numeric) Phylum classification key.
kingdomKey	(numeric) Kingdom classification key.

classKey	(numeric) Class classification key.
orderKey	(numeric) Order classification key.
familyKey	(numeric) Family classification key.
genusKey	(numeric) Genus classification key.
establishmentMeans	(character) EstablishmentMeans, possible values include: INTRODUCED, INVASIVE, MANAGED, NATIVE, NATURALISED, UNCERTAIN
protocol	(character) Protocol or mechanism used to provide the occurrence record. See Details for possible values
license	(character) The type license applied to the dataset or record. Possible values: CC0_1_0, CC_BY_4_0, CC_BY_NC_4_0, UNSPECIFIED, and UNSUPPORTED
organismId	(numeric) An identifier for the Organism instance (as opposed to a particular digital record of the Organism). May be a globally unique identifier or an identifier specific to the data set.
publishingOrg	(character) The publishing organization key (a UUID).
stateProvince	(character) The name of the next smaller administrative region than country (state, province, canton, department, region, etc.) in which the Location occurs.
waterBody	(character) The name of the water body in which the locations occur
locality	(character) The specific description of the place.
limit	Number of records to return. Default: 500. Note that the per request maximum is 300, but since we set it at 500 for the function, we do two requests to get you the 500 records (if there are that many). Note that there is a hard maximum of 100,000, which is calculated as the limit+start, so start=99,000 and limit=2000 won't work
start	Record number to start at. Use in combination with limit to page through results. Note that we do the paging internally for you, but you can manually set the start parameter
skip_validate	(logical) whether to skip wellknown::validate_wkt call or not. passed down to check_wkt() . Default: TRUE
curlopts	list of named curl options passed on to HttpClient . see curl::curl_options for curl options

Value

An object of class `gbif_data`, which is a S3 class list, with slots for metadata (`meta`) and the occurrence data itself (`data`), and with attributes listing the user supplied arguments and whether it was a "single" or "many" search; that is, if you supply two values of the `datasetKey` parameter to searches are done, and it's a "many". `meta` is a list of length four with `offset`, `limit`, `endOfRecords` and `count` fields. `data` is a tibble (aka `data.frame`)

protocol parameter options

- BIOCASE - A BioCASE protocol compliant service.
- DIGIR - A DiGIR service endpoint.
- DIGIR_MANIS - A DiGIR service slightly modified for the MANIS network.
- DWC_ARCHIVE - A Darwin Core Archive as defined by the Darwin Core Text Guidelines.
- EML - A single EML metadata document in any EML version.
- FEED - Syndication feeds like RSS or ATOM of various flavors.
- OAI_PMH - The Open Archives Initiative Protocol for Metadata Harvesting.
- OTHER - Any other service not covered by this enum so far.
- TAPIR - A TAPIR service.
- TCS_RDF - Taxon Concept data given as RDF based on the TDWG ontology.
- TCS_XML - A Taxon Concept Schema document.
- WFS - An OGC Web Feature Service.
- WMS - An OGC Web Map Service.

Multiple values passed to a parameter

There are some parameters you can pass multiple values to in a vector, each value of which produces a different request (MDR: multiple different requests). Some parameters allow multiple values to be passed in the same request (MSR: multiple same request) in a semicolon separated string (e.g., 'a;b'); if given we'll do a single request with that parameter repeated for each value given (e.g., foo=a&foo=b if the parameter is foo). Some parameters allow both MDR and MSR.

The following list shows which parameters support MDR and MSR.

- basisOfRecord: MDR, MSR
- classKey: MDR, MSR
- country: MDR, MSR
- familyKey: MDR, MSR
- genusKey: MDR, MSR
- identifiedByID: MDR, MSR
- kingdomKey: MDR, MSR
- license: MDR, MSR
- locality: MDR, MSR
- catalogNumber: MDR, MSR
- collectionCode: MDR, MSR
- continent: MDR, MSR
- datasetKey: MDR, MSR
- establishmentMeans: MDR, MSR
- geometry: MDR, MSR
- institutionCode: MDR, MSR

- mediaType: MDR, MSR
- orderKey: MDR, MSR
- organismId: MDR, MSR
- phylumKey: MDR, MSR
- protocol: MDR, MSR
- publishingCountry: MDR, MSR
- publishingOrg: MDR, MSR
- recordedBy: MDR, MSR
- recordedByID: MDR, MSR
- recordNumber: MDR, MSR
- scientificName: MDR, MSR
- stateProvince: MDR, MSR
- subgenusKey: MDR, MSR
- taxonKey: MDR, MSR
- typeStatus: MDR, MSR
- waterBody: MDR, MSR
- depth: MDR
- limit: MDR
- q: MDR
- year: MDR
- repatriated: MDR
- lastInterpreted: MDR
- decimalLatitude: MDR
- decimalLongitude: MDR

Note that you can not pass a vector > length 1 to more than 1 of the above MDR parameters at the same time.

see also [many-values](#)

Range queries

A range query is as it sounds - you query on a range of values defined by a lower and upper limit. Do a range query by specifying the lower and upper limit in a string like `depth='50,100'`. It would be more R like to specify the range in a vector like `c(50,100)`, but that sort of syntax allows you to do many searches, one for each element in the vector - thus range queries have to differ. The following parameters support range queries.

- decimalLatitude
- decimalLongitude
- depth
- elevation

- eventDate
- lastInterpreted
- month
- year

See also above section: semicolon and comma separated strings lead to different outcomes for some parameters.

Hierarchies

Hierarchies are returned with each occurrence object. There is no option no to return them from the API. However, within the `occ_search` function you can select whether to return just hierarchies, just data, all of data and hierarchies and metadata, or just metadata. If all hierarchies are the same we just return one for you.

curl debugging

You can pass parameters not defined in this function into the call to the GBIF API to control things about the call itself using `curl_opts`. See an example below that passes in the `verbose` function to get details on the http call.

Scientific names vs. taxon keys

In the previous GBIF API and the version of `rgbif` that wrapped that API, you could search the equivalent of this function with a species name, which was convenient. However, names are messy right. So it sorta makes sense to sort out the species key numbers you want exactly, and then get your occurrence data with this function. GBIF has added a parameter `scientificName` to allow searches by scientific names in this function - which includes synonym taxa. *Note:* that if you do use the `scientificName` parameter, we will check internally that it's not a synonym of an accepted name, and if it is, we'll search on the accepted name. If you want to force searching by a synonym do so by finding the GBIF identifier first with any `name_*` functions, then pass that ID to the `taxonKey` parameter.

WKT

Examples of valid WKT objects:

- 'POLYGON((-19.5 34.1, 27.8 34.1, 35.9 68.1, -25.3 68.1, -19.5 34.1))'
- 'MULTIPOLYGON(((-123 38, -116 38, -116 43, -123 43, -123 38)), ((-97 41, -93 41, -93 45, -97 45, -97 41)))'
- 'POINT(-120 40)'
- 'LINESTRING(3 4,10 50,20 25)'
- 'LINEARRING' ???' - Not sure how to specify this. Anyone?

Note that GBIF expects counter-clockwise winding order for WKT. You can supply clockwise WKT, but GBIF treats it as an exclusion, so you get all data not inside the WKT area. [occ_download\(\)](#) behaves differently in that you should simply get no data back at all with clockwise WKT.

Long WKT

Options for handling long WKT strings: Note that long WKT strings are specially handled when using [occ_search](#) or [occ_data](#). Here are the three options for long WKT strings (> 1500 characters), set one of these three via the parameter `geom_big`:

- `asis` - the default setting. This means we don't do anything internally. That is, we just pass on your WKT string just as we've done before in this package.
- `axe` - this option uses the **geoaxe** package to chop up your WKT string in to many polygons, which then leads to a separate data request for each polygon piece, then we combine all dat back together to give to you. Note that if your WKT string is not of type polygon, we drop back to `asis` as there's no way to chop up linestrings, etc. This option will in most cases be slower than the other two options. However, this polygon splitting approach won't have the problem of the disconnect between how many records you want and what you actually get back as with the `bbox` option.

This method uses [chop](#), which uses `GridTopology` from the **sp** package, which has two parameters `cellsize` and `cells.dim` that we use to chop up polygons. You can tweak those parameters here by tweaking `geom_size` and `geom_n`. `geom_size` seems to be more useful in toggling the number of WKT strings you get back.

See [wkt_parse](#) to manually break make WKT bounding box from a larger WKT string, or break a larger WKT string into many smaller ones.

- `bbox` - this option checks whether your WKT string is longer than 1500 characters, and if it is we create a bounding box from the WKT, do the GBIF search with that bounding box, then prune the resulting data to only those occurrences in your original WKT string. There is a big caveat however. Because we create a bounding box from the WKT, and the `limit` parameter determines some subset of records to get, then when we prune the resulting data to the WKT, the number of records you get could be less than what you set with your `limit` parameter. However, you could set the limit to be high enough so that you get all records back found in that bounding box, then you'll get all the records available within the WKT.

issue parameter

The options for the issue parameter (from <https://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/OccurrenceIssue.htm>):

- `BASIS_OF_RECORD_INVALID` The given basis of record is impossible to interpret or seriously different from the recommended vocabulary.
- `CONTINENT_COUNTRY_MISMATCH` The interpreted continent and country do not match up.
- `CONTINENT_DERIVED_FROM_COORDINATES` The interpreted continent is based on the coordinates, not the verbatim string information.
- `CONTINENT_INVALID` Uninterpretable continent values found.
- `COORDINATE_INVALID` Coordinate value given in some form but GBIF is unable to interpret it.
- `COORDINATE_OUT_OF_RANGE` Coordinate has invalid lat/lon values out of their decimal max range.
- `COORDINATE_REPROJECTED` The original coordinate was successfully reprojected from a different geodetic datum to WGS84.

- **COORDINATE_REPROJECTION_FAILED** The given decimal latitude and longitude could not be reprojected to WGS84 based on the provided datum.
- **COORDINATE_REPROJECTION_SUSPICIOUS** Indicates successful coordinate reprojec-tion according to provided datum, but which results in a datum shift larger than 0.1 decimal degrees.
- **COORDINATE_ROUNDED** Original coordinate modified by rounding to 5 decimals.
- **COUNTRY_COORDINATE_MISMATCH** The interpreted occurrence coordinates fall out-side of the indicated country.
- **COUNTRY_DERIVED_FROM_COORDINATES** The interpreted country is based on the co-ordinates, not the verbatim string information.
- **COUNTRY_INVALID** Uninterpretable country values found.
- **COUNTRY_MISMATCH** Interpreted country for dwc:country and dwc:countryCode contra-dict each other.
- **DEPTH_MIN_MAX_SWAPPED** Set if supplied min>max
- **DEPTH_NON_NUMERIC** Set if depth is a non numeric value
- **DEPTH_NOT_METRIC** Set if supplied depth is not given in the metric system, for example using feet instead of meters
- **DEPTH_UNLIKELY** Set if depth is larger than 11.000m or negative.
- **ELEVATION_MIN_MAX_SWAPPED** Set if supplied min > max elevation
- **ELEVATION_NON_NUMERIC** Set if elevation is a non numeric value
- **ELEVATION_NOT_METRIC** Set if supplied elevation is not given in the metric system, for example using feet instead of meters
- **ELEVATION_UNLIKELY** Set if elevation is above the troposphere (17km) or below 11km (Mariana Trench).
- **GEODETIC_DATUM_ASSUMED_WGS84** Indicating that the interpreted coordinates as-sume they are based on WGS84 datum as the datum was either not indicated or interpretable.
- **GEODETIC_DATUM_INVALID** The geodetic datum given could not be interpreted.
- **IDENTIFIED_DATE_INVALID** The date given for dwc:dateIdentified is invalid and cant be interpreted at all.
- **IDENTIFIED_DATE_UNLIKELY** The date given for dwc:dateIdentified is in the future or before Linnean times (1700).
- **MODIFIED_DATE_INVALID** A (partial) invalid date is given for dc:modified, such as a non existing date, invalid zero month, etc.
- **MODIFIED_DATE_UNLIKELY** The date given for dc:modified is in the future or predates unix time (1970).
- **MULTIMEDIA_DATE_INVALID** An invalid date is given for dc:created of a multimedia object.
- **MULTIMEDIA_URI_INVALID** An invalid uri is given for a multimedia object.
- **PRESUMED_NEGATED_LATITUDE** Latitude appears to be negated, e.g. 32.3 instead of -32.3
- **PRESUMED_NEGATED_LONGITUDE** Longitude appears to be negated, e.g. 32.3 instead of -32.3

- **PRESUMED_SWAPPED_COORDINATE** Latitude and longitude appear to be swapped.
- **RECORDED_DATE_INVALID** A (partial) invalid date is given, such as a non existing date, invalid zero month, etc.
- **RECORDED_DATE_MISMATCH** The recording date specified as the eventDate string and the individual year, month, day are contradicting.
- **RECORDED_DATE_UNLIKELY** The recording date is highly unlikely, falling either into the future or represents a very old date before 1600 that predates modern taxonomy.
- **REFERENCES_URI_INVALID** An invalid uri is given for dc:references.
- **TAXON_MATCH_FUZZY** Matching to the taxonomic backbone can only be done using a fuzzy, non exact match.
- **TAXON_MATCH_HIGHERRANK** Matching to the taxonomic backbone can only be done on a higher rank and not the scientific name.
- **TAXON_MATCH_NONE** Matching to the taxonomic backbone cannot be done cause there was no match at all or several matches with too little information to keep them apart (homonyms).
- **TYPE_STATUS_INVALID** The given type status is impossible to interpret or seriously different from the recommended vocabulary.
- **ZERO_COORDINATE** Coordinate is the exact 0/0 coordinate, often indicating a bad null coordinate.

Counts

There is a slight difference in the way records are counted here vs. results from [occ_count](#). For equivalent outcomes, in this function use `hasCoordinate=TRUE`, and `hasGeospatialIssue=FALSE` to have the same outcome using [occ_count](#) with `isGeoreferenced=TRUE`

occ_data vs. occ_search

This does nearly the same thing as [occ_search\(\)](#), but is simplified for speed, and is for the most common use case where user just wants occurrence data, and not other information like taxon hierarchies and media (e.g., images). A lot of time in [occ_search\(\)](#) is used parsing data to be more useable downstream. We do less of that in this function.

There are a number of data fields GBIF returns that we drop to speed up processing time within R. These fields take extra time to process because they are deeply nested and so take extra time to check if they are empty or not, and if not, figure out how to parse them into a data.frame. The fields are:

- `gadm`
- `media`
- `facts`
- `relations`
- `extensions`
- `identifiers`
- `recordedByIDs`
- `identifiedByIDs`

To get these fields use [occ_search\(\)](#) instead.

Note

Maximum number of records you can get with this function is 100,000. See <https://www.gbif.org/developer/occurrence>

References

<https://www.gbif.org/developer/occurrence#search>

See Also

[downloads\(\)](#), [occ_search\(\)](#)

Examples

```
## Not run:
(key <- name_backbone(name='Encelia californica')$speciesKey)
occ_data(taxonKey = key, limit = 4)
(res <- occ_data(taxonKey = key, limit = 400))

# Return 20 results, this is the default by the way
(key <- name_suggest(q='Helianthus annuus', rank='species')$data$key[1])
occ_data(taxonKey=key, limit=20)

# Instead of getting a taxon key first, you can search for a name directly
## However, note that using this approach (with \code{scientificName="..."})
## you are getting synonyms too. The results for using \code{scientificName}
## and \code{taxonKey} parameters are the same in this case, but I wouldn't
## be surprised if for some names they return different results
occ_data(scientificName = 'Ursus americanus', curlopts=list(verbose=TRUE))
key <- name_backbone(name = 'Ursus americanus', rank='species')$usageKey
occ_data(taxonKey = key)

# Search by dataset key
occ_data(datasetKey='7b5d6a48-f762-11e1-a439-00145eb45e9a', limit=10)

# Search by catalog number
occ_data(catalogNumber="49366", limit=10)
## separate requests: use a vector of strings
occ_data(catalogNumber=c("49366","Bird.27847588"), limit=10)
## one request, many instances of same parameter: use semi-colon sep. string
occ_data(catalogNumber="49366;Bird.27847588", limit=10)

# Use paging parameters (limit and start) to page. Note the different results
# for the two queries below.
occ_data(datasetKey='7b5d6a48-f762-11e1-a439-00145eb45e9a',start=10,limit=5)
occ_data(datasetKey='7b5d6a48-f762-11e1-a439-00145eb45e9a',start=20,limit=5)

# Many dataset keys
## separate requests: use a vector of strings
occ_data(datasetKey=c("50c9509d-22c7-4a22-a47d-8c48425ef4a7",
  "7b5d6a48-f762-11e1-a439-00145eb45e9a"), limit=20)
## one request, many instances of same parameter: use semi-colon sep. string
v="50c9509d-22c7-4a22-a47d-8c48425ef4a7;7b5d6a48-f762-11e1-a439-00145eb45e9a"
```

```

occ_data(datasetKey = v, limit=20)

# Search by recorder
occ_data(recordedBy="smith", limit=20)

# Many collector names
## separate requests: use a vector of strings
occ_data(recordedBy=c("smith","BJ Stacey"), limit=10)
## one request, many instances of same parameter: use semi-colon sep. string
occ_data(recordedBy="smith;BJ Stacey", limit=10)

# recordedByID
occ_data(recordedByID="https://orcid.org/0000-0003-1691-239X", limit=20)
## many at once
### separate searches
ids <- c("https://orcid.org/0000-0003-1691-239X",
        "https://orcid.org/0000-0001-7569-1828",
        "https://orcid.org/0000-0002-0596-5376")
res <- occ_data(recordedByID=ids, limit=20)
res[[1]]$data$recordedByIDs[[1]]
res[[2]]$data$recordedByIDs[[1]]
res[[3]]$data$recordedByIDs[[1]]
### all in one search
res <- occ_data(recordedByID=paste0(ids, collapse=";"), limit=20)
unique(vapply(res$data$recordedByIDs, "[[", "", "value"))

# identifiedByID
occ_data(identifiedByID="https://orcid.org/0000-0003-4710-2648", limit=20)

# Pass in curl options for extra fun
occ_data(taxonKey=2433407, limit=20, curlopts=list(verbose=TRUE))
occ_data(taxonKey=2433407, limit=20,
        curlopts = list(
          noprogess = FALSE,
          progressfunction = function(down, up) {
            cat(sprintf("up: %d | down %d\n", up, down))
            return(TRUE)
          }
        )
)
# occ_data(taxonKey=2433407, limit=20, curlopts=list(timeout_ms=1))

# Search for many species
splist <- c('Cyanocitta stelleri', 'Junco hyemalis', 'Aix sponsa')
keys <- sapply(splist, function(x) name_suggest(x)$data$key[1], USE.NAMES=FALSE)
## separate requests: use a vector of strings
occ_data(taxonKey = keys, limit=5)
## one request, many instances of same parameter: use semi-colon sep. string
occ_data(taxonKey = paste0(keys, collapse = ";"), limit=5)

# Search using a synonym name
# Note that you'll see a message printing out that the accepted name will
# be used

```

```

occ_data(scientificName = 'Pulsatilla patens', limit=5)

# Search on latitude and longitude
occ_data(decimalLatitude=40, decimalLongitude=-120, limit = 10)

# Search on a bounding box
### in well known text format
### polygon
occ_data(geometry='POLYGON((30.1 10.1,40 40,20 40,10 20,30.1 10.1))',
  limit=20)
### multipolygon
wkt <- 'MULTIPOLYGON((( -123 38,-116 38,-116 43,-123 43,-123 38)),
  ((-97 41,-93 41,-93 45,-97 45,-97 41)))'
occ_data(geometry = gsub("\n\\s+", "", wkt), limit = 20)
### polygon and taxonkey
key <- name_suggest(q='Aesculus hippocastanum')$data$key[1]
occ_data(taxonKey=key,
  geometry='POLYGON((30.1 10.1,40 40,20 40,10 20,30.1 10.1))',
  limit=20)
## or using bounding box, converted to WKT internally
occ_data(geometry=c(-125.0,38.4,-121.8,40.9), limit=20)

## you can search on many geometry objects
### separate requests: use a vector of strings
wkts <-
c('POLYGON((-102.2 46,-102.2 43.7,-93.9 43.7,-93.9 46,-102.2 46))',
  'POLYGON((30.1 10.1,40 40,20 40,10 20,30.1 10.1))')
occ_data(geometry = wkts, limit=20)
### one request, many instances of same parameter: use semi-colon sep. string
occ_data(geometry = paste0(wkts, collapse = ";"), limit=20)

# Search on a long WKT string - too long for a GBIF search API request
## By default, a very long WKT string will likely cause a request failure as
## GBIF only handles strings up to about 1500 characters long. You can leave as is, or
## - Alternatively, you can choose to break up your polygon into many, and do a
##   data request on each piece, and the output is put back together (see below)
## - Or, 2nd alternatively, you could use the GBIF download API
wkt <- "POLYGON((-9.178796777343678 53.22769021556159,
-12.167078027343678 51.56540789297837,
-12.958093652343678 49.78333685689162,-11.024499902343678 49.21251756301334,
-12.079187402343678 46.68179685941719,-15.067468652343678 45.83103608186854,
-15.770593652343678 43.58271629699817,-15.067468652343678 41.57676278827219,
-11.815515527343678 40.44938999172728,-12.958093652343678 37.72112962230871,
-11.639734277343678 36.52987439429357,-8.299890527343678 34.96062625095747,
-8.739343652343678 32.62357394385735,-5.223718652343678 30.90497915232165,
1.1044063476563224 31.80562077746643,1.1044063476563224 30.754036557416256,
6.905187597656322 32.02942785462211,5.147375097656322 32.99292810780193,
9.629796972656322 34.164474406524725,10.860265722656322 32.91918014319603,
14.551671972656322 33.72700959356651,13.409093847656322 34.888564192275204,
16.748937597656322 35.104560368110114,19.561437597656322 34.81643887792552,
18.594640722656322 36.38849705969625,22.989171972656322 37.162874858929854,
19.825109472656322 39.50651757842751,13.760656347656322 38.89353140585116,

```



```

14.112218847656322 42.36091601976124,10.596593847656322 41.11488736647705,
9.366125097656322 43.70991402658437,5.059484472656322 42.62015372417812,
2.3348750976563224 45.21526500321446,-0.7412967773436776 46.80225692528942,
6.114171972656322 47.102229890207894,8.047765722656322 45.52399303437107,
12.881750097656322 48.22681126957933,9.190343847656322 48.693079457106684,
8.750890722656322 50.68283120621287,5.059484472656322 50.40356146487845,
4.268468847656322 52.377558897655156,1.4559688476563224 53.28027243658647,
0.8407344726563224 51.62000971578333,0.5770625976563224 49.32721423860726,
-2.5869999023436776 49.49875947592088,-2.4991092773436776 51.18135535408638,
-2.0596561523436776 52.53822562473851,-4.696374902343678 51.67454591918756,
-5.311609277343678 50.009802108095776,-6.629968652343678 48.75106196817059,
-7.684656152343678 50.12263634382465,-6.190515527343678 51.83776110910459,
-5.047937402343678 54.267098895684235,-6.893640527343678 53.69860705549198,
-8.915124902343678 54.77719740243195,-12.079187402343678 54.52294465763567,
-13.573328027343678 53.437631551347174,
-11.288171777343678 53.48995552517918,
-9.178796777343678 53.22769021556159))"
wkt <- gsub("\n", " ", wkt)

#### Default option with large WKT string fails
# res <- occ_data(geometry = wkt)

#### if WKT too long, with 'geom_big=bbox': makes into bounding box
res <- occ_data(geometry = wkt, geom_big = "bbox")
library("rgeos")
library("sp")
wktsp <- readWKT(wkt)
plot(wktsp)
coordinates(res$data) <- ~decimalLongitude+decimalLatitude
points(res$data)

#### Or, use 'geom_big=axe'
(res <- occ_data(geometry = wkt, geom_big = "axe"))
##### manipulate essentially number of polygons that result, so number of requests
##### default geom_size is 40
##### fewer calls
(res <- occ_data(geometry = wkt, geom_big = "axe", geom_size=50))
##### more calls
(res <- occ_data(geometry = wkt, geom_big = "axe", geom_size=30))

# Search on country
occ_data(country='US', limit=20)
isocodes[grep("France", isocodes$name),"code"]
occ_data(country='FR', limit=20)
occ_data(country='DE', limit=20)
### separate requests: use a vector of strings
occ_data(country=c('US','DE'), limit=20)
### one request, many instances of same parameter: use semi-colon sep. string
occ_data(country = 'US;DE', limit=20)

# Get only occurrences with lat/long data
occ_data(taxonKey=key, hasCoordinate=TRUE, limit=20)

```

```

# Get only occurrences that were recorded as living specimens
occ_data(basisOfRecord="LIVING_SPECIMEN", hasCoordinate=TRUE, limit=20)
## multiple values in a vector = a separate request for each value
occ_data(taxonKey=key,
  basisOfRecord=c("OBSERVATION", "HUMAN_OBSERVATION"), limit=20)
## mutiple values in a single string, ";" separated = one request including all values
occ_data(taxonKey=key,
  basisOfRecord="OBSERVATION;HUMAN_OBSERVATION", limit=20)

# Get occurrences for a particular eventDate
occ_data(taxonKey=key, eventDate="2013", limit=20)
occ_data(taxonKey=key, year="2013", limit=20)
occ_data(taxonKey=key, month="6", limit=20)

# Get occurrences based on depth
key <- name_backbone(name='Salmo salar', kingdom='animals')$speciesKey
occ_data(taxonKey=key, depth=1, limit=20)

# Get occurrences based on elevation
key <- name_backbone(name='Puma concolor', kingdom='animals')$speciesKey
occ_data(taxonKey=key, elevation=50, hasCoordinate=TRUE, limit=20)

# Get occurrences based on institutionCode
occ_data(institutionCode="TLMF", limit=20)
### separate requests: use a vector of strings
occ_data(institutionCode=c("TLMF", "ArtDatabanken"), limit=20)
### one request, many instances of same parameter: use semi-colon sep. string
occ_data(institutionCode = "TLMF;ArtDatabanken", limit=20)

# Get occurrences based on collectionCode
occ_data(collectionCode="Floristic Databases MV - Higher Plants", limit=20)
### separate requests: use a vector of strings
occ_data(collectionCode=c("Floristic Databases MV - Higher Plants",
  "Artport"), limit = 20)
### one request, many instances of same parameter: use semi-colon sep. string
occ_data(collectionCode = "Floristic Databases MV - Higher Plants;Artport",
  limit = 20)

# Get only those occurrences with spatial issues
occ_data(taxonKey=key, hasGeospatialIssue=TRUE, limit=20)

# Search using a query string
occ_data(search="kingfisher", limit=20)

# search on repatriated - doesn't work right now
# occ_data(repatriated = "")

# search on phylumKey
occ_data(phylumKey = 7707728, limit = 5)

# search on kingdomKey
occ_data(kingdomKey = 1, limit = 5)

```

```
# search on classKey
occ_data(classKey = 216, limit = 5)

# search on orderKey
occ_data(orderKey = 7192402, limit = 5)

# search on familyKey
occ_data(familyKey = 3925, limit = 5)

# search on genusKey
occ_data(genusKey = 1935496, limit = 5)

# search on establishmentMeans
occ_data(establishmentMeans = "INVASIVE", limit = 5)
occ_data(establishmentMeans = "NATIVE", limit = 5)
occ_data(establishmentMeans = "UNCERTAIN", limit = 5)
### separate requests: use a vector of strings
occ_data(establishmentMeans = c("INVASIVE", "NATIVE"), limit = 5)
### one request, many instances of same parameter: use semi-colon sep. string
occ_data(establishmentMeans = "INVASIVE;NATIVE", limit = 5)

# search on protocol
occ_data(protocol = "DIGIR", limit = 5)

# search on license
occ_data(license = "CC_BY_4_0", limit = 5)

# search on organismId
occ_data(organismId = "100", limit = 5)

# search on publishingOrg
occ_data(publishingOrg = "28eb1a3f-1c15-4a95-931a-4af90ecb574d", limit = 5)

# search on stateProvince
occ_data(stateProvince = "California", limit = 5)

# search on waterBody
occ_data(waterBody = "pacific ocean", limit = 5)

# search on locality
occ_data(locality = "Trondheim", limit = 5)
### separate requests: use a vector of strings
res <- occ_data(locality = c("Trondheim", "Hovekilen"), limit = 5)
res$Trondheim$data
res$Hovekilen$data
### one request, many instances of same parameter: use semi-colon sep. string
occ_data(locality = "Trondheim;Hovekilen", limit = 5)

# Range queries
## See Detail for parameters that support range queries
occ_data(depth='50,100', limit = 20)
### this is not a range search, but does two searches for each depth
```

```

occ_data(depth=c(50,100), limit = 20)

## Range search with year
occ_data(year='1999,2000', limit=20)

## Range search with latitude
occ_data(decimalLatitude='29.59,29.6', limit = 20)

# Search by specimen type status
## Look for possible values of the typeStatus parameter looking at the tpestatus dataset
occ_data(typeStatus = 'allotype', limit = 20)$data[,c('name','typeStatus')]

# Search by specimen record number
## This is the record number of the person/group that submitted the data, not GBIF's numbers
## You can see that many different groups have record number 1, so not super helpful
occ_data(recordNumber = 1, limit = 20)$data[,c('name','recordNumber','recordedBy')]

# Search by last time interpreted: Date the record was last modified in GBIF
## The lastInterpreted parameter accepts ISO 8601 format dates, including
## yyyy, yyyy-MM, yyyy-MM-dd, or MM-dd. Range queries are accepted for lastInterpreted
occ_data(lastInterpreted = '2016-04-02', limit = 20)

# Search for occurrences with images
occ_data(mediaType = 'StillImage', limit = 20)
occ_data(mediaType = 'MovingImage', limit = 20)
occ_data(mediaType = 'Sound', limit = 20)

# Search by continent
## One of africa, antarctica, asia, europe, north_america, oceania, or
## south_america
occ_data(continent = 'south_america', limit = 20)$meta
occ_data(continent = 'africa', limit = 20)$meta
occ_data(continent = 'oceania', limit = 20)$meta
occ_data(continent = 'antarctica', limit = 20)$meta
### separate requests: use a vector of strings
occ_data(continent = c('south_america', 'oceania'), limit = 20)
### one request, many instances of same parameter: use semi-colon sep. string
occ_data(continent = 'south_america;oceania', limit = 20)

# Query based on issues - see Details for options
## one issue
x <- occ_data(taxonKey=1, issue='DEPTH_UNLIKELY', limit = 20)
x$data[,c('name','key','decimalLatitude','decimalLongitude','depth')]
## two issues
occ_data(taxonKey=1, issue=c('DEPTH_UNLIKELY','COORDINATE_ROUNDED'), limit = 20)
# Show all records in the Arizona State Lichen Collection that cant be matched to the GBIF
# backbone properly:
occ_data(datasetKey='84c0e1a0-f762-11e1-a439-00145eb45e9a',
  issue=c('TAXON_MATCH_NONE','TAXON_MATCH_HIGHERRANK'), limit = 20)

# Parsing output by issue
(res <- occ_data(geometry='POLYGON((30.1 10.1,40 40,20 40,10 20,30.1 10.1))', limit = 50))
## what do issues mean, can print whole table, or search for matches

```

```

head(gbif_issues())
gbif_issues()[ gbif_issues()$code %in% c('cdround','cudc','gass84','txmathi'), ]
## or parse issues in various ways
### remove data rows with certain issue classes
library('magrittr')
res %>% occ_issues(gass84)
### split issues into separate columns
res %>% occ_issues(mutate = "split")
### expand issues to more descriptive names
res %>% occ_issues(mutate = "expand")
### split and expand
res %>% occ_issues(mutate = "split_expand")
### split, expand, and remove an issue class
res %>% occ_issues(-cudc, mutate = "split_expand")

## End(Not run)

```

occ_download

Spin up a download request for GBIF occurrence data.

Description

Spin up a download request for GBIF occurrence data.

Usage

```

occ_download(
  ...,
  body = NULL,
  type = "and",
  format = "DWCA",
  user = NULL,
  pwd = NULL,
  email = NULL,
  curlopts = list()
)

```

```

occ_download_prep(
  ...,
  body = NULL,
  type = "and",
  format = "DWCA",
  user = NULL,
  pwd = NULL,
  email = NULL,
  curlopts = list()
)

```

Arguments

...	For <code>occ_download()</code> and <code>occ_download_prep()</code> , one or more objects of class <code>occ_predicate</code> or <code>occ_predicate_list</code> , created by <code>pred*</code> functions (see download_predicate_dsl). If you use this, don't use <code>body</code> parameter.
<code>body</code>	if you prefer to pass in the payload yourself, use this parameter. if use this, don't pass anything to the dots. accepts either an R list, or JSON. JSON is likely easier, since the JSON library <code>jsonlite</code> requires that you unbox strings that shouldn't be auto-converted to arrays, which is a bit tedious for large queries. optional
<code>type</code>	(character) One of <code>equals (=)</code> , <code>and (&)</code> , <code>or (!)</code> , <code>lessThan (<)</code> , <code>lessThanOrEquals (<=)</code> , <code>greaterThan (>)</code> , <code>greaterThanOrEquals (>=)</code> , <code>in</code> , <code>within</code> , <code>not (!)</code> , <code>like</code> , <code>isNotNull</code>
<code>format</code>	(character) The download format. One of <code>'DWCA'</code> (default), <code>'SIMPLE_CSV'</code> , or <code>'SPECIES_LIST'</code>
<code>user</code>	(character) User name within GBIF's website. Required. See "Authentication" below
<code>pwd</code>	(character) User password within GBIF's website. Required. See "Authentication" below
<code>email</code>	(character) Email address to receive download notice done email. Required. See "Authentication" below
<code>curlopts</code>	list of named curl options passed on to <code>HttpClient</code> . see <code>curl::curl_options</code> for curl options

geometry

When using the `geometry` parameter, make sure that your well known text (WKT) is formatted as GBIF expects it. They expect WKT to have a counter-clockwise winding order. For example, the following is clockwise `POLYGON((-19.5 34.1, -25.3 68.1, 35.9 68.1, 27.8 34.1, -19.5 34.1))`, whereas they expect the other order: `POLYGON((-19.5 34.1, 27.8 34.1, 35.9 68.1, -25.3 68.1, -19.5 34.1))`

note that coordinate pairs are longitude latitude, longitude first, then latitude

you should not get any results if you supply WKT that has clockwise winding order.

also note that `occ_search()/occ_data()` behave differently with respect to WKT in that you can supply clockwise WKT to those functions but they treat it as an exclusion, so get all data not inside the WKT area.

Methods

- `occ_download_prep`: prepares a download request, but DOES NOT execute it. meant for use with `occ_download_queue()`
- `occ_download`: prepares a download request and DOES execute it

Authentication

For `user`, `pwd`, and `email` parameters, you can set them in one of three ways:

- Set them in your `.Rprofile` file with the names `gbif_user`, `gbif_pwd`, and `gbif_email`

- Set them in your `.Renviron/.bash_profile` (or similar) file with the names `GBIF_USER`, `GBIF_PWD`, and `GBIF_EMAIL`
- Simply pass strings to each of the parameters in the function call

We strongly recommend the second option - storing your details as environment variables as it's the most widely used way to store secrets.

See `?Startup` for help.

Query length

GBIF has a limit of 12,000 characters for a download query. This means that you can have a pretty long query, but at some point it may lead to an error on GBIF's side and you'll have to split your query into a few.

Note

see [downloads](#) for an overview of GBIF downloads methods

References

See the API docs <https://www.gbif.org/developer/occurrence#download> for more info, and the predicates docs <https://www.gbif.org/developer/occurrence#predicates>

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cached\(\)](#), [occ_download_cancel\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_datasets\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_meta\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#)

Examples

```
## Not run:
# occ_download(pred("basisOfRecord", "LITERATURE"))
# occ_download(pred("taxonKey", 3119195), pred_gt("elevation", 5000))
# occ_download(pred_gt("decimalLatitude", 50))
# occ_download(pred_gte("elevation", 9000))
# occ_download(pred_gte('decimalLatitude', 65))
# occ_download(pred("country", "US"))
# occ_download(pred("institutionCode", "TLMF"))
# occ_download(pred("catalogNumber", 217880))

# download format
# z <- occ_download(pred_gte("decimalLatitude", 75),
# format = "SPECIES_LIST")

# res <- occ_download(pred("taxonKey", 7264332), pred("hasCoordinate", TRUE))

# pass output directly, or later, to occ_download_meta for more information
# occ_download(pred_gt('decimalLatitude', 75)) %>% occ_download_meta

# Multiple queries
```

```

# occ_download(pred_gte("decimalLatitude", 65),
# pred_lte("decimalLatitude", -65), type="or")
# gg <- occ_download(pred("depth", 80), pred("taxonKey", 2343454),
# type="or")
# x <- occ_download(pred_and(pred_within("POLYGON((-14 42, 9 38, -7 26, -14 42)")),
# pred_gte("elevation", 5000))

# complex example with many predicates
# shows example of how to do date ranges for both year and month
# res <- occ_download(
# pred_gt("elevation", 5000),
# pred_in("basisOfRecord", c('HUMAN_OBSERVATION', 'OBSERVATION', 'MACHINE_OBSERVATION')),
# pred("country", "US"),
# pred("hasCoordinate", TRUE),
# pred("hasGeospatialIssue", FALSE),
# pred_gte("year", 1999),
# pred_lte("year", 2011),
# pred_gte("month", 3),
# pred_lte("month", 8)
# )

# Using body parameter - pass in your own complete query
## as JSON
query1 <- '{"creator": "sckott",
  "notification_address": ["stuff1@gmail.com"],
  "predicate": {"type": "and", "predicates": [
    {"type": "equals", "key": "TAXON_KEY", "value": "7264332"},
    {"type": "equals", "key": "HAS_COORDINATE", "value": "TRUE"}]}'
# res <- occ_download(body = query1, curlopts=list(verbose=TRUE))

## as a list
library(jsonlite)
query <- list(
  creator = unbox("sckott"),
  notification_address = "stuff1@gmail.com",
  predicate = list(
    type = unbox("and"),
    predicates = list(
      list(type = unbox("equals"), key = unbox("TAXON_KEY"),
        value = unbox("7264332")),
      list(type = unbox("equals"), key = unbox("HAS_COORDINATE"),
        value = unbox("TRUE"))
    )
  )
)
# res <- occ_download(body = query, curlopts = list(verbose = TRUE))

# Prepared query
occ_download_prep(pred("basisOfRecord", "LITERATURE"))
occ_download_prep(pred("basisOfRecord", "LITERATURE"), format = "SIMPLE_CSV")
occ_download_prep(pred("basisOfRecord", "LITERATURE"), format = "SPECIES_LIST")
occ_download_prep(pred_in("taxonKey", c(2977832, 2977901, 2977966, 2977835)))

```



```

occ_download_prep(pred_within("POLYGON((-14 42, 9 38, -7 26, -14 42))"))

## a complicated example
occ_download_prep(
  pred_in("basisOfRecord", c("MACHINE_OBSERVATION", "HUMAN_OBSERVATION")),
  pred_in("taxonKey", c(2498343, 2481776, 2481890)),
  pred_in("country", c("GB", "IE")),
  pred_or(pred_lte("year", 1989), pred("year", 2000))
)

# x = occ_download(
#   pred_in("basisOfRecord", c("MACHINE_OBSERVATION", "HUMAN_OBSERVATION")),
#   pred_in("taxonKey", c(9206251, 3112648)),
#   pred_in("country", c("US", "MX")),
#   pred_and(pred_gte("year", 1989), pred_lte("year", 1991))
# )
# occ_download_meta(x)
# z <- occ_download_get(x)
# df <- occ_download_import(z)
# str(df)
# library(dplyr)
# unique(df$basisOfRecord)
# unique(df$taxonKey)
# unique(df$countryCode)
# sort(unique(df$year))

## End(Not run)

```

occ_download_cached *Check for downloads already in your GBIF account*

Description

Check for downloads already in your GBIF account

Usage

```

occ_download_cached(
  ...,
  body = NULL,
  type = "and",
  format = "DWCA",
  user = NULL,
  pwd = NULL,
  email = NULL,
  refresh = FALSE,
  age = 30,
  curlopts = list()
)

```

Arguments

...	For <code>occ_download()</code> and <code>occ_download_prep()</code> , one or more objects of class <code>occ_predicate</code> or <code>occ_predicate_list</code> , created by <code>pred*</code> functions (see download_predicate_dsl). If you use this, don't use <code>body</code> parameter.
<code>body</code>	if you prefer to pass in the payload yourself, use this parameter. if use this, don't pass anything to the dots. accepts either an R list, or JSON. JSON is likely easier, since the JSON library jsonlite requires that you unbox strings that shouldn't be auto-converted to arrays, which is a bit tedious for large queries. optional
<code>type</code>	(character) One of <code>equals (=)</code> , <code>and (&)</code> , <code>or (!)</code> , <code>lessThan (<)</code> , <code>lessThanOrEquals (<=)</code> , <code>greaterThan (>)</code> , <code>greaterThanOrEquals (>=)</code> , <code>in</code> , <code>within</code> , <code>not (!)</code> , <code>like</code> , <code>isNotNull</code>
<code>format</code>	(character) The download format. One of <code>'DWCA'</code> (default), <code>'SIMPLE_CSV'</code> , or <code>'SPECIES_LIST'</code>
<code>user</code>	(character) User name within GBIF's website. Required. See "Authentication" below
<code>pwd</code>	(character) User password within GBIF's website. Required. See "Authentication" below
<code>email</code>	(character) Email address to receive download notice done email. Required. See "Authentication" below
<code>refresh</code>	(logical) refresh your list of downloads. on the first request of each R session we'll cache your stored GBIF occurrence downloads locally. you can refresh this list by setting <code>refresh=TRUE</code> ; if you're in the same R session, and you've done many download requests, then refreshing may be a good idea if you're using this function
<code>age</code>	(integer) number of days after which you want a new download. default: 30
<code>curlopts</code>	list of named curl options passed on to <code>HttpClient</code> . see <code>curl::curl_options</code> for curl options

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cancel\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_datasets\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_meta\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```
## Not run:
# these are examples from the package maintainer's account;
# outcomes will vary by user
occ_download_cached(pred_gte("elevation", 12000L))
occ_download_cached(pred("catalogNumber", 217880))
occ_download_cached(pred_gte("decimalLatitude", 65),
```

```

    pred_lte("decimalLatitude", -65), type="or")
occ_download_cached(pred_gte("elevation", 12000L))
occ_download_cached(pred_gte("elevation", 12000L), refresh = TRUE)

## End(Not run)

```

occ_download_cancel *Cancel a download creation process.*

Description

Cancel a download creation process.

Usage

```

occ_download_cancel(key, user = NULL, pwd = NULL, curlopts = list())

occ_download_cancel_staged(
  user = NULL,
  pwd = NULL,
  limit = 20,
  start = 0,
  curlopts = list()
)

```

Arguments

key	(character) A key generated from a request, like that from <code>occ_download</code> . Required.
user	(character) User name within GBIF's website. Required. See Details.
pwd	(character) User password within GBIF's website. Required. See Details.
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options
limit	Number of records to return. Default: 20
start	Record number to start at. Default: 0

Details

Note, these functions only cancel a job in progress. If your download is already prepared for you, this won't do anything to change that.

`occ_download_cancel` cancels a specific job by download key - returns success message

`occ_download_cancel_staged` cancels all jobs with status RUNNING or PREPARING - if none are found, returns a message saying so - if some found, they are cancelled, returning message saying so

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cached\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_datasets\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_meta\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```
## Not run:
# occ_download_cancel(key="0003984-140910143529206")
# occ_download_cancel_staged()

## End(Not run)
```

occ_download_datasets *List datasets for a download*

Description

List datasets for a download

Usage

```
occ_download_datasets(key, limit = 20, start = 0, curlopts = list())
```

Arguments

key	A key generated from a request, like that from occ_download()
limit	(integer/numeric) Number of records to return. Default: 20, Max: 1000
start	(integer/numeric) Record number to start at. Default: 0
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

a list with two slots:

- meta: a single row data.frame with columns: offset, limit, endofrecords, count
- results: a tibble with the results, of three columns: downloadKey, datasetKey, numberRecords

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cached\(\)](#), [occ_download_cancel\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_meta\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```
## Not run:
occ_download_datasets(key="0003983-140910143529206")
occ_download_datasets(key="0003983-140910143529206", limit = 3)
occ_download_datasets(key="0003983-140910143529206", limit = 3, start = 10)

## End(Not run)
```

occ_download_dataset_activity

Lists the downloads activity of a dataset

Description

Lists the downloads activity of a dataset

Usage

```
occ_download_dataset_activity(
  dataset,
  limit = 20,
  start = 0,
  curlopts = list()
)
```

Arguments

dataset	(character) A dataset key
limit	(integer/numeric) Number of records to return. Default: 20, Max: 1000
start	(integer/numeric) Record number to start at. Default: 0
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

a list with two slots:

- meta: a single row data.frame with columns: offset, limit, endofrecords, count
- results: a tibble with the nested data flattened, with many columns with the same download. or download.request. prefixes

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cached\(\)](#), [occ_download_cancel\(\)](#), [occ_download_datasets\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_meta\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```
## Not run:
res <- occ_download_dataset_activity("7f2edc10-f762-11e1-a439-00145eb45e9a")
res
res$meta
res$meta$count

# pagination
occ_download_dataset_activity("7f2edc10-f762-11e1-a439-00145eb45e9a",
  limit = 3000)
occ_download_dataset_activity("7f2edc10-f762-11e1-a439-00145eb45e9a",
  limit = 3, start = 10)

## End(Not run)
```

occ_download_get *Get a download from GBIF.*

Description

Get a download from GBIF.

Usage

```
occ_download_get(key, path = ".", overwrite = FALSE, ...)
```

Arguments

key	A key generated from a request, like that from <code>occ_download</code>
path	Path to write zip file to. Default: ".", with a .zip appended to the end.
overwrite	Will only overwrite existing path if TRUE.
...	named curl options passed on to <code>curl::verb-GET</code> . see <code>curl::curl_options()</code> for curl options

Details

Downloads the zip file to a directory you specify on your machine. `curl::HttpClient()` is used internally to write the zip file to disk. See [curl::writing-options](#). This function only downloads the file. See `occ_download_import` to open a downloaded file in your R session. The speed of this function is of course proportional to the size of the file to download. For example, a 58 MB file on my machine took about 26 seconds.

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cached\(\)](#), [occ_download_cancel\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_datasets\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_meta\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```
## Not run:
occ_download_get("0000066-140928181241064")
occ_download_get("0003983-140910143529206", overwrite = TRUE)

## End(Not run)
```

occ_download_import *Import a downloaded file from GBIF.*

Description

Import a downloaded file from GBIF.

Usage

```
occ_download_import(
  x = NULL,
  key = NULL,
  path = ".",
  fill = FALSE,
  encoding = "UTF-8",
  ...
)

as.download(path = ".", key = NULL)

## S3 method for class 'character'
as.download(path = ".", key = NULL)

## S3 method for class 'download'
as.download(path = ".", key = NULL)
```

Arguments

x	The output of a call to <code>occ_download_get</code>
key	A key generated from a request, like that from <code>occ_download</code>
path	Path to unzip file to. Default: "." Writes to folder matching zip file name
fill	(logical) (default: FALSE). If TRUE then in case the rows have unequal length, blank fields are implicitly filled. passed on to <code>fill</code> parameter in <code>data.table::fread</code> .
encoding	(character) encoding to read in data; passed to <code>data.table::fread()</code> . default: "UTF-8". other allowed options: "Latin-1" and "unknown". see <code>?data.table::fread</code> docs
...	parameters passed on to <code>data.table::fread()</code>

Details

You can provide either `x` as input, or both `key` and `path`. We use `data.table::fread()` internally to read data.

Value

a tibble (data.frame)

Problems reading data

You may run into errors when using `occ_download_import()`; most often these are due to `data.table::fread()` not being able to parse the `occurrence.txt` file correctly. The `fill` parameter passes down to `data.table::fread()` and the `...` allows you to pass on any other parameters that `data.table::fread()` accepts. Read the docs for `fread` for help.

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: `download_predicate_dsl`, `occ_download_cached()`, `occ_download_cancel()`, `occ_download_dataset_activity()`, `occ_download_datasets()`, `occ_download_get()`, `occ_download_list()`, `occ_download_meta()`, `occ_download_queue()`, `occ_download_wait()`, `occ_download()`

Examples

```
## Not run:
# First, kick off at least 1 download, then wait for the job to be complete
# Then use your download keys
res <- occ_download_get(key="0000066-140928181241064", overwrite=TRUE)
occ_download_import(res)

occ_download_get(key="0000066-140928181241064", overwrite = TRUE) %>%
  occ_download_import
```



```

# coerce a file path to the right class to feed to occ_download_import
# as.download("0000066-140928181241064.zip")
# as.download(key = "0000066-140928181241064")
# occ_download_import(as.download("0000066-140928181241064.zip"))

# download a dump that has a CSV file
# res <- occ_download_get(key = "0001369-160509122628363", overwrite=TRUE)
# occ_download_import(res)
# occ_download_import(key = "0001369-160509122628363")

# download and import a species list (in csv format)
# x <- occ_download_get("0000172-190415153152247")
# occ_download_import(x)

## End(Not run)

```

occ_download_list *Lists the downloads created by a user.*

Description

Lists the downloads created by a user.

Usage

```

occ_download_list(
  user = NULL,
  pwd = NULL,
  limit = 20,
  start = 0,
  curlopts = list()
)

```

Arguments

user	(character) User name within GBIF's website. Required. See Details.
pwd	(character) User password within GBIF's website. Required. See Details.
limit	(integer/numeric) Number of records to return. Default: 20, Max: 1000
start	(integer/numeric) Record number to start at. Default: 0
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

a list with two slots:

- meta: a single row data.frame with columns: offset, limit, endofrecords, count
- results: a tibble with the nested data flattened, with many columns with the same request. prefix

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cached\(\)](#), [occ_download_cancel\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_datasets\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_meta\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```
## Not run:
occ_download_list(user="sckott")
occ_download_list(user="sckott", limit = 5)
occ_download_list(user="sckott", start = 21)

## End(Not run)
```

occ_download_meta	<i>Retrieves the occurrence download metadata by its unique key.</i>
-------------------	--

Description

Retrieves the occurrence download metadata by its unique key.

Usage

```
occ_download_meta(key, curlopts = list())
```

Arguments

key	A key generated from a request, like that from <code>occ_download</code>
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

an object of class `occ_download_meta`, a list with slots for the download key, the DOI assigned to the download, license link, the request details you sent in the `occ_download()` request, and metadata about the size and date/time of the request

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cached\(\)](#), [occ_download_cancel\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_datasets\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_queue\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```
## Not run:
occ_download_meta(key="0003983-140910143529206")
occ_download_meta("0000066-140928181241064")

## End(Not run)
```

occ_download_queue *Download requests in a queue*

Description

Download requests in a queue

Usage

```
occ_download_queue(..., .list = list(), status_ping = 10)
```

Arguments

...	any number of occ_download() requests
.list	any number of occ_download_prep() requests
status_ping	(integer) seconds between pings checking status of the download request. generally larger numbers for larger requests. default: 10 (i.e., 10 seconds). must be 10 or greater

Details

This function is a convenience wrapper around [occ_download\(\)](#), allowing the user to kick off any number of requests, while abiding by GBIF rules of 3 concurrent requests per user.

Value

a list of `occ_download` class objects, see [occ_download_get\(\)](#) to fetch data

How it works

It works by using lazy evaluation to collect your requests into a queue (but does not use lazy evaluation if use the `.list` parameter). Then it kicks of the first 3 requests. Then in a while loop, we check status of those requests, and when any request finishes (see [When is a job done?](#) below), we kick off the next, and so on. So in theory, there may not always strictly be 3 running concurrently, but the function will usually provide for 3 running concurrently.

When is a job done?

We mark a job as done by checking the `/occurrence/download/` API route with our `occ_download_meta()` function. If the status of the job is any of "succeeded", "killed", or "cancelled", then we mark the job as done and move on to other jobs in the queue.

Beware

This function is still in development. There's a lot of complexity to this problem. We'll be rolling out fixes and improvements in future versions of the package, so expect to have to adjust your code with new versions.

Note

see [downloads](#) for an overview of GBIF downloads methods

See Also

Other downloads: [download_predicate_dsl](#), [occ_download_cached\(\)](#), [occ_download_cancel\(\)](#), [occ_download_dataset_activity\(\)](#), [occ_download_datasets\(\)](#), [occ_download_get\(\)](#), [occ_download_import\(\)](#), [occ_download_list\(\)](#), [occ_download_meta\(\)](#), [occ_download_wait\(\)](#), [occ_download\(\)](#)

Examples

```
## Not run:
if (interactive()) { # dont run in automated example runs, too costly
# passing occ_download() requests via ...
out <- occ_download_queue(
  occ_download(pred('taxonKey', 3119195), pred("year", 1976)),
  occ_download(pred('taxonKey', 3119195), pred("year", 2001)),
  occ_download(pred('taxonKey', 3119195), pred("year", 2001),
    pred_lte("month", 8)),
  occ_download(pred('taxonKey', 5229208), pred("year", 2011)),
  occ_download(pred('taxonKey', 2480946), pred("year", 2015)),
  occ_download(pred("country", "NZ"), pred("year", 1999),
    pred("month", 3)),
  occ_download(pred("catalogNumber", "Bird.27847588"),
    pred("year", 1998), pred("month", 2))
)

# supports <= 3 requests too
out <- occ_download_queue(
  occ_download(pred("country", "NZ"), pred("year", 1999), pred("month", 3)),
  occ_download(pred("catalogNumber", "Bird.27847588"), pred("year", 1998),
    pred("month", 2))
)

# using pre-prepared requests via .list
keys <- c(7905507, 5384395, 8911082)
queries <- list()
for (i in seq_along(keys)) {
  queries[[i]] <- occ_download_prep(
```

```

    pred("taxonKey", keys[i]),
    pred_in("basisOfRecord", c("HUMAN_OBSERVATION", "OBSERVATION")),
    pred("hasCoordinate", TRUE),
    pred("hasGeospatialIssue", FALSE),
    pred("year", 1993)
  )
}
out <- occ_download_queue(.list = queries)
out

# another pre-prepared example
yrs <- 1930:1934
queries <- list()
for (i in seq_along(yrs)) {
  queries[[i]] <- occ_download_prep(
    pred("taxonKey", 2877951),
    pred_in("basisOfRecord", c("HUMAN_OBSERVATION", "OBSERVATION")),
    pred("hasCoordinate", TRUE),
    pred("hasGeospatialIssue", FALSE),
    pred("year", yrs[i])
  )
}
out <- occ_download_queue(.list = queries)
out
}
## End(Not run)

```

occ_download_wait *Wait for an occurrence download to be done*

Description

Wait for an occurrence download to be done

Usage

```
occ_download_wait(x, status_ping = 5, curlopts = list(), quiet = FALSE)
```

Arguments

x	and object of class <code>occ_download</code>
status_ping	(integer) seconds between each <code>occ_download_meta()</code> request. default is 5, and cannot be < 3
curlopts	(list) curl options, as named list, passed on to <code>occ_download_meta()</code>
quiet	(logical) suppress messages. default: FALSE

Value

an object of class `occ_download_meta`, see `occ_download_meta()` for details

Note

`occ_download_queue()` is similar, but handles many requests at once; `occ_download_wait` handles one request at a time

See Also

Other downloads: `download_predicate_dsl`, `occ_download_cached()`, `occ_download_cancel()`, `occ_download_dataset_activity()`, `occ_download_datasets()`, `occ_download_get()`, `occ_download_import()`, `occ_download_list()`, `occ_download_meta()`, `occ_download_queue()`, `occ_download()`

Examples

```
## Not run:
x <- occ_download(
  pred("taxonKey", 9206251),
  pred_in("country", c("US", "MX")),
  pred_gte("year", 1971)
)
res <- occ_download_wait(x)
occ_download_meta(x)

## End(Not run)
```

occ_facet

Facet GBIF occurrences

Description

Facet GBIF occurrences

Usage

```
occ_facet(facet, facetMincount = NULL, curlopts = list(), ...)
```

Arguments

facet	(character) a character vector of length 1 or greater. Required.
facetMincount	(numeric) minimum number of records to be included in the faceting results
curlopts	list of named curl options passed on to <code>HttpClient</code> . see <code>curl::curl_options</code> for curl options
...	Facet parameters, such as for paging based on each facet variable, e.g., <code>country.facetLimit</code>

Details

All fields can be faceted on except for last "lastInterpreted", "eventDate", and "geometry"

If a faceted variable is not found, it is silently dropped, returning nothing for that query

Value

A list of tibbles (data.frame's) for each facet (each element of the facet parameter).

See Also

[occ_search\(\)](#) also has faceting ability, but can include occurrence data in addition to facets

Examples

```
## Not run:
occ_facet(facet = "country")

# facetMincount - minimum number of records to be included
# in the faceting results
occ_facet(facet = "country", facetMincount = 30000000L)
occ_facet(facet = c("country", "basisOfRecord"))

# paging with many facets
occ_facet(
  facet = c("country", "basisOfRecord", "hasCoordinate"),
  country.facetLimit = 3,
  basisOfRecord.facetLimit = 6
)

# paging
## limit
occ_facet(facet = "country", country.facetLimit = 3)
## offset
occ_facet(facet = "country", country.facetLimit = 3,
  country.facetOffset = 3)

# Pass on curl options
occ_facet(facet = "country", country.facetLimit = 3,
  curlopts = list(verbose = TRUE))

## End(Not run)
```

occ_fields

Vector of fields in the output for the function [occ_search\(\)](#)

Description

These fields can be specified in the fields parameter in the [occ_search\(\)](#) function.

 occ_get

 Get data for GBIF occurrences by occurrence key

Description

Get data for GBIF occurrences by occurrence key

Usage

```
occ_get(
  key,
  fields = "minimal",
  curlopts = list(),
  return = NULL,
  verbatim = NULL
)

occ_get_verbatim(key, fields = "minimal", curlopts = list())
```

Arguments

key	(numeric/integer) one or more occurrence keys. required
fields	(character) Default ("minimal") will return just taxon name, key, latitude, and longitude. 'all' returns all fields. Or specify each field you want returned by name, e.g. fields = c('name', 'decimalLatitude', 'altitude').
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options
return	Defunct. All components are returned now; index to the one(s) you want
verbatim	Defunct. verbatim records can now be retrieved using <code>occ_get_verbatim()</code>

Value

For `occ_get` a list of lists. For `occ_get_verbatim` a `data.frame`

References

<https://www.gbif.org/developer/occurrence#occurrence>

Examples

```
## Not run:
occ_get(key=855998194)

# many occurrences
occ_get(key=c(101010, 240713150, 855998194))

# Verbatim data
```



```

occ_get_verbatim(key=855998194)
occ_get_verbatim(key=855998194, fields='all')
occ_get_verbatim(key=855998194,
  fields=c('scientificName', 'lastCrawled', 'county'))
occ_get_verbatim(key=c(855998194, 620594291))
occ_get_verbatim(key=c(855998194, 620594291), fields='all')
occ_get_verbatim(key=c(855998194, 620594291),
  fields=c('scientificName', 'decimalLatitude', 'basisOfRecord'))

# curl options, pass in a named list
occ_get(key=855998194, curlopts = list(verbose=TRUE))

## End(Not run)

```

occ_issues

Parse and examine further GBIF occurrence issues on a dataset.

Description

Parse and examine further GBIF occurrence issues on a dataset.

Usage

```
occ_issues(.data, ..., mutate = NULL)
```

Arguments

.data	Output from a call to <code>occ_search()</code> , <code>occ_data()</code> , or <code>occ_download_import()</code> . The data from <code>occ_download_import</code> is just a regular data.frame so you can pass in a data.frame to this function, but if it doesn't have certain columns it will fail.
...	Named parameters to only get back (e.g. <code>cdround</code>), or to remove (e.g. <code>-cdround</code>).
mutate	(character) One of: <ul style="list-style-type: none"> <code>split</code> Split issues into new columns. <code>expand</code> Expand issue abbreviated codes into descriptive names. for downloads datasets, this is not super useful since the issues come to you as expanded already. <code>split_expand</code> Split into new columns, and expand issue names. For <code>split</code> and <code>split_expand</code> , values in cells become y ("yes") or n ("no")

Details

See also the vignette **Cleaning data using GBIF issues**

Note that you can also query based on issues, e.g., `occ_search(taxonKey=1, issue='DEPTH_UNLIKELY')`. However, I imagine it's more likely that you want to search for occurrences based on a taxonomic name, or geographic area, not based on issues, so it makes sense to pull data down, then clean as needed using this function.

This function only affects the data element in the `gbif` class that is returned from a call to `occ_search()`. Maybe in a future version we will remove the associated records from the hierarchy and media elements as they are removed from the data element.

You'll notice that we sort columns to make it easier to glimpse the important parts of your data, namely taxonomic name, taxon key, latitude and longitude, and the issues. The columns are unchanged otherwise.

References

<https://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/OccurrenceIssue.html>

Examples

```
## Not run:
# what do issues mean, can print whole table
head(gbif_issues())
# or just occurrence related issues
gbif_issues()[which(gbif_issues()$type %in% c("occurrence")),]
# or search for matches
iss <- c('cdround', 'cudc', 'gass84', 'txmathi')
gbif_issues()[ gbif_issues()$code %in% iss, ]

# compare out data to after occ_issues use
(out <- occ_search(limit=100))
out %>% occ_issues(cdround)

# occ_data
(out <- occ_data(limit=100))
out %>% occ_issues(cdround)

# Parsing output by issue
(res <- occ_data(
  geometry='POLYGON((30.1 10.1,40 40,20 40,10 20,30.1 10.1))',
  limit = 600))

## or parse issues in various ways
### include only rows with cdround issue
gg <- res %>% occ_issues(cdround)
NROW(res$data)
NROW(gg$data)
head(res$data)[,c(1:5)]
head(gg$data)[,c(1:5)]

### remove data rows with certain issue classes
res %>% occ_issues(-cdround, -cudc)

### split issues into separate columns
res %>% occ_issues(mutate = "split")
res %>% occ_issues(-cudc, -mdatunl, mutate = "split")
res %>% occ_issues(gass84, mutate = "split")

### expand issues to more descriptive names
```

```

res %>% occ_issues(mutate = "expand")

### split and expand
res %>% occ_issues(mutate = "split_expand")

### split, expand, and remove an issue class
res %>% occ_issues(-cdround, mutate = "split_expand")

## Or you can use occ_issues without %>%
occ_issues(res, -cdround, mutate = "split_expand")

# from GBIF downloaded data via occ_download_* functions
res <- occ_download_get(key="0000066-140928181241064", overwrite=TRUE)
x <- occ_download_import(res)
occ_issues(x, -txmathi)
occ_issues(x, txmathi)
occ_issues(x, gass84)
occ_issues(x, zerocd)
occ_issues(x, gass84, txmathi)
occ_issues(x, mutate = "split")
occ_issues(x, -gass84, mutate = "split")
occ_issues(x, mutate = "expand")
occ_issues(x, mutate = "split_expand")

# occ_search/occ_data with many inputs - give slightly different output
# format than normal 2482598, 2498387
xyz <- occ_data(taxonKey = c(9362842, 2492483, 2435099), limit = 300)
xyz
length(xyz) # length 3
names(xyz) # matches taxonKey values passed in
occ_issues(xyz, -gass84)
occ_issues(xyz, -cdround)
occ_issues(xyz, -cdround, -gass84)

## End(Not run)

```

occ_metadata	<i>Search for catalog numbers, collection codes, collector names, and institution codes.</i>
--------------	--

Description

Search for catalog numbers, collection codes, collector names, and institution codes.

Usage

```

occ_metadata(
  type = "catalogNumber",
  q = NULL,
  limit = 5,

```

```

    pretty = TRUE,
    curlopts = list()
  )

```

Arguments

type	Type of data, one of catalogNumber, collectionCode, recordedBy, or institutionCode. Unique partial strings work too, like 'cat' for catalogNumber
q	Search term
limit	Number of results, default=5
pretty	Pretty as true (Default) uses cat to print data, FALSE gives character strings.
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

References

<https://www.gbif.org/developer/occurrence#search>

Examples

```

## Not run:
# catalog number
occ_metadata(type = "catalogNumber", q=122)

# collection code
occ_metadata(type = "collectionCode", q=12)

# institution code
occ_metadata(type = "institutionCode", q='GB')

# recorded by
occ_metadata(type = "recordedBy", q='scott')

# data as character strings
occ_metadata(type = "catalogNumber", q=122, pretty=FALSE)

# Change number of results returned
occ_metadata(type = "catalogNumber", q=122, limit=10)

# Partial unique type strings work too
occ_metadata(type = "cat", q=122)

# Pass on curl options
occ_metadata(type = "cat", q=122, curlopts = list(verbose = TRUE))

## End(Not run)

```

occ_search	<i>Search for GBIF occurrences</i>
------------	------------------------------------

Description

Search for GBIF occurrences

Usage

```
occ_search(  
  taxonKey = NULL,  
  scientificName = NULL,  
  country = NULL,  
  publishingCountry = NULL,  
  hasCoordinate = NULL,  
  typeStatus = NULL,  
  recordNumber = NULL,  
  lastInterpreted = NULL,  
  continent = NULL,  
  geometry = NULL,  
  geom_big = "asis",  
  geom_size = 40,  
  geom_n = 10,  
  recordedBy = NULL,  
  recordedByID = NULL,  
  identifiedByID = NULL,  
  basisOfRecord = NULL,  
  datasetKey = NULL,  
  eventDate = NULL,  
  catalogNumber = NULL,  
  year = NULL,  
  month = NULL,  
  decimalLatitude = NULL,  
  decimalLongitude = NULL,  
  elevation = NULL,  
  depth = NULL,  
  institutionCode = NULL,  
  collectionCode = NULL,  
  hasGeospatialIssue = NULL,  
  issue = NULL,  
  search = NULL,  
  mediaType = NULL,  
  subgenusKey = NULL,  
  repatriated = NULL,  
  phylumKey = NULL,  
  kingdomKey = NULL,  
  classKey = NULL,
```

```

orderKey = NULL,
familyKey = NULL,
genusKey = NULL,
establishmentMeans = NULL,
protocol = NULL,
license = NULL,
organismId = NULL,
publishingOrg = NULL,
stateProvince = NULL,
waterBody = NULL,
locality = NULL,
limit = 500,
start = 0,
fields = "all",
return = NULL,
facet = NULL,
facetMincount = NULL,
facetMultiselect = NULL,
skip_validate = TRUE,
curlopts = list(),
...
)

```

Arguments

taxonKey	(numeric) A taxon key from the GBIF backbone. All included and synonym taxa are included in the search, so a search for aves with taxonKey=212 (i.e. /occurrence/search?taxonKey=212) will match all birds, no matter which species. You can pass many keys by passing occ_search in a call to an lapply-family function (see last example below).
scientificName	A scientific name from the GBIF backbone. All included and synonym taxa are included in the search.
country	The 2-letter country code (as per ISO-3166-1) of the country in which the occurrence was recorded. See here https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2
publishingCountry	The 2-letter country code (as per ISO-3166-1) of the country in which the occurrence was recorded.
hasCoordinate	(logical) Return only occurrence records with lat/long data (TRUE) or all records (FALSE, default).
typeStatus	Type status of the specimen. One of many options. See ?typestatus
recordNumber	Number recorded by collector of the data, different from GBIF record number. See http://rs.tdwg.org/dwc/terms/#recordNumber for more info
lastInterpreted	Date the record was last modified in GBIF, in ISO 8601 format: yyyy, yyyy-MM, yyyy-MM-dd, or MM-dd. Supports range queries, smaller, larger (e.g., '1990,1991', whereas '1991,1990' wouldn't work)

continent	Continent. One of africa, antarctica, asia, europe, north_america (North America includes the Caribbean and reaches down and includes Panama), oceania, or south_america
geometry	Searches for occurrences inside a polygon described in Well Known Text (WKT) format. A WKT shape written as either POINT, LINESTRING, LINEARRING POLYGON, or MULTIPOLYGON. Example of a polygon: POLYGON((30.1 10.1, 20, 20 40, 40 40, 30.1 10.1)) would be queried as http://bit.ly/1BzNwDq See also the section WKT below.
geom_big	(character) One of "axe", "bbox", or "asis" (default). See Details.
geom_size	(integer) An integer indicating size of the cell. Default: 40. See Details.
geom_n	(integer) An integer indicating number of cells in each dimension. Default: 10. See Details.
recordedBy	The person who recorded the occurrence.
recordedByID	(character) Identifier (e.g. ORCID) for the person who recorded the occurrence
identifiedByID	(character) Identifier (e.g. ORCID) for the person who provided the taxonomic identification of the occurrence.
basisOfRecord	Basis of record, as defined in our BasisOfRecord enum here https://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/BasisOfRecord.html Acceptable values are: <ul style="list-style-type: none"> • FOSSIL_SPECIMEN An occurrence record describing a fossilized specimen. • HUMAN_OBSERVATION An occurrence record describing an observation made by one or more people. • LITERATURE An occurrence record based on literature alone. • LIVING_SPECIMEN An occurrence record describing a living specimen, e.g. • MACHINE_OBSERVATION An occurrence record describing an observation made by a machine. • OBSERVATION An occurrence record describing an observation. • PRESERVED_SPECIMEN An occurrence record describing a preserved specimen. • UNKNOWN Unknown basis for the record.
datasetKey	The occurrence dataset key (a uuid)
eventDate	Occurrence date in ISO 8601 format: yyyy, yyyy-MM, yyyy-MM-dd, or MM-dd. Supports range queries, smaller,larger (e.g., '1990,1991', whereas '1991,1990' wouldn't work)
catalogNumber	An identifier of any form assigned by the source within a physical collection or digital dataset for the record which may not unique, but should be fairly unique in combination with the institution and collection code.
year	The 4 digit year. A year of 98 will be interpreted as AD 98. Supports range queries, smaller,larger (e.g., '1990,1991', whereas '1991,1990' wouldn't work)
month	The month of the year, starting with 1 for January. Supports range queries, smaller,larger (e.g., '1,2', whereas '2,1' wouldn't work)

decimalLatitude	Latitude in decimals between -90 and 90 based on WGS 84. Supports range queries, smaller,larger (e.g., '25,30', whereas '30,25' wouldn't work)
decimalLongitude	Longitude in decimals between -180 and 180 based on WGS 84. Supports range queries (e.g., '-0.4,-0.2', whereas '-0.2,-0.4' wouldn't work).
elevation	Elevation in meters above sea level. Supports range queries, smaller,larger (e.g., '5,30', whereas '30,5' wouldn't work)
depth	Depth in meters relative to elevation. For example 10 meters below a lake surface with given elevation. Supports range queries, smaller,larger (e.g., '5,30', whereas '30,5' wouldn't work)
institutionCode	An identifier of any form assigned by the source to identify the institution the record belongs to. Not guaranteed to be que.
collectionCode	An identifier of any form assigned by the source to identify the physical collection or digital dataset uniquely within the text of an institution.
hasGeospatialIssue	(logical) Includes/excludes occurrence records which contain spatial issues (as determined in our record interpretation), i.e. hasGeospatialIssue=TRUE returns only those records with spatial issues while hasGeospatialIssue=FALSE includes only records without spatial issues. The absence of this parameter returns any record with or without spatial issues.
issue	(character) One or more of many possible issues with each occurrence record. See Details. Issues passed to this parameter filter results by the issue.
search	Query terms. The value for this parameter can be a simple word or a phrase.
mediaType	Media type. Default is NULL, so no filtering on mediatype. Options: NULL, 'MovingImage', 'Sound', and 'StillImage'.
subgenusKey	(numeric) Subgenus classification key.
repatriated	(character) Searches for records whose publishing country is different to the country where the record was recorded in.
phylumKey	(numeric) Phylum classification key.
kingdomKey	(numeric) Kingdom classification key.
classKey	(numeric) Class classification key.
orderKey	(numeric) Order classification key.
familyKey	(numeric) Family classification key.
genusKey	(numeric) Genus classification key.
establishmentMeans	(character) EstablishmentMeans, possible values include: INTRODUCED, INVASIVE, MANAGED, NATIVE, NATURALISED, UNCERTAIN
protocol	(character) Protocol or mechanism used to provide the occurrence record. See Details for possible values
license	(character) The type license applied to the dataset or record. Possible values: CC0_1_0, CC_BY_4_0, CC_BY_NC_4_0, UNSPECIFIED, and UNSUPPORTED

organismId	(numeric) An identifier for the Organism instance (as opposed to a particular digital record of the Organism). May be a globally unique identifier or an identifier specific to the data set.
publishingOrg	(character) The publishing organization key (a UUID).
stateProvince	(character) The name of the next smaller administrative region than country (state, province, canton, department, region, etc.) in which the Location occurs.
waterBody	(character) The name of the water body in which the locations occur
locality	(character) The specific description of the place.
limit	Number of records to return. Default: 500. Note that the per request maximum is 300, but since we set it at 500 for the function, we do two requests to get you the 500 records (if there are that many). Note that there is a hard maximum of 100,000, which is calculated as the limit+start, so start=99,000 and limit=2000 won't work
start	Record number to start at. Use in combination with limit to page through results. Note that we do the paging internally for you, but you can manually set the start parameter
fields	(character) Default ('all') returns all fields. 'minimal' returns just taxon name, key, latitude, and longitude. Or specify each field you want returned by name, e.g. fields = c('name','latitude','elevation').
return	Defunct. All components (meta, hierarchy, data, media, facets) are returned now; index to the one(s) you want. See occ_data() if you just want the data component
facet	(character) a character vector of length 1 or greater. Required.
facetMincount	(numeric) minimum number of records to be included in the faceting results
facetMultiselect	(logical) Set to TRUE to still return counts for values that are not currently filtered. See examples. Default: FALSE Faceting: All fields can be faceted on except for last "lastInterpreted", "eventDate", and "geometry" You can do facet searches alongside searching occurrence data, and return both, or only return facets, or only occurrence data, etc.
skip_validate	(logical) whether to skip <code>wellknown::validate_wkt</code> call or not. passed down to check_wkt() . Default: TRUE
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options
...	additional facet parameters

Value

An object of class `gbif`, which is a S3 class list, with slots for metadata (`meta`), the occurrence data itself (`data`), the taxonomic hierarchy data (`hier`), and media metadata (`media`). In addition, the object has attributes listing the user supplied arguments and whether it was a 'single' or 'many' search; that is, if you supply two values of the `datasetKey` parameter to searches are done, and it's a 'many'. `meta` is a list of length four with `offset`, `limit`, `endOfRecords` and `count` fields. `data`

is a tibble (aka data.frame). hier is a list of data.frames of the unique set of taxa found, where each data.frame is its taxonomic classification. media is a list of media objects, where each element holds a set of metadata about the media object.

protocol parameter options

- BIOCASE - A BioCASE protocol compliant service.
- DIGIR - A DiGIR service endpoint.
- DIGIR_MANIS - A DiGIR service slightly modified for the MANIS network.
- DWC_ARCHIVE - A Darwin Core Archive as defined by the Darwin Core Text Guidelines.
- EML - A single EML metadata document in any EML version.
- FEED - Syndication feeds like RSS or ATOM of various flavors.
- OAI_PMH - The Open Archives Initiative Protocol for Metadata Harvesting.
- OTHER - Any other service not covered by this enum so far.
- TAPIR - A TAPIR service.
- TCS_RDF - Taxon Concept data given as RDF based on the TDWG ontology.
- TCS_XML - A Taxon Concept Schema document.
- WFS - An OGC Web Feature Service.
- WMS - An OGC Web Map Service.

Multiple values passed to a parameter

There are some parameters you can pass multiple values to in a vector, each value of which produces a different request (MDR: multiple different requests). Some parameters allow multiple values to be passed in the same request (MSR: multiple same request) in a semicolon separated string (e.g., 'a;b'); if given we'll do a single request with that parameter repeated for each value given (e.g., foo=a&foo=b if the parameter is foo). Some parameters allow both MDR and MSR.

The following list shows which parameters support MDR and MSR.

- basisOfRecord: MDR, MSR
- classKey: MDR, MSR
- country: MDR, MSR
- familyKey: MDR, MSR
- genusKey: MDR, MSR
- identifiedByID: MDR, MSR
- kingdomKey: MDR, MSR
- license: MDR, MSR
- locality: MDR, MSR
- catalogNumber: MDR, MSR
- collectionCode: MDR, MSR
- continent: MDR, MSR

- datasetKey: MDR, MSR
- establishmentMeans: MDR, MSR
- geometry: MDR, MSR
- institutionCode: MDR, MSR
- mediaType: MDR, MSR
- orderKey: MDR, MSR
- organismId: MDR, MSR
- phylumKey: MDR, MSR
- protocol: MDR, MSR
- publishingCountry: MDR, MSR
- publishingOrg: MDR, MSR
- recordedBy: MDR, MSR
- recordedById: MDR, MSR
- recordNumber: MDR, MSR
- scientificName: MDR, MSR
- stateProvince: MDR, MSR
- subgenusKey: MDR, MSR
- taxonKey: MDR, MSR
- typeStatus: MDR, MSR
- waterBody: MDR, MSR
- depth: MDR
- limit: MDR
- q: MDR
- year: MDR
- repatriated: MDR
- lastInterpreted: MDR
- decimalLatitude: MDR
- decimalLongitude: MDR

Note that you can not pass a vector > length 1 to more than 1 of the above MDR parameters at the same time.

see also [many-values](#)

Range queries

A range query is as it sounds - you query on a range of values defined by a lower and upper limit. Do a range query by specifying the lower and upper limit in a string like `depth='50,100'`. It would be more R like to specify the range in a vector like `c(50,100)`, but that sort of syntax allows you to do many searches, one for each element in the vector - thus range queries have to differ. The following parameters support range queries.

- decimalLatitude
- decimalLongitude
- depth
- elevation
- eventDate
- lastInterpreted
- month
- year

See also above section: semicolon and comma separated strings lead to different outcomes for some parameters.

Hierarchies

Hierarchies are returned with each occurrence object. There is no option no to return them from the API. However, within the `occ_search` function you can select whether to return just hierarchies, just data, all of data and hierarchies and metadata, or just metadata. If all hierarchies are the same we just return one for you.

curl debugging

You can pass parameters not defined in this function into the call to the GBIF API to control things about the call itself using `curlOpts`. See an example below that passes in the `verbose` function to get details on the http call.

Scientific names vs. taxon keys

In the previous GBIF API and the version of `rgbif` that wrapped that API, you could search the equivalent of this function with a species name, which was convenient. However, names are messy right. So it sorta makes sense to sort out the species key numbers you want exactly, and then get your occurrence data with this function. GBIF has added a parameter `scientificName` to allow searches by scientific names in this function - which includes synonym taxa. *Note:* that if you do use the `scientificName` parameter, we will check internally that it's not a synonym of an accepted name, and if it is, we'll search on the accepted name. If you want to force searching by a synonym do so by finding the GBIF identifier first with any `name_*` functions, then pass that ID to the `taxonKey` parameter.

WKT

Examples of valid WKT objects:

- `'POLYGON((-19.5 34.1, 27.8 34.1, 35.9 68.1, -25.3 68.1, -19.5 34.1))'`
- `'MULTIPOLYGON(((-123 38, -116 38, -116 43, -123 43, -123 38)), ((-97 41, -93 41, -93 45, -97 45, -97 41)))'`
- `'POINT(-120 40)'`
- `'LINESTRING(3 4, 10 50, 20 25)'`
- `'LINEARRING' '???'` - Not sure how to specify this. Anyone?

Note that GBIF expects counter-clockwise winding order for WKT. You can supply clockwise WKT, but GBIF treats it as an exclusion, so you get all data not inside the WKT area. [occ_download\(\)](#) behaves differently in that you should simply get no data back at all with clockwise WKT.

Long WKT

Options for handling long WKT strings: Note that long WKT strings are specially handled when using [occ_search](#) or [occ_data](#). Here are the three options for long WKT strings (> 1500 characters), set one of these three via the parameter `geom_big`:

- `asis` - the default setting. This means we don't do anything internally. That is, we just pass on your WKT string just as we've done before in this package.
- `axe` - this option uses the **geoaxe** package to chop up your WKT string in to many polygons, which then leads to a separate data request for each polygon piece, then we combine all data back together to give to you. Note that if your WKT string is not of type polygon, we drop back to `asis` as there's no way to chop up linestrings, etc. This option will in most cases be slower than the other two options. However, this polygon splitting approach won't have the problem of the disconnect between how many records you want and what you actually get back as with the `bbox` option.

This method uses [chop](#), which uses `GridTopology` from the **sp** package, which has two parameters `cellsize` and `cells.dim` that we use to chop up polygons. You can tweak those parameters here by tweaking `geom_size` and `geom_n`. `geom_size` seems to be more useful in toggling the number of WKT strings you get back.

See [wkt_parse](#) to manually break make WKT bounding box from a larger WKT string, or break a larger WKT string into many smaller ones.

- `bbox` - this option checks whether your WKT string is longer than 1500 characters, and if it is we create a bounding box from the WKT, do the GBIF search with that bounding box, then prune the resulting data to only those occurrences in your original WKT string. There is a big caveat however. Because we create a bounding box from the WKT, and the `limit` parameter determines some subset of records to get, then when we prune the resulting data to the WKT, the number of records you get could be less than what you set with your `limit` parameter. However, you could set the limit to be high enough so that you get all records back found in that bounding box, then you'll get all the records available within the WKT.

issue parameter

The options for the issue parameter (from <https://gbif.github.io/gbif-api/apidocs/org/gbif/api/vocabulary/OccurrenceIssue.htm>)

- `BASIS_OF_RECORD_INVALID` The given basis of record is impossible to interpret or seriously different from the recommended vocabulary.
- `CONTINENT_COUNTRY_MISMATCH` The interpreted continent and country do not match up.
- `CONTINENT_DERIVED_FROM_COORDINATES` The interpreted continent is based on the coordinates, not the verbatim string information.
- `CONTINENT_INVALID` Uninterpretable continent values found.
- `COORDINATE_INVALID` Coordinate value given in some form but GBIF is unable to interpret it.

- **COORDINATE_OUT_OF_RANGE** Coordinate has invalid lat/lon values out of their decimal max range.
- **COORDINATE_REPROJECTED** The original coordinate was successfully reprojected from a different geodetic datum to WGS84.
- **COORDINATE_REPROJECTION_FAILED** The given decimal latitude and longitude could not be reprojected to WGS84 based on the provided datum.
- **COORDINATE_REPROJECTION_SUSPICIOUS** Indicates successful coordinate reprojection according to provided datum, but which results in a datum shift larger than 0.1 decimal degrees.
- **COORDINATE_ROUNDED** Original coordinate modified by rounding to 5 decimals.
- **COUNTRY_COORDINATE_MISMATCH** The interpreted occurrence coordinates fall outside of the indicated country.
- **COUNTRY_DERIVED_FROM_COORDINATES** The interpreted country is based on the coordinates, not the verbatim string information.
- **COUNTRY_INVALID** Uninterpretable country values found.
- **COUNTRY_MISMATCH** Interpreted country for dwc:country and dwc:countryCode contradict each other.
- **DEPTH_MIN_MAX_SWAPPED** Set if supplied min>max
- **DEPTH_NON_NUMERIC** Set if depth is a non numeric value
- **DEPTH_NOT_METRIC** Set if supplied depth is not given in the metric system, for example using feet instead of meters
- **DEPTH_UNLIKELY** Set if depth is larger than 11.000m or negative.
- **ELEVATION_MIN_MAX_SWAPPED** Set if supplied min > max elevation
- **ELEVATION_NON_NUMERIC** Set if elevation is a non numeric value
- **ELEVATION_NOT_METRIC** Set if supplied elevation is not given in the metric system, for example using feet instead of meters
- **ELEVATION_UNLIKELY** Set if elevation is above the troposphere (17km) or below 11km (Mariana Trench).
- **GEODETIC_DATUM_ASSUMED_WGS84** Indicating that the interpreted coordinates assume they are based on WGS84 datum as the datum was either not indicated or interpretable.
- **GEODETIC_DATUM_INVALID** The geodetic datum given could not be interpreted.
- **IDENTIFIED_DATE_INVALID** The date given for dwc:dateIdentified is invalid and cant be interpreted at all.
- **IDENTIFIED_DATE_UNLIKELY** The date given for dwc:dateIdentified is in the future or before Linnean times (1700).
- **MODIFIED_DATE_INVALID** A (partial) invalid date is given for dc:modified, such as a non existing date, invalid zero month, etc.
- **MODIFIED_DATE_UNLIKELY** The date given for dc:modified is in the future or predates unix time (1970).
- **MULTIMEDIA_DATE_INVALID** An invalid date is given for dc:created of a multimedia object.

- MULTIMEDIA_URI_INVALID An invalid uri is given for a multimedia object.
- PRESUMED_NEGATED_LATITUDE Latitude appears to be negated, e.g. 32.3 instead of -32.3
- PRESUMED_NEGATED_LONGITUDE Longitude appears to be negated, e.g. 32.3 instead of -32.3
- PRESUMED_SWAPPED_COORDINATE Latitude and longitude appear to be swapped.
- RECORDED_DATE_INVALID A (partial) invalid date is given, such as a non existing date, invalid zero month, etc.
- RECORDED_DATE_MISMATCH The recording date specified as the eventDate string and the individual year, month, day are contradicting.
- RECORDED_DATE_UNLIKELY The recording date is highly unlikely, falling either into the future or represents a very old date before 1600 that predates modern taxonomy.
- REFERENCES_URI_INVALID An invalid uri is given for dc:references.
- TAXON_MATCH_FUZZY Matching to the taxonomic backbone can only be done using a fuzzy, non exact match.
- TAXON_MATCH_HIGHERRANK Matching to the taxonomic backbone can only be done on a higher rank and not the scientific name.
- TAXON_MATCH_NONE Matching to the taxonomic backbone cannot be done cause there was no match at all or several matches with too little information to keep them apart (homonyms).
- TYPE_STATUS_INVALID The given type status is impossible to interpret or seriously different from the recommended vocabulary.
- ZERO_COORDINATE Coordinate is the exact 0/0 coordinate, often indicating a bad null coordinate.

Counts

There is a slight difference in the way records are counted here vs. results from [occ_count](#). For equivalent outcomes, in this function use `hasCoordinate=TRUE`, and `hasGeospatialIssue=FALSE` to have the same outcome using [occ_count](#) with `isGeoreferenced=TRUE`

Note

Maximum number of records you can get with this function is 100,000. See <https://www.gbif.org/developer/occurrence>

References

<https://www.gbif.org/developer/occurrence#search>

See Also

[downloads\(\)](#), [occ_data\(\)](#), [occ_facet\(\)](#)

Examples

```
## Not run:
# Search by species name, using \code{\link{name_backbone}} first to get key
(key <- name_suggest(q='Helianthus annuus', rank='species')$data$key[1])
occ_search(taxonKey=key, limit=2)

# Return 20 results, this is the default by the way
occ_search(taxonKey=key, limit=20)

# Get just metadata
occ_search(taxonKey=key, limit=0)$meta

# Instead of getting a taxon key first, you can search for a name directly
## However, note that using this approach (with \code{scientificName="..."})
## you are getting synonyms too. The results for using \code{scientificName} and
## \code{taxonKey} parameters are the same in this case, but I wouldn't be surprised if for some
## names they return different results
occ_search(scientificName = 'Ursus americanus')
key <- name_backbone(name = 'Ursus americanus', rank='species')$usageKey
occ_search(taxonKey = key)

# Search by dataset key
occ_search(datasetKey='7b5d6a48-f762-11e1-a439-00145eb45e9a', limit=20)$data

# Search by catalog number
occ_search(catalogNumber="49366", limit=20)
## separate requests: use a vector of strings
occ_search(catalogNumber=c("49366","Bird.27847588"), limit=10)
## one request, many instances of same parameter: use semi-colon sep. string
occ_search(catalogNumber="49366;Bird.27847588", limit=10)

# Get all data, not just lat/long and name
occ_search(taxonKey=key, fields='all', limit=20)

# Or get specific fields. Note that this isn't done on GBIF's side of things. This
# is done in R, but before you get the return object, so other fields are garbage
# collected
occ_search(taxonKey=key, fields=c('name','basisOfRecord','protocol'), limit=20)

# Use paging parameters (limit and start) to page. Note the different results
# for the two queries below.
occ_search(datasetKey='7b5d6a48-f762-11e1-a439-00145eb45e9a',start=10,limit=5)$data
occ_search(datasetKey='7b5d6a48-f762-11e1-a439-00145eb45e9a',start=20,limit=5)$data

# Many dataset keys
## separate requests: use a vector of strings
occ_search(datasetKey=c("50c9509d-22c7-4a22-a47d-8c48425ef4a7",
  "7b5d6a48-f762-11e1-a439-00145eb45e9a"), limit=20)
## one request, many instances of same parameter: use semi-colon sep. string
v="50c9509d-22c7-4a22-a47d-8c48425ef4a7;7b5d6a48-f762-11e1-a439-00145eb45e9a"
occ_search(datasetKey = v, limit=20)
```



```

# Occurrence data: lat/long data, and associated metadata with occurrences
## The `data` slot has a data.frame of all data together
## for easy manipulation
occ_search(taxonKey=key, limit=20)$data

# Taxonomic hierarchy data
## In the `hier` slot
occ_search(taxonKey=key, limit=10)$hier

# Search by recorder
occ_search(recordedBy="smith", limit=20)

# Many collector names
occ_search(recordedBy=c("smith", "BJ Stacey"), limit=20)

# recordedByID
occ_search(recordedByID="https://orcid.org/0000-0003-1691-239X", limit=20)

# identifiedByID
occ_search(identifiedByID="https://orcid.org/0000-0003-4710-2648", limit=20)

# Pass in curl options for extra fun
occ_search(taxonKey=2433407, limit=20, curlopts=list(verbose=TRUE))$hier
occ_search(taxonKey=2433407, limit=20,
  curlopts = list(
    noprocess = FALSE,
    progressfunction = function(down, up) {
      cat(sprintf("up: %d | down %d\n", up, down))
      return(TRUE)
    }
  )
)$hier
# occ_search(taxonKey=2433407, limit=20,
#   curlopts = list(timeout_ms = 1))

# Search for many species
splist <- c('Cyanocitta stelleri', 'Junco hyemalis', 'Aix sponsa')
keys <- sapply(splist, function(x) name_suggest(x)$data$key[1], USE.NAMES=FALSE)
## separate requests: use a vector of strings
occ_search(taxonKey = keys, limit=5)
## one request, many instances of same parameter: use semi-colon sep. string
occ_search(taxonKey = paste0(keys, collapse = ";"), limit=5)

# Search using a synonym name
# Note that you'll see a message printing out that the accepted name will be used
occ_search(scientificName = 'Pulsatilla patens', fields = c('name', 'scientificName'), limit=5)

# Search on latitude and longitude
occ_search(decimalLatitude=48, decimalLongitude=10)

# Search on a bounding box
## in well known text format
### polygon

```

```

occ_search(geometry='POLYGON((30.1 10.1,40 40,20 40,10 20,30.1 10.1))', limit=20)
### multipolygon
wkt <- 'MULTIPOLYGON((( -123 38,-116 38,-116 43,-123 43,-123 38)),
  ((-97 41,-93 41,-93 45,-97 45,-97 41)))'
occ_search(geometry = gsub("\n\\s+", "", wkt), limit = 20)

## taxonKey + WKT
key <- name_suggest(q='Aesculus hippocastanum')$data$key[1]
occ_search(taxonKey=key, geometry='POLYGON((30.1 10.1,40 40,20 40,10 20,30.1 10.1))',
  limit=20)
## or using bounding box, converted to WKT internally
occ_search(geometry=c(-125.0,38.4,-121.8,40.9), limit=20)

# Search on a long WKT string - too long for a GBIF search API request
## We internally convert your WKT string to a bounding box
## then do the query
## then clip the results down to just those in the original polygon
## - Alternatively, you can set the parameter `geom_big="bbox"`
## - An additional alternative is to use the GBIF download API, see ?downloads
wkt <- "POLYGON((-9.178796777343678 53.22769021556159,
-12.167078027343678 51.56540789297837,
-12.958093652343678 49.78333685689162,-11.024499902343678 49.21251756301334,
-12.079187402343678 46.68179685941719,-15.067468652343678 45.83103608186854,
-15.770593652343678 43.58271629699817,-15.067468652343678 41.57676278827219,
-11.815515527343678 40.44938999172728,-12.958093652343678 37.72112962230871,
-11.639734277343678 36.52987439429357,-8.299890527343678 34.96062625095747,
-8.739343652343678 32.62357394385735,-5.223718652343678 30.90497915232165,
1.1044063476563224 31.80562077746643,1.1044063476563224 30.754036557416256,
6.905187597656322 32.02942785462211,5.147375097656322 32.99292810780193,
9.629796972656322 34.164474406524725,10.860265722656322 32.91918014319603,
14.551671972656322 33.72700959356651,13.409093847656322 34.888564192275204,
16.748937597656322 35.104560368110114,19.561437597656322 34.81643887792552,
18.594640722656322 36.38849705969625,22.989171972656322 37.162874858929854,
19.825109472656322 39.50651757842751,13.760656347656322 38.89353140585116,
14.112218847656322 42.36091601976124,10.596593847656322 41.114887306647705,
9.366125097656322 43.70991402658437,5.059484472656322 42.62015372417812,
2.3348750976563224 45.21526500321446,-0.7412967773436776 46.80225692528942,
6.114171972656322 47.102229890207894,8.047765722656322 45.52399303437107,
12.881750097656322 48.22681126957933,9.190343847656322 48.693079457106684,
8.750890722656322 50.68283120621287,5.059484472656322 50.40356146487845,
4.268468847656322 52.377558897655156,1.4559688476563224 53.28027243658647,
0.8407344726563224 51.62000971578333,0.5770625976563224 49.32721423860726,
-2.5869999023436776 49.49875947592088,-2.4991092773436776 51.18135535408638,
-2.0596561523436776 52.53822562473851,-4.696374902343678 51.67454591918756,
-5.311609277343678 50.009802108095776,-6.629968652343678 48.75106196817059,
-7.684656152343678 50.12263634382465,-6.190515527343678 51.83776110910459,
-5.047937402343678 54.267098895684235,-6.893640527343678 53.69860705549198,
-8.915124902343678 54.77719740243195,-12.079187402343678 54.52294465763567,
-13.573328027343678 53.437631551347174,
-11.288171777343678 53.48995552517918,
-9.178796777343678 53.22769021556159))"
wkt <- gsub("\n", " ", wkt)

```

```

#### Default option with large WKT string fails
# res <- occ_search(geometry = wkt)

#### if WKT too long, with 'geom_big=bbox': makes into bounding box
res <- occ_search(geometry = wkt, geom_big = "bbox")$data
library("rgeos")
library("sp")
wktsp <- readWKT(wkt)
plot(wktsp)
coordinates(res) <- ~decimalLongitude+decimalLatitude
points(res)

#### Or, use 'geom_big=axe'
(res <- occ_search(geometry = wkt, geom_big = "axe"))
##### manipulate essentially number of polygons that result, so number of requests
##### default geom_size is 40
##### fewer calls
(res <- occ_search(geometry = wkt, geom_big = "axe", geom_size=50))
##### more calls
(res <- occ_search(geometry = wkt, geom_big = "axe", geom_size=30))

# Search on country
occ_search(country='US', fields=c('name','country'), limit=20)
isocodes[grep("France", isocodes$name),"code"]
occ_search(country='FR', fields=c('name','country'), limit=20)
occ_search(country='DE', fields=c('name','country'), limit=20)
### separate requests: use a vector of strings
occ_search(country=c('US','DE'), limit=20)
### one request, many instances of same parameter: use semi-colon sep. string
occ_search(country = 'US;DE', limit=20)

# Get only occurrences with lat/long data
occ_search(taxonKey=key, hasCoordinate=TRUE, limit=20)

# Get only occurrences that were recorded as living specimens
occ_search(taxonKey=key, basisOfRecord="LIVING_SPECIMEN", hasCoordinate=TRUE, limit=20)
## multiple values in a vector = a separate request for each value
occ_search(taxonKey=key,
  basisOfRecord=c("LIVING_SPECIMEN", "HUMAN_OBSERVATION"), limit=20)
## multiple values in a single string, ";" separated = one request including all values
occ_search(taxonKey=key,
  basisOfRecord="LIVING_SPECIMEN;HUMAN_OBSERVATION", limit=20)

# Get occurrences for a particular eventDate
occ_search(taxonKey=key, eventDate="2013", limit=20)
occ_search(taxonKey=key, year="2013", limit=20)
occ_search(taxonKey=key, month="6", limit=20)

# Get occurrences based on depth
key <- name_backbone(name='Salmo salar', kingdom='animals')$speciesKey
occ_search(taxonKey=key, depth="5", limit=20)

```

```
# Get occurrences based on elevation
key <- name_backbone(name='Puma concolor', kingdom='animals')$speciesKey
occ_search(taxonKey=key, elevation=50, hasCoordinate=TRUE, limit=20)

# Get occurrences based on institutionCode
occ_search(institutionCode="TLMF", limit=20)
### separate requests: use a vector of strings
occ_search(institutionCode=c("TLMF","ArtDatabanken"), limit=20)
### one request, many instances of same parameter: use semi-colon sep. string
occ_search(institutionCode = "TLMF;ArtDatabanken", limit=20)

# Get occurrences based on collectionCode
occ_search(collectionCode="Floristic Databases MV - Higher Plants", limit=20)
occ_search(collectionCode=c("Floristic Databases MV - Higher Plants","Artport"))

# Get only those occurrences with spatial issues
occ_search(taxonKey=key, hasGeospatialIssue=TRUE, limit=20)

# Search using a query string
occ_search(search = "kingfisher", limit=20)

# search on repatriated - doesn't work right now
# occ_search(repatriated = "")

# search on phylumKey
occ_search(phylumKey = 7707728, limit = 5)

# search on kingdomKey
occ_search(kingdomKey = 1, limit = 5)

# search on classKey
occ_search(classKey = 216, limit = 5)

# search on orderKey
occ_search(orderKey = 7192402, limit = 5)

# search on familyKey
occ_search(familyKey = 3925, limit = 5)

# search on genusKey
occ_search(genusKey = 1935496, limit = 5)

# search on establishmentMeans
occ_search(establishmentMeans = "INVASIVE", limit = 5)
occ_search(establishmentMeans = "NATIVE", limit = 5)
occ_search(establishmentMeans = "UNCERTAIN", limit = 5)

# search on protocol
occ_search(protocol = "DIGIR", limit = 5)

# search on license
occ_search(license = "CC_BY_4_0", limit = 5)
```

```
# search on organismId
occ_search(organismId = "100", limit = 5)

# search on publishingOrg
occ_search(publishingOrg = "28eb1a3f-1c15-4a95-931a-4af90ecb574d", limit = 5)

# search on stateProvince
occ_search(stateProvince = "California", limit = 5)

# search on waterBody
occ_search(waterBody = "AMAZONAS BASIN, RIO JURUA", limit = 5)

# search on locality
res <- occ_search(locality = c("Trondheim", "Hovekilen"), limit = 5)
res$Trondheim$data
res$Hovekilen$data

# Range queries
## See Detail for parameters that support range queries
occ_search(depth='50,100') # this is a range depth, with lower/upper limits in character string
occ_search(depth=c(50,100)) # this is not a range search, but does two searches for each depth

## Range search with year
occ_search(year='1999,2000', limit=20)

## Range search with latitude
occ_search(decimalLatitude='29.59,29.6')

# Search by specimen type status
## Look for possible values of the typeStatus parameter looking at the tpestatus dataset
occ_search(typeStatus = 'allotype', fields = c('name','typeStatus'))

# Search by specimen record number
## This is the record number of the person/group that submitted the data, not GBIF's numbers
## You can see that many different groups have record number 1, so not super helpful
occ_search(recordNumber = 1, fields = c('name','recordNumber','recordedBy'))

# Search by last time interpreted: Date the record was last modified in GBIF
## The lastInterpreted parameter accepts ISO 8601 format dates, including
## yyyy, yyyy-MM, yyyy-MM-dd, or MM-dd. Range queries are accepted for lastInterpreted
occ_search(lastInterpreted = '2014-04-02', fields = c('name','lastInterpreted'))

# Search by continent
## One of africa, antarctica, asia, europe, north_america, oceania, or south_america
occ_search(continent = 'south_america')$meta
occ_search(continent = 'africa')$meta
occ_search(continent = 'oceania')$meta
occ_search(continent = 'antarctica')$meta

# Search for occurrences with images
occ_search(mediaType = 'StillImage')$media
```

```

occ_search(mediaType = 'MovingImage')$media
occ_search(mediaType = 'Sound')$media

# Query based on issues - see Details for options
## one issue
occ_search(taxonKey=1, issue='DEPTH_UNLIKELY', fields =
  c('name','key','decimalLatitude','decimalLongitude','depth'))
## two issues
occ_search(taxonKey=1, issue=c('DEPTH_UNLIKELY','COORDINATE_ROUNDED'))
# Show all records in the Arizona State Lichen Collection that cant be matched to the GBIF
# backbone properly:
occ_search(datasetKey='84c0e1a0-f762-11e1-a439-00145eb45e9a',
  issue=c('TAXON_MATCH_NONE','TAXON_MATCH_HIGHERRANK'))

# Parsing output by issue
(res <- occ_search(geometry='POLYGON((30.1 10.1,40 40,20 40,10 20,30.1 10.1))', limit = 50))
## what do issues mean, can print whole table, or search for matches
head(gbif_issues())
gbif_issues()[ gbif_issues()$code %in% c('cdround','cudc','gass84','txmathi'), ]
## or parse issues in various ways
### remove data rows with certain issue classes
library('magrittr')
res %>% occ_issues(gass84)
### split issues into separate columns
res %>% occ_issues(mutate = "split")
### expand issues to more descriptive names
res %>% occ_issues(mutate = "expand")
### split and expand
res %>% occ_issues(mutate = "split_expand")
### split, expand, and remove an issue class
res %>% occ_issues(-cudc, mutate = "split_expand")

# If you try multiple values for two different parameters you are wacked on the hand
# occ_search(taxonKey=c(2482598,2492010), recordedBy=c("smith","BJ Stacey"))

# Get a lot of data, here 1500 records for Helianthus annuus
# out <- occ_search(taxonKey=key, limit=1500)
# nrow(out$data)

# If you pass in an invalid polygon you get hopefully informative errors

### the WKT string is fine, but GBIF says bad polygon
wkt <- 'POLYGON((-178.59375 64.83258989321493,-165.9375 59.24622380205539,
-147.3046875 59.065977905449806,-130.78125 51.04484764446178,-125.859375 36.70806354647625,
-112.1484375 23.367471303759686,-105.1171875 16.093320185359257,-86.8359375 9.23767076398516,
-82.96875 2.9485268155066175,-82.6171875 -14.812060061226388,-74.8828125 -18.849111862023985,
-77.34375 -47.661687803329166,-84.375 -49.975955187343295,174.7265625 -50.649460483096114,
179.296875 -42.19189902447192,-176.8359375 -35.634976650677295,176.8359375 -31.835565983656227,
163.4765625 -6.528187613695323,152.578125 1.894796132058301,135.703125 4.702353722559447,
127.96875 15.077427674847987,127.96875 23.689804541429606,139.921875 32.06861069132688,
149.4140625 42.65416193033991,159.2578125 48.3160811030533,168.3984375 57.019804336633165,
178.2421875 59.95776046458139,-179.6484375 61.16708631440347,-178.59375 64.83258989321493))'

```

```

# occ_search(geometry = gsub("\n", '', wkt))

### unable to parse due to last number pair needing two numbers, not one
# wkt <- 'POLYGON((-178.5 64.8,-165.9 59.2,-147.3 59.0,-130.7 51.0,-125.8))'
# occ_search(geometry = wkt)

### unable to parse due to unclosed string
# wkt <- 'POLYGON((-178.5 64.8,-165.9 59.2,-147.3 59.0,-130.7 51.0))'
# occ_search(geometry = wkt)
### another of the same
# wkt <- 'POLYGON((-178.5 64.8,-165.9 59.2,-147.3 59.0,-130.7 51.0,-125.8 36.7))'
# occ_search(geometry = wkt)

### returns no results
# wkt <- 'LINESTRING(3 4,10 50,20 25)'
# occ_search(geometry = wkt)

### Apparently a point is allowed, but errors
# wkt <- 'POINT(45 -122)'
# occ_search(geometry = wkt)

## Faceting
x <- occ_search(facet = "country", limit = 0)
x$facets
x <- occ_search(facet = "establishmentMeans", limit = 10)
x$facets
x$data
x <- occ_search(facet = c("country", "basisOfRecord"), limit = 10)
x$data
x$facets
x$facets$country
x$facets$basisOfRecord
x$facets$basisOfRecord$count
x <- occ_search(facet = "country", facetMincount = 30000000L, limit = 10)
x$facets
x$data
# paging per each faceted variable
(x <- occ_search(
  facet = c("country", "basisOfRecord", "hasCoordinate"),
  country.facetLimit = 3,
  basisOfRecord.facetLimit = 6,
  limit = 0
))
x$facets

# You can set limit=0 to get number of results found
occ_search(datasetKey = '7b5d6a48-f762-11e1-a439-00145eb45e9a', limit = 0)$meta
occ_search(scientificName = 'Ursus americanus', limit = 0)$meta
occ_search(scientificName = 'Ursus americanus', limit = 0)$meta

## End(Not run)

```

organizations *Organizations metadata.*

Description

Organizations metadata.

Usage

```
organizations(
  data = "all",
  uuid = NULL,
  query = NULL,
  limit = 100,
  start = NULL,
  curlopts = list()
)
```

Arguments

data	(character) The type of data to get. One or more of: 'organization', 'contact', 'endpoint', 'identifier', 'tag', 'machineTag', 'comment', 'hostedDataset', 'ownedDataset', 'deleted', 'pending', 'nonPublishing', or the special 'all'. Default: 'all'
uuid	(character) UUID of the data node provider. This must be specified if data is anything other than 'all'.
query	(character) Query nodes. Only used when data='all'
limit	Number of records to return. Default: 100. Maximum: 1000.
start	Record number to start at. Default: 0. Use in combination with limit to page through results.
curlopts	list of named curl options passed on to HttpClient . see <code>curl::curl_options</code> for curl options

Value

A list of length one or two. If uuid is NULL, then a data.frame with call metadata, and a data.frame, but if uuid given, then a list.

References

<https://www.gbif.org/developer/registry#organizations>

Examples

```
## Not run:
organizations(limit=5)
organizations(query="france", limit=5)
organizations(uuid="4b4b2111-ee51-45f5-bf5e-f535f4a1c9dc")
organizations(data='contact', uuid="4b4b2111-ee51-45f5-bf5e-f535f4a1c9dc")
organizations(data='pending')
organizations(data=c('contact', 'endpoint'),
  uuid="4b4b2111-ee51-45f5-bf5e-f535f4a1c9dc")

# Pass on curl options
organizations(query="spain", curlopts = list(verbose=TRUE))

## End(Not run)
```

parsenames	<i>Parse taxon names using the GBIF name parser.</i>
------------	--

Description

Parse taxon names using the GBIF name parser.

Usage

```
parsenames(scientificname, curlopts = list())
```

Arguments

`scientificname` A character vector of scientific names.

`curlopts` list of named curl options passed on to [HttpClient](#). see `curl::curl_options` for curl options

Value

A data.frame containing fields extracted from parsed taxon names. Fields returned are the union of fields extracted from all species names in `scientificname`.

Author(s)

John Baumgartner (johnbb@student.unimelb.edu.au)

References

<https://www.gbif.org/developer/species#parser>

Examples

```
## Not run:
parsenames(scientificname='x Agropogon littoralis')
parsenames(c('Arrhenatherum elatius var. elatius',
             'Secale cereale subsp. cereale', 'Secale cereale ssp. cereale',
             'Vanessa atalanta (Linnaeus, 1758)'))
parsenames("Ajuga pyramidata")
parsenames("Ajuga pyramidata x reptans")

# Pass on curl options
# res <- parsenames(c('Arrhenatherum elatius var. elatius',
#                   'Secale cereale subsp. cereale', 'Secale cereale ssp. cereale',
#                   'Vanessa atalanta (Linnaeus, 1758)'), curlopts=list(verbose=TRUE))

## End(Not run)
```

rgbif-defunct

Defunct functions in rgbif

Description

- `density_spplist()`: service no longer provided
- `densitylist()`: service no longer provided
- `gbifdata()`: service no longer provided
- `gbifmap_dens()`: service no longer provided
- `gbifmap_list()`: service no longer provided
- `occurrencedensity()`: service no longer provided
- `providers()`: service no longer provided
- `resources()`: service no longer provided
- `taxoncount()`: service no longer provided
- `taxonget()`: service no longer provided
- `taxonsearch()`: service no longer provided
- `stylegeojson()`: moving this functionality to spocc package, will be removed soon
- `togeojson()`: moving this functionality to spocc package, will be removed soon
- `gist()`: moving this functionality to spocc package, will be removed soon
- `occ_spellcheck()`: GBIF has removed the spellCheck parameter from their API

Details

The above functions have been removed. See <https://github.com/ropensci/rgbif> and poke around the code if you want to find the old functions in previous versions of the package

rgb_country_codes *Look up 2 character ISO country codes*

Description

Look up 2 character ISO country codes

Usage

```
rgb_country_codes(country_name, fuzzy = FALSE, ...)
```

Arguments

country_name	Name of country to look up
fuzzy	If TRUE, uses agrep to do fuzzy search on names.
...	Further arguments passed on to agrep or grep

Examples

```
rgb_country_codes(country_name="United")
```

taxrank *Get the possible values to be used for (taxonomic) rank arguments in GBIF API methods.*

Description

Get the possible values to be used for (taxonomic) rank arguments in GBIF API methods.

Usage

```
taxrank()
```

Examples

```
## Not run:  
taxrank()  
  
## End(Not run)
```

typestatus	<i>Type status options for GBIF searching</i>
------------	---

Description

- name. Name of type.
- description. Description of the type.

wkt_parse	<i>parse wkt into smaller bits</i>
-----------	------------------------------------

Description

parse wkt into smaller bits

Usage

```
wkt_parse(wkt, geom_big, geom_size = 40, geom_n = 10)
```

Arguments

wkt	(character) A WKT string. Required.
geom_big	(character) One of "axe" or "bbox". Required.
geom_size	(integer) An integer indicating size of the cell. Default: 40.
geom_n	(integer) An integer indicating number of cells in each dimension. Default: 10.

Examples

```
wkt <- "POLYGON((13.26349675655365 52.53991761181831,18.36115300655365 54.11445544219924,
21.87677800655365 53.80418956368524,24.68927800655365 54.217364774722455,28.20490300655365
54.320018299365124,30.49005925655365 52.85948216284084,34.70880925655365 52.753220564427814,
35.93927800655365 50.46131871049754,39.63068425655365 49.55761261299145,40.86115300655365
46.381388009130845,34.00568425655365 45.279102926537,33.30255925655365 48.636868465271846,
30.13849675655365 49.78513301801265,28.38068425655365 47.2236377039631,29.78693425655365
44.6572866068524,27.67755925655365 42.62220075124676,23.10724675655365 43.7754205800212,
24.51349675655365 47.10412345120368,26.79865300655365 49.55761261299145,23.98615300655365
52.00209943876426,23.63459050655365 49.44345313705238,19.41584050655365 47.580567827212114,
19.59162175655365 44.90682206053508,20.11896550655365 42.36297154876359,22.93146550655365
40.651849782081555,25.56818425655365 39.98171166226459,29.61115300655365 40.78507856230178,
32.95099675655365 40.38459278067577,32.95099675655365 37.37491910393631,26.27130925655365
33.65619609886799,22.05255925655365 36.814081996401605,18.71271550655365 36.1072176729021,
18.53693425655365 39.16878677351903,15.37287175655365 38.346355762190846,15.19709050655365
41.578843777436326,12.56037175655365 41.050735748143424,12.56037175655365 44.02872991212046,
15.19709050655365 45.52594200494078,16.42755925655365 48.05271546733352,17.48224675655365
48.86865641518059,10.62677800655365 47.817178329053135,9.57209050655365 44.154980365192,
8.16584050655365 40.51835445724746,6.05646550655365 36.53210972067291,0.9588092565536499
```

```
31.583640057148145,-5.54509699344635 35.68001485298146,-6.77556574344635 40.51835445724746,
-9.41228449344635 38.346355762190846,-12.40056574344635 35.10683619158607,-15.74040949344635
38.07010978950028,-14.68572199344635 41.31532459432774,-11.69744074344635 43.64836179231387,
-8.88494074344635 42.88035509418534,-4.31462824344635 43.52103366008421,-8.35759699344635
47.2236377039631,-8.18181574344635 50.12441989397795,-5.01775324344635 49.55761261299145,
-2.73259699344635 46.25998980446569,-1.67790949344635 44.154980365192,-1.32634699344635
39.30493590580802,2.18927800655365 41.44721797271696,4.47443425655365 43.26556960420879,
2.18927800655365 46.7439668697322,1.83771550655365 50.3492841273576,6.93537175655365
49.671505849335254,5.00177800655365 52.32557322466785,7.81427800655365 51.67627099802223,
7.81427800655365 54.5245591562317,10.97834050655365 51.89375191441792,10.97834050655365
55.43241335888528,13.26349675655365 52.53991761181831))"
wkt <- gsub("\n", " ", wkt)

# to a bounding box in wkt format
wkt_parse(wkt, geom_big = "bbox")

# to many wkt strings, chopped up from input
wkt_parse(wkt, geom_big = "axe")
wkt_parse(wkt, geom_big = "axe", 60)
wkt_parse(wkt, geom_big = "axe", 30)
wkt_parse(wkt, geom_big = "axe", 20)
wkt_parse(wkt, geom_big = "axe", 10)
wkt_parse(wkt, geom_big = "axe", 5)
```

Index

- * **data**
 - isocodes, [32](#)
 - occ_fields, [95](#)
 - typestatus, [124](#)
- * **downloads**
 - download_predicate_dsl, [16](#)
 - occ_download, [77](#)
 - occ_download_cached, [81](#)
 - occ_download_cancel, [83](#)
 - occ_download_dataset_activity, [85](#)
 - occ_download_datasets, [84](#)
 - occ_download_get, [86](#)
 - occ_download_import, [87](#)
 - occ_download_list, [89](#)
 - occ_download_meta, [90](#)
 - occ_download_queue, [91](#)
 - occ_download_wait, [93](#)
- as.download(occ_download_import), [87](#)
- cat, [10](#), [12](#)
- check_wkt, [4](#)
- check_wkt(), [63](#), [105](#)
- chop, [67](#), [109](#)
- count_facet, [5](#)
- crul::HttpClient, [34](#), [37](#)
- crul::HttpClient(), [86](#)
- crul::verb-GET, [20](#), [86](#)
- crul::writing-options, [86](#)
- data.table::fread, [88](#)
- data.table::fread(), [88](#)
- dataset_metrics, [8](#)
- dataset_search, [8](#)
- dataset_search(), [33](#)
- dataset_suggest, [11](#)
- dataset_suggest(), [33](#)
- datasets, [6](#)
- density_splist(), [122](#)
- densitylist(), [122](#)
- download_predicate_dsl, [15](#), [16](#), [78](#), [79](#), [82](#),
[84](#), [86–88](#), [90–92](#), [94](#)
- downloads, [14](#), [79](#), [82–85](#), [87](#), [88](#), [90](#), [92](#)
- downloads(), [70](#), [111](#)
- elevation, [20](#)
- enumeration, [22](#)
- enumeration_country(enumeration), [22](#)
- gbif_bbox2wkt, [23](#)
- gbif_citation, [24](#)
- gbif_issues, [25](#)
- gbif_issues_lookup, [26](#)
- gbif_names, [27](#)
- gbif_oai, [27](#)
- gbif_oai_get_records(gbif_oai), [27](#)
- gbif_oai_identify(gbif_oai), [27](#)
- gbif_oai_list_identifiers(gbif_oai), [27](#)
- gbif_oai_list_metadataformats(gbif_oai), [27](#)
- gbif_oai_list_records(gbif_oai), [27](#)
- gbif_oai_list_sets(gbif_oai), [27](#)
- gbif_photos, [29](#)
- gbif_wkt2bbox(gbif_bbox2wkt), [23](#)
- gbifdata(), [122](#)
- gbifmap_dens(), [122](#)
- gbifmap_list(), [122](#)
- gist(), [122](#)
- HttpClient, [7](#), [8](#), [10](#), [12](#), [22](#), [31](#), [40](#), [45](#), [48](#),
[50](#), [52](#), [54](#), [57](#), [63](#), [78](#), [82–85](#), [89](#), [90](#),
[94](#), [96](#), [100](#), [105](#), [120](#), [121](#)
- installations, [30](#)
- isocodes, [32](#)
- many-values, [4](#), [32](#), [48](#)
- map_fetch, [33](#)
- map_fetch(), [38](#)
- mvt_fetch, [36](#)
- mvt_fetch(), [35](#)

- name_backbone, 39
- name_backbone_verbose (name_backbone), 39
- name_issues, 41
- name_issues(), 50
- name_lookup, 42
- name_lookup(), 33, 50
- name_suggest, 47
- name_suggest(), 33
- name_usage, 49
- name_usage(), 33, 41
- networks, 52
- nodes, 53

- occ_count, 56, 69, 111
- occ_data, 59, 67, 109
- occ_data(), 24, 33, 78, 97, 105, 111
- occ_download, 19, 77, 82, 84, 86–88, 90–92, 94
- occ_download(), 14, 15, 66, 84, 91, 109
- occ_download_cached, 19, 79, 81, 84, 86–88, 90–92, 94
- occ_download_cached(), 15
- occ_download_cancel, 19, 79, 82, 83, 84, 86–88, 90–92, 94
- occ_download_cancel(), 15
- occ_download_cancel_staged (occ_download_cancel), 83
- occ_download_cancel_staged(), 15
- occ_download_dataset_activity, 19, 79, 82, 84, 85, 87, 88, 90–92, 94
- occ_download_dataset_activity(), 15
- occ_download_datasets, 19, 79, 82, 84, 84, 86–88, 90–92, 94
- occ_download_datasets(), 15
- occ_download_get, 19, 79, 82, 84, 86, 86, 88, 90–92, 94
- occ_download_get(), 15, 24, 91
- occ_download_import, 19, 79, 82, 84, 86, 87, 87, 90–92, 94
- occ_download_import(), 15, 97
- occ_download_list, 19, 79, 82, 84, 86–88, 89, 91, 92, 94
- occ_download_list(), 15
- occ_download_meta, 19, 79, 82, 84, 86–88, 90, 90, 92, 94
- occ_download_meta(), 15, 24, 92, 93
- occ_download_prep (occ_download), 77
- occ_download_prep(), 15, 91

- occ_download_queue, 19, 79, 82, 84, 86–88, 90, 91, 91, 94
- occ_download_queue(), 15, 78, 94
- occ_download_wait, 19, 79, 82, 84, 86–88, 90–92, 93
- occ_download_wait(), 15
- occ_facet, 94
- occ_facet(), 111
- occ_fields, 95
- occ_get, 96
- occ_get_verbatim (occ_get), 96
- occ_issues, 97
- occ_metadata, 99
- occ_search, 67, 101, 109
- occ_search(), 14, 24, 33, 56, 57, 69, 70, 78, 95, 97, 98
- occ_spellcheck(), 122
- occurrence_density(), 122
- options(), 14
- organizations, 9, 12, 120

- parsenames, 121
- pred (download_predicate_dsl), 16
- pred_and (download_predicate_dsl), 16
- pred_gt (download_predicate_dsl), 16
- pred_gte (download_predicate_dsl), 16
- pred_in (download_predicate_dsl), 16
- pred_like (download_predicate_dsl), 16
- pred_lt (download_predicate_dsl), 16
- pred_lte (download_predicate_dsl), 16
- pred_not (download_predicate_dsl), 16
- pred_notnull (download_predicate_dsl), 16
- pred_or (download_predicate_dsl), 16
- pred_within (download_predicate_dsl), 16
- providers(), 122

- resources(), 122
- rgb_country_codes, 123
- rgbif (rgbif-package), 3
- rgbif-defunct, 122
- rgbif-package, 3

- stylegeojson(), 122
- Sys.setenv(), 14

- taxoncount(), 122
- taxonget(), 122
- taxonsearch(), 122

taxrank, [123](#)

togeojson(), [122](#)

typestatus, [124](#)

typestatus(), [56](#)

wkt_parse, [67](#), [109](#), [124](#)