

Package ‘APCI’

January 9, 2021

Type Package

Title A New Age-Period-Cohort Model for Describing and Investigating Inter-Cohort Differences and Life Course Dynamics

Version 0.1.0

Author Liying Luo, Jiahui Xu

Maintainer Jiahui Xu <jpx5053@psu.edu>

Depends R (>= 3.6.0)

Description

It implemented APC-I Model proposed in the paper of Luo and Hodges (2019). A new age-period-cohort model for describing and investigating inter-cohort differences and life course dynamics.

Imports haven, survey, magrittr, tidyverse, dplyr, ggplot2, data.table, ggpubr, stringr

License GPL-2

Encoding UTF-8

LazyData true

NeedsCompilation no

Repository CRAN

Date/Publication 2021-01-09 06:30:35 UTC

R topics documented:

apci	2
apci.bar	4
apci.plot	5
apci.plot.heatmap	6
apci.plot.hexagram	7
apci.plot.raw	8
blackmen	9
blackwomen	9
cohortdeviation	10
compute_xcoordinate	10

compute_ycoordinate	11
maineffect	11
simulation	12
temp_model	12
tests	13
whitemen	14
whitewomen	15
women9017	15

Index	17
--------------	-----------

apci	<i>run apci model</i>
------	-----------------------

Description

run apci model

Usage

```
apci(
  outcome = "inlfc", age = "acc",
  period = "pcc", cohort = NULL,
  weight = NULL, covariate = NULL,
  data, family = "quasibinomial",
  dev.test = TRUE, print = TRUE, ...
)
```

Arguments

outcome	An object of class character containing the name of the outcome variable. The outcome variable can be continuous, categorical, or count.
age	An object of class character representing the age group index taking on a small number of distinct values in the data. Usually, the vector should be converted to a factor (or the terms of "category" and "enumerated type").
period	An object of class character, similar to the argument of age, representing the time period index in the data.
cohort	An optional object of class character representing cohort membership index in the data. Usually, the cohort index can be generated from the age group index and time period index in the data because of the intrinsic relationship among these three time-related indices.
weight	An optional vector of sample weights to be used in the model fitting process. If non-NULL, the weights will be used in the first step to estimate the model. Observations with negative weights will be automatically dropped in modeling.
covariate	An optional vector of characters, representing the name(s) of the user-specified covariate(s) to be used in the model. If the variable(s) are not found in data, there will be an error message reminding the users to check the data again.

<code>data</code>	A data frame containing the outcome variable, age group indicator, period group indicator, and covariates to be used in the model. If the variable(s) are not found in data, there will be an error message reminding the users to check the input data again.
<code>family</code>	Used to specify the statistical distribution of the error term and link function to be used in the model. Usually, it is a character string naming a family function. For example, family can be "binomial", "multinomial", or "gaussian". Users could also check R package glm for more details of family functions.
<code>dev.test</code>	Logical, specifying if the global F test (step 1) should be implemented before running the APC-I model. If TRUE, apci will first run the global F test and report the test results; otherwise, apci will skip this step and return NULL. The default setting is TRUE. But users should be careful that the algorithm will not automatically stop even if there is no significant cohort average deviation.
<code>print</code>	Logical, specifying if the intermediate results should be displayed on the screen in running the model. The default setting is TRUE in order to show the results explicitly although it can be too clumpy when the intermediate results are shown on the screen.
<code>...</code>	

Value

<code>model</code>	A summary of the fitted generalized linear regression. It displays the coefficients, standard errors, etc.
<code>dev_global</code>	The results of the global F test. It shows that if the interaction terms are significant as a component of the generalized linear regression model.
<code>intercept</code>	The overall intercept.
<code>age_effect</code>	A vector, representing the estimated age effect for each age group.
<code>period_effect</code>	A vector, representing the estimated period effect for each time period.
<code>cohort_average</code>	A vector, representing the cohort average effects for comparing inter-cohort differences.
<code>cohort_slope</code>	A vector, representing intra-cohort life-course changes.

Examples

```
library("APCI")
## load data
test_data <- APCI::women9017
test_data$acc <- as.factor(test_data$acc)
test_data$pcc <- as.factor(test_data$pcc)
## run APCI model
APC_I <- apci(outcome = "inlfc",
              age = "acc",
              period = "pcc",
              cohort = "ccc",
              weight = "wt",
              data = test_data, dev.test=FALSE,
              family = "gaussian")
```

```
## check model results
summary(APC_I)

APC_I$model
APC_I$dev_global
APC_I$dev_local
APC_I$intercept
APC_I$age_effect
APC_I$period_effect
APC_I$cohort_average
APC_I$cohort_slope
```

apci.bar

make bar plot

Description

make barplot for cohort effect

Usage

```
apci.bar(model, age, period, outcome_var,
         cohort_label = NULL, ...)
```

Arguments

model	A list, inheriting the corresponding results generated by function apci.
age	A vector, representing the age group index taking on a small number of distinct values in the data. Usually, the vector should be converted to a factor (or the terms of "category" and "enumerated type").
period	An object of class character, similar to the argument of age, representing the time period index in the data.
outcome_var	An object of class character representing the name of the outcome variable used in APC-I model. The outcome variable itself can be numerical and categorical.
cohort_label	A vector, representing the labels of cohort groups in the x axis.
...	

Examples

```
library("APCI")
## load data
test_data <- APCI::women9017
test_data$acc <- as.factor(test_data$acc)
test_data$pcc <- as.factor(test_data$pcc)

## run APCI model
```

```

APC_I <- apci(outcome = "inlfc",
             age = "acc",
             period = "pcc",
             cohort = "ccc",
             weight = "wt",
             data = test_data, dev.test=FALSE,
             family = "gaussian")

## plot the bar plot
apci.bar(model = APC_I, age = "acc", period = "pcc")

```

apci.plot

plot

Description

plotting raw scores or APC-I model results

Usage

```

apci.plot(model, age, period, outcome_var,
          type = "model", quantile = NULL, ...)

```

Arguments

model	A list, inheriting the corresponding results generated by function apci.
outcome_var	An object of class character representing the name of the outcome variable used in APC-I model. The outcome variable itself can be numerical and categorical.
age	An object of class character representing the age group index taking on a small number of distinct values in the data. Usually, the vector should be converted to a factor (or the terms of "category" and "enumerated type").
period	An object of class character, similar to the argument of age, representing the time period index in the data.
type	Character, "explore" or "model". If type is "explore", plots for age and period raw scores will be generated. If type is "model", model results will be plotted. The default setting is "model".
quantile	A number between 0 and 1, representing the percentiles to be used in visualizing the data or model. If NULL, the original magnitude will be used.
...	

apci.plot.heatmap *plot the heatmap for APC-I model*

Description

plot the heatmap to show cohort effects

Usage

```
apci.plot.heatmap(model, age, period, color_map = NULL,
  color_scale = NULL, quantile = NULL, ...)
```

Arguments

model	A list, inheriting the corresponding results generated by function apci.
age	A vector, representing the age group index taking on a small number of distinct values in the data. Usually, the vector should be converted to a factor (or the terms of "category" and "enumerated type").
period	An object of class character, similar to the argument of age, representing the time period index in the data.
color_map	A vector, representing the color palettes to be used in the figure. The default setting is greys if color_map is NULL. Alternations, for example, can be c("blue", "yellow"), blues, etc.
color_scale	A vector including two numbers indicating the limit of the values to be plotted. The first number is the minimum value to be visualized and the second is the maximum value to be visualized. If NULL, the algorithm will automatically select the limits from the data (estimation results) to set up the scale.
quantile	A number between 0 and 1, representing the percentiles to be used in visualizing the data or model. If NULL, the original magnitude will be used.
...	

Examples

```
library("APCI")
## load data
test_data <- APCI::women9017
test_data$acc <- as.factor(test_data$acc)
test_data$pcc <- as.factor(test_data$pcc)

## run APCI model
APC_I <- apci(outcome = "inlfc",
  age = "acc",
  period = "pcc",
  cohort = "ccc",
  weight = "wt",
  data = test_data, dev.test=FALSE,
```

```

        family = "gaussian")

## plot heatmap
apci.plot.heatmap(model = APC_I, age = "acc", period = 'pcc',
                  color_map = c('blue', 'yellow'))

```

apci.plot.hexagram *plot the hexagram heatmap*

Description

plot the cohort effect in the style of hexagram

Usage

```

apci.plot.hexagram(model, age, period, first_age,
                  first_period, interval, first_age_isoline = NULL,
                  first_period_isoline = NULL, isoline_interval = NULL,
                  color_scale = NULL, color_map = NULL, line_width = 0.5,
                  line_color = "grey", label_size = 0.5,
                  label_color = "black", scale_units = "Quintile",
                  wrap_cohort_labels = TRUE, quantile = NULL)

```

Arguments

model	A list, inheriting the corresponding results generated by function apci.
age	An object of class character representing the age group index taking on a small number of distinct values in the data. Usually, the vector should be converted to a factor (or the terms of "category" and "enumerated type").
period	An object of class character, similar to the argument of age, representing the time period index in the data.
color_scale	A vector including two numbers indicating the limit of the values to be plotted. The first number is the minimum value to be visualized and the second is the maximum value to be visualized. If NULL, the algorithm will automatically select the limits from the data (estimation results) to set up the scale.
color_map	A vector, representing the color palettes to be used in the figure. The default setting is greys if color_map is NULL. Alternations, for example, can be c("blue", "yellow"), blues, etc.
first_age	
first_period	
interval	
first_age_isoline	
first_period_isoline	

```
isoline_interval  
  
line_width  
line_color  
label_size  
label_color  
scale_units  
wrap_cohort_labels  
  
quantile
```

```
apci.plot.raw      plot the raw scores
```

Description

plot the raw scores in each age and period square

Usage

```
apci.plot.raw(data, outcome_var, age, period, ...)
```

Arguments

data	A data frame containing the outcome variable, age group indicator, period group indicator, and covariates to be used in the model. If the variable(s) are not found in data, there will be an error message reminding the users to check the input data again.
outcome_var	An object of class character containing the name of the outcome variable. The outcome variable can be continuous, categorical, or count.
age	An object of class character representing the age group index taking on a small number of distinct values in the data. Usually, the vector should be converted to a factor (or the terms of "category" and "enumerated type").
period	An object of class character, similar to the argument of age, representing the time period index in the data.
...	

Examples

```
# plot the raw scores  
apci.plot.raw(data = simulation, outcome_var = "y",  
              age = "age", period = "period")
```

blackmen	<i>Black Men</i>
----------	------------------

Description

the dataset for black men

Usage

```
data("blackmen")
```

Format

A data frame with 10000 observations on the following 7 variables.

asecwt weight

year a factor indicating period groups with levels 1 2 3 4 5 6

age a factor indicating age groups with levels 1 2 3 4 5 6 7 8 9

labforce labor Force participation rate

educ education level

educr education level

educc education level

blackwomen	<i>Black Women</i>
------------	--------------------

Description

Dataset for black women

Usage

```
data("blackwomen")
```

Format

A data frame with 10000 observations on the following 7 variables.

asecwt weight

year a factor indicating period groups

age a factor indicating age groups

labforce labor Force participation rate

educ education level

educr education level

educc education level

cohortdeviation	<i>calculate cohort deviation</i>
-----------------	-----------------------------------

Description

calculate cohort deviation

Usage

```
cohortdeviation(A, P, C, model = temp6,
weight = "wt", covariate, ...)
```

Arguments

A, P, C	The numbers of age groups, period groups, and cohort groups separately.
model	A generalized linear regression model generated from the internal function temp_model
weight	An optional vector of sample weights to be used in the model fitting process. If non-NULL, the weights will be used in the first step to estimate the model. Observations with negative weights will be automatically dropped in modeling.
covariate	An optional vector of characters, representing the name(s) of the user-specified covariate(s) to be used in the model. If the variable(s) are not found in data, there will be an error message reminding the users to check the data again.
...	

compute_xcoordinate	<i>calculate x coordinate value</i>
---------------------	-------------------------------------

Description

Calculate x coordinate value for the hexagram. This is an intermediate function.

Usage

```
compute_xcoordinate(p)
```

Arguments

p

compute_ycoordinate	<i>calculate y coordinate value</i>
---------------------	-------------------------------------

Description

Calculate y coordinate value for the hexagram. This is an intermediate function.

Usage

```
compute_ycoordinate(p, a)
```

Arguments

p
a

maineffect	<i>estimate age effect and period effect</i>
------------	--

Description

estimate age and period effect from APCI model

Usage

```
maineffect(A, P, C, model = temp6, data, ...)
```

Arguments

A, P, C	The numbers of age groups, period groups, and cohort groups separately.
model	A generalized linear regression model generated from the internal function temp_model
data	A data frame containing the outcome variable, age group indicator, period group indicator, and covariates to be used in the model. If the variable(s) are not found in data, there will be an error message reminding the users to check the input data again.
...	

simulation	<i>Simulated Dataset</i>
------------	--------------------------

Description

A simulated dataset for APC-I analysis.

Usage

```
data("simulation")
```

Format

A data frame with 10000 observations on the following 3 variables.

y a numeric

age a numeric

period a numeric

temp_model	<i>Estimate APC-I model</i>
------------	-----------------------------

Description

Estimate the APCI original model. This is a generalized linear regression model.

Usage

```
temp_model(data, outcome = "inlfc", age = "acc",
  period = "pcc", cohort = NULL, weight = NULL,
  covariate = NULL, family = "quasibinomial", ...)
```

Arguments

data	A data frame containing the outcome variable, age group indicator, period group indicator, and covariates to be used in the model. If the variable(s) are not found in data, there will be an error message reminding the users to check the input data again.
outcome	An object of class character containing the name of the outcome variable. The outcome variable can be continuous, categorical, or count.
age	An object of class character representing the age group index taking on a small number of distinct values in the data. Usually, the vector should be converted to a factor (or the terms of "category" and "enumerated type").
period	An object of class character, similar to the argument of age, representing the time period index in the data.

cohort	An optional object of class character representing cohort membership index in the data. Usually, the cohort index can be generated from the age group index and time period index in the data because of the intrinsic relationship among these three time-related indices.
weight	An optional vector of sample weights to be used in the model fitting process. If non-NULL, the weights will be used in the first step to estimate the model. Observations with negative weights will be automatically dropped in modeling.
covariate	An optional vector of characters, representing the name(s) of the user-specified covariate(s) to be used in the model. If the variable(s) are not found in data, there will be an error message reminding the users to check the data again.
family	Used to specify the statistical distribution of the error term and link function to be used in the model. Usually, it is a character string naming a family function. For example, family can be "binomial", "multinomial", or "gaussian". Users could also check R package glm for more details of family functions.
...	

tests	<i>local and global F test</i>
-------	--------------------------------

Description

implement local and global F test for APCI model

Usage

```
tests(model, age = "acc", period = "pcc",
       cohort = "ccc", A, P, C, data, weight = "wt",
       family, outcome, ...)
```

Arguments

model	A generalized linear regression model generated from the internal function temp_model
age	An object of class character representing the age group index taking on a small number of distinct values in the data. Usually, the vector should be converted to a factor (or the terms of "category" and "enumerated type").
period	An object of class character, similar to the argument of age, representing the time period index in the data.
cohort	An optional object of class character representing cohort membership index in the data. Usually, the cohort index can be generated from the age group index and time period index in the data because of the intrinsic relationship among these three time-related indices.
A, P, C	The numbers of age groups, period groups, and cohort groups separately.
data	A data frame containing the outcome variable, age group indicator, period group indicator, and covariates to be used in the model. If the variable(s) are not found in data, there will be an error message reminding the users to check the input data again.

weight	An optional vector of sample weights to be used in the model fitting process. If non-NULL, the weights will be used in the first step to estimate the model. Observations with negative weights will be automatically dropped in modeling.
family	Used to specify the statistical distribution of the error term and link function to be used in the model. Usually, it is a character string naming a family function. For example, family can be "binomial", "multinomial", or "gaussian". Users could also check R package glm for more details of family functions.
outcome	An object of class character containing the name of the outcome variable. The outcome variable can be continuous, categorical, or count.
...	

whitemen

White Men

Description

A dataset for white men.

Usage

```
data("whitemen")
```

Format

A data frame with 10000 observations on the following 7 variables.

asecwt weight

year a factor indicating period groups

age a factor indicating age groups

labforce labor Force participation rate

educ education level

educr education level

educc education level

whitewomen

White Women

Description

A dataset for white women.

Usage

```
data("whitewomen")
```

Format

A data frame with 10000 observations on the following 7 variables.

asecwt weight
year a factor indicating period groups
age a factor indicating age groups
labforce labor Force participation rate
educ education level
educr education level
educc education level

women9017

women9017

Description

A sample dataset

Usage

```
women9017
```

Format

A data frame with 1000 observations on the following 23 variables.

ac a numeric vector
acc a numeric vector
age a numeric vector
cc a numeric vector
ccc a numeric vector

cohort a numeric vector
educ a numeric vector
educc a numeric vector
educr a numeric vector
inlfc a numeric vector
labforce a numeric vector
lfc a numeric vector
marst a numeric vector
marstc a numeric vector
marstr a numeric vector
nc a numeric vector
ncc a numeric vector
nchild a numeric vector
pc a numeric vector
pcc a numeric vector
wt a numeric vector
wtsupp a numeric vector
year a numeric vector

Details

test

Source

CPS

References

Luo and Hodges (2019)

Index

* datasets

- blackmen, 9
- blackwomen, 9
- simulation, 12
- whitemen, 14
- whitewomen, 15

- apci, 2
- apci.bar, 4
- apci.plot, 5
- apci.plot.heatmap, 6
- apci.plot.hexagram, 7
- apci.plot.raw, 8

- blackmen, 9
- blackwomen, 9

- cohortdeviation, 10
- compute_xcoordinate, 10
- compute_ycoordinate, 11

- maineffect, 11

- simulation, 12

- temp_model, 12
- tests, 13

- whitemen, 14
- whitewomen, 15
- women9017, 15