

# Package ‘yardstick’

April 21, 2023

**Type** Package

**Title** Tidy Characterizations of Model Performance

**Version** 1.2.0

**Description** Tidy tools for quantifying how well model fits to a data set such as confusion matrices, class probability curve summaries, and regression metrics (e.g., RMSE).

**License** MIT + file LICENSE

**URL** <https://github.com/tidymodels/yardstick>,  
<https://yardstick.tidymodels.org>

**BugReports** <https://github.com/tidymodels/yardstick/issues>

**Depends** R (>= 3.4.0)

**Imports** cli, dplyr (>= 1.1.0), generics (>= 0.1.2), hardhat (>= 1.3.0), lifecycle (>= 1.0.3), rlang (>= 1.0.6), tibble, tidyselect (>= 1.2.0), utils, vctrs (>= 0.5.0)

**Suggests** covr, crayon, ggplot2, knitr, probably (>= 0.0.6), rmarkdown, survival (>= 3.5-0), testthat (>= 3.0.0), tidy

**VignetteBuilder** knitr

**Config/Needs/website** tidyverse/tidytemplate

**Config/testthat/edition** 3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.2.3

**NeedsCompilation** yes

**Author** Max Kuhn [aut],  
Davis Vaughan [aut],  
Emil Hvitfeldt [aut, cre] (<<https://orcid.org/0000-0002-0679-1945>>),  
Posit Software, PBC [cph, fnd]

**Maintainer** Emil Hvitfeldt <[emil.hvitfeldt@posit.co](mailto:emil.hvitfeldt@posit.co)>

**Repository** CRAN

**Date/Publication** 2023-04-21 08:40:02 UTC

**R topics documented:**

accuracy	3
average_precision	4
bal_accuracy	8
brier_class	10
ccc	12
check_metric	15
classification_cost	16
conf_mat	19
detection_prevalence	22
developer-helpers	24
f_meas	27
gain_capture	30
gain_curve	34
hpc_cv	37
huber_loss	38
huber_loss_pseudo	40
iic	42
j_index	44
kap	47
lift_curve	49
lung_surv	52
mae	53
mape	55
mase	56
mcc	59
metric-summarizers	61
metrics	64
metric_set	66
metric_tweak	68
mn_log_loss	70
mpe	72
msd	74
new-metric	76
npv	77
pathology	81
poisson_log_loss	81
ppv	83
precision	86
pr_auc	90
pr_curve	93
recall	95
rmse	99
roc_auc	101
roc_aunp	104
roc_aunu	107
roc_curve	110

rpd . . . . .	112
rpiq . . . . .	115
rsq . . . . .	117
rsq_trad . . . . .	119
sens . . . . .	121
smape . . . . .	125
solubility_test . . . . .	127
spec . . . . .	128
summary.conf_mat . . . . .	132
two_class_example . . . . .	133
yardstick_remove_missing . . . . .	134

## Index 135

---

accuracy	<i>Accuracy</i>
----------	-----------------

---

### Description

Accuracy is the proportion of the data that are predicted correctly.

### Usage

```
accuracy(data, ...)

## S3 method for class 'data.frame'
accuracy(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

accuracy_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

### Arguments

data	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
...	Not currently used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquoteation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimate	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `accuracy_vec()`, a single numeric value (or NA).

**Multiclass**

Accuracy extends naturally to multiclass scenarios. Because of this, macro and micro averaging are not implemented.

**Author(s)**

Max Kuhn

**See Also**

Other class metrics: [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

**Examples**

```
library(dplyr)
data("two_class_example")
data("hpc_cv")

# Two class
accuracy(two_class_example, truth, predicted)

# Multiclass
# accuracy() has a natural multiclass extension
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  accuracy(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  accuracy(obs, pred)
```

---

average\_precision      *Area under the precision recall curve*

---

**Description**

`average_precision()` is an alternative to `pr_auc()` that avoids any ambiguity about what the value of precision should be when `recall == 0` and there are not yet any false positive values (some say it should be 0, others say 1, others say undefined).

It computes a weighted average of the precision values returned from [pr\\_curve\(\)](#), where the weights are the increase in recall from the previous threshold. See [pr\\_curve\(\)](#) for the full curve.

**Usage**

```

average_precision(data, ...)

## S3 method for class 'data.frame'
average_precision(
  data,
  truth,
  ...,
  estimator = NULL,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL
)

average_precision_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL,
  ...
)

```

**Arguments**

data	A <code>data.frame</code> containing the columns specified by <code>truth</code> and <code>...</code>
...	A set of unquoted column names or one or more <code>dplyr</code> selector functions to choose which variables contain the class probabilities. If <code>truth</code> is binary, only 1 column should be selected, and it should correspond to the value of <code>event_level</code> . Otherwise, there should be as many columns as factor levels of <code>truth</code> and the ordering of the columns should be the same as the factor levels of <code>truth</code> .
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimator	One of "binary", "macro", or "macro_weighted" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other two are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on <code>truth</code> .
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
event_level	A single string. Either "first" or "second" to specify which level of <code>truth</code> to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.
estimate	If truth is binary, a numeric vector of class probabilities corresponding to the "relevant" class. Otherwise, a matrix with as many columns as factor levels of truth. <i>It is assumed that these are in the same order as the levels of truth.</i>

### Details

The computation for average precision is a weighted average of the precision values. Assuming you have  $n$  rows returned from `pr_curve()`, it is a sum from 2 to  $n$ , multiplying the precision value  $p_i$  by the increase in recall over the previous threshold,  $r_i - r_{(i-1)}$ .

$$AP = \sum (r_i - r_{i-1}) * p_i$$

By summing from 2 to  $n$ , the precision value  $p_1$  is never used. While `pr_curve()` returns a value for  $p_1$ , it is technically undefined as  $tp / (tp + fp)$  with  $tp = 0$  and  $fp = 0$ . A common convention is to use 1 for  $p_1$ , but this metric has the nice property of avoiding the ambiguity. On the other hand,  $r_1$  is well defined as long as there are some events ( $p$ ), and it is  $tp / p$  with  $tp = 0$ , so  $r_1 = 0$ .

When  $p_1$  is defined as 1, the `average_precision()` and `roc_auc()` values are often very close to one another.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `average_precision_vec()`, a single numeric value (or NA).

### Multiclass

Macro and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

**See Also**

[pr\\_curve\(\)](#) for computing the full precision recall curve.

[pr\\_auc\(\)](#) for computing the area under the precision recall curve using the trapezoidal rule.

Other class probability metrics: [brier\\_class\(\)](#), [classification\\_cost\(\)](#), [gain\\_capture\(\)](#), [mn\\_log\\_loss\(\)](#), [pr\\_auc\(\)](#), [roc\\_auc\(\)](#), [roc\\_aunp\(\)](#), [roc\\_aunu\(\)](#)

**Examples**

```
# -----
# Two class example

# `truth` is a 2 level factor. The first level is `"Class1"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(two_class_example)

# Binary metrics using class probabilities take a factor `truth` column,
# and a single class probability column containing the probabilities of
# the event of interest. Here, since `"Class1"` is the first level of
# `truth`, it is the event of interest and we pass in probabilities for it.
average_precision(two_class_example, truth, Class1)

# -----
# Multiclass example

# `obs` is a 4 level factor. The first level is `"VF"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(hpc_cv)

# You can use the col1:colN tidyselect syntax
library(dplyr)
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  average_precision(obs, VF:L)

# Change the first level of `obs` from `"VF"` to `"M"` to alter the
# event of interest. The class probability columns should be supplied
# in the same order as the levels.
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  mutate(obs = relevel(obs, "M")) %>%
  average_precision(obs, M, VF:L)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  average_precision(obs, VF:L)

# Weighted macro averaging
hpc_cv %>%
```

```

group_by(Resample) %>%
  average_precision(obs, VF:L, estimator = "macro_weighted")

# Vector version
# Supply a matrix of class probabilities
fold1 <- hpc_cv %>%
  filter(Resample == "Fold01")

average_precision_vec(
  truth = fold1$obs,
  matrix(
    c(fold1$VF, fold1$F, fold1$M, fold1$L),
    ncol = 4
  )
)

```

---

bal\_accuracy

*Balanced accuracy*


---

### Description

Balanced accuracy is computed here as the average of [sens\(\)](#) and [spec\(\)](#).

### Usage

```

bal_accuracy(data, ...)

## S3 method for class 'data.frame'
bal_accuracy(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

bal_accuracy_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

```

**Arguments**

data	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
...	Not currently used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimate	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
estimator	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on <code>estimate</code> .
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
event_level	A single string. Either "first" or "second" to specify which level of <code>truth</code> to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `bal_accuracy_vec()`, a single numeric value (or NA).

**Relevant Level**

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

**Multiclass**

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a `truth` factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

**Author(s)**

Max Kuhn

**See Also**

Other class metrics: [accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

**Examples**

```
# Two class
data("two_class_example")
bal_accuracy(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  bal_accuracy(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  bal_accuracy(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  bal_accuracy(obs, pred, estimator = "macro_weighted")

# Vector version
bal_accuracy_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
bal_accuracy_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)
```

**Description**

Compute the Brier score for a classification model.

**Usage**

```
brier_class(data, ...)

## S3 method for class 'data.frame'
brier_class(data, truth, ..., na_rm = TRUE, case_weights = NULL)

brier_class_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

**Arguments**

data	A data.frame containing the columns specified by truth and ....
...	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of event_level. Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For _vec() functions, a factor vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For _vec() functions, a numeric vector.
estimate	If truth is binary, a numeric vector of class probabilities corresponding to the "relevant" class. Otherwise, a matrix with as many columns as factor levels of truth. <i>It is assumed that these are in the same order as the levels of truth.</i>

**Details**

The Brier score is analogous to the mean squared error in regression models. The difference between a binary indicator for a class and its corresponding class probability are squared and averaged.

This function uses the convention in Kruppa *et al* (2014) and divides the result by two.

Smaller values of the score are associated with better model performance.

**Value**

A tibble with columns .metric, .estimator, and .estimate and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For brier\_class\_vec(), a single numeric value (or NA).

## Multiclass

Brier scores can be computed in the same way for any number of classes. Because of this, no averaging types are supported.

## Author(s)

Max Kuhn

## References

Kruppa, J., Liu, Y., Diener, H.-C., Holste, T., Weimar, C., Koonig, I. R., and Ziegler, A. (2014) Probability estimation with machine learning methods for dichotomous and multicategory outcome: Applications. *Biometrical Journal*, 56 (4): 564-583.

## See Also

Other class probability metrics: [average\\_precision\(\)](#), [classification\\_cost\(\)](#), [gain\\_capture\(\)](#), [mn\\_log\\_loss\(\)](#), [pr\\_auc\(\)](#), [roc\\_auc\(\)](#), [roc\\_aunp\(\)](#), [roc\\_aunu\(\)](#)

## Examples

```
# Two class
data("two_class_example")
brier_class(two_class_example, truth, Class1)

# Multiclass
library(dplyr)
data(hpc_cv)

# You can use the col1:colN tidyselect syntax
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  brier_class(obs, VF:L)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  brier_class(obs, VF:L)
```

---

ccc

*Concordance correlation coefficient*

---

## Description

Calculate the concordance correlation coefficient.

**Usage**

```
ccc(data, ...)

## S3 method for class 'data.frame'
ccc(
  data,
  truth,
  estimate,
  bias = FALSE,
  na_rm = TRUE,
  case_weights = NULL,
  ...
)

ccc_vec(truth, estimate, bias = FALSE, na_rm = TRUE, case_weights = NULL, ...)
```

**Arguments**

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is <code>numeric</code> ). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquoteotation</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also <code>numeric</code> ). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
<code>bias</code>	A logical; should the biased estimate of variance be used (as is Lin (1989))?
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

**Details**

`ccc()` is a metric of both consistency/correlation and accuracy, while metrics such as `rmse()` are strictly for accuracy and metrics such as `rsq()` are strictly for consistency/correlation

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `ccc_vec()`, a single numeric value (or NA).

**Author(s)**

Max Kuhn

**References**

Lin, L. (1989). A concordance correlation coefficient to evaluate reproducibility. *Biometrics*, 45 (1), 255-268.

Nickerson, C. (1997). A note on "A concordance correlation coefficient to evaluate reproducibility". *Biometrics*, 53(4), 1503-1507.

**See Also**

Other numeric metrics: [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other consistency metrics: [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#)

Other accuracy metrics: [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [smape\(\)](#)

**Examples**

```
# Supply truth and predictions as bare column names
ccc(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  ccc(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
```

---

`check_metric`*Developer function for checking inputs in new metrics*

---

### Description

`check_numeric_metric()`, `check_class_metric()`, and `check_prob_metric()` are useful alongside [metric-summarizers](#) for implementing new custom metrics. [metric-summarizers](#) call the metric function inside `dplyr::summarise()`. These functions perform checks on the inputs in accordance with the type of metric that is used.

### Usage

```
check_numeric_metric(truth, estimate, case_weights, call = caller_env())
```

```
check_class_metric(  
  truth,  
  estimate,  
  case_weights,  
  estimator,  
  call = caller_env()  
)
```

```
check_prob_metric(  
  truth,  
  estimate,  
  case_weights,  
  estimator,  
  call = caller_env()  
)
```

```
check_dynamic_survival_metric(  
  truth,  
  estimate,  
  case_weights,  
  call = caller_env()  
)
```

```
check_static_survival_metric(  
  truth,  
  estimate,  
  case_weights,  
  call = caller_env()  
)
```

### Arguments

`truth`            The realized vector of truth.

	<ul style="list-style-type: none"> <li>• For <code>check_numeric_metric()</code>, a numeric vector.</li> <li>• For <code>check_class_metric()</code>, a factor.</li> <li>• For <code>check_prob_metric()</code>, a factor.</li> <li>• For <code>check_dynamic_survival_metric()</code>, a <code>Surv</code> object.</li> <li>• For <code>check_static_survival_metric()</code>, a <code>Surv</code> object.</li> </ul>
<code>estimate</code>	<p>The realized estimate result.</p> <ul style="list-style-type: none"> <li>• For <code>check_numeric_metric()</code>, a numeric vector.</li> <li>• For <code>check_class_metric()</code>, a factor.</li> <li>• For <code>check_prob_metric()</code>, a numeric vector for binary truth, a numeric matrix for multic-class truth.</li> <li>• For <code>check_dynamic_survival_metric()</code>, list-column of <code>data.frames</code>.</li> <li>• For <code>check_static_survival_metric()</code>, a numeric vector.</li> </ul>
<code>case_weights</code>	The realized case weights, as a numeric vector. This must be the same length as truth.
<code>call</code>	The execution environment of a currently running function, e.g. <code>caller_env()</code> . The function will be mentioned in error messages as the source of the error. See the <code>call</code> argument of <code>abort()</code> for more information.
<code>estimator</code>	This can either be <code>NULL</code> for the default auto-selection of averaging ("binary" or "macro"), or a single character to pass along to the metric implementation describing the kind of averaging to use.

**See Also**

[metric-summarizers](#)

---

`classification_cost`    *Costs function for poor classification*

---

**Description**

`classification_cost()` calculates the cost of a poor prediction based on user-defined costs. The costs are multiplied by the estimated class probabilities and the mean cost is returned.

**Usage**

```
classification_cost(data, ...)

## S3 method for class 'data.frame'
classification_cost(
  data,
  truth,
  ...,
  costs = NULL,
  na_rm = TRUE,
```

```

    event_level = yardstick_event_level(),
    case_weights = NULL
  )

classification_cost_vec(
  truth,
  estimate,
  costs = NULL,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL,
  ...
)

```

### Arguments

data	A data.frame containing the columns specified by truth and ...
...	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of event_level. Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For _vec() functions, a factor vector.
costs	A data frame with columns "truth", "estimate", and "cost". "truth" and "estimate" should be character columns containing unique combinations of the levels of the truth factor. "costs" should be a numeric column representing the cost that should be applied when the "estimate" is predicted, but the true result is "truth". It is often the case that when "truth" == "estimate", the cost is zero (no penalty for correct predictions). If any combinations of the levels of truth are missing, their costs are assumed to be zero. If NULL, equal costs are used, applying a cost of 0 to correct predictions, and a cost of 1 to incorrect predictions.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option yardstick.event_first is set, that will be used instead with a warning.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For _vec() functions, a numeric vector.

`estimate` If truth is binary, a numeric vector of class probabilities corresponding to the "relevant" class. Otherwise, a matrix with as many columns as factor levels of truth. *It is assumed that these are in the same order as the levels of truth.*

### Details

As an example, suppose that there are three classes: "A", "B", and "C". Suppose there is a truly "A" observation with class probabilities  $A = 0.3$  /  $B = 0.3$  /  $C = 0.4$ . Suppose that, when the true result is class "A", the costs for each class were  $A = 0$  /  $B = 5$  /  $C = 10$ , penalizing the probability of incorrectly predicting "C" more than predicting "B". The cost for this prediction would be  $0.3 * 0 + 0.3 * 5 + 0.4 * 10$ . This calculation is done for each sample and the individual costs are averaged.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `class_cost_vec()`, a single numeric value (or NA).

### Author(s)

Max Kuhn

### See Also

Other class probability metrics: [average\\_precision\(\)](#), [brier\\_class\(\)](#), [gain\\_capture\(\)](#), [mn\\_log\\_loss\(\)](#), [pr\\_auc\(\)](#), [roc\\_auc\(\)](#), [roc\\_aunp\(\)](#), [roc\\_aunu\(\)](#)

### Examples

```
library(dplyr)

# -----
# Two class example
data(two_class_example)

# Assuming `Class1` is our "event", this penalizes false positives heavily
costs1 <- tribble(
  ~truth, ~estimate, ~cost,
  "Class1", "Class2", 1,
  "Class2", "Class1", 2
)

# Assuming `Class1` is our "event", this penalizes false negatives heavily
costs2 <- tribble(
  ~truth, ~estimate, ~cost,
  "Class1", "Class2", 2,
  "Class2", "Class1", 1
)

classification_cost(two_class_example, truth, Class1, costs = costs1)
```

```

classification_cost(two_class_example, truth, Class1, costs = costs2)

# -----
# Multiclass
data(hpc_cv)

# Define cost matrix from Kuhn and Johnson (2013)
hpc_costs <- tribble(
  ~estimate, ~truth, ~cost,
  "VF",      "VF",    0,
  "VF",      "F",     1,
  "VF",      "M",     5,
  "VF",      "L",    10,
  "F",       "VF",    1,
  "F",       "F",     0,
  "F",       "M",     5,
  "F",       "L",     5,
  "M",       "VF",    1,
  "M",       "F",     1,
  "M",       "M",     0,
  "M",       "L",     1,
  "L",       "VF",    1,
  "L",       "F",     1,
  "L",       "M",     1,
  "L",       "L",     0
)

# You can use the col1:colN tidyselct syntax
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  classification_cost(obs, VF:L, costs = hpc_costs)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  classification_cost(obs, VF:L, costs = hpc_costs)

```

---

conf\_mat

*Confusion Matrix for Categorical Data*


---

## Description

Calculates a cross-tabulation of observed and predicted classes.

## Usage

```
conf_mat(data, ...)
```

```
## S3 method for class 'data.frame'
```

```
conf_mat(
```

```

  data,
  truth,
  estimate,
  dnn = c("Prediction", "Truth"),
  case_weights = NULL,
  ...
)

## S3 method for class 'conf_mat'
tidy(x, ...)
```

### Arguments

data	A data frame or a <a href="#">base::table()</a> .
...	Not used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimate	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
dnn	A character vector of dimnames for the table.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
x	A <code>conf_mat</code> object.

### Details

For `conf_mat()` objects, a broom `tidy()` method has been created that collapses the cell counts by cell into a data frame for easy manipulation.

There is also a `summary()` method that computes various classification metrics at once. See [summary.conf\\_mat\(\)](#)

There is a [ggplot2::autoplot\(\)](#) method for quickly visualizing the matrix. Both a heatmap and mosaic type is implemented.

The function requires that the factors have exactly the same levels.

### Value

`conf_mat()` produces an object with class `conf_mat`. This contains the table and other objects. `tidy.conf_mat()` generates a tibble with columns `name` (the cell identifier) and `value` (the cell count).

When used on a grouped data frame, `conf_mat()` returns a tibble containing columns for the groups along with `conf_mat`, a list-column where each element is a `conf_mat` object.

**See Also**

[summary.conf\\_mat\(\)](#) for computing a large number of metrics from one confusion matrix.

**Examples**

```
library(dplyr)
data("hpc_cv")

# The confusion matrix from a single assessment set (i.e. fold)
cm <- hpc_cv %>%
  filter(Resample == "Fold01") %>%
  conf_mat(obs, pred)
cm

# Now compute the average confusion matrix across all folds in
# terms of the proportion of the data contained in each cell.
# First get the raw cell counts per fold using the `tidy` method
library(tidyr)

cells_per_resample <- hpc_cv %>%
  group_by(Resample) %>%
  conf_mat(obs, pred) %>%
  mutate(tidied = lapply(conf_mat, tidy)) %>%
  unnest(tidied)

# Get the totals per resample
counts_per_resample <- hpc_cv %>%
  group_by(Resample) %>%
  summarize(total = n()) %>%
  left_join(cells_per_resample, by = "Resample") %>%
  # Compute the proportions
  mutate(prop = value / total) %>%
  group_by(name) %>%
  # Average
  summarize(prop = mean(prop))

counts_per_resample

# Now reshape these into a matrix
mean_cmat <- matrix(counts_per_resample$prop, byrow = TRUE, ncol = 4)
rownames(mean_cmat) <- levels(hpc_cv$obs)
colnames(mean_cmat) <- levels(hpc_cv$obs)

round(mean_cmat, 3)

# The confusion matrix can quickly be visualized using autoplot()
library(ggplot2)

autoplot(cm, type = "mosaic")
autoplot(cm, type = "heatmap")
```

---

detection\_prevalence *Detection prevalence*

---

### Description

Detection prevalence is defined as the number of *predicted* positive events (both true positive and false positive) divided by the total number of predictions.

### Usage

```
detection_prevalence(data, ...)
```

```
## S3 method for class 'data.frame'
detection_prevalence(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)
```

```
detection_prevalence_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)
```

### Arguments

data	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
...	Not currently used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimate	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.

estimator	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on estimate.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `detection_prevalence_vec()`, a single numeric value (or NA).

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Multiclass

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

### Author(s)

Max Kuhn

### See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

## Examples

```
# Two class
data("two_class_example")
detection_prevalence(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  detection_prevalence(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  detection_prevalence(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  detection_prevalence(obs, pred, estimator = "macro_weighted")

# Vector version
detection_prevalence_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
detection_prevalence_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)
```

---

developer-helpers

*Developer helpers*

---

## Description

Helpers to be used alongside [check\\_metric](#), [yardstick\\_remove\\_missing](#) and [metric summarizers](#) when creating new metrics. See [Custom performance metrics](#) for more information.

## Usage

```
dots_to_estimate(data, ...)
```

```
get_weights(data, estimator)
```

```

finalize_estimator(
  x,
  estimator = NULL,
  metric_class = "default",
  call = caller_env()
)

finalize_estimator_internal(
  metric_dispatcher,
  x,
  estimator,
  call = caller_env()
)

validate_estimator(estimator, estimator_override = NULL, call = caller_env())

```

### Arguments

<code>data</code>	A table with truth values as columns and predicted values as rows.
<code>...</code>	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of <code>event_level</code> . Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
<code>estimator</code>	Either NULL for auto-selection, or a single character for the type of estimator to use.
<code>x</code>	The column used to autoselect the estimator. This is generally the truth column, but can also be a table if your metric has table methods.
<code>metric_class</code>	A single character of the name of the metric to autoselect the estimator for. This should match the method name created for <code>finalize_estimator_internal()</code> .
<code>call</code>	The execution environment of a currently running function, e.g. <code>caller_env()</code> . The function will be mentioned in error messages as the source of the error. See the <code>call</code> argument of <a href="#">abort()</a> for more information.
<code>metric_dispatcher</code>	A simple dummy object with the class provided to <code>metric_class</code> . This is created and passed along for you.
<code>estimator_override</code>	A character vector overriding the default allowed estimator list of <code>c("binary", "macro", "micro", "macro_weighted")</code> . Set this if your classification estimator does not support all of these methods.

### Dots -> Estimate

#### [Deprecated]

`dots_to_estimate()` is useful with class probability metrics that take `...` rather than `estimate` as an argument. It constructs either a single name if 1 input is provided to `...` or it constructs a

quosure where the expression constructs a matrix of as many columns as are provided to . . . These are eventually evaluated in the summarise() call in [metric-summarizers](#) and evaluate to either a vector or a matrix for further use in the underlying vector functions.

### Weight Calculation

get\_weights() accepts a confusion matrix and an estimator of type "macro", "micro", or "macro\_weighted" and returns the correct weights. It is useful when creating multiclass metrics.

### Estimator Selection

finalize\_estimator() is the engine for auto-selection of estimator based on the type of x. Generally x is the truth column. This function is called from the vector method of your metric.

finalize\_estimator\_internal() is an S3 generic that you should extend for your metric if it does not implement *only* the following estimator types: "binary", "macro", "micro", and "macro\_weighted". If your metric does support all of these, the default version of finalize\_estimator\_internal() will autoselect estimator appropriately. If you need to create a method, it should take the form: finalize\_estimator\_internal.metric\_name. Your method for finalize\_estimator\_internal() should do two things:

1. If estimator is NULL, autoselect the estimator based on the type of x and return a single character for the estimator.
2. If estimator is not NULL, validate that it is an allowed estimator for your metric and return it.

If you are using the default for finalize\_estimator\_internal(), the estimator is selected using the following heuristics:

1. If estimator is not NULL, it is validated and returned immediately as no auto-selection is needed.
2. If x is a:
  - factor - Then "binary" is returned if it has 2 levels, otherwise "macro" is returned.
  - numeric - Then "binary" is returned.
  - table - Then "binary" is returned if it has 2 columns, otherwise "macro" is returned. This is useful if you have table methods.
  - matrix - Then "macro" is returned.

### Estimator Validation

validate\_estimator() is called from your metric specific method of finalize\_estimator\_internal() and ensures that a user provided estimator is of the right format and is one of the allowed values.

### See Also

[metric-summarizers check\\_metric yardstick\\_remove\\_missing](#)

---

f\_meas

*F Measure*

---

### Description

These functions calculate the `f_meas()` of a measurement system for finding relevant documents compared to reference results (the truth regarding relevance). Highly related functions are `recall()` and `precision()`.

### Usage

```
f_meas(data, ...)  
  
## S3 method for class 'data.frame'  
f_meas(  
  data,  
  truth,  
  estimate,  
  beta = 1,  
  estimator = NULL,  
  na_rm = TRUE,  
  case_weights = NULL,  
  event_level = yardstick_event_level(),  
  ...  
)  
  
f_meas_vec(  
  truth,  
  estimate,  
  beta = 1,  
  estimator = NULL,  
  na_rm = TRUE,  
  case_weights = NULL,  
  event_level = yardstick_event_level(),  
  ...  
)
```

### Arguments

data	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
...	Not currently used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.

estimate	The column identifier for the predicted class results (that is also factor). As with truth this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
beta	A numeric value used to weight precision and recall. A value of 1 is traditionally used and corresponds to the harmonic mean of the two values but other values weight recall beta times more important than precision.
estimator	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on estimate.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

### Details

The measure "F" is a combination of precision and recall (see below).

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `f_meas_vec()`, a single numeric value (or NA).

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Multiclass

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

## Implementation

Suppose a 2x2 table with notation:

	Reference	
Predicted	Relevant	Irrelevant
Relevant	A	B
Irrelevant	C	D

The formulas used here are:

$$recall = A/(A + C)$$

$$precision = A/(A + B)$$

$$F_{meas} = (1 + \beta^2) * precision * recall / ((\beta^2 * precision) + recall)$$

See the references for discussions of the statistics.

## Author(s)

Max Kuhn

## References

Buckland, M., & Gey, F. (1994). The relationship between Recall and Precision. *Journal of the American Society for Information Science*, 45(1), 12-19.

Powers, D. (2007). Evaluation: From Precision, Recall and F Factor to ROC, Informedness, Markedness and Correlation. Technical Report SIE-07-001, Flinders University

## See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

Other relevance metrics: [precision\(\)](#), [recall\(\)](#)

## Examples

```
# Two class
data("two_class_example")
f_meas(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  f_meas(obs, pred)
```

```

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  f_meas(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  f_meas(obs, pred, estimator = "macro_weighted")

# Vector version
f_meas_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
f_meas_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)

```

---

gain\_capture

*Gain capture*

---

## Description

gain\_capture() is a measure of performance similar to an AUC calculation, but applied to a gain curve.

## Usage

```

gain_capture(data, ...)

## S3 method for class 'data.frame'
gain_capture(
  data,
  truth,
  ...,
  estimator = NULL,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL
)

gain_capture_vec(
  truth,
  estimate,

```

```

    estimator = NULL,
    na_rm = TRUE,
    event_level = yardstick_event_level(),
    case_weights = NULL,
    ...
  )

```

## Arguments

data	A <code>data.frame</code> containing the columns specified by <code>truth</code> and ...
...	A set of unquoted column names or one or more <code>dplyr</code> selector functions to choose which variables contain the class probabilities. If <code>truth</code> is binary, only 1 column should be selected, and it should correspond to the value of <code>event_level</code> . Otherwise, there should be as many columns as factor levels of <code>truth</code> and the ordering of the columns should be the same as the factor levels of <code>truth</code> .
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimator	One of "binary", "macro", or "macro_weighted" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other two are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on <code>truth</code> .
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
event_level	A single string. Either "first" or "second" to specify which level of <code>truth</code> to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
estimate	If <code>truth</code> is binary, a numeric vector of class probabilities corresponding to the "relevant" class. Otherwise, a matrix with as many columns as factor levels of <code>truth</code> . <i>It is assumed that these are in the same order as the levels of truth.</i>

## Details

`gain_capture()` calculates the area *under* the gain curve, but *above* the baseline, and then divides that by the area *under* a perfect gain curve, but *above* the baseline. It is meant to represent the amount of potential gain "captured" by the model.

The `gain_capture()` metric is identical to the *accuracy ratio (AR)*, which is also sometimes called the *gini coefficient*. These two are generally calculated on a cumulative accuracy profile curve, but this is the same as a gain curve. See the Engelmann reference for more information.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `gain_capture_vec()`, a single numeric value (or NA).

**Relevant Level**

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

**Multiclass**

Macro and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

**Author(s)**

Max Kuhn

**References**

Engelmann, Bernd & Hayden, Evelyn & Tasche, Dirk (2003). "Measuring the Discriminative Power of Rating Systems," Discussion Paper Series 2: Banking and Financial Studies 2003,01, Deutsche Bundesbank.

**See Also**

[gain\\_curve\(\)](#) to compute the full gain curve.

Other class probability metrics: [average\\_precision\(\)](#), [brier\\_class\(\)](#), [classification\\_cost\(\)](#), [mn\\_log\\_loss\(\)](#), [pr\\_auc\(\)](#), [roc\\_auc\(\)](#), [roc\\_aunp\(\)](#), [roc\\_aunu\(\)](#)

**Examples**

```
# -----
# Two class example

# `truth` is a 2 level factor. The first level is `Class1`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(two_class_example)

# Binary metrics using class probabilities take a factor `truth` column,
# and a single class probability column containing the probabilities of
# the event of interest. Here, since `Class1` is the first level of
```

```

# `truth`, it is the event of interest and we pass in probabilities for it.
gain_capture(two_class_example, truth, Class1)

# -----
# Multiclass example

# `obs` is a 4 level factor. The first level is `VF`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(hpc_cv)

# You can use the col1:colN tidyselect syntax
library(dplyr)
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  gain_capture(obs, VF:L)

# Change the first level of `obs` from `VF` to `M` to alter the
# event of interest. The class probability columns should be supplied
# in the same order as the levels.
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  mutate(obs = relevel(obs, "M")) %>%
  gain_capture(obs, M, VF:L)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  gain_capture(obs, VF:L)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  gain_capture(obs, VF:L, estimator = "macro_weighted")

# Vector version
# Supply a matrix of class probabilities
fold1 <- hpc_cv %>%
  filter(Resample == "Fold01")

gain_capture_vec(
  truth = fold1$obs,
  matrix(
    c(fold1$VF, fold1$F, fold1$M, fold1$L),
    ncol = 4
  )
)

# -----
# Visualize gain_capture()

# Visually, this represents the area under the black curve, but above the
# 45 degree line, divided by the area of the shaded triangle.

```

```
library(ggplot2)
autoplot(gain_curve(two_class_example, truth, Class1))
```

---

gain\_curve

*Gain curve*

---

## Description

gain\_curve() constructs the full gain curve and returns a tibble. See [gain\\_capture\(\)](#) for the relevant area under the gain curve. Also see [lift\\_curve\(\)](#) for a closely related concept.

## Usage

```
gain_curve(data, ...)

## S3 method for class 'data.frame'
gain_curve(
  data,
  truth,
  ...,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL
)
```

## Arguments

data	A data.frame containing the columns specified by truth and ...
...	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of event_level. Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For _vec() functions, a factor vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option yardstick.event_first is set, that will be used instead with a warning.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For _vec() functions, a numeric vector.

## Details

There is a `ggplot2::autoplot()` method for quickly visualizing the curve. This works for binary and multiclass output, and also works with grouped data (i.e. from resamples). See the examples.

The greater the area between the gain curve and the baseline, the better the model.

Gain curves are identical to CAP curves (cumulative accuracy profile). See the Engelmann reference for more information on CAP curves.

## Value

A tibble with class `gain_df` or `gain_grouped_df` having columns:

- `.n` The index of the current sample.
- `.n_events` The index of the current *unique* sample. Values with repeated estimate values are given identical indices in this column.
- `.percent_tested` The cumulative percentage of values tested.
- `.percent_found` The cumulative percentage of true results relative to the total number of true results.

If using the `case_weights` argument, all of the above columns will be weighted. This makes the most sense with frequency weights, which are integer weights representing the number of times a particular observation should be repeated.

## Gain and Lift Curves

The motivation behind cumulative gain and lift charts is as a visual method to determine the effectiveness of a model when compared to the results one might expect without a model. As an example, without a model, if you were to advertise to a random 10% of your customer base, then you might expect to capture 10% of the of the total number of positive responses had you advertised to your entire customer base. Given a model that predicts which customers are more likely to respond, the hope is that you can more accurately target 10% of your customer base and capture >10% of the total number of positive responses.

The calculation to construct gain curves is as follows:

1. `truth` and `estimate` are placed in descending order by the `estimate` values (`estimate` here is a single column supplied in `. . .`).
2. The cumulative number of samples with true results relative to the entire number of true results are found. This is the y-axis in a gain chart.

## Multiclass

If a multiclass `truth` column is provided, a one-vs-all approach will be taken to calculate multiple curves, one per level. In this case, there will be an additional column, `.level`, identifying the "one" column in the one-vs-all calculation.

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Author(s)

Max Kuhn

### References

Engelmann, Bernd & Hayden, Evelyn & Tasche, Dirk (2003). "Measuring the Discriminative Power of Rating Systems," Discussion Paper Series 2: Banking and Financial Studies 2003,01, Deutsche Bundesbank.

### See Also

Compute the relevant area under the gain curve with `gain_capture()`.

Other curve metrics: `lift_curve()`, `pr_curve()`, `roc_curve()`

### Examples

```
# -----
# Two class example

# `truth` is a 2 level factor. The first level is `"Class1"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(two_class_example)

# Binary metrics using class probabilities take a factor `truth` column,
# and a single class probability column containing the probabilities of
# the event of interest. Here, since `"Class1"` is the first level of
# `"truth"`, it is the event of interest and we pass in probabilities for it.
gain_curve(two_class_example, truth, Class1)

# -----
# `autoplot()`

library(ggplot2)
library(dplyr)

# Use autoplot to visualize
# The top left hand corner of the grey triangle is a "perfect" gain curve
autoplot(gain_curve(two_class_example, truth, Class1))

# Multiclass one-vs-all approach
# One curve per level
```

```

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  gain_curve(obs, VF:L) %>%
  autoplot()

# Same as above, but will all of the resamples
# The resample with the minimum (farthest to the left) "perfect" value is
# used to draw the shaded region
hpc_cv %>%
  group_by(Resample) %>%
  gain_curve(obs, VF:L) %>%
  autoplot()

```

---

hpc\_cv

*Multiclass Probability Predictions*


---

## Description

Multiclass Probability Predictions

## Details

This data frame contains the predicted classes and class probabilities for a linear discriminant analysis model fit to the HPC data set from Kuhn and Johnson (2013). These data are the assessment sets from a 10-fold cross-validation scheme. The data column columns for the true class (obs), the class prediction (pred) and columns for each class probability (columns VF, F, M, and L). Additionally, a column for the resample indicator is included.

## Value

hpc\_cv            a data frame

## Source

Kuhn, M., Johnson, K. (2013) *Applied Predictive Modeling*, Springer

## Examples

```

data(hpc_cv)
str(hpc_cv)

# `obs` is a 4 level factor. The first level is `"VF"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section in any classification function (such as `pr_auc`) to see how
# to change this.
levels(hpc_cv$obs)

```

---

huber_loss	<i>Huber loss</i>
------------	-------------------

---

### Description

Calculate the Huber loss, a loss function used in robust regression. This loss function is less sensitive to outliers than `rmse()`. This function is quadratic for small residual values and linear for large residual values.

### Usage

```
huber_loss(data, ...)  
  
## S3 method for class 'data.frame'  
huber_loss(  
  data,  
  truth,  
  estimate,  
  delta = 1,  
  na_rm = TRUE,  
  case_weights = NULL,  
  ...  
)  
  
huber_loss_vec(  
  truth,  
  estimate,  
  delta = 1,  
  na_rm = TRUE,  
  case_weights = NULL,  
  ...  
)
```

### Arguments

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.

delta	A single numeric value. Defines the boundary where the loss function transitions from quadratic to linear. Defaults to 1.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `huber_loss_vec()`, a single numeric value (or NA).

### Author(s)

James Blair

### References

Huber, P. (1964). Robust Estimation of a Location Parameter. *Annals of Statistics*, 53 (1), 73-101.

### See Also

Other numeric metrics: `ccc()`, `huber_loss_pseudo()`, `iic()`, `mae()`, `mape()`, `mase()`, `mpe()`, `msd()`, `poisson_log_loss()`, `rmse()`, `rpd()`, `rpiq()`, `rsq_trad()`, `rsq()`, `smape()`

Other accuracy metrics: `ccc()`, `huber_loss_pseudo()`, `iic()`, `mae()`, `mape()`, `mase()`, `mpe()`, `msd()`, `poisson_log_loss()`, `rmse()`, `smape()`

### Examples

```
# Supply truth and predictions as bare column names
huber_loss(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)
```

```
# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  huber_loss(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
```

---

huber\_loss\_pseudo      *Pseudo-Huber Loss*

---

### Description

Calculate the Pseudo-Huber Loss, a smooth approximation of `huber_loss()`. Like `huber_loss()`, this is less sensitive to outliers than `rmse()`.

### Usage

```
huber_loss_pseudo(data, ...)
```

```
## S3 method for class 'data.frame'
huber_loss_pseudo(
  data,
  truth,
  estimate,
  delta = 1,
  na_rm = TRUE,
  case_weights = NULL,
  ...
)
```

```
huber_loss_pseudo_vec(
  truth,
  estimate,
  delta = 1,
  na_rm = TRUE,
  case_weights = NULL,
  ...
)
```

### Arguments

<code>data</code>	A data.frame containing the columns specified by the truth and estimate arguments.
<code>...</code>	Not currently used.

truth	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
estimate	The column identifier for the predicted results (that is also numeric). As with truth this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
delta	A single numeric value. Defines the boundary where the loss function transitions from quadratic to linear. Defaults to 1.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `huber_loss_pseudo_vec()`, a single numeric value (or NA).

### Author(s)

James Blair

### References

Huber, P. (1964). Robust Estimation of a Location Parameter. *Annals of Statistics*, 53 (1), 73-101.

Hartley, Richard (2004). Multiple View Geometry in Computer Vision. (Second Edition). Page 619.

### See Also

Other numeric metrics: `ccc()`, `huber_loss()`, `iic()`, `mae()`, `mape()`, `mase()`, `mpe()`, `msd()`, `poisson_log_loss()`, `rmse()`, `rpd()`, `rpiq()`, `rsq_trad()`, `rsq()`, `smape()`

Other accuracy metrics: `ccc()`, `huber_loss()`, `iic()`, `mae()`, `mape()`, `mase()`, `mpe()`, `msd()`, `poisson_log_loss()`, `rmse()`, `smape()`

### Examples

```
# Supply truth and predictions as bare column names
huber_loss_pseudo(solubility_test, solubility, prediction)
```

```
library(dplyr)
```

```
set.seed(1234)
size <- 100
times <- 10
```

```

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  huber_loss_pseudo(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))

```

---

iic

*Index of ideality of correlation*


---

## Description

Calculate the index of ideality of correlation. This metric has been studied in QSPR/QSAR models as a good criterion for the predictive potential of these models. It is highly dependent on the correlation coefficient as well as the mean absolute error.

Note the application of IIC is useless under two conditions:

- When the negative mean absolute error and positive mean absolute error are both zero.
- When the outliers are symmetric. Since outliers are context dependent, please use your own checks to validate whether this restriction holds and whether the resulting IIC has interpretative value.

The IIC is seen as an alternative to the traditional correlation coefficient and is in the same units as the original data.

## Usage

```

iic(data, ...)

## S3 method for class 'data.frame'
iic(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

iic_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

```

**Arguments**

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is <code>numeric</code> ). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a <code>numeric</code> vector.
<code>estimate</code>	The column identifier for the predicted results (that is also <code>numeric</code> ). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a <code>numeric</code> vector.
<code>na_rm</code>	A <code>logical</code> value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a <code>numeric</code> column in <code>data</code> . For <code>_vec()</code> functions, a <code>numeric</code> vector.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `iic_vec()`, a single `numeric` value (or NA).

**Author(s)**

Joyce Cahoon

**References**

Toropova, A. and Toropov, A. (2017). "The index of ideality of correlation. A criterion of predictability of QSAR models for skin permeability?" *Science of the Total Environment*. 586: 466-472.

**See Also**

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other accuracy metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [smape\(\)](#)

**Examples**

```
# Supply truth and predictions as bare column names
iic(solubility_test, solubility, prediction)

library(dplyr)
```

```

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  iic(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))

```

---

j\_index

*J-index*


---

## Description

Youden's J statistic is defined as:

`sens()` + `spec()` - 1

A related metric is Informedness, see the Details section for the relationship.

## Usage

```
j_index(data, ...)
```

```
## S3 method for class 'data.frame'
```

```

j_index(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

```

```

)

j_index_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

```

### Arguments

data	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
...	Not currently used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimate	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
estimator	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on <code>estimate</code> .
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
event_level	A single string. Either "first" or "second" to specify which level of <code>truth</code> to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

### Details

The value of the J-index ranges from [0, 1] and is 1 when there are no false positives and no false negatives.

The binary version of J-index is equivalent to the binary concept of Informedness. Macro-weighted J-index is equivalent to multiclass informedness as defined in Powers, David M W (2011), equation (42).

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `j_index_vec()`, a single numeric value (or NA).

**Relevant Level**

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

**Multiclass**

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

**Author(s)**

Max Kuhn

**References**

Youden, W.J. (1950). "Index for rating diagnostic tests". *Cancer*. 3: 32-35.

Powers, David M W (2011). "Evaluation: From Precision, Recall and F-Score to ROC, Informedness, Markedness and Correlation". *Journal of Machine Learning Technologies*. 2 (1): 37-63.

**See Also**

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

**Examples**

```
# Two class
data("two_class_example")
j_index(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  j_index(obs, pred)
```

```

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  j_index(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  j_index(obs, pred, estimator = "macro_weighted")

# Vector version
j_index_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
j_index_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)

```

---

kap

*Kappa*


---

## Description

Kappa is a similar measure to [accuracy\(\)](#), but is normalized by the accuracy that would be expected by chance alone and is very useful when one or more classes have large frequency distributions.

## Usage

```

kap(data, ...)

## S3 method for class 'data.frame'
kap(
  data,
  truth,
  estimate,
  weighting = "none",
  na_rm = TRUE,
  case_weights = NULL,
  ...
)

kap_vec(
  truth,

```

```

  estimate,
  weighting = "none",
  na_rm = TRUE,
  case_weights = NULL,
  ...
)

```

## Arguments

<code>data</code>	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
<code>estimate</code>	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
<code>weighting</code>	A weighting to apply when computing the scores. One of: "none", "linear", or "quadratic". Linear and quadratic weighting penalizes mis-predictions that are "far away" from the true value. Note that distance is judged based on the ordering of the levels in <code>truth</code> and <code>estimate</code> . It is recommended to provide ordered factors for <code>truth</code> and <code>estimate</code> to explicitly code the ordering, but this is not required.  In the binary case, all 3 weightings produce the same value, since it is only ever possible to be 1 unit away from the true value.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

## Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `kap_vec()`, a single numeric value (or NA).

## Multiclass

Kappa extends naturally to multiclass scenarios. Because of this, macro and micro averaging are not implemented.

**Author(s)**

Max Kuhn  
Jon Harmon

**References**

Cohen, J. (1960). "A coefficient of agreement for nominal scales". *Educational and Psychological Measurement*. 20 (1): 37-46.

Cohen, J. (1968). "Weighted kappa: Nominal scale agreement provision for scaled disagreement or partial credit". *Psychological Bulletin*. 70 (4): 213-220.

**See Also**

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

**Examples**

```
library(dplyr)
data("two_class_example")
data("hpc_cv")

# Two class
kap(two_class_example, truth, predicted)

# Multiclass
# kap() has a natural multiclass extension
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  kap(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  kap(obs, pred)
```

---

lift\_curve

*Lift curve*

---

**Description**

`lift_curve()` constructs the full lift curve and returns a tibble. See [gain\\_curve\(\)](#) for a closely related concept.

**Usage**

```
lift_curve(data, ...)

## S3 method for class 'data.frame'
lift_curve(
  data,
  truth,
  ...,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL
)
```

**Arguments**

<code>data</code>	A <code>data.frame</code> containing the columns specified by <code>truth</code> and <code>...</code>
<code>...</code>	A set of unquoted column names or one or more <code>dplyr</code> selector functions to choose which variables contain the class probabilities. If <code>truth</code> is binary, only 1 column should be selected, and it should correspond to the value of <code>event_level</code> . Otherwise, there should be as many columns as factor levels of <code>truth</code> and the ordering of the columns should be the same as the factor levels of <code>truth</code> .
<code>truth</code>	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>event_level</code>	A single string. Either "first" or "second" to specify which level of <code>truth</code> to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

**Details**

There is a `ggplot2::autoplot()` method for quickly visualizing the curve. This works for binary and multiclass output, and also works with grouped data (i.e. from `resamples`). See the examples.

**Value**

A tibble with class `lift_df` or `lift_grouped_df` having columns:

- `.n` The index of the current sample.

- `.n_events` The index of the current *unique* sample. Values with repeated estimate values are given identical indices in this column.
- `.percent_tested` The cumulative percentage of values tested.
- `.lift` First calculate the cumulative percentage of true results relative to the total number of true results. Then divide that by `.percent_tested`.

If using the `case_weights` argument, all of the above columns will be weighted. This makes the most sense with frequency weights, which are integer weights representing the number of times a particular observation should be repeated.

### Gain and Lift Curves

The motivation behind cumulative gain and lift charts is as a visual method to determine the effectiveness of a model when compared to the results one might expect without a model. As an example, without a model, if you were to advertise to a random 10% of your customer base, then you might expect to capture 10% of the of the total number of positive responses had you advertised to your entire customer base. Given a model that predicts which customers are more likely to respond, the hope is that you can more accurately target 10% of your customer base and capture >10% of the total number of positive responses.

The calculation to construct lift curves is as follows:

1. `truth` and `estimate` are placed in descending order by the `estimate` values (`estimate` here is a single column supplied in . . .).
2. The cumulative number of samples with true results relative to the entire number of true results are found.
3. The cumulative % found is divided by the cumulative % tested to construct the lift value. This ratio represents the factor of improvement over an uninformed model. Values >1 represent a valuable model. This is the y-axis of the lift chart.

### Multiclass

If a multiclass `truth` column is provided, a one-vs-all approach will be taken to calculate multiple curves, one per level. In this case, there will be an additional column, `.level`, identifying the "one" column in the one-vs-all calculation.

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Author(s)

Max Kuhn

**See Also**

Other curve metrics: [gain\\_curve\(\)](#), [pr\\_curve\(\)](#), [roc\\_curve\(\)](#)

**Examples**

```
# -----
# Two class example

# `truth` is a 2 level factor. The first level is `Class1`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(two_class_example)

# Binary metrics using class probabilities take a factor `truth` column,
# and a single class probability column containing the probabilities of
# the event of interest. Here, since `Class1` is the first level of
# `truth`, it is the event of interest and we pass in probabilities for it.
lift_curve(two_class_example, truth, Class1)

# -----
# `autoplot()`

library(ggplot2)
library(dplyr)

# Use autoplot to visualize
autoplot(lift_curve(two_class_example, truth, Class1))

# Multiclass one-vs-all approach
# One curve per level
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  lift_curve(obs, VF:L) %>%
  autoplot()

# Same as above, but will all of the resamples
hpc_cv %>%
  group_by(Resample) %>%
  lift_curve(obs, VF:L) %>%
  autoplot()
```

---

lung\_surv

*Survival Analysis Results*

---

**Description**

Survival Analysis Results

**Details**

These data contain plausible results from applying predictive survival models to the [lung](#) data set using the censored package.

**Value**

lung\_surv      a data frame

**Examples**

```
data(lung_surv)
str(lung_surv)

# `surv_obj` is a `Surv()` object
```

---

mae	<i>Mean absolute error</i>
-----	----------------------------

---

**Description**

Calculate the mean absolute error. This metric is in the same units as the original data.

**Usage**

```
mae(data, ...)
```

```
## S3 method for class 'data.frame'
mae(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

```
mae_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

**Arguments**

data	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
...	Not currently used.
truth	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
estimate	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `mae_vec()`, a single numeric value (or NA).

**Author(s)**

Max Kuhn

**See Also**

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other accuracy metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [smape\(\)](#)

**Examples**

```
# Supply truth and predictions as bare column names
mae(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  mae(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
```

---

mape	<i>Mean absolute percent error</i>
------	------------------------------------

---

### Description

Calculate the mean absolute percentage error. This metric is in *relative units*.

### Usage

```
mape(data, ...)

## S3 method for class 'data.frame'
mape(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

mape_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

### Arguments

data	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
...	Not currently used.
truth	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
estimate	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

### Details

Note that a value of `Inf` is returned for `mape()` when the observed value is negative.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `mape_vec()`, a single numeric value (or NA).

**Author(s)**

Max Kuhn

**See Also**

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other accuracy metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [smape\(\)](#)

**Examples**

```
# Supply truth and predictions as bare column names
mase(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  mase(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
```

---

mase

*Mean absolute scaled error*

---

**Description**

Calculate the mean absolute scaled error. This metric is *scale independent* and *symmetric*. It is generally used for comparing forecast error in time series settings. Due to the time series nature of this metric, it is necessary to order observations in ascending order by time.

**Usage**

```

mase(data, ...)

## S3 method for class 'data.frame'
mase(
  data,
  truth,
  estimate,
  m = 1L,
  mae_train = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  ...
)

mase_vec(
  truth,
  estimate,
  m = 1L,
  mae_train = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  ...
)

```

**Arguments**

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquoteotation</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
<code>m</code>	An integer value of the number of lags used to calculate the in-sample seasonal naive error. The default is used for non-seasonal time series. If each observation was at the daily level and the data showed weekly seasonality, then <code>m = 7L</code> would be a reasonable choice for a 7-day seasonal naive calculation.
<code>mae_train</code>	A numeric value which allows the user to provide the in-sample seasonal naive mean absolute error. If this value is not provided, then the out-of-sample seasonal naive mean absolute error will be calculated from <code>truth</code> and will be used instead.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.

`case_weights` The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For `_vec()` functions, a numeric vector.

### Details

`mase()` is different from most numeric metrics. The original implementation of `mase()` calls for using the *in-sample* naive mean absolute error to compute scaled errors with. It uses this instead of the out-of-sample error because there is a chance that the out-of-sample error cannot be computed when forecasting a very short horizon (i.e. the out of sample size is only 1 or 2). However, `yardstick` only knows about the out-of-sample truth and estimate values. Because of this, the out-of-sample error is used in the computation by default. If the in-sample naive mean absolute error is required and known, it can be passed through in the `mae_train` argument and it will be used instead. If the in-sample data is available, the naive mean absolute error can easily be computed with `mae(data, truth, lagged_truth)`.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `mase_vec()`, a single numeric value (or NA).

### Author(s)

Alex Hallam

### References

Rob J. Hyndman (2006). ANOTHER LOOK AT FORECAST-ACCURACY METRICS FOR INTERMITTENT DEMAND. *Foresight*, 4, 46.

### See Also

Other numeric metrics: `ccc()`, `huber_loss_pseudo()`, `huber_loss()`, `iic()`, `mae()`, `mape()`, `mpe()`, `msd()`, `poisson_log_loss()`, `rmse()`, `rpd()`, `rpiq()`, `rsq_trad()`, `rsq()`, `smape()`

Other accuracy metrics: `ccc()`, `huber_loss_pseudo()`, `huber_loss()`, `iic()`, `mae()`, `mape()`, `mpe()`, `msd()`, `poisson_log_loss()`, `rmse()`, `smape()`

### Examples

```
# Supply truth and predictions as bare column names
mase(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
```

```

solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  mase(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))

```

mcc

*Matthews correlation coefficient***Description**

Matthews correlation coefficient

**Usage**

```

mcc(data, ...)

## S3 method for class 'data.frame'
mcc(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

mcc_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

```

**Arguments**

data	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
...	Not currently used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimate	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.

na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `mcc_vec()`, a single numeric value (or NA).

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Multiclass

`mcc()` has a known multiclass generalization and that is computed automatically if a factor with more than 2 levels is provided. Because of this, no averaging methods are provided.

### Author(s)

Max Kuhn

### References

Giuseppe, J. (2012). "A Comparison of MCC and CEN Error Measures in Multi-Class Prediction". *PLOS ONE*. Vol 7, Iss 8, e41882.

### See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

### Examples

```
library(dplyr)
data("two_class_example")
data("hpc_cv")

# Two class
mcc(two_class_example, truth, predicted)

# Multiclass
```

```

# mcc() has a natural multiclass extension
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  mcc(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  mcc(obs, pred)

```

---

metric-summarizers      *Developer function for summarizing new metrics*

---

## Description

`numeric_metric_summarizer()`, `class_metric_summarizer()`, `prob_metric_summarizer()`, `curve_metric_summarizer()`, `dynamic_survival_metric_summarizer()`, and `static_survival_metric_summarizer()` are useful alongside [check\\_metric](#) and [yardstick\\_remove\\_missing](#) for implementing new custom metrics. These functions call the metric function inside `dplyr::summarise()` or `dplyr::reframe()` for `curve_metric_summarizer()`. See [Custom performance metrics](#) for more information.

## Usage

```

numeric_metric_summarizer(
  name,
  fn,
  data,
  truth,
  estimate,
  ...,
  na_rm = TRUE,
  case_weights = NULL,
  fn_options = list(),
  error_call = caller_env()
)

```

```

class_metric_summarizer(
  name,
  fn,
  data,
  truth,
  estimate,
  ...,
  estimator = NULL,
  na_rm = TRUE,
  event_level = NULL,
  case_weights = NULL,
  fn_options = list(),
)

```

```
    error_call = caller_env()
  )

  prob_metric_summarizer(
    name,
    fn,
    data,
    truth,
    ...,
    estimator = NULL,
    na_rm = TRUE,
    event_level = NULL,
    case_weights = NULL,
    fn_options = list(),
    error_call = caller_env()
  )

  curve_metric_summarizer(
    name,
    fn,
    data,
    truth,
    ...,
    estimator = NULL,
    na_rm = TRUE,
    event_level = NULL,
    case_weights = NULL,
    fn_options = list(),
    error_call = caller_env()
  )

  dynamic_survival_metric_summarizer(
    name,
    fn,
    data,
    truth,
    ...,
    na_rm = TRUE,
    case_weights = NULL,
    fn_options = list(),
    error_call = caller_env()
  )

  static_survival_metric_summarizer(
    name,
    fn,
    data,
    truth,
```

```

    estimate,
    ...,
    na_rm = TRUE,
    case_weights = NULL,
    fn_options = list(),
    error_call = caller_env()
  )

curve_survival_metric_summarizer(
  name,
  fn,
  data,
  truth,
  ...,
  na_rm = TRUE,
  case_weights = NULL,
  fn_options = list(),
  error_call = caller_env()
)

```

### Arguments

name	A single character representing the name of the metric to use in the tibble output. This will be modified to include the type of averaging if appropriate.
fn	The vector version of your custom metric function. It generally takes truth, estimate, na_rm, and any other extra arguments needed to calculate the metric.
data	The data frame with truth and estimate columns passed in from the data frame version of your metric function that called <code>numeric_metric_summarizer()</code> , <code>class_metric_summarizer()</code> , <code>prob_metric_summarizer()</code> , <code>curve_metric_summarizer()</code> , <code>dynamic_survival_metric_summarizer()</code> , or <code>static_survival_metric_summarizer()</code> .
truth	The unquoted column name corresponding to the truth column.
estimate	Generally, the unquoted column name corresponding to the estimate column. For metrics that take multiple columns through ... like class probability metrics, this is a result of <code>dots_to_estimate()</code> .
...	These dots are for future extensions and must be empty.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds. The removal is executed in <code>yardstick_remove_missing()</code> .
case_weights	For metrics supporting case weights, an unquoted column name corresponding to case weights can be passed here. If not NULL, the case weights will be passed on to fn as the named argument <code>case_weights</code> .
fn_options	A named list of metric specific options. These are spliced into the metric function call using <code>!!!</code> from <code>rlang</code> . The default results in nothing being spliced into the call.
error_call	The execution environment of a currently running function, e.g. <code>caller_env()</code> . The function will be mentioned in error messages as the source of the error. See the call argument of <code>abort()</code> for more information.

estimator	This can either be NULL for the default auto-selection of averaging ("binary" or "macro"), or a single character to pass along to the metric implementation describing the kind of averaging to use.
event_level	This can either be NULL to use the default event_level value of the fn or a single string of either "first" or "second" to pass along describing which level should be considered the "event".

### Details

numeric\_metric\_summarizer(), class\_metric\_summarizer(), prob\_metric\_summarizer(), curve\_metric\_summarizer(), dynamic\_survival\_metric\_summarizer(), and dynamic\_survival\_metric\_summarize are generally called from the data frame version of your metric function. It knows how to call your metric over grouped data frames and returns a tibble consistent with other metrics.

### See Also

[check\\_metric](#) [yardstick\\_remove\\_missing](#) [finalize\\_estimator\(\)](#) [dots\\_to\\_estimate\(\)](#)

---

metrics

*General Function to Estimate Performance*

---

### Description

This function estimates one or more common performance estimates depending on the class of truth (see **Value** below) and returns them in a three column tibble.

### Usage

```
metrics(data, ...)
```

```
## S3 method for class 'data.frame'
metrics(data, truth, estimate, ..., na_rm = TRUE, options = list())
```

### Arguments

data	A data.frame containing the columns specified by truth, estimate, and ....
...	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of event_level. Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
truth	The column identifier for the true results (that is numeric or factor). This should be an unquoted column name although this argument is passed by expression and support <a href="#">quasiquotation</a> (you can unquote column names).
estimate	The column identifier for the predicted results (that is also numeric or factor). As with truth this can be specified different ways but the primary method is to use an unquoted variable name.

<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>options</code>	[deprecated] No longer supported as of yardstick 1.0.0. If you pass something here it will be ignored with a warning. Previously, these were options passed on to <code>pROC::roc()</code> . If you need support for this, use the <code>pROC</code> package directly.

### Value

A three column tibble.

- When `truth` is a factor, there are rows for `accuracy()` and the Kappa statistic (`kap()`).
- When `truth` has two levels and 1 column of class probabilities is passed to `...`, there are rows for the two class versions of `mn_log_loss()` and `roc_auc()`.
- When `truth` has more than two levels and a full set of class probabilities are passed to `...`, there are rows for the multiclass version of `mn_log_loss()` and the Hand Till generalization of `roc_auc()`.
- When `truth` is numeric, there are rows for `rmse()`, `rsq()`, and `mae()`.

### See Also

`metric_set()`

### Examples

```
# Accuracy and kappa
metrics(two_class_example, truth, predicted)

# Add on multinomial log loss and ROC AUC by specifying class prob columns
metrics(two_class_example, truth, predicted, Class1)

# Regression metrics
metrics(solubility_test, truth = solubility, estimate = prediction)

# Multiclass metrics work, but you cannot specify any averaging
# for roc_auc() besides the default, hand_till. Use the specific function
# if you need more customization
library(dplyr)

hpc_cv %>%
  group_by(Resample) %>%
  metrics(obs, pred, VF:L) %>%
  print(n = 40)
```

---

 metric\_set

*Combine metric functions*


---

### Description

metric\_set() allows you to combine multiple metric functions together into a new function that calculates all of them at once.

### Usage

```
metric_set(...)
```

### Arguments

...                    The bare names of the functions to be included in the metric set.

### Details

All functions must be either:

- Only numeric metrics
- A mix of class metrics or class prob metrics
- A mix of dynamic, integrated, and static survival metrics

For instance, rmse() can be used with mae() because they are numeric metrics, but not with accuracy() because it is a classification metric. But accuracy() can be used with roc\_auc().

The returned metric function will have a different argument list depending on whether numeric metrics or a mix of class/prob metrics were passed in.

```
# Numeric metric set signature:
```

```
fn(
  data,
  truth,
  estimate,
  na_rm = TRUE,
  case_weights = NULL,
  ...
)
```

```
# Class / prob metric set signature:
```

```
fn(
  data,
  truth,
  ...,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
```

```

    event_level = yardstick_event_level(),
    case_weights = NULL
  )

# Dynamic / integrated / static survival metric set signature:
fn(
  data,
  truth,
  ...,
  estimate,
  na_rm = TRUE,
  case_weights = NULL
)

```

When mixing class and class prob metrics, pass in the hard predictions (the factor column) as the named argument `estimate`, and the soft predictions (the class probability columns) as bare column names or `tidyselect` selectors to `...`

When mixing dynamic, integrated, and static survival metrics, pass in the time predictions as the named argument `estimate`, and the survival predictions as bare column names or `tidyselect` selectors to `...`

If `metric_tweak()` has been used to "tweak" one of these arguments, like `estimator` or `event_level`, then the tweaked version wins. This allows you to set the estimator on a metric by metric basis and still use it in a `metric_set()`.

### See Also

[metrics\(\)](#)

### Examples

```

library(dplyr)

# Multiple regression metrics
multi_metric <- metric_set(rmse, rsq, ccc)

# The returned function has arguments:
# fn(data, truth, estimate, na_rm = TRUE, ...)
multi_metric(solubility_test, truth = solubility, estimate = prediction)

# Groups are respected on the new metric function
class_metrics <- metric_set(accuracy, kap)

hpc_cv %>%
  group_by(Resample) %>%
  class_metrics(obs, estimate = pred)

# -----

# If you need to set options for certain metrics,
# do so by wrapping the metric and setting the options inside the wrapper,

```

```

# passing along truth and estimate as quoted arguments.
# Then add on the function class of the underlying wrapped function,
# and the direction of optimization.
ccc_with_bias <- function(data, truth, estimate, na_rm = TRUE, ...) {
  ccc(
    data = data,
    truth = !!rlang::enquo(truth),
    estimate = !!rlang::enquo(estimate),
    # set bias = TRUE
    bias = TRUE,
    na_rm = na_rm,
    ...
  )
}

# Use `new_numeric_metric()` to formalize this new metric function
ccc_with_bias <- new_numeric_metric(ccc_with_bias, "maximize")

multi_metric2 <- metric_set(rmse, rsq, ccc_with_bias)

multi_metric2(solubility_test, truth = solubility, estimate = prediction)

# -----
# A class probability example:

# Note that, when given class or class prob functions,
# metric_set() returns a function with signature:
# fn(data, truth, ..., estimate)
# to be able to mix class and class prob metrics.

# You must provide the `estimate` column by explicitly naming
# the argument

class_and_probs_metrics <- metric_set(roc_auc, pr_auc, accuracy)

hpc_cv %>%
  group_by(Resample) %>%
  class_and_probs_metrics(obs, VF:L, estimate = pred)

```

---

metric\_tweak

*Tweak a metric function*


---

## Description

`metric_tweak()` allows you to tweak an existing metric `.fn`, giving it a new `.name` and setting new optional argument defaults through `...`. It is similar to `purrr::partial()`, but is designed specifically for yardstick metrics.

`metric_tweak()` is especially useful when constructing a `metric_set()` for tuning with the `tune` package. After the metric set has been constructed, there is no way to adjust the value of any

optional arguments (such as `beta` in `f_meas()`). Using `metric_tweak()`, you can set optional arguments to custom values ahead of time, before they go into the metric set.

## Usage

```
metric_tweak(.name, .fn, ...)
```

## Arguments

<code>.name</code>	A single string giving the name of the new metric. This will be used in the <code>".metric"</code> column of the output.
<code>.fn</code>	An existing yardstick metric function to tweak.
<code>...</code>	Name-value pairs specifying which optional arguments to override and the values to replace them with.  Arguments <code>data</code> , <code>truth</code> , and <code>estimate</code> are considered <i>protected</i> , and cannot be overridden, but all other optional arguments can be altered.

## Details

The function returned from `metric_tweak()` only takes `...` as arguments, which are passed through to the original `.fn`. Passing `data`, `truth`, and `estimate` through by position should generally be safe, but it is recommended to pass any other optional arguments through by name to ensure that they are evaluated correctly.

## Value

A tweaked version of `.fn`, updated to use new defaults supplied in `...`

## Examples

```
mase12 <- metric_tweak("mase12", mase, m = 12)

# Defaults to `m = 1`
mase(solubility_test, solubility, prediction)

# Updated to use `m = 12`. `mase12()` has this set already.
mase(solubility_test, solubility, prediction, m = 12)
mase12(solubility_test, solubility, prediction)

# This is most useful to set optional argument values ahead of time when
# using a metric set
mase10 <- metric_tweak("mase10", mase, m = 10)
metrics <- metric_set(mase, mase10, mase12)
metrics(solubility_test, solubility, prediction)
```

mn\_log\_loss

*Mean log loss for multinomial data***Description**

Compute the logarithmic loss of a classification model.

**Usage**

```
mn_log_loss(data, ...)

## S3 method for class 'data.frame'
mn_log_loss(
  data,
  truth,
  ...,
  na_rm = TRUE,
  sum = FALSE,
  event_level = yardstick_event_level(),
  case_weights = NULL
)

mn_log_loss_vec(
  truth,
  estimate,
  na_rm = TRUE,
  sum = FALSE,
  event_level = yardstick_event_level(),
  case_weights = NULL,
  ...
)
```

**Arguments**

data	A <code>data.frame</code> containing the columns specified by <code>truth</code> and <code>...</code>
...	A set of unquoted column names or one or more <code>dplyr</code> selector functions to choose which variables contain the class probabilities. If <code>truth</code> is binary, only 1 column should be selected, and it should correspond to the value of <code>event_level</code> . Otherwise, there should be as many columns as factor levels of <code>truth</code> and the ordering of the columns should be the same as the factor levels of <code>truth</code> .
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.

sum	A logical. Should the sum of the likelihood contributions be returned (instead of the mean value)?
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.
estimate	If truth is binary, a numeric vector of class probabilities corresponding to the "relevant" class. Otherwise, a matrix with as many columns as factor levels of truth. <i>It is assumed that these are in the same order as the levels of truth.</i>

### Details

Log loss is a measure of the performance of a classification model. A perfect model has a log loss of 0.

Compared with `accuracy()`, log loss takes into account the uncertainty in the prediction and gives a more detailed view into the actual performance. For example, given two input probabilities of .6 and .9 where both are classified as predicting a positive value, say, "Yes", the accuracy metric would interpret them as having the same value. If the true output is "Yes", log loss penalizes .6 because it is "less sure" of it's result compared to the probability of .9.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `mn_log_loss_vec()`, a single numeric value (or NA).

### Multiclass

Log loss has a known multiclass extension, and is simply the sum of the log loss values for each class prediction. Because of this, no averaging types are supported.

### Author(s)

Max Kuhn

### See Also

Other class probability metrics: `average_precision()`, `brier_class()`, `classification_cost()`, `gain_capture()`, `pr_auc()`, `roc_auc()`, `roc_aunp()`, `roc_aunu()`

**Examples**

```

# Two class
data("two_class_example")
mn_log_loss(two_class_example, truth, Class1)

# Multiclass
library(dplyr)
data(hpc_cv)

# You can use the col1:colN tidyselect syntax
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  mn_log_loss(obs, VF:L)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  mn_log_loss(obs, VF:L)

# Vector version
# Supply a matrix of class probabilities
fold1 <- hpc_cv %>%
  filter(Resample == "Fold01")

mn_log_loss_vec(
  truth = fold1$obs,
  matrix(
    c(fold1$VF, fold1$F, fold1$M, fold1$L),
    ncol = 4
  )
)

# Supply `...` with quasiquotation
prob_cols <- levels(two_class_example$truth)
mn_log_loss(two_class_example, truth, Class1)
mn_log_loss(two_class_example, truth, !!prob_cols[1])

```

---

mpe

*Mean percentage error*


---

**Description**

Calculate the mean percentage error. This metric is in *relative units*. It can be used as a measure of the estimate's bias.

Note that if *any* truth values are 0, a value of: -Inf (estimate > 0), Inf (estimate < 0), or NaN (estimate == 0) is returned for mpe().

**Usage**

```
mpe(data, ...)

## S3 method for class 'data.frame'
mpe(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

mpe_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

**Arguments**

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is <code>numeric</code> ). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also <code>numeric</code> ). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `mpe_vec()`, a single numeric value (or NA).

**Author(s)**

Thomas Bierhance

**See Also**

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other accuracy metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [smape\(\)](#)

**Examples**

```

# `solubility_test$solubility` has zero values with corresponding
# `$prediction` values that are negative. By definition, this causes `Inf`
# to be returned from `mpe()`.
solubility_test[solubility_test$solubility == 0, ]

mpe(solubility_test, solubility, prediction)

# We'll remove the zero values for demonstration
solubility_test <- solubility_test[solubility_test$solubility != 0, ]

# Supply truth and predictions as bare column names
mpe(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  mpe(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))

```

---

msd

*Mean signed deviation*


---

**Description**

Mean signed deviation (also known as mean signed difference, or mean signed error) computes the average differences between truth and estimate. A related metric is the mean absolute error ([mae\(\)](#)).

**Usage**

```
msd(data, ...)

## S3 method for class 'data.frame'
msd(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

msd_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

**Arguments**

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

**Details**

Mean signed deviation is rarely used, since positive and negative errors cancel each other out. For example, `msd_vec(c(100, -100), c(0, 0))` would return a seemingly "perfect" value of 0, even though `estimate` is wildly different from `truth`. `mae()` attempts to remedy this by taking the absolute value of the differences before computing the mean.

This metric is computed as `mean(truth - estimate)`, following the convention that an "error" is computed as observed - predicted. If you expected this metric to be computed as `mean(estimate - truth)`, reverse the sign of the result.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `msd_vec()`, a single numeric value (or NA).

**Author(s)**

Thomas Bierhance

**See Also**

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other accuracy metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [smape\(\)](#)

**Examples**

```
# Supply truth and predictions as bare column names
msd(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  msd(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
```

---

new-metric

*Construct a new metric function*


---

**Description**

These functions provide convenient wrappers to create the three types of metric functions in yardstick: numeric metrics, class metrics, and class probability metrics. They add a metric-specific class to fn and attach a direction attribute. These features are used by [metric\\_set\(\)](#) and by [tune](#) when model tuning.

See [Custom performance metrics](#) for more information about creating custom metrics.

**Usage**

```

new_class_metric(fn, direction)

new_prob_metric(fn, direction)

new_numeric_metric(fn, direction)

new_dynamic_survival_metric(fn, direction)

new_integrated_survival_metric(fn, direction)

new_static_survival_metric(fn, direction)

```

**Arguments**

fn	A function. The metric function to attach a metric-specific class and direction attribute to.
direction	A string. One of: <ul style="list-style-type: none"> <li>• "maximize"</li> <li>• "minimize"</li> <li>• "zero"</li> </ul>

---

npv	<i>Negative predictive value</i>
-----	----------------------------------

---

**Description**

These functions calculate the `npv()` (negative predictive value) of a measurement system compared to a reference result (the "truth" or gold standard). Highly related functions are `spec()`, `sens()`, and `ppv()`.

**Usage**

```

npv(data, ...)

## S3 method for class 'data.frame'
npv(
  data,
  truth,
  estimate,
  prevalence = NULL,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

```

```

)

npv_vec(
  truth,
  estimate,
  prevalence = NULL,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

```

### Arguments

<code>data</code>	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
<code>estimate</code>	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
<code>prevalence</code>	A numeric value for the rate of the "positive" class of the data.
<code>estimator</code>	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on <code>estimate</code> .
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
<code>event_level</code>	A single string. Either "first" or "second" to specify which level of <code>truth</code> to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

### Details

The positive predictive value ([ppv\(\)](#)) is defined as the percent of predicted positives that are actually positive while the negative predictive value ([npv\(\)](#)) is defined as the percent of negative positives that are actually negative.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `npv_vec()`, a single numeric value (or NA).

**Relevant Level**

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

**Multiclass**

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

**Implementation**

Suppose a 2x2 table with notation:

	Reference	
Predicted	Positive	Negative
Positive	A	B
Negative	C	D

The formulas used here are:

$$Sensitivity = A / (A + C)$$

$$Specificity = D / (B + D)$$

$$Prevalence = (A + C) / (A + B + C + D)$$

$$PPV = (Sensitivity * Prevalence) / ((Sensitivity * Prevalence) + ((1 - Specificity) * (1 - Prevalence)))$$

$$NPV = (Specificity * (1 - Prevalence)) / (((1 - Sensitivity) * Prevalence) + (Specificity * (1 - Prevalence)))$$

See the references for discussions of the statistics.

**Author(s)**

Max Kuhn

## References

Altman, D.G., Bland, J.M. (1994) "Diagnostic tests 2: predictive values," *British Medical Journal*, vol 309, 102.

## See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

Other sensitivity metrics: [ppv\(\)](#), [sens\(\)](#), [spec\(\)](#)

## Examples

```
# Two class
data("two_class_example")
npv(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  npv(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  npv(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  npv(obs, pred, estimator = "macro_weighted")

# Vector version
npv_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
npv_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)
```

---

pathology	<i>Liver Pathology Data</i>
-----------	-----------------------------

---

**Description**

Liver Pathology Data

**Details**

These data have the results of a *x*-ray examination to determine whether liver is abnormal or not (in the *scan* column) versus the more extensive pathology results that approximate the truth (in *pathology*).

**Value**

*pathology* a data frame

**Source**

Altman, D.G., Bland, J.M. (1994) "Diagnostic tests 1: sensitivity and specificity," *British Medical Journal*, vol 308, 1552.

**Examples**

```
data(pathology)
str(pathology)
```

---

<i>poisson_log_loss</i>	<i>Mean log loss for Poisson data</i>
-------------------------	---------------------------------------

---

**Description**

Calculate the loss function for the Poisson distribution.

**Usage**

```
poisson_log_loss(data, ...)

## S3 method for class 'data.frame'
poisson_log_loss(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

poisson_log_loss_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

**Arguments**

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true counts (that is <code>integer</code> ). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, an <code>integer</code> vector.
<code>estimate</code>	The column identifier for the predicted results (that is also <code>numeric</code> ). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a <code>numeric</code> vector.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a <code>numeric</code> vector.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `poisson_log_loss_vec()`, a single numeric value (or NA).

**Author(s)**

Max Kuhn

**See Also**

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other accuracy metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [rmse\(\)](#), [smape\(\)](#)

**Examples**

```
count_truth <- c(2L, 7L, 1L, 1L, 0L, 3L)
count_pred  <- c(2.14, 5.35, 1.65, 1.56, 1.3, 2.71)
count_results <- dplyr::tibble(count = count_truth, pred = count_pred)

# Supply truth and predictions as bare column names
poisson_log_loss(count_results, count, pred)
```

---

ppv *Positive predictive value*

---

### Description

These functions calculate the `ppv()` (positive predictive value) of a measurement system compared to a reference result (the "truth" or gold standard). Highly related functions are `spec()`, `sens()`, and `npv()`.

### Usage

```
ppv(data, ...)
```

```
## S3 method for class 'data.frame'
ppv(
  data,
  truth,
  estimate,
  prevalence = NULL,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)
```

```
ppv_vec(
  truth,
  estimate,
  prevalence = NULL,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)
```

### Arguments

<code>data</code>	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.

estimate	The column identifier for the predicted class results (that is also factor). As with truth this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
prevalence	A numeric value for the rate of the "positive" class of the data.
estimator	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on estimate.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

### Details

The positive predictive value (`ppv()`) is defined as the percent of predicted positives that are actually positive while the negative predictive value (`npv()`) is defined as the percent of negative positives that are actually negative.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `ppv_vec()`, a single numeric value (or NA).

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Multiclass

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

## Implementation

Suppose a 2x2 table with notation:

	Reference	
Predicted	Positive	Negative
Positive	A	B
Negative	C	D

The formulas used here are:

$$\text{Sensitivity} = A / (A + C)$$

$$\text{Specificity} = D / (B + D)$$

$$\text{Prevalence} = (A + C) / (A + B + C + D)$$

$$\text{PPV} = (\text{Sensitivity} * \text{Prevalence}) / ((\text{Sensitivity} * \text{Prevalence}) + ((1 - \text{Specificity}) * (1 - \text{Prevalence})))$$

$$\text{NPV} = (\text{Specificity} * (1 - \text{Prevalence})) / (((1 - \text{Sensitivity}) * \text{Prevalence}) + (\text{Specificity} * (1 - \text{Prevalence})))$$

See the references for discussions of the statistics.

## Author(s)

Max Kuhn

## References

Altman, D.G., Bland, J.M. (1994) "Diagnostic tests 2: predictive values," *British Medical Journal*, vol 309, 102.

## See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

Other sensitivity metrics: [npv\(\)](#), [sens\(\)](#), [spec\(\)](#)

## Examples

```
# Two class
data("two_class_example")
ppv(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  ppv(obs, pred)
```

```

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  ppv(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  ppv(obs, pred, estimator = "macro_weighted")

# Vector version
ppv_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
ppv_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)

# But what if we think that Class 1 only occurs 40% of the time?
ppv(two_class_example, truth, predicted, prevalence = 0.40)

```

---

```
precision
```

```
Precision
```

---

## Description

These functions calculate the `precision()` of a measurement system for finding relevant documents compared to reference results (the truth regarding relevance). Highly related functions are `recall()` and `f_meas()`.

## Usage

```

precision(data, ...)

## S3 method for class 'data.frame'
precision(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),

```

```

    ...
  )

precision_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

```

### Arguments

data	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
...	Not currently used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimate	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
estimator	One of: <code>"binary"</code> , <code>"macro"</code> , <code>"macro_weighted"</code> , or <code>"micro"</code> to specify the type of averaging to be done. <code>"binary"</code> is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose <code>"binary"</code> or <code>"macro"</code> based on <code>estimate</code> .
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
event_level	A single string. Either <code>"first"</code> or <code>"second"</code> to specify which level of <code>truth</code> to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to <code>"first"</code> , however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

### Details

The precision is the percentage of predicted truly relevant results of the total number of predicted relevant results and characterizes the "purity in retrieval performance" (Buckland and Gey, 1994).

When the denominator of the calculation is 0, precision is undefined. This happens when both `# true_positive = 0` and `# false_positive = 0` are true, which mean that there were no predicted events. When computing binary precision, a NA value will be returned with a warning. When computing multiclass precision, the individual NA values will be removed, and the computation will proceed, with a warning.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `precision_vec()`, a single numeric value (or NA).

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Multiclass

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

### Implementation

Suppose a 2x2 table with notation:

	Reference	
Predicted	Relevant	Irrelevant
Relevant	A	B
Irrelevant	C	D

The formulas used here are:

$$recall = A / (A + C)$$

$$precision = A / (A + B)$$

$$F_{meas} = (1 + \beta^2) * precision * recall / ((\beta^2 * precision) + recall)$$

See the references for discussions of the statistics.

### Author(s)

Max Kuhn

## References

Buckland, M., & Gey, F. (1994). The relationship between Recall and Precision. *Journal of the American Society for Information Science*, 45(1), 12-19.

Powers, D. (2007). Evaluation: From Precision, Recall and F Factor to ROC, Informedness, Markedness and Correlation. Technical Report SIE-07-001, Flinders University

## See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [recall\(\)](#), [sens\(\)](#), [spec\(\)](#)

Other relevance metrics: [f\\_meas\(\)](#), [recall\(\)](#)

## Examples

```
# Two class
data("two_class_example")
precision(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  precision(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  precision(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  precision(obs, pred, estimator = "macro_weighted")

# Vector version
precision_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
precision_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)
```

pr\_auc

*Area under the precision recall curve***Description**

pr\_auc() is a metric that computes the area under the precision recall curve. See [pr\\_curve\(\)](#) for the full curve.

**Usage**

```
pr_auc(data, ...)

## S3 method for class 'data.frame'
pr_auc(
  data,
  truth,
  ...,
  estimator = NULL,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL
)

pr_auc_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL,
  ...
)
```

**Arguments**

data	A data.frame containing the columns specified by truth and ...
...	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of event_level. Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For _vec() functions, a factor vector.

estimator	One of "binary", "macro", or "macro_weighted" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other two are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on truth.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.
estimate	If truth is binary, a numeric vector of class probabilities corresponding to the "relevant" class. Otherwise, a matrix with as many columns as factor levels of truth. <i>It is assumed that these are in the same order as the levels of truth.</i>

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `pr_auc_vec()`, a single numeric value (or NA).

### Multiclass

Macro and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Author(s)

Max Kuhn

### See Also

[pr\\_curve\(\)](#) for computing the full precision recall curve.

Other class probability metrics: [average\\_precision\(\)](#), [brier\\_class\(\)](#), [classification\\_cost\(\)](#), [gain\\_capture\(\)](#), [mn\\_log\\_loss\(\)](#), [roc\\_auc\(\)](#), [roc\\_aunp\(\)](#), [roc\\_aunu\(\)](#)

## Examples

```

# -----
# Two class example

# `truth` is a 2 level factor. The first level is `"Class1"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(two_class_example)

# Binary metrics using class probabilities take a factor `truth` column,
# and a single class probability column containing the probabilities of
# the event of interest. Here, since `"Class1"` is the first level of
# `"truth"`, it is the event of interest and we pass in probabilities for it.
pr_auc(two_class_example, truth, Class1)

# -----
# Multiclass example

# `obs` is a 4 level factor. The first level is `"VF"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(hpc_cv)

# You can use the col1:colN tidyselect syntax
library(dplyr)
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  pr_auc(obs, VF:L)

# Change the first level of `obs` from `"VF"` to `"M"` to alter the
# event of interest. The class probability columns should be supplied
# in the same order as the levels.
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  mutate(obs = relevel(obs, "M")) %>%
  pr_auc(obs, M, VF:L)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  pr_auc(obs, VF:L)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  pr_auc(obs, VF:L, estimator = "macro_weighted")

# Vector version
# Supply a matrix of class probabilities
fold1 <- hpc_cv %>%
  filter(Resample == "Fold01")

```

```

pr_auc_vec(
  truth = fold1$obs,
  matrix(
    c(fold1$VF, fold1$F, fold1$M, fold1$L),
    ncol = 4
  )
)

```

---

pr\_curve

*Precision recall curve*


---

### Description

pr\_curve() constructs the full precision recall curve and returns a tibble. See [pr\\_auc\(\)](#) for the area under the precision recall curve.

### Usage

```

pr_curve(data, ...)

## S3 method for class 'data.frame'
pr_curve(
  data,
  truth,
  ...,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL
)

```

### Arguments

data	A data.frame containing the columns specified by truth and ....
...	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of event_level. Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For _vec() functions, a factor vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.

event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option yardstick.event_first is set, that will be used instead with a warning.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For _vec() functions, a numeric vector.

### Details

pr\_curve() computes the precision at every unique value of the probability column (in addition to infinity).

There is a `ggplot2::autoplot()` method for quickly visualizing the curve. This works for binary and multiclass output, and also works with grouped data (i.e. from resamples). See the examples.

### Value

A tibble with class pr\_df or pr\_grouped\_df having columns .threshold, recall, and precision.

### Multiclass

If a multiclass truth column is provided, a one-vs-all approach will be taken to calculate multiple curves, one per level. In this case, there will be an additional column, .level, identifying the "one" column in the one-vs-all calculation.

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In yardstick, the default is to use the *first* level. To alter this, change the argument event\_level to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Author(s)

Max Kuhn

### See Also

Compute the area under the precision recall curve with `pr_auc()`.

Other curve metrics: `gain_curve()`, `lift_curve()`, `roc_curve()`

### Examples

```
# -----
# Two class example
```

```

# `truth` is a 2 level factor. The first level is `"Class1"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(two_class_example)

# Binary metrics using class probabilities take a factor `truth` column,
# and a single class probability column containing the probabilities of
# the event of interest. Here, since `"Class1"` is the first level of
# `"truth"`, it is the event of interest and we pass in probabilities for it.
pr_curve(two_class_example, truth, Class1)

# -----
# `autoplot()`

# Visualize the curve using ggplot2 manually
library(ggplot2)
library(dplyr)
pr_curve(two_class_example, truth, Class1) %>%
  ggplot(aes(x = recall, y = precision)) +
  geom_path() +
  coord_equal() +
  theme_bw()

# Or use autoplot
autoplot(pr_curve(two_class_example, truth, Class1))

# Multiclass one-vs-all approach
# One curve per level
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  pr_curve(obs, VF:L) %>%
  autoplot()

# Same as above, but will all of the resamples
hpc_cv %>%
  group_by(Resample) %>%
  pr_curve(obs, VF:L) %>%
  autoplot()

```

---

recall

*Recall*


---

### Description

These functions calculate the `recall()` of a measurement system for finding relevant documents compared to reference results (the truth regarding relevance). Highly related functions are `precision()` and `f_meas()`.

**Usage**

```
recall(data, ...)

## S3 method for class 'data.frame'
recall(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

recall_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)
```

**Arguments**

<code>data</code>	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
<code>estimate</code>	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
<code>estimator</code>	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on estimate.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

`event_level` A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when `estimator = "binary"`. The default uses an internal helper that generally defaults to "first", however, if the deprecated global option `yardstick.event_first` is set, that will be used instead with a warning.

### Details

The recall (aka sensitivity) is defined as the proportion of relevant results out of the number of samples which were actually relevant. When there are no relevant results, recall is not defined and a value of NA is returned.

When the denominator of the calculation is 0, recall is undefined. This happens when both `# true_positive = 0` and `# false_negative = 0` are true, which mean that there were no true events. When computing binary recall, a NA value will be returned with a warning. When computing multiclass recall, the individual NA values will be removed, and the computation will proceed, with a warning.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `recall_vec()`, a single numeric value (or NA).

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Multiclass

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

### Implementation

Suppose a 2x2 table with notation:

	Reference	
Predicted	Relevant	Irrelevant
Relevant	A	B
Irrelevant	C	D

The formulas used here are:

$$recall = A/(A + C)$$

$$precision = A/(A + B)$$

$$F_{meas} = (1 + \beta^2) * precision * recall / ((\beta^2 * precision) + recall)$$

See the references for discussions of the statistics.

### Author(s)

Max Kuhn

### References

Buckland, M., & Gey, F. (1994). The relationship between Recall and Precision. *Journal of the American Society for Information Science*, 45(1), 12-19.

Powers, D. (2007). Evaluation: From Precision, Recall and F Factor to ROC, Informedness, Markedness and Correlation. Technical Report SIE-07-001, Flinders University

### See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [sens\(\)](#), [spec\(\)](#)

Other relevance metrics: [f\\_meas\(\)](#), [precision\(\)](#)

### Examples

```
# Two class
data("two_class_example")
recall(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  recall(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  recall(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  recall(obs, pred, estimator = "macro_weighted")

# Vector version
recall_vec(
```

```

    two_class_example$truth,
    two_class_example$predicted
  )

# Making Class2 the "relevant" level
recall_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)

```

---

rmse	<i>Root mean squared error</i>
------	--------------------------------

---

## Description

Calculate the root mean squared error. `rmse()` is a metric that is in the same units as the original data.

## Usage

```

rmse(data, ...)

## S3 method for class 'data.frame'
rmse(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

rmse_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

```

## Arguments

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `rmse_vec()`, a single numeric value (or NA).

**Author(s)**

Max Kuhn

**See Also**

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other accuracy metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [smape\(\)](#)

**Examples**

```
# Supply truth and predictions as bare column names
rmse(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  rmse(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
```

---

roc_auc	<i>Area under the receiver operator curve</i>
---------	---

---

### Description

roc\_auc() is a metric that computes the area under the ROC curve. See [roc\\_curve\(\)](#) for the full curve.

### Usage

```
roc_auc(data, ...)

## S3 method for class 'data.frame'
roc_auc(
  data,
  truth,
  ...,
  estimator = NULL,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL,
  options = list()
)

roc_auc_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL,
  options = list(),
  ...
)
```

### Arguments

data	A data.frame containing the columns specified by truth and ...
...	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of event_level. Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For _vec() functions, a factor vector.

estimator	One of "binary", "hand_till", "macro", or "macro_weighted" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The others are general methods for calculating multiclass metrics. The default will automatically choose "binary" if truth is binary, "hand_till" if truth has >2 levels and case_weights isn't specified, or "macro" if truth has >2 levels and case_weights is specified (in which case "hand_till" isn't well-defined).
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option yardstick.event_first is set, that will be used instead with a warning.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For _vec() functions, a numeric vector.
options	[deprecated] No longer supported as of yardstick 1.0.0. If you pass something here it will be ignored with a warning. Previously, these were options passed on to pROC::roc(). If you need support for this, use the pROC package directly.
estimate	If truth is binary, a numeric vector of class probabilities corresponding to the "relevant" class. Otherwise, a matrix with as many columns as factor levels of truth. <i>It is assumed that these are in the same order as the levels of truth.</i>

### Details

Generally, an ROC AUC value is between 0.5 and 1, with 1 being a perfect prediction model. If your value is between 0 and 0.5, then this implies that you have meaningful information in your model, but it is being applied incorrectly because doing the opposite of what the model predicts would result in an AUC >0.5.

Note that you can't combine estimator = "hand\_till" with case\_weights.

### Value

A tibble with columns .metric, .estimator, and .estimate and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For roc\_auc\_vec(), a single numeric value (or NA).

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In yardstick, the default is to use the *first* level. To alter this, change the argument event\_level to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

## Multiclass

The default multiclass method for computing `roc_auc()` is to use the method from Hand, Till, (2001). Unlike macro-averaging, this method is insensitive to class distributions like the binary ROC AUC case. Additionally, while other multiclass techniques will return NA if any levels in truth occur zero times in the actual data, the Hand-Till method will simply ignore those levels in the averaging calculation, with a warning.

Macro and macro-weighted averaging are still provided, even though they are not the default. In fact, macro-weighted averaging corresponds to the same definition of multiclass AUC given by Provost and Domingos (2001).

## Author(s)

Max Kuhn

## References

Hand, Till (2001). "A Simple Generalisation of the Area Under the ROC Curve for Multiple Class Classification Problems". *Machine Learning*. Vol 45, Iss 2, pp 171-186.

Fawcett (2005). "An introduction to ROC analysis". *Pattern Recognition Letters*. 27 (2006), pp 861-874.

Provost, F., Domingos, P., 2001. "Well-trained PETs: Improving probability estimation trees", CeDER Working Paper #IS-00-04, Stern School of Business, New York University, NY, NY 10012.

## See Also

[roc\\_curve\(\)](#) for computing the full ROC curve.

Other class probability metrics: [average\\_precision\(\)](#), [brier\\_class\(\)](#), [classification\\_cost\(\)](#), [gain\\_capture\(\)](#), [mn\\_log\\_loss\(\)](#), [pr\\_auc\(\)](#), [roc\\_aunp\(\)](#), [roc\\_aunu\(\)](#)

## Examples

```
# -----
# Two class example

# `truth` is a 2 level factor. The first level is `"Class1"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(two_class_example)

# Binary metrics using class probabilities take a factor `truth` column,
# and a single class probability column containing the probabilities of
# the event of interest. Here, since `"Class1"` is the first level of
# ``truth``, it is the event of interest and we pass in probabilities for it.
roc_auc(two_class_example, truth, Class1)

# -----
# Multiclass example

# `obs` is a 4 level factor. The first level is `"VF"`, which is the
```

```

# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(hpc_cv)

# You can use the col1:colN tidymethod syntax
library(dplyr)
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  roc_auc(obs, VF:L)

# Change the first level of `obs` from `VF` to `M` to alter the
# event of interest. The class probability columns should be supplied
# in the same order as the levels.
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  mutate(obs = relevel(obs, "M")) %>%
  roc_auc(obs, M, VF:L)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  roc_auc(obs, VF:L)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  roc_auc(obs, VF:L, estimator = "macro_weighted")

# Vector version
# Supply a matrix of class probabilities
fold1 <- hpc_cv %>%
  filter(Resample == "Fold01")

roc_auc_vec(
  truth = fold1$obs,
  matrix(
    c(fold1$VF, fold1$F, fold1$M, fold1$L),
    ncol = 4
  )
)

```

---

roc\_aunp

*Area under the ROC curve of each class against the rest, using the a priori class distribution*

---

### Description

roc\_aunp() is a multiclass metric that computes the area under the ROC curve of each class against the rest, using the a priori class distribution. This is equivalent to roc\_auc(estimator = "macro\_weighted").

**Usage**

```
roc_aunp(data, ...)

## S3 method for class 'data.frame'
roc_aunp(data, truth, ..., na_rm = TRUE, case_weights = NULL, options = list())

roc_aunp_vec(
  truth,
  estimate,
  na_rm = TRUE,
  case_weights = NULL,
  options = list(),
  ...
)
```

**Arguments**

data	A <code>data.frame</code> containing the columns specified by <code>truth</code> and <code>...</code>
...	A set of unquoted column names or one or more <code>dplyr</code> selector functions to choose which variables contain the class probabilities. There should be as many columns as factor levels of <code>truth</code> .
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
options	[deprecated] No longer supported as of <code>yardstick</code> 1.0.0. If you pass something here it will be ignored with a warning. Previously, these were options passed on to <code>pROC::roc()</code> . If you need support for this, use the <code>pROC</code> package directly.
estimate	A matrix with as many columns as factor levels of <code>truth</code> . <i>It is assumed that these are in the same order as the levels of truth.</i>

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `roc_aunp_vec()`, a single numeric value (or NA).

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Multiclass

This multiclass method for computing the area under the ROC curve uses the a priori class distribution and is equivalent to `roc_auc(estimator = "macro_weighted")`.

### Author(s)

Julia Silge

### References

Ferri, C., Hernández-Orallo, J., & Modroi, R. (2009). "An experimental comparison of performance measures for classification". *Pattern Recognition Letters*. 30 (1), pp 27-38.

### See Also

`roc_aunu()` for computing the area under the ROC curve of each class against the rest, using the uniform class distribution.

Other class probability metrics: `average_precision()`, `brier_class()`, `classification_cost()`, `gain_capture()`, `mn_log_loss()`, `pr_auc()`, `roc_auc()`, `roc_aunu()`

### Examples

```
# Multiclass example

# `obs` is a 4 level factor. The first level is `VF`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(hpc_cv)

# You can use the col1:colN tidyselect syntax
library(dplyr)
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  roc_aunp(obs, VF:L)

# Change the first level of `obs` from `VF` to `M` to alter the
# event of interest. The class probability columns should be supplied
# in the same order as the levels.
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  mutate(obs = relevel(obs, "M")) %>%
```

```

roc_aunp(obs, M, VF:L)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  roc_aunp(obs, VF:L)

# Vector version
# Supply a matrix of class probabilities
fold1 <- hpc_cv %>%
  filter(Resample == "Fold01")

roc_aunp_vec(
  truth = fold1$obs,
  matrix(
    c(fold1$VF, fold1$F, fold1$M, fold1$L),
    ncol = 4
  )
)

```

---

roc\_aunu

*Area under the ROC curve of each class against the rest, using the uniform class distribution*

---

## Description

roc\_aunu() is a multiclass metric that computes the area under the ROC curve of each class against the rest, using the uniform class distribution. This is equivalent to roc\_auc(estimator = "macro").

## Usage

```

roc_aunu(data, ...)

## S3 method for class 'data.frame'
roc_aunu(data, truth, ..., na_rm = TRUE, case_weights = NULL, options = list())

roc_aunu_vec(
  truth,
  estimate,
  na_rm = TRUE,
  case_weights = NULL,
  options = list(),
  ...
)

```

**Arguments**

data	A <code>data.frame</code> containing the columns specified by <code>truth</code> and . . .
. . .	A set of unquoted column names or one or more <code>dplyr</code> selector functions to choose which variables contain the class probabilities. There should be as many columns as factor levels of <code>truth</code> .
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
options	[deprecated] No longer supported as of <code>yardstick</code> 1.0.0. If you pass something here it will be ignored with a warning. Previously, these were options passed on to <code>pROC::roc()</code> . If you need support for this, use the <code>pROC</code> package directly.
estimate	A matrix with as many columns as factor levels of <code>truth</code> . <i>It is assumed that these are in the same order as the levels of truth.</i>

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `roc_aunu_vec()`, a single numeric value (or NA).

**Relevant Level**

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

**Multiclass**

This multiclass method for computing the area under the ROC curve uses the uniform class distribution and is equivalent to `roc_auc(estimator = "macro")`.

**Author(s)**

Julia Silge

## References

Ferri, C., Hernández-Orallo, J., & Modroui, R. (2009). "An experimental comparison of performance measures for classification". *Pattern Recognition Letters*. 30 (1), pp 27-38.

## See Also

[roc\\_aunp\(\)](#) for computing the area under the ROC curve of each class against the rest, using the a priori class distribution.

Other class probability metrics: [average\\_precision\(\)](#), [brier\\_class\(\)](#), [classification\\_cost\(\)](#), [gain\\_capture\(\)](#), [mn\\_log\\_loss\(\)](#), [pr\\_auc\(\)](#), [roc\\_auc\(\)](#), [roc\\_aunp\(\)](#)

## Examples

```
# Multiclass example

# `obs` is a 4 level factor. The first level is `VF`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
data(hpc_cv)

# You can use the col1:colN tidyselect syntax
library(dplyr)
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  roc_aunu(obs, VF:L)

# Change the first level of `obs` from `VF` to `M` to alter the
# event of interest. The class probability columns should be supplied
# in the same order as the levels.
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  mutate(obs = relevel(obs, "M")) %>%
  roc_aunu(obs, M, VF:L)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  roc_aunu(obs, VF:L)

# Vector version
# Supply a matrix of class probabilities
fold1 <- hpc_cv %>%
  filter(Resample == "Fold01")

roc_aunu_vec(
  truth = fold1$obs,
  matrix(
    c(fold1$VF, fold1$F, fold1$M, fold1$L),
    ncol = 4
  )
)
```

roc\_curve

*Receiver operator curve***Description**

roc\_curve() constructs the full ROC curve and returns a tibble. See [roc\\_auc\(\)](#) for the area under the ROC curve.

**Usage**

```
roc_curve(data, ...)

## S3 method for class 'data.frame'
roc_curve(
  data,
  truth,
  ...,
  na_rm = TRUE,
  event_level = yardstick_event_level(),
  case_weights = NULL,
  options = list()
)
```

**Arguments**

data	A data.frame containing the columns specified by truth and ...
...	A set of unquoted column names or one or more dplyr selector functions to choose which variables contain the class probabilities. If truth is binary, only 1 column should be selected, and it should correspond to the value of event_level. Otherwise, there should be as many columns as factor levels of truth and the ordering of the columns should be the same as the factor levels of truth.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For _vec() functions, a factor vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option yardstick.event_first is set, that will be used instead with a warning.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For _vec() functions, a numeric vector.

options [deprecated]  
 No longer supported as of yardstick 1.0.0. If you pass something here it will be ignored with a warning.  
 Previously, these were options passed on to `pROC::roc()`. If you need support for this, use the `pROC` package directly.

### Details

`roc_curve()` computes the sensitivity at every unique value of the probability column (in addition to infinity and minus infinity).

There is a `ggplot2::autoplot()` method for quickly visualizing the curve. This works for binary and multiclass output, and also works with grouped data (i.e. from resamples). See the examples.

### Value

A tibble with class `roc_df` or `roc_grouped_df` having columns `.threshold`, `specificity`, and `sensitivity`.

### Multiclass

If a multiclass truth column is provided, a one-vs-all approach will be taken to calculate multiple curves, one per level. In this case, there will be an additional column, `.level`, identifying the "one" column in the one-vs-all calculation.

### Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

### Author(s)

Max Kuhn

### See Also

Compute the area under the ROC curve with `roc_auc()`.

Other curve metrics: `gain_curve()`, `lift_curve()`, `pr_curve()`

### Examples

```
# -----
# Two class example

# `truth` is a 2 level factor. The first level is `Class1`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section above.
```

```

data(two_class_example)

# Binary metrics using class probabilities take a factor `truth` column,
# and a single class probability column containing the probabilities of
# the event of interest. Here, since `"Class1"` is the first level of
# `"truth"`, it is the event of interest and we pass in probabilities for it.
roc_curve(two_class_example, truth, Class1)

# -----
# `autoplot()`

# Visualize the curve using ggplot2 manually
library(ggplot2)
library(dplyr)
roc_curve(two_class_example, truth, Class1) %>%
  ggplot(aes(x = 1 - specificity, y = sensitivity)) +
  geom_path() +
  geom_abline(lty = 3) +
  coord_equal() +
  theme_bw()

# Or use autoplot
autoplot(roc_curve(two_class_example, truth, Class1))

## Not run:

# Multiclass one-vs-all approach
# One curve per level
hpc_cv %>%
  filter(Resample == "Fold01") %>%
  roc_curve(obs, VF:L) %>%
  autoplot()

# Same as above, but will all of the resamples
hpc_cv %>%
  group_by(Resample) %>%
  roc_curve(obs, VF:L) %>%
  autoplot()

## End(Not run)

```

---

rpd

*Ratio of performance to deviation*


---

### Description

These functions are appropriate for cases where the model outcome is a numeric. The ratio of performance to deviation (`rpd()`) and the ratio of performance to inter-quartile (`rpiq()`) are both measures of consistency/correlation between observed and predicted values (and not of accuracy).

**Usage**

```
rpd(data, ...)

## S3 method for class 'data.frame'
rpd(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

rpd_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

**Arguments**

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquoteation</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

**Details**

In the field of spectroscopy in particular, the ratio of performance to deviation (RPD) has been used as the standard way to report the quality of a model. It is the ratio between the standard deviation of a variable and the standard error of prediction of that variable by a given model. However, its systematic use has been criticized by several authors, since using the standard deviation to represent the spread of a variable can be misleading on skewed dataset. The ratio of performance to inter-quartile has been introduced by Bellon-Maurel et al. (2010) to address some of these issues, and generalise the RPD to non-normally distributed variables.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `rpd_vec()`, a single numeric value (or NA).

**Author(s)**

Pierre Roudier

## References

Williams, P.C. (1987) Variables affecting near-infrared reflectance spectroscopic analysis. In: Near Infrared Technology in the Agriculture and Food Industries. 1st Ed. P.Williams and K.Norris, Eds. Am. Cereal Assoc. Cereal Chem., St. Paul, MN.

Bellon-Maurel, V., Fernandez-Ahumada, E., Palagos, B., Roger, J.M. and McBratney, A., (2010). Critical review of chemometric indicators commonly used for assessing the quality of the prediction of soil attributes by NIR spectroscopy. TrAC Trends in Analytical Chemistry, 29(9), pp.1073-1081.

## See Also

The closely related inter-quartile metric: [rpiq\(\)](#)

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other consistency metrics: [ccc\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#)

## Examples

```
# Supply truth and predictions as bare column names
rpd(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  rpd(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
```

---

rpiq	<i>Ratio of performance to inter-quartile</i>
------	---

---

### Description

These functions are appropriate for cases where the model outcome is a numeric. The ratio of performance to deviation (`rpd()`) and the ratio of performance to inter-quartile (`rpiq()`) are both measures of consistency/correlation between observed and predicted values (and not of accuracy).

### Usage

```
rpiq(data, ...)

## S3 method for class 'data.frame'
rpiq(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

rpiq_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

### Arguments

data	A data.frame containing the columns specified by the truth and estimate arguments.
...	Not currently used.
truth	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquoteotation</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
estimate	The column identifier for the predicted results (that is also numeric). As with truth this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.

### Details

In the field of spectroscopy in particular, the ratio of performance to deviation (RPD) has been used as the standard way to report the quality of a model. It is the ratio between the standard deviation of a variable and the standard error of prediction of that variable by a given model. However, its systematic use has been criticized by several authors, since using the standard deviation to represent the spread of a variable can be misleading on skewed dataset. The ratio of performance to inter-quartile has been introduced by Bellon-Maurel et al. (2010) to address some of these issues, and generalise the RPD to non-normally distributed variables.

**Value**

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `rpd_vec()`, a single numeric value (or NA).

**Author(s)**

Pierre Roudier

**References**

Williams, P.C. (1987) Variables affecting near-infrared reflectance spectroscopic analysis. In: Near Infrared Technology in the Agriculture and Food Industries. 1st Ed. P.Williams and K.Norris, Eds. Am. Cereal Assoc. Cereal Chem., St. Paul, MN.

Bellon-Maurel, V., Fernandez-Ahumada, E., Palagos, B., Roger, J.M. and McBratney, A., (2010). Critical review of chemometric indicators commonly used for assessing the quality of the prediction of soil attributes by NIR spectroscopy. *TrAC Trends in Analytical Chemistry*, 29(9), pp.1073-1081.

**See Also**

The closely related deviation metric: [rpd\(\)](#)

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#), [smape\(\)](#)

Other consistency metrics: [ccc\(\)](#), [rpd\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#)

**Examples**

```
# Supply truth and predictions as bare column names
rpd(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
```

```

    rpd(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))

```

---

rsq	<i>R squared</i>
-----	------------------

---

### Description

Calculate the coefficient of determination using correlation. For the traditional measure of R squared, see [rsq\\_trad\(\)](#).

### Usage

```

rsq(data, ...)

## S3 method for class 'data.frame'
rsq(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

rsq_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

```

### Arguments

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

## Details

The two estimates for the coefficient of determination, `rsq()` and `rsq_trad()`, differ by their formula. The former guarantees a value on (0, 1) while the latter can generate inaccurate values when the model is non-informative (see the examples). Both are measures of consistency/correlation and not of accuracy.

`rsq()` is simply the squared correlation between truth and estimate.

Because `rsq()` internally computes a correlation, if either truth or estimate are constant it can result in a divide by zero error. In these cases, a warning is thrown and NA is returned. This can occur when a model predicts a single value for all samples. For example, a regularized model that eliminates all predictors except for the intercept would do this. Another example would be a CART model that contains no splits.

## Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `rsq_vec()`, a single numeric value (or NA).

## Author(s)

Max Kuhn

## References

Kvalseth. Cautionary note about  $R^2$ . American Statistician (1985) vol. 39 (4) pp. 279-285.

## See Also

Other numeric metrics: `ccc()`, `huber_loss_pseudo()`, `huber_loss()`, `iic()`, `mae()`, `mape()`, `mase()`, `mpe()`, `msd()`, `poisson_log_loss()`, `rmse()`, `rpd()`, `rpiq()`, `rsq_trad()`, `smape()`

Other consistency metrics: `ccc()`, `rpd()`, `rpiq()`, `rsq_trad()`

## Examples

```
# Supply truth and predictions as bare column names
rsq(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
```

```

    ),
    .id = "resample"
  )

  # Compute the metric by group
  metric_results <- solubility_resampled %>%
    group_by(resample) %>%
    rsq(solubility, prediction)

  metric_results

  # Resampled mean estimate
  metric_results %>%
    summarise(avg_estimate = mean(.estimate))
  # With uninformative data, the traditional version of R^2 can return
  # negative values.
  set.seed(2291)
  solubility_test$randomized <- sample(solubility_test$prediction)
  rsq(solubility_test, solubility, randomized)
  rsq_trad(solubility_test, solubility, randomized)

  # A constant `truth` or `estimate` vector results in a warning from
  # a divide by zero error in the correlation calculation.
  # `NA` will be returned in these cases.
  truth <- c(1, 2)
  estimate <- c(1, 1)
  rsq_vec(truth, estimate)

```

---

 rsq\_trad

*R squared - traditional*


---

### Description

Calculate the coefficient of determination using the traditional definition of R squared using sum of squares. For a measure of R squared that is strictly between (0, 1), see [rsq\(\)](#).

### Usage

```

rsq_trad(data, ...)

## S3 method for class 'data.frame'
rsq_trad(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

rsq_trad_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

```

### Arguments

**data** A data.frame containing the columns specified by the truth and estimate arguments.

...	Not currently used.
truth	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
estimate	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.

### Details

The two estimates for the coefficient of determination, `rsq()` and `rsq_trad()`, differ by their formula. The former guarantees a value on (0, 1) while the latter can generate inaccurate values when the model is non-informative (see the examples). Both are measures of consistency/correlation and not of accuracy.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `rsq_trad_vec()`, a single numeric value (or NA).

### Author(s)

Max Kuhn

### References

Kvalseth. Cautionary note about  $R^2$ . *American Statistician* (1985) vol. 39 (4) pp. 279-285.

### See Also

Other numeric metrics: `ccc()`, `huber_loss_pseudo()`, `huber_loss()`, `iic()`, `mae()`, `mape()`, `mase()`, `mpe()`, `msd()`, `poisson_log_loss()`, `rmse()`, `rpd()`, `rpiq()`, `rsq()`, `smape()`

Other consistency metrics: `ccc()`, `rpd()`, `rpiq()`, `rsq()`

### Examples

```
# Supply truth and predictions as bare column names
rsq_trad(solubility_test, solubility, prediction)

library(dplyr)
```

```

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  rsq_trad(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
# With uninformative data, the traditional version of R^2 can return
# negative values.
set.seed(2291)
solubility_test$randomized <- sample(solubility_test$prediction)
rsq(solubility_test, solubility, randomized)
rsq_trad(solubility_test, solubility, randomized)

```

---

sens

*Sensitivity*


---

### Description

These functions calculate the `sens()` (sensitivity) of a measurement system compared to a reference result (the "truth" or gold standard). Highly related functions are `spec()`, `ppv()`, and `npv()`.

### Usage

```

sens(data, ...)

## S3 method for class 'data.frame'
sens(
  data,
  truth,
  estimate,

```

```

    estimator = NULL,
    na_rm = TRUE,
    case_weights = NULL,
    event_level = yardstick_event_level(),
    ...
  )

sens_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

sensitivity(data, ...)

## S3 method for class 'data.frame'
sensitivity(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

sensitivity_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

```

### Arguments

<code>data</code>	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true class results (that is a factor). This should be

	an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
<code>estimate</code>	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
<code>estimator</code>	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on <code>estimate</code> .
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in data. For <code>_vec()</code> functions, a numeric vector.
<code>event_level</code>	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

## Details

The sensitivity (`sens()`) is defined as the proportion of positive results out of the number of samples which were actually positive.

When the denominator of the calculation is 0, sensitivity is undefined. This happens when both `# true_positive = 0` and `# false_negative = 0` are true, which mean that there were no true events. When computing binary sensitivity, a NA value will be returned with a warning. When computing multiclass sensitivity, the individual NA values will be removed, and the computation will proceed, with a warning.

## Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `sens_vec()`, a single numeric value (or NA).

## Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

## Multiclass

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See vignette("multiclass", "yardstick") for more information.

## Implementation

Suppose a 2x2 table with notation:

	Reference	
Predicted	Positive	Negative
Positive	A	B
Negative	C	D

The formulas used here are:

$$\text{Sensitivity} = A / (A + C)$$

$$\text{Specificity} = D / (B + D)$$

$$\text{Prevalence} = (A + C) / (A + B + C + D)$$

$$\text{PPV} = (\text{Sensitivity} * \text{Prevalence}) / ((\text{Sensitivity} * \text{Prevalence}) + ((1 - \text{Specificity}) * (1 - \text{Prevalence})))$$

$$\text{NPV} = (\text{Specificity} * (1 - \text{Prevalence})) / (((1 - \text{Sensitivity}) * \text{Prevalence}) + ((\text{Specificity}) * (1 - \text{Prevalence})))$$

See the references for discussions of the statistics.

## Author(s)

Max Kuhn

## References

Altman, D.G., Bland, J.M. (1994) "Diagnostic tests 1: sensitivity and specificity," *British Medical Journal*, vol 308, 1552.

## See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [spec\(\)](#)

Other sensitivity metrics: [npv\(\)](#), [ppv\(\)](#), [spec\(\)](#)

**Examples**

```

# Two class
data("two_class_example")
sens(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  sens(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  sens(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  sens(obs, pred, estimator = "macro_weighted")

# Vector version
sens_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
sens_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
)

```

---

smape

*Symmetric mean absolute percentage error*


---

**Description**

Calculate the symmetric mean absolute percentage error. This metric is in *relative units*.

**Usage**

```

smape(data, ...)

## S3 method for class 'data.frame'
smape(data, truth, estimate, na_rm = TRUE, case_weights = NULL, ...)

```

```
smape_vec(truth, estimate, na_rm = TRUE, case_weights = NULL, ...)
```

### Arguments

<code>data</code>	A <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments.
<code>...</code>	Not currently used.
<code>truth</code>	The column identifier for the true results (that is numeric). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquote</a> (you can unquote column names). For <code>_vec()</code> functions, a numeric vector.
<code>estimate</code>	The column identifier for the predicted results (that is also numeric). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a numeric vector.
<code>na_rm</code>	A logical value indicating whether NA values should be stripped before the computation proceeds.
<code>case_weights</code>	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.

### Details

This implementation of `smape()` is the "usual definition" where the denominator is divided by two.

### Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `smape_vec()`, a single numeric value (or NA).

### Author(s)

Max Kuhn, Riaz Hedayati

### See Also

Other numeric metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#), [rpd\(\)](#), [rpiq\(\)](#), [rsq\\_trad\(\)](#), [rsq\(\)](#)

Other accuracy metrics: [ccc\(\)](#), [huber\\_loss\\_pseudo\(\)](#), [huber\\_loss\(\)](#), [iic\(\)](#), [mae\(\)](#), [mape\(\)](#), [mase\(\)](#), [mpe\(\)](#), [msd\(\)](#), [poisson\\_log\\_loss\(\)](#), [rmse\(\)](#)

**Examples**

```
# Supply truth and predictions as bare column names
smape(solubility_test, solubility, prediction)

library(dplyr)

set.seed(1234)
size <- 100
times <- 10

# create 10 resamples
solubility_resampled <- bind_rows(
  replicate(
    n = times,
    expr = sample_n(solubility_test, size, replace = TRUE),
    simplify = FALSE
  ),
  .id = "resample"
)

# Compute the metric by group
metric_results <- solubility_resampled %>%
  group_by(resample) %>%
  smape(solubility, prediction)

metric_results

# Resampled mean estimate
metric_results %>%
  summarise(avg_estimate = mean(.estimate))
```

---

solubility\_test

*Solubility Predictions from MARS Model*

---

**Description**

Solubility Predictions from MARS Model

**Details**

For the solubility data in Kuhn and Johnson (2013), these data are the test set results for the MARS model. The observed solubility (in column solubility) and the model results (prediction) are contained in the data.

**Value**

solubility\_test  
a data frame

**Source**

Kuhn, M., Johnson, K. (2013) *Applied Predictive Modeling*, Springer

**Examples**

```
data(solubility_test)
str(solubility_test)
```

---

spec	<i>Specificity</i>
------	--------------------

---

**Description**

These functions calculate the `spec()` (specificity) of a measurement system compared to a reference result (the "truth" or gold standard). Highly related functions are `sens()`, `ppv()`, and `npv()`.

**Usage**

```
spec(data, ...)

## S3 method for class 'data.frame'
spec(
  data,
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

spec_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

specificity(data, ...)

## S3 method for class 'data.frame'
specificity(
  data,
```

```

    truth,
    estimate,
    estimator = NULL,
    na_rm = TRUE,
    case_weights = NULL,
    event_level = yardstick_event_level(),
    ...
  )

specificity_vec(
  truth,
  estimate,
  estimator = NULL,
  na_rm = TRUE,
  case_weights = NULL,
  event_level = yardstick_event_level(),
  ...
)

```

### Arguments

data	Either a <code>data.frame</code> containing the columns specified by the <code>truth</code> and <code>estimate</code> arguments, or a <code>table/matrix</code> where the true class results should be in the columns of the table.
...	Not currently used.
truth	The column identifier for the true class results (that is a factor). This should be an unquoted column name although this argument is passed by expression and supports <a href="#">quasiquotation</a> (you can unquote column names). For <code>_vec()</code> functions, a factor vector.
estimate	The column identifier for the predicted class results (that is also factor). As with <code>truth</code> this can be specified different ways but the primary method is to use an unquoted variable name. For <code>_vec()</code> functions, a factor vector.
estimator	One of: <code>"binary"</code> , <code>"macro"</code> , <code>"macro_weighted"</code> , or <code>"micro"</code> to specify the type of averaging to be done. <code>"binary"</code> is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose <code>"binary"</code> or <code>"macro"</code> based on <code>estimate</code> .
na_rm	A logical value indicating whether NA values should be stripped before the computation proceeds.
case_weights	The optional column identifier for case weights. This should be an unquoted column name that evaluates to a numeric column in <code>data</code> . For <code>_vec()</code> functions, a numeric vector.
event_level	A single string. Either <code>"first"</code> or <code>"second"</code> to specify which level of truth to consider as the "event". This argument is only applicable when <code>estimator = "binary"</code> . The default uses an internal helper that generally defaults to <code>"first"</code> , however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.

## Details

The specificity measures the proportion of negatives that are correctly identified as negatives.

When the denominator of the calculation is 0, specificity is undefined. This happens when both `# true_negative = 0` and `# false_positive = 0` are true, which mean that there were no true negatives. When computing binary specificity, a NA value will be returned with a warning. When computing multiclass specificity, the individual NA values will be removed, and the computation will proceed, with a warning.

## Value

A tibble with columns `.metric`, `.estimator`, and `.estimate` and 1 row of values.

For grouped data frames, the number of rows returned will be the same as the number of groups.

For `spec_vec()`, a single numeric value (or NA).

## Relevant Level

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

## Multiclass

Macro, micro, and macro-weighted averaging is available for this metric. The default is to select macro averaging if a truth factor with more than 2 levels is provided. Otherwise, a standard binary calculation is done. See `vignette("multiclass", "yardstick")` for more information.

## Implementation

Suppose a 2x2 table with notation:

	Reference	
Predicted	Positive	Negative
Positive	A	B
Negative	C	D

The formulas used here are:

$$Sensitivity = A / (A + C)$$

$$Specificity = D / (B + D)$$

$$Prevalence = (A + C) / (A + B + C + D)$$

$$PPV = (Sensitivity * Prevalence) / ((Sensitivity * Prevalence) + ((1 - Specificity) * (1 - Prevalence)))$$

$$NPV = (Specificity * (1 - Prevalence)) / (((1 - Sensitivity) * Prevalence) + (Specificity * (1 - Prevalence)))$$

See the references for discussions of the statistics.

### Author(s)

Max Kuhn

### References

Altman, D.G., Bland, J.M. (1994) "Diagnostic tests 1: sensitivity and specificity," *British Medical Journal*, vol 308, 1552.

### See Also

Other class metrics: [accuracy\(\)](#), [bal\\_accuracy\(\)](#), [detection\\_prevalence\(\)](#), [f\\_meas\(\)](#), [j\\_index\(\)](#), [kap\(\)](#), [mcc\(\)](#), [npv\(\)](#), [ppv\(\)](#), [precision\(\)](#), [recall\(\)](#), [sens\(\)](#)

Other sensitivity metrics: [npv\(\)](#), [ppv\(\)](#), [sens\(\)](#)

### Examples

```
# Two class
data("two_class_example")
spec(two_class_example, truth, predicted)

# Multiclass
library(dplyr)
data(hpc_cv)

hpc_cv %>%
  filter(Resample == "Fold01") %>%
  spec(obs, pred)

# Groups are respected
hpc_cv %>%
  group_by(Resample) %>%
  spec(obs, pred)

# Weighted macro averaging
hpc_cv %>%
  group_by(Resample) %>%
  spec(obs, pred, estimator = "macro_weighted")

# Vector version
spec_vec(
  two_class_example$truth,
  two_class_example$predicted
)

# Making Class2 the "relevant" level
spec_vec(
  two_class_example$truth,
  two_class_example$predicted,
  event_level = "second"
```

)

summary.conf\_mat

*Summary Statistics for Confusion Matrices***Description**

Various statistical summaries of confusion matrices are produced and returned in a tibble. These include those shown in the help pages for [sens\(\)](#), [recall\(\)](#), and [accuracy\(\)](#), among others.

**Usage**

```
## S3 method for class 'conf_mat'
summary(
  object,
  prevalence = NULL,
  beta = 1,
  estimator = NULL,
  event_level = yardstick_event_level(),
  ...
)
```

**Arguments**

object	An object of class <a href="#">conf_mat()</a> .
prevalence	A number in (0, 1) for the prevalence (i.e. prior) of the event. If left to the default, the data are used to derive this value.
beta	A numeric value used to weight precision and recall for <a href="#">f_meas()</a> .
estimator	One of: "binary", "macro", "macro_weighted", or "micro" to specify the type of averaging to be done. "binary" is only relevant for the two class case. The other three are general methods for calculating multiclass metrics. The default will automatically choose "binary" or "macro" based on estimate.
event_level	A single string. Either "first" or "second" to specify which level of truth to consider as the "event". This argument is only applicable when estimator = "binary". The default uses an internal helper that generally defaults to "first", however, if the deprecated global option <code>yardstick.event_first</code> is set, that will be used instead with a warning.
...	Not currently used.

**Value**

A tibble containing various classification metrics.

**Relevant Level**

There is no common convention on which factor level should automatically be considered the "event" or "positive" result when computing binary classification metrics. In `yardstick`, the default is to use the *first* level. To alter this, change the argument `event_level` to "second" to consider the *last* level of the factor the level of interest. For multiclass extensions involving one-vs-all comparisons (such as macro averaging), this option is ignored and the "one" level is always the relevant result.

**See Also**

[conf\\_mat\(\)](#)

**Examples**

```
data("two_class_example")

cmat <- conf_mat(two_class_example, truth = "truth", estimate = "predicted")
summary(cmat)
summary(cmat, prevalence = 0.70)

library(dplyr)
library(tidyr)
data("hpc_cv")

# Compute statistics per resample then summarize
all_metrics <- hpc_cv %>%
  group_by(Resample) %>%
  conf_mat(obs, pred) %>%
  mutate(summary_tbl = lapply(conf_mat, summary)) %>%
  unnest(summary_tbl)

all_metrics %>%
  group_by(.metric) %>%
  summarise(
    mean = mean(.estimate, na.rm = TRUE),
    sd = sd(.estimate, na.rm = TRUE)
  )
```

---

two\_class\_example      *Two Class Predictions*

---

**Description**

Two Class Predictions

**Details**

These data are a test set form a model built for two classes ("Class1" and "Class2"). There are columns for the true and predicted classes and column for the probabilities for each class.

**Value**

```
two_class_example
      a data frame
```

**Examples**

```
data(two_class_example)
str(two_class_example)

# `truth` is a 2 level factor. The first level is `"Class1"`, which is the
# "event of interest" by default in yardstick. See the Relevant Level
# section in any classification function (such as `?pr_auc`) to see how
# to change this.
levels(hpc_cv$obs)
```

---

```
yardstick_remove_missing
```

*Developer function for handling missing values in new metrics*

---

**Description**

yardstick\_remove\_missing(), and yardstick\_any\_missing() are useful alongside the [metric-summarizers](#) functions for implementing new custom metrics. yardstick\_remove\_missing() removes any observations that contains missing values across, truth, estimate and case\_weights. yardstick\_any\_missing() returns FALSE if there is any missing values in the inputs.

**Usage**

```
yardstick_remove_missing(truth, estimate, case_weights)
```

```
yardstick_any_missing(truth, estimate, case_weights)
```

**Arguments**

```
truth, estimate
```

Vectors of the same length.

```
case_weights
```

A vector of the same length as truth and estimate, or NULL if case weights are not being used.

**See Also**

[metric-summarizers](#)

# Index

- \* **accuracy metrics**
  - ccc, [12](#)
  - huber\_loss, [38](#)
  - huber\_loss\_pseudo, [40](#)
  - iic, [42](#)
  - mae, [53](#)
  - mape, [55](#)
  - mase, [56](#)
  - mpe, [72](#)
  - msd, [74](#)
  - poisson\_log\_loss, [81](#)
  - rmse, [99](#)
  - smape, [125](#)
- \* **class metrics**
  - accuracy, [3](#)
  - bal\_accuracy, [8](#)
  - detection\_prevalence, [22](#)
  - f\_meas, [27](#)
  - j\_index, [44](#)
  - kap, [47](#)
  - mcc, [59](#)
  - npv, [77](#)
  - ppv, [83](#)
  - precision, [86](#)
  - recall, [95](#)
  - sens, [121](#)
  - spec, [128](#)
- \* **class probability metrics**
  - average\_precision, [4](#)
  - brier\_class, [10](#)
  - classification\_cost, [16](#)
  - gain\_capture, [30](#)
  - mn\_log\_loss, [70](#)
  - pr\_auc, [90](#)
  - roc\_auc, [101](#)
  - roc\_aunp, [104](#)
  - roc\_aunu, [107](#)
- \* **consistency metrics**
  - ccc, [12](#)
  - rpd, [112](#)
  - rpiq, [115](#)
  - rsq, [117](#)
  - rsq\_trad, [119](#)
- \* **curve metrics**
  - gain\_curve, [34](#)
  - lift\_curve, [49](#)
  - pr\_curve, [93](#)
  - roc\_curve, [110](#)
- \* **datasets**
  - hpc\_cv, [37](#)
  - lung\_surv, [52](#)
  - pathology, [81](#)
  - solubility\_test, [127](#)
  - two\_class\_example, [133](#)
- \* **numeric metrics**
  - ccc, [12](#)
  - huber\_loss, [38](#)
  - huber\_loss\_pseudo, [40](#)
  - iic, [42](#)
  - mae, [53](#)
  - mape, [55](#)
  - mase, [56](#)
  - mpe, [72](#)
  - msd, [74](#)
  - poisson\_log\_loss, [81](#)
  - rmse, [99](#)
  - rpd, [112](#)
  - rpiq, [115](#)
  - rsq, [117](#)
  - rsq\_trad, [119](#)
  - smape, [125](#)
- \* **relevance metrics**
  - f\_meas, [27](#)
  - precision, [86](#)
  - recall, [95](#)
- \* **sensitivity metrics**
  - npv, [77](#)
  - ppv, [83](#)

- sens, 121
- spec, 128
- abort(), 16, 25, 63
- accuracy, 3, 10, 23, 29, 46, 49, 60, 80, 85, 89, 98, 124, 131
- accuracy(), 47, 65, 71, 132
- accuracy\_vec (accuracy), 3
- average\_precision, 4, 12, 18, 32, 71, 91, 103, 106, 109
- average\_precision\_vec (average\_precision), 4
- bal\_accuracy, 4, 8, 23, 29, 46, 49, 60, 80, 85, 89, 98, 124, 131
- bal\_accuracy\_vec (bal\_accuracy), 8
- base::table(), 20
- brier\_class, 7, 10, 18, 32, 71, 91, 103, 106, 109
- brier\_class\_vec (brier\_class), 10
- ccc, 12, 39, 41, 43, 54, 56, 58, 73, 76, 82, 100, 114, 116, 118, 120, 126
- ccc(), 13
- ccc\_vec (ccc), 12
- check\_class\_metric (check\_metric), 15
- check\_dynamic\_survival\_metric (check\_metric), 15
- check\_metric, 15, 24, 26, 61, 64
- check\_numeric\_metric (check\_metric), 15
- check\_prob\_metric (check\_metric), 15
- check\_static\_survival\_metric (check\_metric), 15
- class\_metric\_summarizer (metric-summarizers), 61
- classification\_cost, 7, 12, 16, 32, 71, 91, 103, 106, 109
- classification\_cost\_vec (classification\_cost), 16
- conf\_mat, 19
- conf\_mat(), 20, 132, 133
- curve\_metric\_summarizer (metric-summarizers), 61
- curve\_survival\_metric\_summarizer (metric-summarizers), 61
- detection\_prevalence, 4, 10, 22, 29, 46, 49, 60, 80, 85, 89, 98, 124, 131
- detection\_prevalence\_vec (detection\_prevalence), 22
- developer-helpers, 24
- dots\_to\_estimate (developer-helpers), 24
- dots\_to\_estimate(), 63, 64
- dynamic\_survival\_metric\_summarizer (metric-summarizers), 61
- f\_meas, 4, 10, 23, 27, 46, 49, 60, 80, 85, 89, 98, 124, 131
- f\_meas(), 27, 69, 86, 95, 132
- f\_meas\_vec (f\_meas), 27
- finalize\_estimator (developer-helpers), 24
- finalize\_estimator(), 64
- finalize\_estimator\_internal (developer-helpers), 24
- gain\_capture, 7, 12, 18, 30, 71, 91, 103, 106, 109
- gain\_capture(), 34, 36
- gain\_capture\_vec (gain\_capture), 30
- gain\_curve, 34, 52, 94, 111
- gain\_curve(), 32, 49
- get\_weights (developer-helpers), 24
- ggplot2::autoplot(), 20, 35, 50, 94, 111
- hpc\_cv, 37
- huber\_loss, 14, 38, 41, 43, 54, 56, 58, 73, 76, 82, 100, 114, 116, 118, 120, 126
- huber\_loss(), 40
- huber\_loss\_pseudo, 14, 39, 40, 43, 54, 56, 58, 73, 76, 82, 100, 114, 116, 118, 120, 126
- huber\_loss\_pseudo\_vec (huber\_loss\_pseudo), 40
- huber\_loss\_vec (huber\_loss), 38
- iic, 14, 39, 41, 42, 54, 56, 58, 73, 76, 82, 100, 114, 116, 118, 120, 126
- iic\_vec (iic), 42
- j\_index, 4, 10, 23, 29, 44, 49, 60, 80, 85, 89, 98, 124, 131
- j\_index\_vec (j\_index), 44
- kap, 4, 10, 23, 29, 46, 47, 60, 80, 85, 89, 98, 124, 131
- kap(), 65
- kap\_vec (kap), 47
- lift\_curve, 36, 49, 94, 111

- lift\_curve(), 34
- lung, 53
- lung\_surv, 52
- mae, 14, 39, 41, 43, 53, 56, 58, 73, 76, 82, 100, 114, 116, 118, 120, 126
- mae(), 65, 74, 75
- mae\_vec (mae), 53
- mape, 14, 39, 41, 43, 54, 55, 58, 73, 76, 82, 100, 114, 116, 118, 120, 126
- mape\_vec (mape), 55
- mase, 14, 39, 41, 43, 54, 56, 56, 73, 76, 82, 100, 114, 116, 118, 120, 126
- mase\_vec (mase), 56
- mcc, 4, 10, 23, 29, 46, 49, 59, 80, 85, 89, 98, 124, 131
- mcc\_vec (mcc), 59
- metric summarizers, 24
- metric-summarizers, 15, 16, 26, 61, 134
- metric\_set, 66
- metric\_set(), 65, 68, 76
- metric\_tweak, 68
- metrics, 64
- metrics(), 67
- mn\_log\_loss, 7, 12, 18, 32, 70, 91, 103, 106, 109
- mn\_log\_loss(), 65
- mn\_log\_loss\_vec (mn\_log\_loss), 70
- mpe, 14, 39, 41, 43, 54, 56, 58, 72, 76, 82, 100, 114, 116, 118, 120, 126
- mpe\_vec (mpe), 72
- msd, 14, 39, 41, 43, 54, 56, 58, 73, 74, 82, 100, 114, 116, 118, 120, 126
- msd\_vec (msd), 74
- new-metric, 76
- new\_class\_metric (new-metric), 76
- new\_dynamic\_survival\_metric (new-metric), 76
- new\_integrated\_survival\_metric (new-metric), 76
- new\_numeric\_metric (new-metric), 76
- new\_prob\_metric (new-metric), 76
- new\_static\_survival\_metric (new-metric), 76
- npv, 4, 10, 23, 29, 46, 49, 60, 77, 85, 89, 98, 124, 131
- npv(), 77, 78, 83, 84, 121, 128
- npv\_vec (npv), 77
- numeric\_metric\_summarizer (metric-summarizers), 61
- pathology, 81
- poisson\_log\_loss, 14, 39, 41, 43, 54, 56, 58, 73, 76, 81, 100, 114, 116, 118, 120, 126
- poisson\_log\_loss\_vec (poisson\_log\_loss), 81
- ppv, 4, 10, 23, 29, 46, 49, 60, 80, 83, 89, 98, 124, 131
- ppv(), 77, 78, 83, 84, 121, 128
- ppv\_vec (ppv), 83
- pr\_auc, 7, 12, 18, 32, 71, 90, 103, 106, 109
- pr\_auc(), 7, 93, 94
- pr\_auc\_vec (pr\_auc), 90
- pr\_curve, 36, 52, 93, 111
- pr\_curve(), 4, 6, 7, 90, 91
- precision, 4, 10, 23, 29, 46, 49, 60, 80, 85, 86, 98, 124, 131
- precision(), 27, 86, 95
- precision\_vec (precision), 86
- prob\_metric\_summarizer (metric-summarizers), 61
- quasiquoteation, 3, 5, 9, 11, 13, 17, 20, 22, 27, 31, 34, 38, 41, 43, 45, 48, 50, 53, 55, 57, 59, 64, 70, 73, 75, 78, 82, 83, 87, 90, 93, 96, 99, 101, 105, 108, 110, 113, 115, 117, 120, 123, 126, 129
- recall, 4, 10, 23, 29, 46, 49, 60, 80, 85, 89, 95, 124, 131
- recall(), 27, 86, 95, 132
- recall\_vec (recall), 95
- rmse, 14, 39, 41, 43, 54, 56, 58, 73, 76, 82, 99, 114, 116, 118, 120, 126
- rmse(), 13, 38, 40, 65
- rmse\_vec (rmse), 99
- roc\_auc, 7, 12, 18, 32, 71, 91, 101, 106, 109
- roc\_auc(), 65, 110, 111
- roc\_auc\_vec (roc\_auc), 101
- roc\_aunp, 7, 12, 18, 32, 71, 91, 103, 104, 109
- roc\_aunp(), 109
- roc\_aunp\_vec (roc\_aunp), 104
- roc\_aunu, 7, 12, 18, 32, 71, 91, 103, 106, 107
- roc\_aunu(), 106
- roc\_aunu\_vec (roc\_aunu), 107

roc\_curve, [36](#), [52](#), [94](#), [110](#)  
 roc\_curve(), [101](#), [103](#)  
 rpd, [14](#), [39](#), [41](#), [43](#), [54](#), [56](#), [58](#), [73](#), [76](#), [82](#), [100](#),  
     [112](#), [116](#), [118](#), [120](#), [126](#)  
 rpd(), [112](#), [115](#), [116](#)  
 rpd\_vec (rpd), [112](#)  
 rpiq, [14](#), [39](#), [41](#), [43](#), [54](#), [56](#), [58](#), [73](#), [76](#), [82](#),  
     [100](#), [114](#), [115](#), [118](#), [120](#), [126](#)  
 rpiq(), [112](#), [114](#), [115](#)  
 rpiq\_vec (rpiq), [115](#)  
 rsq, [14](#), [39](#), [41](#), [43](#), [54](#), [56](#), [58](#), [73](#), [76](#), [82](#), [100](#),  
     [114](#), [116](#), [117](#), [120](#), [126](#)  
 rsq(), [13](#), [65](#), [118–120](#)  
 rsq\_trad, [14](#), [39](#), [41](#), [43](#), [54](#), [56](#), [58](#), [73](#), [76](#),  
     [82](#), [100](#), [114](#), [116](#), [118](#), [119](#), [126](#)  
 rsq\_trad(), [117](#), [118](#), [120](#)  
 rsq\_trad\_vec (rsq\_trad), [119](#)  
 rsq\_vec (rsq), [117](#)  
  
 sens, [4](#), [10](#), [23](#), [29](#), [46](#), [49](#), [60](#), [80](#), [85](#), [89](#), [98](#),  
     [121](#), [131](#)  
 sens(), [8](#), [44](#), [77](#), [83](#), [121](#), [128](#), [132](#)  
 sens\_vec (sens), [121](#)  
 sensitivity (sens), [121](#)  
 sensitivity\_vec (sens), [121](#)  
 smape, [14](#), [39](#), [41](#), [43](#), [54](#), [56](#), [58](#), [73](#), [76](#), [82](#),  
     [100](#), [114](#), [116](#), [118](#), [120](#), [125](#)  
 smape\_vec (smape), [125](#)  
 solubility\_test, [127](#)  
 spec, [4](#), [10](#), [23](#), [29](#), [46](#), [49](#), [60](#), [80](#), [85](#), [89](#), [98](#),  
     [124](#), [128](#)  
 spec(), [8](#), [44](#), [77](#), [83](#), [121](#), [128](#)  
 spec\_vec (spec), [128](#)  
 specificity (spec), [128](#)  
 specificity\_vec (spec), [128](#)  
 static\_survival\_metric\_summarizer  
     (metric-summarizers), [61](#)  
 summary.conf\_mat, [132](#)  
 summary.conf\_mat(), [20](#), [21](#)  
  
 tidy.conf\_mat (conf\_mat), [19](#)  
 two\_class\_example, [133](#)  
  
 validate\_estimator (developer-helpers),  
     [24](#)  
  
 yardstick\_any\_missing  
     (yardstick\_remove\_missing), [134](#)  
 yardstick\_remove\_missing, [24](#), [26](#), [61](#), [64](#),  
     [134](#)